


Guided drive DGRC-GF-40-25-PA

Part number: 8218219

FESTO



Data sheet

| Feature | Value |
|---|--|
| Distance of centre of gravity of payload to yoke plate xs | 50 mm |
| Stroke | 25 mm |
| Piston diameter | 40 mm |
| Drive unit operating mode | Yoke |
| Cushioning | Elastic cushioning rings/pads at both ends |
| Mounting position | Any |
| Guide | Sliding guide |
| Structural design | Guide |
| Position sensing | For proximity sensor |
| Protection against torsion/guide | Guide rod with yoke |
| Operating pressure | 0.15 MPa...1 MPa 1.5 bar...10 bar |
| Max. speed | 0.8 m/s |
| Mode of operation | Double-acting |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 0 - No corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Suitability for the production of Li-ion batteries | Suitable for battery production in accordance with Festo's internal definition in degree of severity F1A with restrictions regarding the use of Cu/Zn/Ni |
| Ambient temperature | -10 °C...60 °C |
| Impact energy in the end positions | 0.7 Nm |
| Max. force Fy | 1057 N |
| Max. force Fy static | 1057 N |
| Max. force Fz | 1057 N |
| Max. force Fz static | 1057 N |
| Max. torque Mx | 44.39 Nm |
| Max. static moment Mx | 44.39 Nm |
| Max. torque My | 21.67 Nm |
| Max. static moment My | 21.67 Nm |
| Max. torque Mz | 21.67 Nm |

| Feature | Value |
|--|----------------------------------|
| Max. static moment Mz | 21.67 Nm |
| Max. permissible torque load Mx as a function of the stroke | 10.95 Nm |
| Max. payload as a function of the stroke at defined distance xs | 162 N |
| Theoretical force at 6 bar, retracting | 686 N |
| Theoretical force at 6 bar, advancing | 754 N |
| Torsional backlash | 0.035 deg |
| Moving mass | 595.2 g |
| Product weight | 1083.8 g |
| Basic weight with 0 mm stroke | 488.6 g |
| Center of gravity of the moving mass as a function of the stroke | 32.5 mm |
| Pneumatic connection | G1/8 |
| Note on materials | RoHS-compliant |
| Cover material | Wrought aluminum alloy |
| Seals material | NBR |
| Material of dynamic seals | TPE-U(PU) |
| End plate material | Wrought aluminum alloy, anodized |
| Guide rod material | High-alloy steel |
| Housing material | Wrought aluminum alloy, anodized |
| Piston rod material | High-alloy steel |