


bus module

CPX-E-EP

Gaminio numeris: 4080499

FESTO



Tech. Duomenys

Savybės	Reikšmė
Matmenys B x L x H	42,2 mm x 125,8 mm x 76,5 mm
Tinklelio matmuo	18,9 mm
Montavimo tipas	su bėgeliu
Didžiausias modulių skaičius	10
Produkto svoris	145 g
Montavimo pozicija	Vertikalus Horizontaliai
Aplinkos temperatūra	-5 ... 50 °C
Note on ambient temperature	-5 - 60°C for vertical installation
Saugojimo temperatūra	-20 ... 70 °C
Sąlyginė oro drėgmė	95 % nesikondensuojantis
Apsaugos klasė	IP20
Atsparumo korozijai klasė CRC	0 - No corrosion stress
Atsparumas vibracijoms	Transport application test with severity level 1 as per FN 942017-4 and EN 60068-2-6
Atsparumas smūgiams	Shock test with severity level 1 in accordance with FN 942017-5 and EN 60068-2-27
Apsauga nuo tiesioginio ir netiesioginio kontakto	Protective extra-low voltage with safe disconnection (PELV)
PWIS conformity	VDMA24364 zone III
CE ženklas (žr. deklaraciją)	atitinka EU-EMV reikalvimus in accordance with EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
KC mark	KC-EMV
Leidimas	RCM Mark c UL us - Listed (OL)
Skyriaus sertifikatas	UL E239998
Informacija	atitinka RoHS
Material housing	PA
Material screws	Plienas, cinkuotas
Diagnostics via LED	Module status Network status Modify Power supply electronics/sensors Power supply load System error Connection status
Diagnostics via bus	Wire break Short circuit parameterisation error Upper limit value not observed Overtemperature Lower limit value not observed Minimali įtampa
Feldbus jungtis	Ethernet

Savybės	Reikšmė
Fieldbus interface, protocol	ACD (Addr. Conflict Detection) DLR (Device Level Ring) EtherNet/IP EtherNet/IP QoS EtherNet/IP Quickconnect Modbus/TCP SNMP
Fieldbus interface, type of connection	2x rozetė
Fieldbus interface, connection technology	RJ45
Fieldbus interface, number of pins/wires	8
Feldbus jungtis, galvaninis atskyrimas	Taip
Feldbus jungtis, perdavimo greitis	100 Mbit/s
Fieldbus interface, note on transmission rate	100 Mb, switched Fast Ethernet
Maksimali adreso apimtis išėjimams	64 Byte
Fieldbus interface, max. address volume for inputs	64 Byte
Pastaba dėl jėjimų	62 bytes with I/O diagnostic interface 63 bytes with status bits 64 bytes without diagnostics
Maksimali adreso apimtis išėjimams	64 Byte
Fieldbus interface, max. address volume for outputs	64 Byte
Nuoroda išėjimui	62 bytes with I/O diagnostic interface 64 bytes with status bits 64 bytes without diagnostics
System parameters	Diagnostic memory Fail-safe reaction Force mode Idle response System start
Module parameters	Channel alarms bundling Undervoltage diagnostics Channel alarms undervoltage
Parama konfigūruojant	EDS failas
Power supply, function	Electronics and sensors
Power supply, type of connection	Galinė juosta
Power supply, connection technology	Spryuliniai gnybtai
Power supply, number of pins/wires	4
Nominal operating voltage DC for electronics/sensors	24 V
Permissible voltage fluctuations for electronics/sensors	± 25 %
Power supply, conductor diameter	0,2 ... 1,5 mm ²
Power supply, note on conductor diameter	0,2 - 2,5 mm ² for flexible conductors without wire end sleeves
Didžiausia leistina srovė	8 A
Intrinsic current consumption at nominal operating voltage for electronics/sensors	typ. 65 mA
Galios susilpnėjimo mažinimas	20 ms
Apsaugotas nuo poliariskumo pakeitimo	24 V sensor supply against 0 V sensor supply