


插頭插座, 具電纜

KMPYE-5

料號: 151909

FESTO

預裝配, 用於比例方向控制閥.



技術參數

特性	值
符合標準	EN 61076-2-101
Cable identification	具配件
產品重量	305 g
Electrical connection 1, function	Field device side
Electrical connection 1, design	圓形
Electrical connection 1, connection type	插頭插座
Electrical connection 1, cable outlet	直的
Electrical connection 1, connection technology	M12x1, A-coded in accordance with EN 61076-2-101
Electrical connection 1, number of pins/wires	4
Electrical connection 1, occupied pins/wires	4
Electrical connection 1, type of mounting	Screw-type lock with hex A/F 18 mm and longitudinal knurl
Electrical connection 2, function	Controller side
Electrical connection 2, connection type	電纜
Electrical connection 2, connection technology	開放式終端
Electrical connection 2, number of pins/wires	4
Electrical connection 2, occupied pins/wires	4
工作電壓範圍 DC	0 ... 30 V
額定工作電壓 DC	24 V
容許的電流負載	4 A
浪湧強度	2.5 kV
電纜長度	5 m
電纜的測試條件	視需求的測試條件
Bending radius, flexible cable installation	>= 90 mm
電纜直徑	6.2 mm
電纜直徑公差	± 0,3 mm
電纜結構	4x0,25 已屏蔽
導體的額定截面	0.25 mm ²
導線末端	Cut off bluntly
防護等級	IP65
Note on degree of protection	裝配狀態
環境溫度	-40 ... 80 °C
Ambient temperature with flexible cable installation	-25 ... 80 °C
CE 符號 (參見符合的標準)	in accordance with EU RoHS directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
PWIS conformity	VDMA24364-B2-L
材料備註	符合 RoHS
污染程度	3
Material cable sheath	PVC
電纜外套顏色	灰色
Material housing	PA
外殼顏色	黑色
Material screw-type lock	PA
Material electrical contact	黃銅