



- Extremely short cycle times
- Compact design
- Simple planning, installation and commissioning
- Choice of pneumatic or electrical actuation



Handling modules HSW

Key features at a glance

FESTO

Range of applications


The handling module is a new generation of function modules for the automatic transfer, feed and removal of small parts in extremely confined spaces.

This is achieved by means of a guided swivel and linear motion sequence. A backlash-free guide with recirculating




ball bearing elements ensures high precision and good rigidity. The combination of a semi-rotary drive and a slotted guide system produces a compact unit for a complete pick & place cycle at an operating angle of 90°.

Special features

- Compact design
- Extremely short cycle times
- Cost optimised
- Simple commissioning
- For effective loads up to 1.6 kg
- Angle and stroke adjustment
- Wait positions possible
- No planning costs



Product range overview – Two drive variants are available

	Pneumatic: HSW-...-AP, with swivel module DSM	Electrical: HSW-...-AE, with motor unit MTR-DCI	Without drive: HSW-...-AS, with drive shaft
			
Advantages			
	• Fast • Cost effective • Ready to install • No system planning required • Simple commissioning	• Freely positionable • Freely selectable speed • Smooth motion sequence • Ready to install • No system planning required • Simple commissioning using teach-in procedure	• Compact • Universal applications • Variable drive interface • On request: Drive options in combination with servo motors MTR-AC
Technical data			
Max. linear stroke at 90° swivel angle	[mm] 90 ... 175		
Working stroke	[mm] 9 ... 35		
Min. cycle time	[s] 0.6 ... 1.0	0.8 ... 1.2	Dependent on drive
Effective load	[g] 0 ... 1,600		
Repetition accuracy at end positions	[mm] ±0.02	±0.02	±0.02
Wait positions	Max. 2	Any	Dependent on drive
Function of wait position	Pushing via actuating cylinder	Freely approachable	Dependent on drive
Repetition accuracy at wait positions	[mm] < 1	< 2	Dependent on drive
Technical data	➔ 1 / 7.2-9	➔ 1 / 7.2-26	➔ 1 / 7.2-36

Handling modules HSW

Application examples


FESTO

Handling units
Handling modules

7.2


HSW-...-AP, pneumatic / HSW-...-AE, electrical

Rotary indexing table




- Fast feed and removal at a linear transfer unit or rotary indexing table, for example

Machine equipment



- Loading and unloading of small parts on a grinding or injection moulding machine, for example


Planar surface gantry



- Fast equipping of pallets

HSW-...-AS, without drive

Rotary indexing table, linear transfer




- Fast and flexible 90° pick & place unit with servo motor MTR-AC
- Electrical variant using third-party motor

Handling modules HSW

Key features at a glance


FESTO

Design of HSW-...-AP – pneumatic variant with swivel module DSM



- 1 Slotted guide plate
- 2 Adjustable stop
- 3 Sensor rail
- 4 Shock absorber
- 5 Pressure piece
- 6 Swivel module DSM
- 7 Swivel lever
- 8 Guide with recirculating ball bearing element

Design of HSW-...-AS – variant without drive (rear side)



- 1 Base plate
- 2 Shaft with Woodruff key
- 3 Slotted guide plate
- 4 Ball bearings

Handling modules HSW


Key features at a glance

FESTO

Handling units
Handling modules

7.2

Design of HSW-...-AE – electrical variant with motor unit MTR-DCI-...-HM



Cable binder holder and protective conduit



- 1 Holder and protective conduit facilitate the secure routing of tubing and cables.

Stroke adjustment



- 2 The adjustable slotted guide plate permits precise adjustment of the swivel angle.

Adjustment of proximity sensors



- 3 The sensor rail facilitates readily accessible and easy adjustment of the proximity sensors.

Stop element and pressure piece



- 4+5 The stop element and pressure piece guarantee freedom from backlash and precision in the end positions and in the effective linear stroke.


Handling modules HSW

Peripherals overview

FESTO

Handling units
Handling modules

7.2



Handling modules HSW

Peripherals overview

FESTO


Accessories					
	Brief description	10	12	16	→ Page
1	Handling module HSW	■	■	■	1 / 7.2-9
2	Adapter kit HAPG-...-B	■	■	■	1 / 7.2-38
3	Swivel module DSM	■	■	■	1 / 4.1-2
4	Motor unit MTR-DCI-...-HM	■	■	■	1 / 7.2-26
5	Motor unit MTR-DCI-...-HM	■	■	■	1 / 7.2-26
6	Installation kit MKRP	■	■	■	1 / 7.2-39
7	Wait position module BW-HSW	■	■	■	1 / 7.2-39
8	Cover kit BSD-HSW	■	■	■	1 / 7.2-39
9	Adapter kit HAPG	–	■	■	1 / 7.2-40
10	Adapter kit HAPG	–	■	■	1 / 7.2-40
11	Adapter kit HAPG	■	■	■	1 / 7.2-40
12	Adapter kit HAPG	–	■	■	1 / 7.2-40
13	Adapter kit HAPS	–	■	■	1 / 7.2-40
14	Parallel gripper HGPC	–	■	■	1 / 7.2-40
15	Parallel gripper HGPP	–	■	■	1 / 7.2-40
16	Angle gripper HGW	■	■	■	1 / 7.2-40
17	Radial gripper HGR	■	■	■	1 / 7.2-40
18	Parallel gripper HGP	■	■	■	1 / 7.2-40
19	Three-point gripper HGD	–	–	■	1 / 7.2-40
20	Parallel gripper HGPT	–	■	■	1 / 7.2-40
21	Semi-rotary drive DRQD	–	■	■	1 / 4.2-24
22	Suction cups	■	■	■	Volume 6
23	Proximity sensor SME-/SMT-8	■	■	■	1 / 7.2-42
24	Non-return and flow control valve GRLA	■	■	■	Volume 2

Handling units
Handling modules

7.2

Handling modules HSW, pneumatic

Type codes



Handling modules HSW, pneumatic

Technical data

FESTO

Function



[www.festo.com/en/
Spare_parts_service](http://www.festo.com/en/Spare_parts_service)




-  Size
10, 12 and 16
-  Swivel angle
80 ... 100
-  Stroke range
90 ... 175

General technical data	
Type	HSW-...-AP
Pneumatic connection	M5
Mode of operation	Double-acting
Constructional design	Swivel module
	Linear guide plus ball bearing
	Force-guided motion sequence
Cushioning	Shock absorber at both ends, soft characteristic curve
Position sensing	Via proximity sensor
Type of mounting	Via through-holes
	Via slot nuts
Mounting position	Any

Operating and environmental conditions	
Type	HSW-...-AP
Operating medium	Filtered compressed air, lubricated or unlubricated
Operating pressure [bar]	4 ... 8
Ambient temperature [°C]	0 ... +60

Stroke [mm] and angle range [°]				
Size		10	12	16
Max. linear stroke at 90°	H	90/90	142/142	175/175
swivel angle				
Working stroke	Ha	9 ... 15	15 ... 25	20 ... 35
Angle range	α	80 ... 100		



Forces [N]			
Size	10	12	16
Along Y and Z axes (depending on lever position)			
Effective force at 6 bar	30	35	55
Along Z and Y axes			
Permissible process force ¹⁾	30	35	50

1) Due to the pretension force on the guide

Handling modules HSW, pneumatic

Technical data


FESTO

Weight [g]			
Size	10	12	16
HSW-...-AP	1,300	3,000	5,400
HSW-...-AP-SD	1,400	3,200	5,700
HSW-...-AP-W	1,350	3,140	5,550
HSW-...-AP-SD-W	1,450	3,340	5,850

Repetition accuracy [mm]

To ensure low-vibration operation, the effective load should be mounted as close as possible to the guide rail of the handling module.
Repetition accuracy is guaranteed by

mounting the effective load (adapter plate, semi-rotary drive and/or gripper, gripper finger, workpiece) within the mounting surface of the adapter kit HAPG/HAPG-...-B.




Mounting surface of HAPG

Size	10	12	16
Repetition accuracy at end positions	±0.02		

Travel times t as a function of effective load m with observance of repetition accuracy

The travel time t is the time taken for the handling module to move from one end position to the other and back again.

The effective load m is the load attached to the guide rail (e.g. adapter, gripper, semi-rotary drive and workpiece).



— HSW-10-AP
- - - HSW-12-AP
- · - HSW-16-AP

Note
Higher speeds are possible at a constant load with restriction of the repetition accuracy.

Cycle times [s]

The cycle time t_t comprises the travel time t and the dwell time t_e at the end positions.

$t_t = \text{travel time } t + \text{dwell time } t_e$
The value must not fall below the minimum cycle time.

Size	10	12	16
Min. cycle time	0.6	0.8	1.0

Example for HSW-10-AP

Step 1:
The following values are assumed:
Effective load $m = 0.2 \text{ kg}$
Dwell time $t_e = 2 \times 350 \text{ ms}$
(350 ms per end position)

Step 2:
The travel time can be determined from the graph:
 $t = 800 \text{ ms}$

Step 3:
This gives us a cycle time:
 $t_t = 800 \text{ ms} + 700 \text{ ms}$
 $= 1,500 \text{ ms}$


Handling modules HSW, pneumatic

Technical data



Permissible static/dynamic characteristic load values

Linear guide and ball bearing



Combined load

The following torque equation must be satisfied with combined load:

$$\frac{M_x}{M_{xperm.}} + \frac{M_y}{M_{yperm.}} + \frac{M_z}{M_{zperm.}} \leq 1$$

Dynamic characteristic load values			
Size	10	12	16
Max. torques [Nm]	0.6	1.5	2.5
$M_{xperm.}, M_{yperm.}, M_{zperm.}$			

Handling modules HSW, pneumatic

Technical data

FESTO


Stroke adjustment

Swivel angle:


- An angle offset of $\alpha = \pm 5^\circ$ per end position can be set to adapt the handling module to the transfer system.

Linear stroke:

- Once the HSW has been mounted, the linear stroke of the pick and place position can be set independently of each other.




Swivel angle



Procedure:

- 1 Loosen the screws
- 2 Adjust the slotted guide plate using the adjusting screw (the slotted guide plate must always make contact with the guide ring)
- 3 Tighten the screws

Linear stroke



Procedure:

- 1 Loosen the lock nut
- 2 Set the desired linear stroke using the cushioning component/adjusting screw
- 3 Tighten the lock nut

Handling modules HSW, pneumatic

Technical data

FESTO

Wait position module

Application and mode of operation

Figure 1:




Figure 2:






Figure 3:




- 1 The handling module HSW is in the horizontal end position. The actuating cylinder is retracted in its initial position.
- 2 The 5/3-way valve is reset once the handling module reaches the vertical end position (Figure 1). The actuating cylinder must always be retracted before reaching an end position.
- 3 During extension the actuating cylinder pushes the handling module upwards into its wait position. The operating range is then free (Figure 2). The actuating cylinder can be used at both end positions.
- 4 From the wait position, the handling module can move either to the initial position or to the other end position (Figure 3).

Cycle




Circuit diagram for HSW with wait position module

Handling modules HSW



Actuating cylinder




Note

When used in combination with the wait position module, the handling module HSW must be actuated using a 5/3-way valve (normally pressurised). The actuating cylinder is actuated using a 5/2-way valve.

Size	10	12	16
Max. stroke of wait position module	10	15	25


Mounting options

Directly via through-holes




- 1 With or without centring rings

Via slot nuts on profile supports



User-specific



Note

The handling module HSW-10 can also be attached with the adjusting unit HMX-1.


Handling modules HSW, pneumatic

Technical data



Materials

Sectional view of handling module HSW



Size	10	12	16
1 Back plate	Wrought aluminium alloy, anodised		
2 Slotted guide plate	Case-hardened steel		
3 Adjusting screw	–	High-alloy steel	
4 Swivel lever	Case-hardened steel		
5 Stop sleeve	High-alloy steel		
6 Retainer	Wrought aluminium alloy, anodised		
7 Sensor rail	Wrought aluminium alloy, anodised		
8 Flange	Wrought aluminium alloy, anodised		
9 Top plate	Wrought aluminium alloy, anodised		
10 Pressure piece	High-alloy steel		
11 Guide	Tempered steel		
– Housing	Wrought aluminium alloy, anodised		
Note on materials	Free of copper, PTFE and silicone		


Handling modules HSW, pneumatic

Technical data



Materials

Sectional view of swivel module DSM



Swivel module		
1	Housing	Wrought aluminium alloy
2	Shaft	Steel with nickel-plated surface
3	Rotary vane	Fibreglass-reinforced plastic
4	Stop lever	Anodised aluminium
5	Stop/shock absorber retainer	Stainless steel
6	Stop screw	Stainless steel
7	Cap	Fibreglass-reinforced plastic
-	Seals	Polyurethane
Note on materials		Free of copper, PTFE and silicone

Handling modules HSW, pneumatic



Technical data

FESTO



Dimensions

Download CAD data → www.festo.com/en/engineering

with swivel module DSM



View A



- 1 Compressed air connections
- 2 Manual override (internal hex)
- 3 Angle adjustment for slotted guide plate
- 4 Sensor slot for SME-/SMT-8
- 5 Stroke adjustment

Handling modules HSW, pneumatic


Technical data

FESTO


Handling units
Handling modules

7.2

with swivel module DSM and protective cover



with wait position module



1 Compressed air connections

Size	B1	B2	B3	B4	B9	D7 Ø	D8 Ø	EE	H1	H2	H3	H4	H5	L1	L2
	±2	±3	±0.5						±0.3	±0.2	±0.5	±1		±2	±0.2
10	121	80	45	5.5	47	3.5	6	M3	120	37	56	89.6	12	123	–
12	148	95	48.5	9.5	59	4.5	8	M5	175	50	84	142	12	180	80
16	168	105	57	12.5	70	4.5	7.5	M5	215	58.5	103.5	174	12	219	100

Size	L3	L4	L8	L9	L10	L11	L12	R1	R2	T3	≈C1	≈C2	≈C3	≈C4
	±0.2	±0.2	±2	±3		max.	±2	±3	±3					
10	–	–	62	103	95	102.5	61.8	113	55	3.3	4.5	2	3	3
12	12.5	37.5	60	113	116	159	75.5	162	82	6.5	6	2	3	4
16	12	50	71.5	134	131	202.5	80.8	200	100	5.3	8	2.5	4	4

Handling modules HSW, pneumatic


Technical data

FESTO

Ordering data for HSW-...-AP									
Size	10			12			16		
	Part No.	Type		Part No.	Type		Part No.	Type	
Without protective cover									
–	540 222	HSW-10-AP		540 228	HSW-12-AP		540 234	HSW-16-AP	
Wait position module	540 225	HSW-10-AP-W		540 231	HSW-12-AP-W		540 237	HSW-16-AP-W	
With protective cover									
–	540 223	HSW-10-AP-SD		540 229	HSW-12-AP-SD		540 235	HSW-16-AP-SD	
Wait position module	540 224	HSW-10-AP-SD-W		540 230	HSW-12-AP-SD-W		540 236	HSW-16-AP-SD-W	

Handling modules HSW, electrical

Type codes




Handling modules HSW, electrical

Technical data

FESTO

Function



[www.festo.com/en/
Spare_parts_service](http://www.festo.com/en/Spare_parts_service)




-  Diameter
10, 12 and 16
-  Swivel angle
80 ... 100
-  Stroke range
90 ... 175

General technical data	
Type	HSW-...-AE
Constructional design	Motor unit
	Linear guide plus ball bearing
	Force-guided motion sequence
Cushioning	Noise reduction via buffers
Type of mounting	Via through-holes
	Via slot nuts
Mounting position	Any

Operating and environmental conditions	
Type	HSW-...-AE
Ambient temperature [°C]	0 ... +50
Protection class of motor	IP54
CE marking (see declaration of conformity)	In accordance with EU EMC directive

Stroke [mm] and angle range [°]				
Size		10	12	16
Max. linear stroke at 90° swivel angle	H	90/90	142/142	175/175
Working stroke	Ha	9 ... 15	15 ... 25	20 ... 35
Angle range	α	80 ... 100		



Forces [N]			
Size	10	12	16
Along Y and Z axes (depending on lever position)			
Feed force at 80 % of the nominal motor force	15	30	70
Along Z and Y axes			
Permissible process force ¹⁾	30	35	50

1) Due to the pretension force on the guide

Handling modules HSW, electrical

Technical data

FESTO


Weight [g]			
Size	10	12	16
HSW-...-AE	2,000	4,500	8,900
HSW-...-AE-SD	2,110	4,700	9,200
HSW-...-AE-GE	2,410	5,000	10,000
HSW-...-AE-SD-GE	2,520	5,200	10,300

Repetition accuracy [mm]

To ensure low-vibration operation, the effective load should be mounted as close as possible to the guide rail of the handling module.

Repetition accuracy is guaranteed by

mounting the effective load (adapter plate, semi-rotary drive and/or gripper, gripper finger, workpiece) within the mounting surface of the adapter kit HAPG/HAPG-...-B.




Size			10	12	16
Repetition accuracy	At end positions		±0.02		
	Intermediate positions		< 2		

Travel times t as a function of effective load m

The travel time t is the time taken for the handling module to move from one end position to the other and back again.

The effective load m is the load attached to the vertical guide rail (e.g. adapter, gripper, semi-rotary drive and workpiece)




Handling modules HSW, electrical

Technical data

FESTO

Permissible static/dynamic characteristic load values

Cross-guide



 **Note**

The torques apply to the centre of the vertical guide.

Combined load

The following torque equation must be satisfied with combined load:

$$\frac{M_x}{M_{xperm.}} + \frac{M_y}{M_{yperm.}} + \frac{M_z}{M_{zperm.}} \leq 1$$

Dynamic characteristic load values			
Size	10	12	16
Max. torques [Nm]	0.6	1.5	2.5
$M_{xperm.}, M_{yperm.}, M_{zperm.}$			


Handling modules HSW, electrical

Technical data

FESTO

Materials

Sectional view of handling module HSW



Size	10	12	16
1 Back plate	Wrought aluminium alloy, anodised		
2 Slotted guide plate	Case-hardened steel		
3 Adjusting screw	–	High-alloy steel	
4 Swivel lever	Case-hardened steel		
5 Stop sleeve	High-alloy steel		
6 Retainer	Wrought aluminium alloy, anodised		
7 Sensor rail	Wrought aluminium alloy, anodised		
8 Flange	Wrought aluminium alloy, anodised		
9 Top plate	Wrought aluminium alloy, anodised		
10 Pressure piece	High-alloy steel		
11 Guide	Tempered steel		
– Housing	Wrought aluminium alloy, anodised		
Note on materials	Free of copper, PTFE and silicone		

Handling modules HSW, electrical

Technical data

FESTO


Stroke adjustment

Swivel angle:


- An angle offset of $\alpha = \pm 5^\circ$ per end position can be set to adapt the handling module to the transfer system.

Linear stroke:

- Once the HSW has been mounted, the linear stroke of the pick and place position can be set independently of each other.




Swivel angle



Procedure:

- 1 Loosen the screws
- 2 Adjust the slotted guide plate using the adjusting screw (the slotted guide plate must always make contact with the guide ring)
- 3 Tighten the screws

Linear stroke



Procedure:

- 1 Loosen the lock nut
- 2 Set the desired linear stroke using the cushioning component/adjusting screw
- 3 Tighten the lock nut

Handling modules HSW, electrical


Technical data

FESTO


Motor mounting variants

Motor pointing upwards/to side

Motor towards rear



Mounting options




1 Directly via through-holes

Examples:

Via slot nuts on profile supports

User-specific



Handling modules HSW, electrical

Technical data

FESTO

Motor unit MTR-DCI-...-HM



General technical data				→ Volume 5
Type	MTR-DCI-32-...-HM	MTR-DCI-42-...-HM	MTR-DCI-52-...-HM	
For handling module	HSW-10-...-AE	HSW-12-...-AE	HSW-16-...-AE	
Rotary position generator	Optical encoder			
No. of increments/revolution	300	500		
Temperature monitoring	Silicon absolute temperature sensor, switches off at temperatures >80 °C			
Display resolution	128 x 64 pixels			
Type of mounting	Can be bolted on or clamped to gear unit flange			
Gear unit type	Planetary gearing			
Gear reduction ratio	13.73 (14:1), 2-stage			


Electrical data				➔ Volume 5
Type		MTR-DCI-32-...-HM	MTR-DCI-42-...-HM	MTR-DCI-52-...-HM
For handling module		HSW-10-...-AE	HSW-12-...-AE	HSW-16-...-AE
Nominal voltage	[V DC]	24 ±10%		
Nominal current (motor)	[A]	0.73	2	5.1
Peak current	[A]	2.1	3.8	7.7
Nominal power (motor)	[W]	17.5	48	122.4
Max. current (digital logic outputs)	[mA]	200	200	60
No. of digital logic inputs (with I/O interface)	–	6		
No. of digital logic outputs (with I/O interface)	–	2		
Parameterisation interface		RS232; 9,600 baud		

Handling modules HSW, electrical

Technical data

FESTO

Pin allocation



1 3-pin M8 socket	
Pin	Function
1	Unused
3	Unused
4	Unused
–	

2 RS232 interface, 4-pin M8 socket	
Pin	Function
1	0 V
2	Transmitted data (TxD)
3	Received data (RxD)
4	–

3 I/O interface, 9-pin SUB-D plug	
Pin	Function
1	Traversing record coding, bit 0
2	Traversing record coding, bit 1
3	Traversing record coding, bit 2
4	Traversing record coding, bit 3
5	Start bit
6	Enable bit
7	Ready signal output
8	MC signal output
9	0 V

4 Power supply, 2-pin plug	
Pin	Function
1	24 V DC
2	0 V
–	
–	
–	
–	
–	
–	

Handling modules HSW, electrical

Technical data

FESTO


Simple solution for your application

Advantages of the handling module HSW-...-AE for installation and commissioning

- Handling module is supplied with motor already attached.
- Less wiring required thanks to integration of controller concept.
- Motor with gear unit, controller and power electronics are all fitted in one housing. This means that only one unit has to be taken into consideration when planning the system.
- Only one voltage supply of 24 V is required for commissioning.
- Commissioning via:
 - Control panel on handling module.
 - PC using FESTO Configuration Tool (FCT) software.

Installation and commissioning


Step 1: Mount the handling module



- Wide choice of mounting options

→ 1 / 7.2-25


Step 2: Mechanically adjust the end positions



- Set the desired linear stroke using the cushioning component and adjusting screw

→ 1 / 7.2-24

Step 3: Connect the 24 V voltage supply




- Plug and work: Connect the voltage – HSW is ready for operation

→ 1 / 7.2-26


Step 4: Parameterisation either via control panel on motor or using FCT software

Control panel on motor



- Clearly arranged LCD display
- All data is entered and saved using 4 keys:
 - Menu key
 - Arrow keys for changing parameter values or traversing records
 - Key for confirming the entered actions

FCT software – Festo Configuration Tool




- All the drives in a system can be managed and archived in a common project
- Project and data management for all supported device types
- Simple to use thanks to graphically supported parameter entry
- Universal mode of operation for all drives
- Working offline at your desk or online at the machine

Handling modules HSW, electrical


Technical data

FESTO

Step 5: Selection of predefined motion sequences (HSW mode) via the control panel or using the FCT software




HSW mode 1



- Precise travel to the mechanical end position

HSW mode 2




- Additional adjustable wait position module directly above workpiece/ workpiece carrier
- Handling of parts with different heights
- Insertion procedures at different speeds

HSW mode 3




- Additional ejector station for reject parts or quality inspection
- Precise travel to end position via setup position

HSW mode 4



- Insertion procedures with defined force
- Continued travel from wait position with adjustable torque

HSW mode 5



- Insertion procedures with defined force and additional intermediate position
- Continued travel from wait position with adjustable torque

Step 6: Fine adjustment

- Adjustment of preset positions, speeds and torques
- Addition of new traversing records (where necessary)

Handling modules HSW, electrical


Technical data

FESTO

Dimensions

Download CAD data → www.festo.com/en/engineering

with motor unit pointing upwards



Handling modules HSW, electrical


Technical data

FESTO

Dimensions

Download CAD data → www.festo.com/en/engineering

with motor unit pointing upwards and protective cover



Size	B1	B2	B3	B4	B5	B6	D7 Ø
	±3	±3	±0.5				
10	148	80	45	5.5	60	46	3.5
12	160.5	95	48.5	9.5	60	53.3	4.5
16	193	105	57	12.5	100	69.5	4.5

Size	D8 Ø	H1	H2	H4 ¹⁾	H5	H6	H7
		±0.3	±0.2	±1		±0.4	±3
10	6	120	37	89.6	12	66	239
12	8	175	50	142	12	70.8	291
16	7.5	215	58.5	174	12	94.8	344.5

Size	L1	L2	L3	L4	L5	L8	L9
	±2	±0.2	±0.2	±0.2	±3	±2	±3
10	123	–	–	–	276	62	121
12	180	80	12.5	37.5	357	60	128
16	219	100	12	50	420	71.5	156

Size	R1 ¹⁾	R2 ¹⁾	T3	≈C2	≈C3	≈C4	≈C5	≈C6
	±3	±3						
10	113	55	3.3	2	3	3	2.5	2.5
12	162	82	6.5	2	3	4	2.5	2.5
16	200	100	5.3	2.5	4	4	5	3

1) Maximum stroke and 90° angle

Handling modules HSW, electrical



Technical data

FESTO


Dimensions

Download CAD data → www.festo.com/en/engineering


with motor unit towards the rear



View A



HSW-10



HSW-12

HSW-16

- 3 Angle adjustment for slotted guide plate
- 4 Sensor slot for SME/SMT-8
- 5 Stroke adjustment

Handling modules HSW, electrical


Technical data

FESTO

Handling units
Handling modules

7.2

with motor unit towards the rear and protective cover



Size	B1	B2	B3	B4	B6	D7 Ø
	±3	±2	±0.5			
10	263	80	45	5.5	46	3.5
12	323	95	48.5	9.5	53.3	4.5
16	363	105	57	12.5	69.5	4.5

Size	D8	H1	H2	H4 ¹⁾	H5	H6
		±0.3	±0.2	±1		±0.4
10	6	120	37	89.6	12	66
12	8	175	50	142	12	70.8
16	7.5	215	58.5	174	12	94.8

Size	L1	L2	L3	L4	L8	L9
	±2	±0.2	±0.2	±0.2	±2	±3
10	123	–	–	–	62	245
12	180	80	12.5	37.5	60	290
16	219	100	12	50	71.5	328.5

Size	R1 ¹⁾	R2 ¹⁾	T3	≈C2	≈C3	≈C4
	±3	±3				
10	113	55	3.3	2	3	3
12	162	82	6.5	2	3	4
16	200	100	5.3	2.5	4	4

Handling modules HSW, electrical


Technical data

FESTO

Ordering data for HSW-...-AE						
Size	10		12		16	
	Part No.	Type	Part No.	Type	Part No.	Type
I/O interface						
without gear unit						
without protective cover	540 250	HSW-10-AE-IO	540 266	HSW-12-AE-IO	540 282	HSW-16-AE-IO
with protective cover	540 252	HSW-10-AE-IO-SD	540 268	HSW-12-AE-IO-SD	540 284	HSW-16-AE-IO-SD
with right-angle gear unit						
without protective cover	540 251	HSW-10-AE-IO-GE	540 267	HSW-12-AE-IO-GE	540 283	HSW-16-AE-IO-GE
with protective cover	540 253	HSW-10-AE-IO-SD-GE	540 269	HSW-12-AE-IO-SD-GE	540 285	HSW-16-AE-IO-SD-GE

Handling modules HSW, without drive

Type codes




Handling modules HSW, without drive

Technical data

FESTO

Function



www.festo.com/en/Spare_parts_service




-  Size
10, 12 and 16
-  Swivel angle
80 ... 100
-  Stroke range
90 ... 175

General technical data	
Type	HSW-...-AS
Constructional design	Drive shaft
	Linear guide plus ball bearing
	Force-guided motion sequence
Cushioning	Noise reduction via buffers
Type of mounting	Via through-holes
	Via centring sleeves
Mounting position	Any

Weight [g]			
Size	10	12	16
HSW-...-AS	1,200	2,800	5,200
HSW-...-AS-SD	1,300	3,000	5,500

Permissible static/dynamic characteristic load values



-  Note

Technical data for mechanical components → 1 / 7.2-11.


Characteristic load values			
Size	10	12	16
Max. axial force $F_{Yperm.}$ [Nm]	10	18	30
Max. radial force $F_{Zperm.}$ [Nm]	30	45	75
Max. drive torque $M_{Yperm.}$ [Nm]	0.85	1.25	2.5

Handling modules HSW, without drive

Technical data


FESTO

Mass moment of inertia J_0 as a function of effective load m (for sizing drive)



Dimensions

Download CAD data → www.festo.com/en/engineering



Size	B5	B6	B7	B8	D1 Ø g7	D2 Ø	D3	D4 Ø	D5 Ø f8	D10	T1	TK ±0.1
10	25	19	2	16	6	12	M2.5	46	32	M3	6.8	39
12	33	25	4	20	8	13	M3	65	45	M4	8.8	55
16	36.5	28.5	4	23	10	16	M3	70	50	M4	10.6	60

Ordering data for HSW-...-AS

Size	10 Part No.	Type	12 Part No.	Type	16 Part No.	Type
without protective cover	540 226	HSW-10-AS	540 232	HSW-12-AS	540 238	HSW-16-AS
with protective cover	540 227	HSW-10-AS-SD	540 233	HSW-12-AS-SD	540 239	HSW-16-AS-SD

Handling modules HSW


Accessories

FESTO

Adapter kit HAPG/HAPG-B

Material:

Wrought aluminium alloy, anodised



Dimensions and ordering data										
For size	B1	B2	B3	D1	D2	D3	D4	D5	H1	H2
		± 0.2		$\varnothing$	$\varnothing$					
10	5	6	8	33	–	M4	M3	–	34	–
12, 16	8	9.5	14.5	56	7	M4	M4	M4	63.5	35.5

For size	H3	H4	H5	H6	H7	L1	L2	Weight	Part No.	Type
		± 0.2	± 0.2	± 0.2	± 0.2		± 0.1	[g]		
10	10	5	20.5	16.5	15	24	9	25	540 249	HAPG-69
12, 16	12	15.5	40	20.5	40	47	15	110	540 882	HAPG-71-B


Handling modules HSW

Accessories

FESTO

Installation kit MKRP

Material:
Conduit/fitting: Polyamide
Reducer/lock nut:
Nickel-plated brass
Adapter plate/bracket:
Powder-coated steel



Ordering data					
For size	Max. bending radius for conduit ¹⁾ R [mm]	Tubing I.D. [mm]	Weight [g]	Part No.	Type
10, 12	55	12	140	540 247	MKRP-5
12, 16	75	16.5	150	540 248	MKRP-6

1) The conduit must not be filled beyond 70%

Cover kit BSD-HSW

Material:
Wrought aluminium alloy, anodised



Dimensions → 1 / 7.2-17

Ordering data		
For size	Weight [g]	Part No. Type
10	100	540 240 BSD-HSW-10
12	200	540 241 BSD-HSW-12
16	300	540 242 BSD-HSW-16

Wait position module BW-HSW for HSW-...-AP

Material:
Wrought aluminium alloy, anodised



Dimensions → 1 / 7.2-17

Ordering data		
For size	Weight [g]	Part No. Type
10	50	540 243 BW-HSW-10
12	140	540 244 BW-HSW-12
16	150	540 245 BW-HSW-16

Handling units
Handling modules

7.2


Handling modules HSW

Accessories

FESTO

Adapter kits for grippers

For combining HSW with grippers HG-... or semi-rotary drive DRQD



Gripper		Adapter kit		Required mounting attachments	B1	D1	D2	H1	L1
Part No.	Type	Part No.	Type						
HSW-10-... with HAPG-69									
174 815	HGP-06-A	–		M3 x 14 (2x)	–				
174 817	HGR-10-A			M3 x 16 (2x)					
174 818	HGW-10-A			M3 x 16 (2x)					
HSW-12-... with HAPG-71-B									
174 815	HGP-06-A	192 706	HAPG-37-S1	–	12	M3	M5	42	50
174 817	HGR-10-A								
174 818	HGW-10-A								
1) 1)	DRQD-8-...	178 448	HAPS-2 ²⁾		8	M4	M4	28	48
1) 1)	DRQD-12-...								
197 542	HGP-10-A-B	192 705	HAPG-36-S1		12	M3	M5	42	50
161 829	HGR-16-A								
161 833	HGW-16-A								
525 658	HGPP-10-A				529 017	HAPG-57	8	M3	M4
539 269	HGPC-16-A	191 901	HAPG-55		10	M3	M5	40	62
535 858	HGPT-16-A	537 169	HAPG-75	8	M2.5	M3	27	49.6	

- 1) The semi-rotary drive DRQD is a modular product; for information on configuration and ordering → 1 / 4.2-23
2) The centring sleeves for attaching to the adapter kit HAPG-71-B are not required

Handling modules HSW


Accessories

FESTO


Gripper		Adapter kit		Required mounting attachments	B1	D1	D2	H1	L1
Part No.	Type	Part No.	Type						
HSW-16-... with HAPG-71-B									
174 815	HGP-06-A	192 706	HAPG-37-S1	–	12	M3	M5	42	50
174 817	HGR-10-A								
174 818	HGW-10-A								
1) 1)	DRQD-8-... DRQD-12-...	178 448	HAPS-2 ²⁾		8	M4	M4	28	48
197 542	HGP-10-A-B				192 705	HAPG-36-S1	12	M3	M5
161 829	HGR-16-A								
161 833	HGW-16-A								
174 819	HGD-16-A								
525 658	HGPP-10-A	529 017	HAPG-57 ²⁾				8	M3	M4
187 867	HGPP-12-A	191 900	HAPG-54		12	M3	M5	44	52
187 870	HGPP-16-A	191 901	HAPG-55	10	M3	M5	40	62	
539 269	HGPC-16-A								
535 858	HGPT-16-A	537 169	HAPG-75	8	M2.5	M3	27	49.6	
535 861	HGPT-20-A								

- 1) The semi-rotary drive DRQD is a modular product; for information on configuration and ordering → 1 / 4.2-23
2) The centring sleeves for attaching to the adapter kit HAPG-71-B are not required


Adapter kit HAPG-36/-37




Adapter kit HAPG-54/-55/-57



Adapter kit HAPG-75



Adapter kit HAPS-2




Handling modules HSW

Accessories

FESTO

Ordering data – Proximity sensors for T-slot, magneto-resistive					Technical data → www.festo.com/catalogue/sm	
	Type of mounting	Switch output	Electrical connection	Cable length [m]	Part No.	Type
N/O contact						
	Insertable in the slot from above, flush with cylinder profile	PNP	Cable, 3-wire	2.5	543 867	SMT-8M-PS-24V-K-2,5-OE
			Plug M8x1, 3-pin	0.3	543 866	SMT-8M-PS-24V-K-0,3-M8D
			Plug M12x1, 3-pin	0.3	543 869	SMT-8M-PS-24V-K-0,3-M12
		NPN	Cable, 3-wire	2.5	543 870	SMT-8M-NS-24V-K-2,5-OE
			Plug M8x1, 3-pin	0.3	543 871	SMT-8M-NS-24V-K-0,3-M8D
	Insertable in the slot lengthwise, flush with the cylinder profile	PNP	Cable, 3-wire	2.5	175 436	SMT-8-PS-K-LED-24-B
			Plug M8x1, 3-pin	0.3	175 484	SMT-8-PS-S-LED-24-B
N/C contact						
	Insertable in the slot from above, flush with cylinder profile	PNP	Cable, 3-wire	7.5	543 873	SMT-8M-PO-24V-K7,5-OE



Ordering data – Proximity sensors for T-slot, magnetic reed					Technical data → www.festo.com/catalogue/sm	
	Type of mounting	Switch output	Electrical connection	Cable length [m]	Part No.	Type
N/O contact						
	Insertable in the slot from above, flush with cylinder profile	Contacting	Cable, 3-wire	2.5	543 862	SME-8M-DS-24V-K-2,5-OE
				5.0	543 863	SME-8M-DS-24V-K-5,0-OE
			Cable, 3-wire	2.5	543 872	SME-8M-ZS-24V-K-2,5-OE
			Plug M8x1, 3-pin	0.3	543 861	SME-8M-DS-24V-K-0,3-M8D
	Insertable in the slot lengthwise, flush with the cylinder profile	Contacting	Cable, 3-wire	2.5	150 855	SME-8-K-LED-24
			Plug M8x1, 3-pin	0.3	150 857	SME-8-S-LED-24
N/C contact						
	Insertable in the slot lengthwise, flush with the cylinder profile	Contacting	Cable, 3-wire	7.5	160 251	SME-8-O-K-LED-24

Ordering data – Connecting cables				Technical data → www.festo.com/catalogue/nebu	
	Electrical connection, left	Electrical connection, right	Cable length [m]	Part No.	Type
	Straight socket, M8x1, 3-pin	Cable, open end, 3-wire	2.5	541 333	NEBU-M8G3-K-2.5-LE3
			5	541 334	NEBU-M8G3-K-5-LE3
	Straight socket, M12x1, 5-pin	Cable, open end, 3-wire	2.5	541 363	NEBU-M12G5-K-2.5-LE3
			5	541 364	NEBU-M12G5-K-5-LE3
	Angled socket, M8x1, 3-pin	Cable, open end, 3-wire	2.5	541 338	NEBU-M8W3-K-2.5-LE3
			5	541 341	NEBU-M8W3-K-5-LE3
	Angled socket, M12x1, 5-pin	Cable, open end, 3-wire	2.5	541 367	NEBU-M12W5-K-2.5-LE3
			5	541 370	NEBU-M12W5-K-5-LE3

Handling modules HSW

Accessories

FESTO

Ordering data – Cables for HSW-...-AE				
	Brief description	Cable length	Part No.	Type
	Supply cable	2.5 m	537 931	KPWR-MC-1-SUB-9HC-2,5
		5 m	537 932	KPWR-MC-1-SUB-9HC-5
		10 m	537 933	KPWR-MC-1-SUB-9HC-10
	Control cable for I/O connection to any PLC controller	2.5 m	537 923	KES-MC-1-SUB-9-2,5
		5 m	537 924	KES-MC-1-SUB-9-5
		10 m	537 925	KES-MC-1-SUB-9-10
	Programming cable	2.5 m	537 926	KDI-MC-M8-SUB-9-2,5

Handling units
Handling modules

7.2