

## Silencers








**FESTO**



# Silencers

Product range overview

FESTO

Version	Type	Connection D1			Push-in connector	For tubing I.D.	Push-in sleeve diameter	Noise level [dB (A)]	→ Page/ Internet
		M thread	G thread	NPT thread					
Sintered metal									
	U-PK-3	–	–	–	–	3	–	< 70	4
	U-PK-4	–				4		< 74	
	U-M3	M3				–		< 65	
	U-M5	M5				–		< 70	
Polymer, male thread									
	U-1/8	–	G1/8	–	–	–	–	< 77	5
	U-1/4		G1/4					< 77	
	U-3/8		G3/8					< 82	
	U-1/2		G1/2					< 80	
	U-3/4		G3/4					< 83	
	U-1		G1					< 84	
Polymer, female thread									
	U-1/8-I	–	G1/8	–	–	–	–	< 77	6
Die-cast metal									
	U-1/8-B	–	G1/8	–	–	–	–	< 74	7
	U-1/4-B		G1/4					< 80	
	U-3/8-B		G3/8					< 80	
	U-1/2-B		G1/2					< 80	
	U-3/4-B		G3/4					< 81	
	U-1-B		G1					< 80	
	U-3/4-B-NPT	–	NPT3/4-14	–	–	–	< 81	8	
	U-1-B-NPT	–	NPT1-11 1/2	–	–	–	< 80		
With push-in sleeve for push-in fitting QS, Quick Star									
	UC-QS-3H	–	–	–	–	–	3	< 60	9
	UC-QS-4H						4	< 60	
	UC-QS-6H						6	< 60	
	UC-QS-8H						8	< 60	
	UC-QS-10H						10	< 68	
Threaded connection, for solenoid valves CPE, Compact Performance									
	UC-M5	M5	–	–	–	–	–	< 60	10
	UC-M7	M7	–					< 58	
	UC-1/8	–	G1/8					< 59	
	UC-1/4	–	G1/4					< 60	
Push-in connector, for solenoid valves VUVB-ST12/valve terminals type 23 VTUB-12									
	AMTC-P-PC10	–	–	–	For QSP10	–	–	< 58	11





## Note

Clean silencers with kerosene or benzene (not with trichloroethylene).

# Silencers

Product range overview

**FESTO**


Version	Type	Connection D1			Push-in connector	For tubing I.D.	Push-in sleeve diameter	Noise level [dB (A)]	→ Page/ Internet
		M thread	G thread	NPT thread					
For vacuum generators VN-T2/T3									
	UO-M7	M7	–	–	–	–	–		12
	UO-1/8	–	G1/8						
	UO-1/4	–	G1/4						
For vacuum generators VN-T4/T6									
	UOM-1/4	–	G1/4	–	–	–	–		13
	UOM-3/8		G3/8						
	UOMS-1/4		–						
	UOMS-3/8		–						
For soft-start and exhaust valve MS6-SV									
	UOS-1	–	G1	–	–	–	–	< 75	ms6-sv
Filter silencer									
	LFU-1/4	–	G1/4	–	–	–	–	< 40	lfu
	LFU-3/8		G3/8						
	LFU-1/2		G1/2						
	LFU-1		G1						

# Silencers U

Technical data – Sintered metal design

**FESTO**

Function



- For noise reduction and avoiding contamination at the exhaust ports of pneumatic components
- Compact design



General technical data					
Pneumatic connection		PK-3	PK-4	M3	M5
Mounting position		Any			
Noise level <sup>1)</sup>	[dB (A)]	< 70	< 74	< 65	< 70
Flow rate with respect to atmosphere <sup>2)</sup>	[l/min]	80	150	110	320
Product weight	[g]	5	5	4	5

1) Measured at 6 bar with respect to atmosphere at a distance of 1 m

2) Measured at p1 = 6 bar

Operating and environmental conditions	
Operating pressure	[bar] 0 ... 10
Operating medium	Filtered compressed air, lubricated or unlubricated Dried compressed air, lubricated or unlubricated
Ambient temperature	[°C] -10 ... +70

Materials	
Threaded plug	Brass
Silencer insert	Bronze
Note on materials	RoHS-compliant

Dimensions				Download CAD Data → <a href="http://www.festo.com/us/cad">www.festo.com/us/cad</a>
U-PK-3	U-PK-4	U-M3	U-M5	
1 Barbed fitting for tubing I.D. 3 mm	2 Barbed fitting for tubing I.D. 4 mm			

Ordering data			
Pneumatic connection	Part No.	Type	PU <sup>1)</sup>
PK-3	4646	U-PK-3	10
PK-4	4932	U-PK-4	10
M3	163978	U-M3	10
M5	4645	U-M5	10
	534221	U-M5-50	50


1) Packaging unit

# Silencers U

Technical data – Polymer design, male thread

FESTO

Function



- For noise reduction at the exhaust ports of pneumatic components



General technical data							
Pneumatic connection		G1/8	G1/4	G3/8	G1/2	G3/4	G1
Mounting position		Any					
Noise level <sup>1)</sup>	[dB (A)]	< 77	< 77	< 82	< 80	< 83	< 84
Flow rate with respect to atmosphere <sup>2)</sup>	[l/min]	2,050	3,400	5,900	10,600	15,000	19,900
Product weight	[g]	2	8	30	58	83	140

1) Measured at 6 bar with respect to atmosphere at a distance of 1 m


2) Measured at p1 = 6 bar

Operating and environmental conditions	
Operating pressure	[bar] 0 ... 10
Operating medium	Filtered compressed air, lubricated or unlubricated Dried compressed air, lubricated or unlubricated
Ambient temperature	[°C] -10 ... +70

Materials	
Housing	Polyacetal
Silencer insert	Polyethylene
Note on materials	Free of copper and PTFE RoHS-compliant

## Dimensions

Download CAD Data → [www.festo.com/us/cad](http://www.festo.com/us/cad)



Ordering data						
Pneumatic connection	D2	L1	L2	Part No.	Type	PU <sup>1)</sup>
D1	Ø					
G1/8	15.2	35.9	5.5	2307	U-1/8	1
				534222	U-1/8-50	50
G1/4	19	57	6.5	2316	U-1/4	1
				534223	U-1/4-20	20
G3/8	33.5	78.8	7.5	2309	U-3/8	1
				534224	U-3/8-20	20
G1/2	43	88.1	9	2310	U-1/2	1
				534225	U-1/2-20	20
G3/4	45	120.7	10.5	2311	U-3/4	1
G1	55	126.5	11.5	2312	U-1	1


1) Packaging unit

# Silencers U

Technical data – Polymer design, female thread

FESTO

Function



- For noise reduction at the exhaust ports of pneumatic components



General technical data		
Pneumatic connection		G $\frac{1}{8}$
Mounting position		Any
Noise level <sup>1)</sup>	[dB (A)]	< 77
Flow rate with respect to atmosphere <sup>2)</sup>	[l/min]	2,050
Product weight	[g]	4

- 1) Measured at 6 bar with respect to atmosphere at a distance of 1 m  
 2) Measured at p<sub>1</sub> = 6 bar

Operating and environmental conditions		
Operating pressure	[bar]	0 ... 10
Operating medium		Filtered compressed air, lubricated or unlubricated
		Dried compressed air, lubricated or unlubricated
Ambient temperature	[°C]	-10 ... +70

Materials	
Housing	Polyacetal
Silencer insert	Polyethylene
Note on materials	Free of copper and PTFE
	RoHS-compliant

Dimensions	Download CAD Data → <a href="http://www.festo.com/us/cad">www.festo.com/us/cad</a>


Ordering data		
Pneumatic connection	Part No.	Type
G $\frac{1}{8}$	3670	U- $\frac{1}{8}$ -I

# Silencers U

Technical data – Die-cast design

**FESTO**

Function



- For noise reduction at the exhaust ports of pneumatic components



General technical data						
Pneumatic connection	G $\frac{1}{8}$	G $\frac{1}{4}$	G $\frac{3}{8}$	G $\frac{1}{2}$	G $\frac{3}{4}$	G1
Mounting position	Any					
Noise level <sup>1)</sup>	[dB (A)]	< 74	< 80	< 80	< 80	< 81
Flow rate with respect to atmosphere <sup>2)</sup>	[l/min]	1,204	2,838	5,734	7,622	13,266
Product weight	[g]	8	17	37	75	120
						233


1) Measured at 6 bar with respect to atmosphere at a distance of 1 m

2) Measured at p1 = 6 bar

Operating and environmental conditions	
Operating pressure	[bar] 0 ... 10
Operating medium	Filtered compressed air, lubricated or unlubricated Dried compressed air, lubricated or unlubricated
Ambient temperature	[°C] -10 ... +70

Materials	
Housing	Die-cast aluminium
Silencer insert	Polyethylene
Note on materials	Free of copper and PTFE RoHS-compliant

## Dimensions Download CAD Data → [www.festo.com/us/cad](http://www.festo.com/us/cad)




Ordering data						
Pneumatic connection	D	L	L1	≡	Part No.	Type
D1	Ø					
G $\frac{1}{8}$	16	39.2	5.5	14	6841	U- $\frac{1}{8}$ -B
G $\frac{1}{4}$	19.5	55.6	6.5	17	6842	U- $\frac{1}{4}$ -B
G $\frac{3}{8}$	25	86.6	7.5	19	6843	U- $\frac{3}{8}$ -B
G $\frac{1}{2}$	28	116.5	9	24	6844	U- $\frac{1}{2}$ -B
G $\frac{3}{4}$	38	138	10.5	32	6845	U- $\frac{3}{4}$ -B
G1	47.8	177	11.5	36	151990	U-1-B

## Silencers U

Technical data – Die-cast design, NPT

**FESTO**

Function



- For noise reduction at the exhaust ports of pneumatic components



General technical data			
Pneumatic connection		NPT $\frac{3}{4}$ -14	NPT1-11 $\frac{1}{2}$
Mounting position		Any	
Noise level <sup>1)</sup>	[dB (A)]	< 81	< 80
Flow rate with respect to atmosphere <sup>2)</sup>	[l/min]	11,834	15,102
Product weight	[g]	128	233


1) Measured at 6 bar with respect to atmosphere at a distance of 1 m

2) Measured at p<sub>1</sub> = 6 bar

Operating and environmental conditions	
Operating pressure	[bar] 0 ... 10
Operating medium	Compressed air in accordance with ISO 8573-1:2010 [7:-:-]
Note on operating/pilot medium	Operation with lubricated medium possible (in which case lubricated operation will always be required)
Ambient temperature	[°C] -10 ... +70

Materials	
Housing	Die-cast aluminium
Threaded plug	Wrought aluminium alloy
Silencer insert	PE
Note on materials	Free of copper and PTFE
	RoHS-compliant

### Dimensions Download CAD Data → [www.festo.com/us/cad](http://www.festo.com/us/cad)



Ordering data						
Pneumatic connection	D	L	L1	$\varnothing$	Part No.	Type
D1	$\varnothing$					
NPT $\frac{3}{4}$ -14	38	151	18	30	566823	U- $\frac{3}{4}$ -B-NPT
NPT1-11 $\frac{1}{2}$	47.8	193.3	22.5	41	571280	U-1-B-NPT




# Silencers UC

FESTO

Technical data – Design with push-in sleeve

Function



- For noise reduction at the exhaust ports of pneumatic components
- For QS push-in connectors 3 ... 10 mm



General technical data					
Push-in sleeve diameter		3	4	6	8 10
Mounting position		Any			
Noise level <sup>1)</sup>	[dB (A)]	< 60	< 60	< 60	< 68
Flow rate with respect to atmosphere <sup>2)</sup>	[l/min]	170	350	800	1,500 3,100
Product weight	[g]	0.4	0.5	1.1	2.3 5.5

1) Measured at 6 bar with respect to atmosphere at a distance of 1 m


2) Measured at p1 = 6 bar

Operating and environmental conditions	
Operating pressure	[bar] 0 ... 10
Operating medium	Filtered compressed air, lubricated or unlubricated
Ambient temperature	[°C] -10 ... +70

Materials	
Threaded plug	PE
Silencer insert	PE
Note on materials	RoHS-compliant

## Dimensions

Download CAD Data → [www.festo.com/us/cad](http://www.festo.com/us/cad)




Ordering data					
Push-in sleeve diameter	D	L	L1	Part No.	Type
D1	Ø				
3	7.8 +0.1/-0.3	29.1 ±0.6	14.4 ±0.2	165005	UC-QS-3H
4	7.8 +0.1/-0.3	31.0 ±0.6	16.3 ±0.2	165006	UC-QS-4H
6	9.8 -0.4	41.3 ±1.4	17.2	165007	UC-QS-6H
8	13.8 +0.2/-0.3	54.4 +0.5/-1.0	23.4	175611	UC-QS-8H
10	17.8 -0.3	68.7 +0.2/-0.8	26.7	526475	UC-QS-10H

# Silencers UC

Technical data – Design with threaded connection

FESTO

Function



- For noise reduction at the exhaust ports of pneumatic components
- For solenoid valves CPE, Compact Performance



General technical data				
Pneumatic connection	M5	M7	G1/8	G1/4
Mounting position	Any			
Noise level <sup>1)</sup>	[dB (A)]	< 60	< 58	< 59
Flow rate with respect to atmosphere <sup>2)</sup>	[l/min]	350	800	1,700
Product weight	[g]	0.4	1.2	2.6
				5.2

- 1) Measured at 6 bar with respect to atmosphere at a distance of 1 m  
 2) Measured at p1 = 6 bar

Operating and environmental conditions	
Operating pressure	[bar] 0 ... 10
Operating medium	Filtered compressed air, lubricated or unlubricated
Ambient temperature	[°C] -10 ... +70

Materials	
Threaded plug	PE
Silencer insert	PE
Note on materials	RoHS-compliant

Dimensions	Download CAD Data → <a href="http://www.festo.com/us/cad">www.festo.com/us/cad</a>


Ordering data						
Pneumatic connection	D	L	L1	Part No.	Type	PU <sup>1)</sup>
D1	Ø					
M5	7.8 +0.1/-0.3	19.4 +0.6/-0.8	4.5 ±0.2	165003	UC-M5	1
				534217	UC-M5-50	50
M7	9.8 -0.4	30.7 +0.6/-0.8	5.5 -0.5	161418	UC-M7	1
				534218	UC-M7-50	50
G1/8	13.8 +0.2/-0.3	38.0 +0.8/-1.0	6.5 ±0.1	161419	UC-1/8	1
				534219	UC-1/8-50	50
G1/4	17.8 -0.3	50.8 +0.8/-1.0	8.5 ±0.15	165004	UC-1/4	1
				534220	UC-1/4-20	20

- 1) Packaging unit

# Silencers AMTC

Technical data

## Function



- For solenoid valves VUVB-ST12/ valve terminals type 23 VTUB-12
- Attached via PIN (spring clip), included in the scope of delivery of the valve



General technical data		
Pneumatic connection		For QSP10
Mounting position		Any
Noise level <sup>1)</sup>	[dB (A)]	≤ 58
Flow rate with respect to atmosphere <sup>2)</sup>	[l/min]	800
Product weight	[g]	2.0

1) Measured at 6 bar with respect to atmosphere at a distance of 1 m


2) Measured at p1 = 6 bar

Operating and environmental conditions		
Operating pressure	[bar]	0 ... 10
Operating medium		Filtered compressed air, lubricated or unlubricated
Ambient temperature	[°C]	-5 ... +60

Materials	
Threaded plug	PE
Silencer insert	PE
Note on materials	RoHS-compliant

## Dimensions

Download CAD Data → [www.festo.com/us/cad](http://www.festo.com/us/cad)



Ordering data							
Pneumatic connection	D	D1	L	L1	Part No.	Type	PU <sup>1)</sup>
For QSP10	9.8	8.9	31.4	6.8	1224460	AMTC-P-PC10	1


1) Packaging unit

# Silencers UO

Technical data

FESTO

Function



- Use only for vacuum generators VN-T2/T3
- Special minimal resistance silencer
- Facilitates trouble-free operation of the vacuum generator



General technical data			
Pneumatic connection	M7	G1/8	G1/4
Mounting position	Any		
Product weight [g]	2.5	5	8

Operating and environmental conditions	
Operating pressure of vacuum generator [bar]	0 ... 8
Operating medium	Dried compressed air
Ambient temperature [°C]	-10 ... +60
Corrosion resistance class CRC <sup>1)</sup>	2

1) Corrosion resistance class 2 according to Festo standard 940 070  
Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Materials	
Threaded plug	Polyethylene
Silencer insert	Polyethylene
Note on materials	Free of copper and PTFE

Dimensions		Download CAD Data → <a href="http://www.festo.com/us/cad">www.festo.com/us/cad</a>


Ordering data						
Pneumatic connection	D	D2	L	L1	Part No.	Type
D1	Ø					
M7	9.8	3	36.7	5.5	197582	UO-M7
G1/8	13.8	3.5	48	6.5	197583	UO-1/8
G1/4	17.8	5.3	62.3	8.5	197584	UO-1/4

# Silencers UOM/silencer extensions UOMS

FESTO

Technical data

Function



- Use only for vacuum generators VN-T4/T6
- Special minimal resistance silencer
- Facilitates trouble-free operation of the vacuum generator
- Silencer extension for extending the silencer for further noise reduction



General technical data				
Type	UOM-1/4	UOM-3/8	UOMS-1/4	UOMS-3/8
Pneumatic connection	G1/4	G3/8	–	
Design	Silencer, open			
Type of mounting	Screw-in		Engaging	
Mounting position	Any			
Type of seal on threaded plug	No seal			
Product weight [g]	11.1	22.7	8.6	17.5

Operating and environmental conditions	
Operating pressure of vacuum generator [bar]	0 ... 8
Operating medium	Compressed air
Ambient temperature [°C]	0 ... +60
Corrosion resistance class CRC <sup>1)</sup>	2

1) Corrosion resistance class 2 according to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Materials	
Housing	Polyacetal
Inner pipe	Wrought aluminium alloy
Threaded plug	Polyacetal
Silencer insert	Polyurethane foam
Note on materials	Free of copper and PTFE
	Contains PWIS (paint-wetting impairment substances)

Dimensions		Download CAD Data → <a href="http://www.festo.com/us/cad">www.festo.com/us/cad</a>
UOM	UOMS	

Ordering data						
Pneumatic connection	D	D2	L	L1	L2	Part No. Type
D1	Ø	Ø				
Silencer						
G1/4	17.8	–	73	8	10	538432 UOM-1/4
G3/8	23.8	–	74	8.6	10.5	538433 UOM-3/8
Silencer extension						
–	17.8	16	64.5	–	10	538436 UOMS-1/4
–	23.8	22	65.2	–	10.5	538437 UOMS-3/8

## Product Range and Company Overview

### A Complete Suite of Automation Services

Our experienced engineers provide complete support at every stage of your development process, including: conceptualization, analysis, engineering, design, assembly, documentation, validation, and production.



**Custom Automation Components**  
Complete custom engineered solutions



**Custom Control Cabinets**  
Comprehensive engineering support and on-site services



**Complete Systems**  
Shipment, stocking and storage services

### The Broadest Range of Automation Components

With a comprehensive line of more than 30,000 automation components, Festo is capable of solving the most complex automation requirements.



**Electromechanical**  
Electromechanical actuators, motors, controllers & drives



**Pneumatics**  
Pneumatic linear and rotary actuators, valves, and air supply



**PLCs and I/O Devices**  
PLC's, operator interfaces, sensors and I/O devices

### Supporting Advanced Automation... As No One Else Can!

Festo is a leading global manufacturer of pneumatic and electromechanical systems, components and controls for industrial automation, with more than 12,000 employees in 56 national headquarters serving more than 180 countries. For more than 80 years, Festo has continuously elevated the state of manufacturing with innovations and optimized motion control solutions that deliver higher performing, more profitable automated manufacturing and processing equipment. Our dedication to the advancement of automation extends beyond technology to the education and development of current and future automation and robotics designers with simulation tools, teaching programs, and on-site services.

### Quality Assurance, ISO 9001 and ISO 14001 Certifications

Festo Corporation is committed to supply all Festo products and services that will meet or exceed our customers' requirements in product quality, delivery, customer service and satisfaction.

To meet this commitment, we strive to ensure a consistent, integrated, and systematic approach to management that will meet or exceed the requirements of the ISO 9001 standard for Quality Management and the ISO 14001 standard for Environmental Management.



© Copyright 2008, Festo Corporation. While every effort is made to ensure that all dimensions and specifications are correct, Festo cannot guarantee that publications are completely free of any error, in particular typing or printing errors. Accordingly, Festo cannot be held responsible for the same. For Liability and Warranty conditions, refer to our "Terms and Conditions of Sale", available from your local Festo office. All rights reserved. No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, electronic, mechanical, photocopying or otherwise, without the prior written permission of Festo. All technical data subject to change according to technical update.



Printed on recycled paper at New Horizon Graphic, Inc., FSC certified as an environmentally friendly printing plant.

# Festo North America

## Festo Regional Contact Center

5300 Explorer Drive  
Mississauga, Ontario L4W 5G4  
Canada

### USA Customers:

For ordering assistance,

**Call:** 1.800.99.FESTO (1.800.993.3786)

**Fax:** 1.800.96.FESTO (1.800.963.3786)

**Email:** [customer.service@us.festo.com](mailto:customer.service@us.festo.com)

For technical support,

**Call:** 1.866.GO.FESTO (1.866.463.3786)

**Fax:** 1.800.96.FESTO (1.800.963.3786)

**Email:** [product.support@us.festo.com](mailto:product.support@us.festo.com)

### Canadian Customers:

**Call:** 1.877.GO.FESTO (1.877.463.3786)

**Fax:** 1.877.FX.FESTO (1.877.393.3786)

**Email:** [festo.canada@ca.festo.com](mailto:festo.canada@ca.festo.com)

## USA Headquarters

Festo Corporation  
395 Moreland Road  
P.O. Box 18023  
Hauppauge, NY 11788, USA  
[www.festo.com/us](http://www.festo.com/us)

## USA Sales Offices

### Appleton

North 922 Tower View Drive, Suite N  
Greenville, WI 54942, USA

### Boston

120 Presidential Way, Suite 330  
Woburn, MA 01801, USA

### Chicago

1441 East Business Center Drive  
Mt. Prospect, IL 60056, USA

### Dallas

1825 Lakeway Drive, Suite 600  
Lewisville, TX 75057, USA

### Detroit – Automotive Engineering Center

2601 Cambridge Court, Suite 320  
Auburn Hills, MI 48326, USA

### New York

395 Moreland Road  
Hauppauge, NY 11788, USA

### Silicon Valley

4935 Southfront Road, Suite F  
Livermore, CA 94550, USA

## United States



**USA Headquarters, East:** Festo Corp., 395 Moreland Road, Hauppauge, NY 11788

Phone: 1.631.435.0800; Fax: 1.631.435.8026;

Email: [info@festo-usa.com](mailto:info@festo-usa.com)

[www.festo.com/us](http://www.festo.com/us)

## Canada



**Headquarters:** Festo Inc., 5300 Explorer Drive, Mississauga, Ontario L4W 5G4

Phone: 1.905.624.9000; Fax: 1.905.624.9001;

Email: [festo.canada@ca.festo.com](mailto:festo.canada@ca.festo.com)

[www.festo.ca](http://www.festo.ca)

## Mexico



**Headquarters:** Festo Pneumatic, S.A., Av. Ceylán 3, Col. Tequesquahuac,  
54020 Tlalneapantla, Edo. de México

Phone: 011 52 [55] 53 21 66 00; Fax: 011 52 [55] 53 21 66 65;

Email: [festo.mexico@mx.festo.com](mailto:festo.mexico@mx.festo.com)

[www.festo.com/mx](http://www.festo.com/mx)

## Central USA

Festo Corporation  
1441 East Business  
Center Drive  
Mt. Prospect, IL 60056, USA  
Phone: 1.847.759.2600  
Fax: 1.847.768.9480



## Western USA

Festo Corporation  
4935 Southfront Road,  
Suite F  
Livermore, CA 94550, USA  
Phone: 1.925.371.1099  
Fax: 1.925.245.1286



## Festo Worldwide

Argentina Australia Austria Belarus Belgium Brazil Bulgaria Canada Chile China Colombia Croatia Czech Republic Denmark  
Estonia Finland France Germany Great Britain Greece Hong Kong Hungary India Indonesia Iran Ireland Israel Italy Japan Latvia  
Lithuania Malaysia Mexico Netherlands New Zealand Norway Peru Philippines Poland Romania Russia Serbia Singapore  
Slovakia Slovenia South Africa South Korea Spain Sweden Switzerland Taiwan Thailand Turkey Ukraine United States Venezuela

[www.festo.com](http://www.festo.com)