

## Cartridge fittings QSP, Quick Star

**FESTO**



## Cartridge fittings QSP, Quick Star

Technical data

**FESTO**

### Cartridge fittings QSP10


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]


Material:

- Housing: Nickel plated brass

-Q- Ambient temperature  
0 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Certification:  
Germanischer Lloyd



Dimensions and ordering data							
Tubing O.D.	D5 Ø	H1	H2	H3	Part No.	Type	PU <sup>1)</sup>
D1							
4	9.8	16.2	6.7	11.6	<b>172972</b>	<b>QSP10-4</b>	<b>10</b>
6	9.8	16.2	6.7	11.9	<b>172973</b>	<b>QSP10-6</b>	<b>10</b>

1) Packaging unit quantity.

### Cartridge fittings QSPKG10


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



Dimensions and ordering data										
Tubing O.D.	Nominal size	D5 Ø	H1	H2	H3	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
D1	[mm]									
3	1.6	9.75	16.1	6.7	11.6	1	1.5	<b>132621</b>	<b>QSPKG10-3</b>	<b>10</b>
4	2.3	9.75	16.1	6.7	11.6	1	1.4	<b>132622</b>	<b>QSPKG10-4</b>	<b>10</b>
6	3.7	10.55	18.1	6.7	11.9	1	1.8	<b>132623</b>	<b>QSPKG10-6</b>	<b>10</b>

1) Corrosion resistance class 1 to Festo standard 940 070  
Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

# Cartridge fittings QSP, Quick Star

Technical data

## Cartridge fittings QSPLKG10

Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:-:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
-5 ... +60 °C

Pressure  
-0,95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



Dimensions and ordering data												
Tubing O.D.	Nominal size	D5	D6	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece	Part No.	Type	PU <sup>2)</sup>
D1	[mm]	Ø	Ø						[g]			
3	1.8	9.75	9.4	13.4	6.7	18.2	11.6	1	2.1	132853	QSPLKG10-3	10
4	2.3	9.75	9.4	13.4	6.7	18.2	11.6	1	2	132920	QSPLKG10-4	10
6	3.3	9.75	10.55	14.4	6.7	19.8	11.9	1	2.7	132921	QSPLKG10-6	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

## Cartridge fittings QSPLKG10

Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:-:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
-5 ... +60 °C

Pressure  
-0,95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



Dimensions and ordering data												
Tubing O.D.	Nominal size	D5	D6	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece	Part No.	Type	PU <sup>2)</sup>
D1	[mm]	Ø	Ø						[g]			
3	1.8	9.75	9.4	23.4	6.7	18.2	11.6	1	2.5	132861	QSPLKG10-3	10
4	2.3	9.75	9.4	23.4	6.7	18.2	11.6	1	2.4	132925	QSPLKG10-4	10
6	3.3	9.75	10.55	26.4	6.7	19.8	11.9	1	3.2	132926	QSPLKG10-6	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

## Cartridge fittings QSP, Quick Star

Technical data

**FESTO**

### Cartridge fittings QSPK10


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



### Dimensions and ordering data

Tubing O.D. D1	Nominal size [mm]	D5 Ø	H1	H2	H3	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
3	1.6	9.75	16.1	6.7	11.6	1	1.5	132978	QSPK10-3	10
4	2.3	9.75	16.1	6.7	11.6	1	1.4	132979	QSPK10-4	10
6	3.7	10.55	18.1	6.7	11.9	1	1.8	132980	QSPK10-6	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

### Cartridge fittings QSPLK10


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



### Dimensions and ordering data

Tubing O.D. D1	Nominal size [mm]	D5 Ø	D6 Ø	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
4	2.3	9.75	9.4	13.4	6.7	19.4	19.4	1	2.1	132601	QSPLK10-4	10
6	3.5	9.75	11	14.4	6.7	20.3	11.9	1	2.8	132602	QSPLK10-6	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

# Cartridge fittings QSP, Quick Star

FESTO

Technical data

## Cartridge fittings QSPLLK10


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

-  - Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



Dimensions and ordering data												
Tubing O.D.	Nominal size	D5 Ø	D6 Ø	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
D1	[mm]											
4	2.3	9.75	9,4	23.4	6.7	19.4	11.6	1	2.4	<b>132603</b>	<b>QSPLLK10-4</b>	<b>10</b>
6	3.5	9.75	11	26.4	6.7	20.3	11.9	1	3.3	<b>132604</b>	<b>QSPLLK10-6</b>	<b>10</b>

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

## Cartridge fittings QSP, Quick Star

Technical data

**FESTO**

### Cartridge fittings QSPKG14


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



Dimensions and ordering data										
Tubing O.D.	Nominal size	D5	H1	H2	H3	CRC <sup>1)</sup>	Weight/piece	Part No.	Type	PU <sup>2)</sup>
D1	[mm]	Ø					[g]			
6	3.5	13.7	16.5	7.75	11.9	1	2.4	132930	QSPKG14-6	10
8	5.2	14.6	25.2	7.75	18.1	1	5.3	132931	QSPKG14-8	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

### Cartridge fittings QSPLKG14


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



Dimensions and ordering data												
Tubing O.D.	Nominal size	D5 Ø	D6 Ø	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece	Part No.	Type	PU <sup>2)</sup>
D1	[mm]								[g]			
6	3.3	13.7	11.9	16	7.75	18.8	11.9	1	3.5	132938	QSPLKG14-6	10
8	4.8	13.7	14.6	17.8	7.75	28.2	18.1	1	7.1	132939	QSPLKG14-8	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

## Cartridge fittings QSP, Quick Star

Technical data

### Cartridge fittings QSPLLKG14


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



### Dimensions and ordering data

Tubing O.D.	Nominal size	D5 Ø	D6 Ø	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
D1	[mm]											
6	3.4	13.7	11.9	28.0	7.75	18.8	11.9	1	4.0	<b>132942</b>	<b>QSPLLKG14-6</b>	<b>10</b>
8	4.7	13.7	14.6	33.3	7.75	28.2	18.1	1	8.1	<b>132943</b>	<b>QSPLLKG14-8</b>	<b>10</b>

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

# Cartridge fittings QSP, Quick Star

Technical data

FESTO

## Cartridge fittings QSPK18


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:-:-]

Material:

- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C


-  - Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS


Certification:  
Germanischer Lloyd




QSP18-4



QSP18-6 / QSP18-8



QSP18-10



Dimensions and ordering data										
Tubing O.D.	Nominal size	D5 Ø	H1	H2	H3	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
D1	[mm]									
4	2.3	17.7	13.6	7.75	11.6	1	2.8	130839	QSPK18-4	10
6	3.8	17.7	13.7	7.75	11.9	1	3	130840	QSPK18-6	10
8	5.5	17.7	20.7	7.75	18.2	1	5.4	130841	QSPK18-8	10
10	6.7	17.7	24.5	7.75	20.2	1	8.1	130842	QSPK18-10	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.



# Cartridge fittings QSP, Quick Star

Technical data

## Cartridge fittings QSPLK18


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



Dimensions and ordering data												
Tubing O.D.	Nominal size	D5	D6	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece	Part No.	Type	PU <sup>2)</sup>
D1	[mm]	Ø	Ø						[g]			
4	2.3	17.7	9	15.3	7.75	19.4	11.6	1	3.2	130843	QSPLK18-4	10
6	3.6	17.7	11	16.3	7.75	20.3	11.9	1	3.9	130844	QSPLK18-6	10
8	5.2	17.7	15	18.3	7.75	27.2	18.2	1	7.5	130845	QSPLK18-8	10
10	6.7	17.7	17.7	19.6	7.75	29.5	20.2	1	10.8	132639	QSPLK18-10	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

## Cartridge fittings QSPLLK18


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



Dimensions and ordering data												
Tubing O.D.	Nominal size	D5	D6	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece	Part No.	Type	PU <sup>2)</sup>
D1	[mm]	Ø	Ø						[g]			
4	2.3	17.7	9	25.3	7.75	19.4	11.6	1	3.5	130846	QSPLLK18-4	10
6	3.6	17.7	11	38.3	7.75	20.3	11.9	1	4.3	130847	QSPLLK18-6	10
8	5.2	17.7	15	34.3	7.75	27.2	18.2	1	8.1	130848	QSPLLK18-8	10
10	6.4	17.7	17.7	38.3	7.75	29.5	20.2	1	12	132640	QSPLLK18-10	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

## Cartridge fittings QSP, Quick Star

Technical data

**FESTO**

### Cartridge fittings QSPKG18


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



#### Dimensions and ordering data

Tubing O.D.	Nominal size	D5	H1	H2	H3	CRC <sup>1)</sup>	Weight/piece	Part No.	Type	PU <sup>2)</sup>
D1	[mm]	Ø					[g]			
8	5.5	17.7	20.7	7.75	18.2	1	5.4	132649	QSPKG18-8	10
10	6.7	17.7	24.5	7.75	20.2	1	8.1	132650	QSPKG18-10	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

### Cartridge fittings QSPLKG18


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



#### Dimensions and ordering data

Tubing O.D.	Nominal size	D5	D6	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece	Part No.	Type	PU <sup>2)</sup>
D1	[mm]	Ø	Ø						[g]			
8	5.2	17.7	15	18.3	7.75	27.2	18.2	1	7.5	132946	QSPLKG18-8	10
10	6.7	17.7	17.7	19.6	7.75	29.5	20.2	1	10.8	132947	QSPLKG18-10	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

## Cartridge fittings QSP, Quick Star

### Technical data

#### Cartridge fittings QSPLLKG18


##### Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

##### Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



### Dimensions and ordering data

Tubing O.D.	Nominal size	D5 Ø	D6 Ø	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
D1	[mm]											
8	5.2	17.7	15	18.3	7.75	27.2	18.2	1	8.1	<b>132950</b>	<b>QSPLLKG18-8</b>	<b>10</b>
10	6.4	17.7	17.7	19.6	7.75	29.5	20.2	1	12	<b>132951</b>	<b>QSPLLKG18-10</b>	<b>10</b>

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

## Cartridge fittings QSP, Quick Star

Technical data

**FESTO**

### Cartridge fittings QSPKG20


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



#### Dimensions and ordering data

Tubing O.D. D1	Nominal size [mm]	D5 Ø	H1	H2	H3	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
8	5.4	19.75	19.1	10.6	18.1	1	6	132633	QSPKG20-8	10
10	6.4	19.75	25	10.6	20.2	1	9	132634	QSPKG20-10	10
12	8.3	21.1	32.7	10.6	23.4	1	13	132635	QSPKG20-12	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

### Cartridge fittings QSPLKG20


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



#### Dimensions and ordering data

Tubing O.D. D1	Nominal size [mm]	D5 Ø	D6 Ø	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
8	4.8	19.75	16.0	21.5	10.6	29.7	18.1	1	10	132855	QSPLKG20-8	10
10	6.1	19.75	19.0	23.0	10.6	32.0	20.2	1	14	132856	QSPLKG20-10	10
12	7.7	19.75	21.1	24.0	10.6	36.2	23.4	1	17	132857	QSPLKG20-12	10

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

## Cartridge fittings QSP, Quick Star

Technical data

### Cartridge fittings QSPLLKG20


Operating medium:

- Compressed air in accordance with ISO 8573-1:2010 [7:--:-]

Material:


- Housing: Reinforced PA
- Release ring: POM
- Tubing seal: NBR
- Tube retaining claw: High-alloy stainless steel

-Q- Ambient temperature  
–5 ... +60 °C

 Operating pressure  
–0.95 ... +10 bar

Note on materials:  
Conforms to RoHS

Certification:  
Germanischer Lloyd



### Dimensions and ordering data

Tubing O.D.	Nominal size	D5 Ø	D6 Ø	H1	H2	L1	L2	CRC <sup>1)</sup>	Weight/piece [g]	Part No.	Type	PU <sup>2)</sup>
D1	[mm]											
8	4.8	19.75	16.0	38.5	10.6	29.7	18.1	1	11	<b>132863</b>	<b>QSPLLKG20-8</b>	<b>10</b>
10	6	19.75	19.0	43.0	10.6	32.0	20.2	1	15	<b>132864</b>	<b>QSPLLKG20-10</b>	<b>10</b>
12	7.3	19.75	21.1	45.9	10.6	36.2	23.4	1	20	<b>132865</b>	<b>QSPLLKG20-12</b>	<b>10</b>

1) Corrosion resistance class 1 to Festo standard 940 070

Components requiring low corrosion resistance. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.

2) Packaging unit quantity.

# Cartridge fittings QSP, Quick Star


Technical data

FESTO

## Blanking plug QSPC10

Material: POM

Note on materials:  
Free of copper and PTFE  
Conforms to RoHS




Dimensions and ordering data						
D1 Ø	D2	H1	H2	Part No.	Type	PU <sup>1)</sup>
9.8	9	8.8	8.0	562243	QSPC10	10

1) Packaging unit quantity.

## Blanking plug QSPC18

Material: PA-GF

Note on materials:  
Free of copper and PTFE  
Conforms to RoHS



Dimensions and ordering data						
D1 Ø	D2	H1	H2	CRC <sup>1)</sup>	Part No.	Type
17.9	15	11.2	9.5	2	537533	QSPC18

1) Corrosion resistance class 2 to Festo standard 940 070  
Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents.

2) Packaging unit quantity.

## Product Range and Company Overview

### A Complete Suite of Automation Services

Our experienced engineers provide complete support at every stage of your development process, including: conceptualization, analysis, engineering, design, assembly, documentation, validation, and production.



**Custom Automation Components**  
Complete custom engineered solutions



**Custom Control Cabinets**  
Comprehensive engineering support and on-site services



**Complete Systems**  
Shipment, stocking and storage services

### The Broadest Range of Automation Components

With a comprehensive line of more than 30,000 automation components, Festo is capable of solving the most complex automation requirements.



**Electromechanical**  
Electromechanical actuators, motors, controllers & drives



**Pneumatics**  
Pneumatic linear and rotary actuators, valves, and air supply



**PLCs and I/O Devices**  
PLC's, operator interfaces, sensors and I/O devices

### Supporting Advanced Automation... As No One Else Can!

Festo is a leading global manufacturer of pneumatic and electromechanical systems, components and controls for industrial automation, with more than 12,000 employees in 56 national headquarters serving more than 180 countries. For more than 80 years, Festo has continuously elevated the state of manufacturing with innovations and optimized motion control solutions that deliver higher performing, more profitable automated manufacturing and processing equipment. Our dedication to the advancement of automation extends beyond technology to the education and development of current and future automation and robotics designers with simulation tools, teaching programs, and on-site services.

### Quality Assurance, ISO 9001 and ISO 14001 Certifications

Festo Corporation is committed to supply all Festo products and services that will meet or exceed our customers' requirements in product quality, delivery, customer service and satisfaction.

To meet this commitment, we strive to ensure a consistent, integrated, and systematic approach to management that will meet or exceed the requirements of the ISO 9001 standard for Quality Management and the ISO 14001 standard for Environmental Management.



© Copyright 2008, Festo Corporation. While every effort is made to ensure that all dimensions and specifications are correct, Festo cannot guarantee that publications are completely free of any error, in particular typing or printing errors. Accordingly, Festo cannot be held responsible for the same. For Liability and Warranty conditions, refer to our "Terms and Conditions of Sale", available from your local Festo office. All rights reserved. No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, electronic, mechanical, photocopying or otherwise, without the prior written permission of Festo. All technical data subject to change according to technical update.



Printed on recycled paper at New Horizon Graphic, Inc., FSC certified as an environmentally friendly printing plant.

# Festo North America

## Festo Regional Contact Center

5300 Explorer Drive  
Mississauga, Ontario L4W 5G4  
Canada

### USA Customers:

For ordering assistance,

**Call:** 1.800.99.FESTO (1.800.993.3786)

**Fax:** 1.800.96.FESTO (1.800.963.3786)

**Email:** [customer.service@us.festo.com](mailto:customer.service@us.festo.com)

For technical support,

**Call:** 1.866.GO.FESTO (1.866.463.3786)

**Fax:** 1.800.96.FESTO (1.800.963.3786)

**Email:** [product.support@us.festo.com](mailto:product.support@us.festo.com)

### Canadian Customers:

**Call:** 1.877.GO.FESTO (1.877.463.3786)

**Fax:** 1.877.FX.FESTO (1.877.393.3786)

**Email:** [festo.canada@ca.festo.com](mailto:festo.canada@ca.festo.com)

## USA Headquarters

Festo Corporation  
395 Moreland Road  
P.O. Box 18023  
Hauppauge, NY 11788, USA  
[www.festo.com/us](http://www.festo.com/us)

## USA Sales Offices

### Appleton

North 922 Tower View Drive, Suite N  
Greenville, WI 54942, USA

### Boston

120 Presidential Way, Suite 330  
Woburn, MA 01801, USA

### Chicago

1441 East Business Center Drive  
Mt. Prospect, IL 60056, USA

### Dallas

1825 Lakeway Drive, Suite 600  
Lewisville, TX 75057, USA

### Detroit – Automotive Engineering Center

2601 Cambridge Court, Suite 320  
Auburn Hills, MI 48326, USA

### New York

395 Moreland Road  
Hauppauge, NY 11788, USA

### Silicon Valley

4935 Southfront Road, Suite F  
Livermore, CA 94550, USA

## United States



**USA Headquarters, East:** Festo Corp., 395 Moreland Road, Hauppauge, NY 11788

Phone: 1.631.435.0800; Fax: 1.631.435.8026;

Email: [info@festo-usa.com](mailto:info@festo-usa.com)

[www.festo.com/us](http://www.festo.com/us)

## Canada



**Headquarters:** Festo Inc., 5300 Explorer Drive, Mississauga, Ontario L4W 5G4

Phone: 1.905.624.9000; Fax: 1.905.624.9001;

Email: [festo.canada@ca.festo.com](mailto:festo.canada@ca.festo.com)

[www.festo.ca](http://www.festo.ca)

## Mexico



**Headquarters:** Festo Pneumatic, S.A., Av. Ceylán 3, Col. Tequesquahuac,  
54020 Tlalneapantla, Edo. de México

Phone: 011 52 [55] 53 21 66 00; Fax: 011 52 [55] 53 21 66 65;

Email: [festo.mexico@mx.festo.com](mailto:festo.mexico@mx.festo.com)

[www.festo.com/mx](http://www.festo.com/mx)

## Central USA

Festo Corporation  
1441 East Business  
Center Drive  
Mt. Prospect, IL 60056, USA  
Phone: 1.847.759.2600  
Fax: 1.847.768.9480



## Western USA

Festo Corporation  
4935 Southfront Road,  
Suite F  
Livermore, CA 94550, USA  
Phone: 1.925.371.1099  
Fax: 1.925.245.1286



## Festo Worldwide

Argentina Australia Austria Belarus Belgium Brazil Bulgaria Canada Chile China Colombia Croatia Czech Republic Denmark  
Estonia Finland France Germany Great Britain Greece Hong Kong Hungary India Indonesia Iran Ireland Israel Italy Japan Latvia  
Lithuania Malaysia Mexico Netherlands New Zealand Norway Peru Philippines Poland Romania Russia Serbia Singapore  
Slovakia Slovenia South Africa South Korea Spain Sweden Switzerland Taiwan Thailand Turkey Ukraine United States Venezuela

[www.festo.com](http://www.festo.com)