

Standard cylinders DDPC, integrated displacement encoder

FESTO



Cylinders with displacement encoder

Product range overview

FESTO

Function	Type	Description
Drives	Rodless	<p>DDLI</p>  <ul style="list-style-type: none"> Without guide With contactless measuring displacement encoder Based on linear drive DGC-K Supply ports on end face System product for handling and assembly technology
	DGCI	<p>DGCI</p>  <ul style="list-style-type: none"> With guide With contactless measuring displacement encoder Based on linear drive DGC Supply ports optionally on end face or front System product for handling and assembly technology
	With piston rod	
	DNCI	<p>DNCI</p>  <ul style="list-style-type: none"> With contactless measuring displacement encoder Various piston rod variants Standards-based cylinder to ISO 15552 <p> DIN </p>
	DDPC	<p>DDPC</p>  <ul style="list-style-type: none"> With contactless measuring displacement encoder Various piston rod variants Standards-based cylinder to ISO 15552 <p> DIN </p>
	DNC/DSBC	<p>DNC/DSBC</p>  <ul style="list-style-type: none"> With attached potentiometer MLO-LWG Various piston rod variants Standards-based cylinder to ISO 15552 <p> DIN </p>
Swivel modules	Swivel modules	<p>DSMI</p>  <ul style="list-style-type: none"> Based on swivel modules DSM Integrated rotary potentiometer Compact design Wide range of mounting options

Cylinders with displacement encoder

FESTO

Product range overview

Piston Ø	Stroke/swivel angle [mm/°]	Suitable			for use as a measuring cylinder
		for positioning with CPX-CMAX	for end-position controller CPX-CMPX	SPC11	
Rodless					
25, 32, 40, 63	100, 160, 225, 300, 360, 450, 500, 600, 750, 850, 1000, 1250, 1500, 1750, 2000	■	■	■	■
18, 25, 32, 40, 63	100, 160, 225, 300, 360, 450, 500, 600, 750, 850, 1000, 1250, 1500, 1750, 2000	■	■	■	■
With piston rod					
32, 40, 50, 63	10 ... 2000	-	-	-	■
	100 ... 750	■	■	■	-
80, 100	10 ... 2000	-	-	-	■
	100 ... 750	■	■	■	-
32, 40, 50, 63, 80	100, 150, 225, 300, 360, 450, 600, 750	■	■	■	■
Swivel modules					
25, 40, 63	270	■	■	■	■

Cylinders with displacement encoder

Features

FESTO


Servopneumatic drive technology

Positioning and Soft Stop applications as an integral component of the valve terminal CPX – the modular peripheral system for decentralised automation tasks.

The modular design means that valves, digital inputs and outputs, positioning modules and end-position controllers, as appropriate to the application, can be combined in almost any way on the CPX terminal.

Advantages:

- Pneumatics and electrics – control and positioning on one platform
- Innovative positioning technology – piston rod drives, rodless drives, rotary drives
- Actuation via fieldbus
- Remote maintenance, remote diagnostics, web server, SMS and e-mail alerts are all possible via TCP/IP
- Modules can be quickly exchanged and expanded without altering the wiring



Axis controller CPX-CMAX



Free choice:

Position and force control, directly actuated or selected from one of 64 configurable position sets. If you are looking for something more: the configurable function for switching to the next set enables simple functional sequences to be realised with the axis controller CPX-CMAX. All stations are recognised as: the auto-identification function identifies each participant with its device data on the controller CPX-CMAX.

Also included:

The functional scope of the controller CPX-CMAX includes actuation of a brake or clamping unit via the proportional directional control valve VPWP. Up to 8 modules (max. 8 axes) can be operated in parallel and independently of each other. Commissioning via FCT (Festo configuration software) or via fieldbus: no programming, only configuration.

Technical data ➔ Internet: cpx-cmax

Advantages:

- Greater flexibility
- OEM friendly – commissioning also via fieldbus
- Easy installation and fast commissioning
- Cost-effective
- You program the system in your PLC environment

Cylinders with displacement encoder

FESTO

Features

End-position controller CPX-CMPX



Fast travel between the mechanical end stops of the cylinder, stopping gently and without impact in the end position.
Fast commissioning via control panel, fieldbus or handheld unit.
Improved control of downtime.
Actuation of a brake or clamping unit via the proportional directional control valve VPWP is an integral part of the controller CMPX.

Depending on the fieldbus chosen, up to 9 end-position controllers can be actuated on the CPX terminal.
All system data can be read and written via the fieldbus, including, for example, the mid positions.

Technical data → Internet: cpx-cmpx

- Advantages:
- Greater flexibility
 - OEM friendly – commissioning also via fieldbus
 - Easy installation and fast commissioning
 - Cost-effective
 - up to 30% faster cycle rates
 - significantly reduced system vibration
 - Improved work ergonomics thanks to significantly reduced noise level
 - The extended diagnostics help to reduce the service time of the machine

Proportional directional control valve VPWP



The 5/3-way proportional directional control valve for applications with Soft Stop and pneumatic positioning.
Fully digitalised – with integrated pressure sensors, with new diagnostic functions.
In sizes 4, 6, 8 and 10
Flow rate of 350, 700, 1400 and 2000 l/min.

With switching output for actuating a brake.
Coloured supply ports.
Pre-assembled cables guarantee faultless and fast connection with the controllers CPX-CMPX and CPX-CMAX.

Technical data → Internet: vpwp

- Advantages:
- Easy installation and fast commissioning
 - Reduction of system downtimes thanks to the new diagnostic options
 - With switching output for actuating a brake/clamping unit

Measuring module CPX-CMIX



Fully digital data acquisition and transmission means that pneumatic cylinders can be used as sensors.
With very high repetition accuracy and incorporating both analogue and digital measuring sensors.

Suitable for the linear drive DGCI with displacement encoder for measuring absolute values, for the piston rod drive DNCI/DDPC with incremental displacement encoder or even for a potentiometer of the type MLO.

Technical data → Internet: cpx-cmix


- Advantages:
- All process steps can be documented, which improves quality
 - An adjustable contact force (via pressure regulator) increases the precision of the "displacement sensor"
 - With displacement encoders for measuring absolute values, the actual position is immediately available after the system is switched on

Cylinders with displacement encoder

Drive options

FESTO

System with linear drive DDLI, DGCI



- [1] Controller module CPX-CMPX or CPX-CMAX
- [2] Proportional directional control valve VPWP
- [3] Linear drive DDLI, DGCI with displacement encoder
- [6] Connecting cable KVI-CP-3-...


Technical data → Internet: ddli or dgci

- Pneumatic rodless linear drive with displacement encoder, with or without recirculating ball bearing guide
- Displacement encoder with absolute and contactless measurement
- Diameters:
 - DGCI: 18 ... 63 mm
 - DDLI: 25 ... 63 mm
- Stroke: 100 ... 2000 mm in fixed lengths
- Range of applications: Soft Stop and pneumatic positioning
- Loads from 1 ... 180 kg
- No sensor interface required

Advantages:

- Complete drive unit
- DDLI for easy connection to customer's guide system
- Excellent running characteristics
- For fast and accurate positioning down to ± 0.2 mm (only with axis controller CPX-CMAX)

System with standard cylinder DNCI, DDPC



- [1] Controller module CPX-CMPX or CPX-CMAX
- [2] Proportional directional control valve VPWP
- [3] Standard cylinder DNCI, DDPC with displacement encoder
- [5] Sensor interface CASM-S-D3-R7
- [6] Connecting cable KVI-CP-3-...

Technical data → Internet: dnci

- Standard cylinder with integrated displacement encoder, conforms to DIN ISO 6432, VDMA 24 562, NF E 49 003.1 and Uni 10 290
- Displacement encoder with contactless and incremental measuring
- Diameter: 32 ... 100 mm
- Stroke: 100 ... 750 mm
- Range of applications: Soft Stop and pneumatic positioning
- Loads from 3 ... 450 kg and a matching sensor interface CASM-S-D3-R7
- Pre-assembled cables guarantee faultless and fast electrical connection

Advantages:


- Compact drive unit
- Can be used universally
- Also with guide unit
- For fast and accurate positioning up to ± 0.5 mm (only with axis controller CPX-CMAX)

Cylinders with displacement encoder

FESTO

Drive options

System with swivel module DSMI



- [1] Controller module CPX-CMPX or CPX-CMAX
- [2] Proportional directional control valve VPWP
- [3] Swivel module DSMI with displacement encoder
- [4] Sensor interface CASM-S-D2-R3
- [6] Connecting cable KVI-CP-3...
- [7] Connecting cable NEBC-P1W4-K-0,3-N-M12G5


Technical data → Internet: dsmi

- Swivel module DSMI with integrated displacement encoder
- Identical design to pneumatic swivel module DSM
- Absolute displacement encoder based on a potentiometer
- Swivel range of 0 ... 270°
- Size: 25, 40, 63
- Max. torque: 5 ... 40 Nm
- Range of applications: Soft Stop and pneumatic positioning
- Mass moments of inertia from 15 ... 6000 kgcm² and a matching sensor interface CASM-S-D2-R3
- Pre-assembled cables guarantee faultless and fast connection with the proportional directional control valve VPWP

Advantages:

- Complete drive unit, compact, can be used immediately
- High angular acceleration
- With adjustable fixed stops
- For fast and accurate positioning down to ±0.2° (only with axis controller CPX-CMAX)

System with potentiometer



- [1] Controller module CPX-CMPX or CPX-CMAX
- [2] Proportional directional control valve VPWP
- [4] Sensor interface CASM-S-D2-R3
- [6] Connecting cable KVI-CP-3...
- [7] Connecting cable NEBC-P1W4-K-0,3-N-M12G5
- [8] Connecting cable NEBC-A1W3-K-0,4-N-M12G5

Technical data → Internet: casm

- Attachable potentiometers with absolute measurement, with high degree of protection
- With connecting rod or moment compensator
- Measuring range:
Connecting rod: 100 ... 750 mm
Moment compensator: 225 ... 2000 mm
- Pre-assembled cables guarantee faultless and fast connection with the sensor interface CASM
- Range of applications: Soft Stop and pneumatic positioning with cylinder Ø 25 ... 80 mm, e.g. DNC or DSBC
- Loads from 1 ... 300 kg

Advantages:

- Easy installation and fast commissioning
- Cost-effective
- Can also be used in harsh ambient conditions
- Variety of drives: CPX-CMPX and CPX-CMAX also support cylinders with external displacement encoder

Cylinders with displacement encoder

Drive options

FESTO

System components for Soft Stop systems with end-position controller CPX-CMPX						➔ Page/ Internet
	Linear drive DDLI/DGCI	Standard cylinder DNCI, DDPC	Swivel module DSMI	Displacement encoder		
End-position controller CPX-CMPX	■	■	■	■	■	cmpx
Prop. directional control valve VPWP	■	■	■	■	■	vpwp
Sensor interface CASM-S-D2-R3	-	-	■	■	-	casm
Sensor interface CASM-S-D3-R7	-	■	-	-	-	casm
Connecting cable KVI-CP-3-...	■	■	■	■	■	kvi
Connecting cable NEBC-P1W4-...	-	-	■	■ / -	-	nebc
Connecting cable NEBC-A1W3-...	-	-	-	- / ■	-	nebc
Connecting cable NEBP-M16W6-...	-	-	-	-	■	vpwp

System components for pneumatic positioning systems with axis controller CPX-CMAX						➔ Page/ Internet
	Linear drive DDLI/DGCI	Standard cylinder DNCI, DDPC	Swivel module DSMI	Displacement encoder		
Axis controller CPX-CMAX	■	■	■	■	■	cmax
Prop. directional control valve VPWP	■	■	■	■	■	vpwp
Sensor interface CASM-S-D2-R3	-	-	■	■	-	casm
Sensor interface CASM-S-D3-R7	-	■	-	-	-	casm
Connecting cable KVI-CP-3-...	■	■	■	■	■	kvi
Connecting cable NEBC-P1W4-...	-	-	■	■ / -	-	nebc
Connecting cable NEBC-A1W3-...	-	-	-	- / ■	-	nebc
Connecting cable NEBP-M16W6-...	-	-	-	-	■	vpwp

System components for measuring cylinders with measuring module CPX-CMIX						➔ Page/ Internet
	Linear drive DDLI/DGCI	Standard cylinder DNCI, DDPC	Swivel module DSMI	Displacement encoder		
Measuring module CPX-CMIX-M1-1	■	■	■	■	■	cmix
Sensor interface CASM-S-D2-R3	-	-	■	■	-	casm
Sensor interface CASM-S-D3-R7	-	■	-	-	-	casm
Connecting cable KVI-CP-3-...	(■) ¹⁾	■	■	■	(■)	kvi
Connecting cable NEBC-P1W4-...	-	-	■	■ / -	-	nebc
Connecting cable NEBC-A1W3-...	-	-	-	- / ■	-	nebc
Connecting cable NEBP-M16W6-...	-	-	-	-	■	vpwp

1) As an extension

Cylinders with displacement encoder

FESTO

Overview

Individual components for positioning

With end-position controller SPC11

→ Internet: spc11



[1]

- [1] End-position controller SPC11-INC
- [2] Proportional directional control valve MPYE
- [3] Standard cylinder DNCI, DDPC
- [4] Connecting cable KMPYE-AIF-...



[4]

[2]



[3]

Individual components for use as a measuring cylinder

With measuring module CPX-CMIX

→ Internet: cmix

With measured-value transducer DADE

→ Internet: dade



[1]



[4]



[2]



[5]



[3]

- [1] Measuring module CPX-CMIX
- [2] Sensor interface
CASM-S-D3-R7
- [3] Standard cylinder DNCI, DDPC



[6]




[3]

- [3] Standard cylinder DNCI, DDPC
- [4] Operator unit FED
- [5] PLC controller FEC
- [6] Measured-value transducer
DADE

Standard cylinders DDPC, integrated displacement encoder

Peripherals overview

FESTO



Note

If the drive DDPC is used without an end-position controller CPX-CMPX, SPC11 or axis controller CPX-CMAX, e.g. as a measuring cylinder, then the standard accessories for the drive DNC can be used.

Standard cylinders DDPC, integrated displacement encoder

FESTO

Peripherals overview

Accessories		
Type	Description	➔ Page/Internet
[1] Rod eye SGS	With spherical bearing	22
[2] Foot mounting HNC	For mounting the drive on the bearing and end cap	22
[3] Flange mounting FNC	For mounting the drive on the bearing and end cap	22
[4] Guide unit ¹⁾ FENG-KF	For protecting against rotation at high torque loads	20
[5] Trunnion support LNZG	For securing the trunnion mounting kit DAMT	24
[6] Trunnion mounting kit DAMT	For swivelling movements of the drive	23
[7] Slot cover ABP-5-S	For protecting against the ingress of dirt	24
[8] Proximity sensor SME/SMT-8	For additional sensing of the piston position, can be ordered optionally, only in combination with the order code A in the modular products section for the drive	sm
[9] Sensor interface CASM	Used to connect pneumatic drives with analogue/incremental displacement encoder to a position controller CPX-CMAX or CPX-CMPX	casm
[10] Push-in fitting QS	For connecting compressed air tubing with standard O.D.	24

1) Guide unit FENG-KF must be attached to the piston rod in a way that eliminates backlash



Note

Allocation table of drives and associated proportional directional control valves ➔ 25

Standard cylinders DDPC, integrated displacement encoder

FESTO

Type codes


DDPC	Standard cylinder	DDPC - Q - [] - [] - [] - [] - [] - P - A - []
Q	With protection against rotation	
Piston Ø [mm]		
Stroke [mm]		
Guide unit		
-	None	
D	Attached	
Clamping unit		
-	None	
C	Attached	
Piston rod type		
-	At one end	
T	Through piston rod	
Cushioning		
P	Elastic cushioning rings/pads at both ends	
Position sensing		
A	Via proximity sensor	
Piston rod extension		
-	None	
...E	1 ... 500 mm	

Standard cylinders DDPC, integrated displacement encoder

FESTO

Technical data

Function



- - Diameter
80 and 100 mm
- - Stroke length
10 ... 2000 mm



General technical data

Piston Ø	80	100
Based on standard	ISO 15552	
Design	Piston	
	Piston rod	
	Profile barrel	
Mode of operation	Double-acting	
Guide ¹⁾	Guide rod with yoke, with ball bearing guide	
Protection against rotation	Square piston rod	
Mounting position	Any	
Type of mounting	Via accessories	
Cushioning	Elastic cushioning rings/pads at both ends	
Position sensing	Integrated displacement encoder	
	Via proximity sensor ²⁾	
Measuring principle (displacement encoder)	Encoder, non-contacting and relative measurement	
Pneumatic connection	G 3/8	G 1/2
Stroke		
DDPC-... ³⁾	[mm]	10 ... 2000
DDPC-...-D	[mm]	100 ... 500
Extended piston rod	[mm]	1 ... 500

1) Guide unit FENG-KF can be ordered via the modular product system (feature D) and is supplied attached. The maximum stroke is restricted.

2) Not included in the scope of delivery, can be ordered as an option

3) Can only be used without restriction as a positioning drive in the range from 100 ... 750 mm.

Note stroke reduction in combination with CPX-CMAX

Operating and environmental conditions

Operating pressure	[bar]	4 ... 12
Operating pressure ¹⁾	[bar]	4 ... 8
Operating medium ²⁾		Compressed air to ISO 8573-1:2010 [6:4:4]
Note on operating/pilot medium		Operation with lubricated medium not possible
		Pressure dew point 10 °C below ambient/medium temperature
Ambient temperature ³⁾	[°C]	-20 ... +80
Vibration resistance to DIN/IEC 68 Part 2-6		Severity level 2
Continuous shock resistance to DIN/IEC 68 Part 2-82		Severity level 2
CE mark (see declaration of conformity) ⁴⁾		To EU EMC Directive
Corrosion resistance class CRC ⁵⁾		1

1) Only applies to applications with end-position controller CPX-CMPX, SPC11 and axis controller CPX-CMAX

2) Characteristic values contingent on the proportional directional control valve VPWP, MPYE

3) Note operating range of proximity sensors

4) For information about the applicability of the component see the manufacturer's EC declaration of conformity at: www.festo.com/sp → User documentation.

If the component is subject to restrictions on usage in residential, office or commercial environments or small businesses, further measures to reduce the emitted interference may be necessary.

5) Corrosion resistance class CRC 1 to Festo standard FN 940070

Low corrosion stress. For dry indoor applications or transport and storage protection. Also applies to parts behind covers, in the non-visible interior area, and parts which are covered in the application (e.g. drive trunnions).

Standard cylinders DDPC, integrated displacement encoder

FESTO

Technical data

Forces [N] and impact energy [Nm]

Piston Ø	80	100
Theoretical force at 6 bar, advancing	3016	4712
Theoretical force at 6 bar, retracting	2721	4418
Impact energy at the end positions	1.8	2.5

Permissible impact velocity:

$$v_{\text{perm.}} = \sqrt{\frac{2 \times E_{\text{perm.}}}{m_{\text{dead}} + m_{\text{load}}}}$$

$v_{\text{perm.}}$ Permissible impact velocity
 $E_{\text{perm.}}$ Max. impact energy
 m_{dead} Moving load (drive)
 m_{load} Moving effective load

Maximum permissible load:

$$m_{\text{load}} = \frac{2 \times E_{\text{perm.}}}{v^2} - m_{\text{dead}}$$

-  Note

These specifications represent the maximum values that can be achieved. Note the maximum permissible impact energy.

Positioning characteristics with axis controller CPX-CMAX

Piston Ø	80	100
Stroke [mm]	100 ... 750	
Mounting position	Any	
Resolution [mm]	0.01	
Repetition accuracy [mm]	$\leq \pm 0.5$	
Min. load, horizontal [kg]	20	32
Max. load, horizontal [kg]	300	450
Min. load, vertical ¹⁾ [kg]	20	32
Max. load, vertical ¹⁾ [kg]	100	150
Min. travel speed [m/s]	0.05	
Max. travel speed [m/s]	1	0.7
Typical positioning time, long stroke ²⁾ [s]	0.88/1.02	0.95/1.10
Typical positioning time, short stroke ³⁾ [s]	0.77/0.95	0.80/1.32
Min. positioning stroke ⁴⁾ [%]	≤ 3	
Stroke reduction ⁵⁾ [mm]	15	
Recommended proportional directional control valve		
For CPX-CMAX	→ 25	

1) Only in combination with external guide

2) At 6 bar, horizontal mounting position, DDPC-XX-500, 400 mm positioning travel at min./max. load

3) At 6 bar, horizontal mounting position, DDPC-XX-500, 200 mm positioning travel at min./max. load

4) Refers to the cylinder stroke, but not more than 10 mm

5) The stroke reduction must be maintained on each side of the drive, the max. positionable stroke is therefore: stroke – 2x stroke reduction

Force control characteristics with axis controller CPX-CMAX

Piston Ø	80	100
Stroke [mm]	100 ... 750	
Mounting position	Any	
Max. controllable force ¹⁾ [N]	2710/2440	4240/3975
Typical friction forces ²⁾ [N]	140	160
Repetition accuracy [%] pressure regulation ³⁾⁴⁾	< ±2	

1) Advancing/retracting at 6 bar

2) These values can fluctuate greatly from cylinder to cylinder and are not guaranteed.

These friction forces must also be taken into consideration when using an external guide or when the cylinder is moving other components subject to friction

3) This value defines the repetition accuracy with which the internal differential pressure in the cylinder is controlled and refers to the maximum controllable force (the internal differential pressure corresponds to the prescribed force setpoint value)

4) The effective force at the workpiece and its accuracy depends largely on the friction in the system as well as the repetition accuracy of the internal control system. Note that friction forces always work against the direction of movement of the piston. The following formula can be used as a rule of thumb for the force F at the workpiece:

$$F = F_{\text{setpoint}} \pm F_{\text{friction forces}} \pm \text{internal repetition accuracy}$$

Standard cylinders DDPC, integrated displacement encoder

FESTO

Technical data

Positioning characteristics with Soft Stop end-position controller CPX-CMPX, SPC11

Piston Ø	80	100
Stroke [mm]	100 ... 750	
Mounting position	Any	
Repetition accuracy [mm]	±2	
Min. load, horizontal [kg]	20	32
Max. load, horizontal [kg]	300	450
Min. load, vertical ¹⁾ [kg]	20	32
Max. load, vertical ¹⁾ [kg]	100	150
Travel time [s]	→ Soft Stop sizing software: → www.festo.com	
Recommended proportional directional control valve		
For CPX-CMPX	→ 25	
For SPC11	→ 25	


1) Only in combination with external guide

Electrical data – Displacement encoder

Output signal	Analogue
Independent linearity	
Strokes up to 500 mm [mm]	< ±0.08
Strokes up to 1000 mm [mm]	< ±0.09
Strokes above 1000 mm [mm]	< ±0.11
Max. travel speed [m/s]	1.5
Protection class	IP65
CE marking (see declaration of conformity)	In accordance with EU EMC Directive ¹⁾
Max. permitted magnetic disruption field ²⁾ [kA/m]	10
Electrical connection	Cable with 8-pin plug, round type M12
Cable length [m]	1.5

- 1) For information about the applicability of the component see the manufacturer's EC declaration of conformity at: www.festo.com/sp → User documentation.
If the component is subject to restrictions on usage in residential, office or commercial environments or small businesses, further measures to reduce the emitted interference may be necessary.
- 2) At 100 mm interval

Pin assignment of plug



Pin	Function	Colour
1	5 V	Black
2	GND	Brown
3	sin+	Red
4	sin-	Orange
5	cos-	Green
6	cos+	Yellow
7	Screening	Screened
8	n.c.	-

Standard cylinders DDPC, integrated displacement encoder


FESTO

Technical data

Weight [g]		
Piston Ø	80	100
DDPC-...		
Basic weight with 0 mm stroke	3053	4330
Additional weight per 10 mm stroke	87	95
Moving load with 0 mm stroke	804	994
Additional weight per 10 mm stroke	31	31
DDPC-...-T – Through piston rod		
Basic weight with 0 mm stroke	3537	5019
Additional weight per 10 mm stroke	127	134
Moving load with 0 mm stroke	1247	1467
Additional weight per 10 mm stroke	70	70
DDPC-...-E – Additional weight with piston rod extension		
Additional weight per 10 mm extension	31	31
DDPC-...-C – Additional weight with clamping unit		
Additional weight	2046	2829
DDPC-...-D – Additional weight with guide unit		
Basic weight with 0 mm stroke	10430	12990
Additional weight per 10 mm stroke	80	80

Materials

Sectional view



Standard cylinder

[1] End cap	Wrought aluminium alloy
[2] Piston rod	High-alloy steel
[3] Cylinder barrel	Wrought aluminium alloy
- Seals	NBR, polyurethane
Note on materials	Free of copper and PTFE RoHS-compliant

Standard cylinders DDPC, integrated displacement encoder

FESTO

Technical data

Torques and lateral forces


Max. torque for protection against rotation

Dynamic $\leq 3 \text{ Nm}$
Static $\leq 5 \text{ Nm}$

An external guide unit FENG-KF is recommended with higher torque loads.
The guide unit is supplied attached.

The permissible static and dynamic characteristic load values with and without attached guide

➔ Internet: feng




Mounting conditions

When mounting a drive A with magnet (for position sensing) next to a standard cylinder DDPC, the following conditions must be observed:

- X Minimum distance between the drives
- Y Offset between the drives on the bearing cap


Parallel assembly

If the offset Y = 0 mm, the drives can be assembled directly next to one another.




Offset assembly, cable outlet between the drives

If the offset is Y > 0 mm and the cable outlet is between the drives, a distance of X > 70 mm must be observed.



Offset assembly, cable outlet upwards or downwards

If the offset is Y > 0 mm and the cable outlet is up or down, a distance of X > 60 mm must be observed.



Standard cylinders DDPC, integrated displacement encoder


FESTO

Technical data

Dimensions

DDPC-...

Download CAD data → www.festo.com



\emptyset [mm]	AM	B \emptyset d11	BG	D7 \emptyset	D8 \emptyset	D9	E	EE	G
80	40	45	17	3.7	14	M12	93	G $\frac{3}{8}$	43
100	40	55	17	3.7	14	M12	110	G $\frac{1}{2}$	48

\emptyset [mm]	KK	L1	L2	L9	L17	MM \emptyset	PL	RT	T1
80	M20x1.5	34.2	128	20	45.7	20	30	M10	8
100	M20x1.5	38	138	21.5	45.7	20	31.5	M10	8

\emptyset [mm]	TG	VA	VD	WH	ZJ	=C 1	=C 2	=C 3
80	72	4	16.7	46	174	22	30	6
100	89	4	20.5	51	189	22	30	6

Standard cylinders DDPC, integrated displacement encoder


FESTO

Technical data


Dimensions

DDPC-...-T – Through piston rod


Download CAD data ➔ www.festo.com



DDPC-...-CT – Through piston rod with clamping unit



DDPC-...-...E – Extended piston rod



∅	A2	D1 ∅ f9	D2	H1	L3	L5
[mm]	max.					
80	500	48	G1/8	165.5	95	31.5
100	500	48	G1/8	174	98	31

∅	VD	WH	ZJ		ZM	
			DDPC-...-T	DDPC-...-CT	DDPC-...-T	DDPC-...-CT
80	16.7	46	174	269	222	317
100	20.5	51	189	287	240	338

Standard cylinders DDPC, integrated displacement encoder




FESTO

Technical data

Dimensions

DDPC-...-D

Download CAD data → www.festo.com



[1] Standard cylinder DDPC
[2] Compensating coupling

[3] Users can drill additional
mounting holes as required

+ = plus stroke length

\emptyset [mm]	B1	B2	B3	B4	D1	D2	D3	D4	D6
80	-0.3	105	100	148	106	78	M10	18	11
100	-0.3	130	120	172	131	78	M10	18	11
									25

\emptyset [mm]	H1	H2	H3	H4	KK	L1	L2	L3	L4
80	-0.5	189	180	130	130	M20x1.5	258	111	194
100	-0.5	213	200	150	150	M20x1.5	263	116	215
							+10	138	220

\emptyset [mm]	L5	L6	L9	L10	L11	L12	L13	L14	=C1
80	40	128	32	20	21	72	11	20	27
100	40	128	32	20	24.5	89	11	20	27

Standard cylinders DDPC, integrated displacement encoder

FESTO

Ordering data – Modular products

Ordering table		Conditions	Code	Enter code
Piston Ø	80	100		
M Module No.	1677705	1691433		
Function	Standard cylinder with integrated displacement encoder		DDPC	DDPC
Protection against rotation	With protection against rotation		-Q	-Q
Piston Ø [mm]	80	100		-...
Stroke [mm]	10 ... 2000		[1]	-...
O Guide unit	None			
	Attached		-D	
O Clamping unit	None			
	Attached	[2]	-C	
O Piston rod type	At one end			
	Through piston rod		T	
M Cushioning	Elastic cushioning rings/pads at both ends		-P	-P
O Position sensing	Via proximity sensor		A	A
O Piston rod extension	None			
	[mm] 1 ... 500			-...E

[1] -... Can only be used without restriction as a positioning drive in the range from 100 ... 750 mm
[2] C Only available with T

Transfer order code

DDPC - **Q** - - - - - - - **P** - **A** -

Standard cylinders DDPC, integrated displacement encoder

Accessories


FESTO

Foot mounting HNC

Materials:

Galvanised steel

Free of copper and PTFE



Dimensions and ordering data

For Ø [mm]	AB Ø	AH	AO	AT	AU	SA	
						DDPC-...	DDPC-...-C
80	12	63	15	6	41	276	371
100	14.5	71	17.5	6	41	220	318

For Ø [mm]	TR	US	XA		XS	CRC ¹⁾ [g]	Weight	Part No.	Type
			DDPC-...	DDPC-...-C					
80	63	93	281	376	81	2	829	174373	HNC-80
100	75	110	230	328	86	2	1009	174374	HNC-100

1) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.


Flange mounting FNC

Materials:

FNC: Galvanised steel

Free of copper and PTFE

RoHS-compliant



Dimensions and ordering data

For Ø [mm]	E	FB Ø	MF	R	TF	UF	W	ZF		CRC ¹⁾ [g]	Weight	Part No.	Type
								DDPC-...	DDPC-...-C				
80	93	12	16	63	126	150	30	256	351	1	1495	174380	FNC-80
100	110	14	16	75	150	175	35	205	303	1	2041	174381	FNC-100

1) Corrosion resistance class CRC 1 to Festo standard FN 940070

Low corrosion stress. For dry indoor applications or transport and storage protection. Also applies to parts behind covers, in the non-visible interior area, and parts which are covered in the application (e.g. drive trunnions).

Standard cylinders DDPC, integrated displacement encoder

FESTO

Accessories

Rod eye SGS


Scope of delivery:

1 rod eye, 1 hex nut to DIN 439

Materials:

Galvanised steel

RoHS-compliant



Dimensions and ordering data

For Ø [mm]	AV	B1	CE	CN Ø H7	D1 Ø	EF ±0.5	EN	EU	Z	=C1	=C2	CRC ¹⁾	Weight [g]	Part No.	Type
M20x1.5	33 -2	10	77	20	34	25	25	18	15	30	30	2	464	9264	SGS-M20x1,5

1) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.

Trunnion mounting kit DAMT


The mounting kit can be attached at any position along the profile barrel of the cylinder.

Materials:

Galvanised steel

Free of copper and PTFE

RoHS-compliant



Dimensions and ordering data

For Ø [mm]	B1	C2	C3	TD Ø e9	TL	TM	UW	XG	
								DDPC-... DDPC-...-C	DDPC-... DDPC-...-C
80	44	136	156	20	20	110	130	111	206
100	48	164	189	25	25	132	145	123	221

For Ø [mm]	XJ		XV		Max. tightening torque [Nm]	CRC ¹⁾	Weight [g]	Part No.	Type
	DDPC-... DDPC-...-C	DDPC-... DDPC-...-C	DDPC-... DDPC-...-C	DDPC-... DDPC-...-C					
80	175	270	143	238	28+2	1	1494	163529	DAMT-V1-80-A
100	117	215	120	218	28+2	1	2095	163530	DAMT-V1-100-A

1) Corrosion resistance class CRC 1 to Festo standard FN 940070

Low corrosion stress. For dry indoor applications or transport and storage protection. Also applies to parts behind covers, in the non-visible interior area, and parts which are covered in the application (e.g. drive trunnions).

Standard cylinders DDPC, integrated displacement encoder

FESTO

Accessories

Trunnion support LNZG



Materials:

Trunnion support: Anodised aluminium

Plain bearing: Plastic

Free of copper and PTFE

RoHS-compliant




Dimensions and ordering data

For Ø [mm]	CR Ø D11	DA Ø H13	FK Ø ±0.1	FN	FS	H1	HB Ø H13	KE	NH	TH	UL	CRC ¹⁾	Weight [g]	Part No.	Type
80	20	18	20	40	13	20	11	11	23	42	65	2	178	32961	LNZG-63/80
100	25	20	25	50	16	24.5	14	13	28.5	50	75	2	306	32962	LNZG-100/125


1) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.

Ordering data

For Ø	Comment	Part No.	Type	PU ¹⁾
Slot cover				
	80, 100 Every 0.5 m	151680	ABP-5-S	2


1) Packaging unit




Standard cylinders DDPC, integrated displacement encoder

FESTO


Accessories

Ordering data – Proportional directional control valves and push-in fittings					
	For Ø [mm]	Stroke [mm]	Proportional directional control valve Technical data → Internet: vpwp	Push-in fitting for DDPC Technical data → Internet: quick star	
			Part No.	Type	Part No. Type PU ¹⁾
For applications with axis controller CPX-CMAX					
	80	100 ... 200	550171 VPWP-6-L-5-Q8-10-E...	186100 QS-G ^{3/8} -8	10
		201 ... 450	550172 VPWP-8-L-5-Q10-10-E...	186102 QS-G ^{3/8} -10	
		451 ... 750	1552544 VPWP-10-L-5-Q-10-E-G-EX1	186103 QS-G ^{3/8} -12	
	100	100 ... 120	550171 VPWP-6-L-5-Q8-10-E...	186104 QS-G ^{1/2} -12 ²⁾	1
		121 ... 330	550172 VPWP-8-L-5-Q10-10-E...	186104 QS-G ^{1/2} -12 ³⁾	
		331 ... 750	1552544 VPWP-10-L-5-Q-10-E-G-EX1	186104 QS-G ^{1/2} -12	

- 1) Packaging unit
- 2) With additional reduction from Ø 12 to Ø 8, with push-in connector QS-12H-8 (part number 130624)
- 3) With additional reduction from Ø 12 to Ø 10, with push-in connector QS-12H-10 (part number 153044)

Ordering data – Proportional directional control valves and push-in fittings					
	For Ø [mm]	Stroke [mm]	Proportional directional control valve Technical data → Internet: vpwp	Push-in fitting for DDPC Technical data → Internet: quick star	
			Part No.	Type	Part No. Type PU ¹⁾
For applications with Soft Stop end-position controller CPX-CMPX					
	80	100 ... 125	550170 VPWP-4-L-5-Q8-10-E...	186100 QS-G ^{3/8} -8	10
		126 ... 160	550171 VPWP-6-L-5-Q8-10-E...	186100 QS-G ^{3/8} -8	
		161 ... 400	550172 VPWP-8-L-5-Q10-10-E...	186102 QS-G ^{3/8} -10	
	100	401 ... 500	1552544 VPWP-10-L-5-Q-10-E-G-EX1	186103 QS-G ^{3/8} -12	1
		100 ... 150	550171 VPWP-6-L-5-Q8-10-E...	186104 QS-G ^{1/2} -12 ²⁾	
		151 ... 350	550172 VPWP-8-L-5-Q10-10-E...	186104 QS-G ^{1/2} -12 ³⁾	
		351 ... 500	1552544 VPWP-10-L-5-Q-10-E-G-EX1	186104 QS-G ^{1/2} -12	

- 1) Packaging unit
- 2) With additional reduction from Ø 12 to Ø 8, with push-in connector QS-12H-8 (part number 130624)
- 3) With additional reduction from Ø 12 to Ø 10, with push-in connector QS-12H-10 (part number 153044)


Ordering data – Proportional directional control valves and push-in fittings					
	For Ø [mm]	Stroke [mm]	Proportional directional control valve Technical data → Internet: mpye	Push-in fitting for DDPC Technical data → Internet: quick star	
			Part No.	Type	Part No. Type PU ¹⁾
For applications with Soft Stop end-position controller SPC11					
	80	100 ... 125	151692 MPYE-5-1/8-LF-010-B	186100 QS-G ^{3/8} -8	10
		126 ... 160	151693 MPYE-5-1/8-HF-010-B	186100 QS-G ^{3/8} -8	
		161 ... 400	151694 MPYE-5-1/4-010-B	186102 QS-G ^{3/8} -10	
	100	401 ... 500	151695 MPYE-5-3/8-010-B	186103 QS-G ^{3/8} -12	1
		100 ... 150	151693 MPYE-5-1/8-HF-010-B	186104 QS-G ^{1/2} -12 ²⁾	
		151 ... 350	151694 MPYE-5-1/4-010-B	186104 QS-G ^{1/2} -12 ³⁾	
		351 ... 500	151695 MPYE-5-3/8-010-B	186104 QS-G ^{1/2} -12	

- 1) Packaging unit
- 2) With additional reduction from Ø 12 to Ø 8, with push-in connector QS-12H-8 (part number 130624)
- 3) With additional reduction from Ø 12 to Ø 10, with push-in connector QS-12H-10 (part number 153044)

Product Range and Company Overview

A Complete Suite and Company Overview

Our experienced engineers provide complete support at every stage of your development process, including: conceptualization, analysis, engineering, design, assembly, documentation, validation, and production.



Custom Automation Components
Complete custom engineered solutions



Custom Control Cabinets
Comprehensive engineering support and on-site services



Complete Systems
Shipment, stocking and storage services

The Broadest Range of Automation Components

With a comprehensive line of more than 30,000 automation components, Festo is capable of solving the most complex automation requirements.



Electromechanical
Electromechanical actuators, motors, controllers & drivers



Pneumatics
Pneumatic linear and rotary actuators, valves, and air supply



PLCs and I/O Devices
PLC's, operator interfaces, sensors and I/O devices

Supporting Advanced Automation... As No One Else Can!

Festo is a leading global manufacturer of pneumatic and electromechanical systems, components and controls for industrial automation, with more than 16,000 employees in 60 national headquarters serving more than 180 countries. For more than 80 years, Festo has continuously elevated the state of manufacturing with innovations and optimized motion control solutions that deliver higher performing, more profitable automated manufacturing and processing equipment. Our dedication to the advancement of automation extends beyond technology to the education and development of current and future automation and robotics designers with simulation tools, teaching programs, and on-site services.

Quality Assurance, ISO 9001 and ISO 14001 Certifications

Festo Corporation is committed to supply all Festo products and services that will meet or exceed our customers' requirements in product quality, delivery, customer service and satisfaction.

To meet this commitment, we strive to ensure a consistent, integrated, and systematic approach to management that will meet or exceed the requirements of the ISO 9001 standard for Quality Management and the ISO 14001 standard for Environmental Management.



© Copyright 2013, Festo Corporation. While every effort is made to ensure that all dimensions and specifications are correct, Festo cannot guarantee that publications are completely free of any error, in particular typing or printing errors. Accordingly, Festo cannot be held responsible for the same. For Liability and Warranty conditions, refer to our "Terms and Conditions of Sale", available from your local Festo office. All rights reserved. No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, electronic, mechanical, photocopying or otherwise, without the prior written permission of Festo. All technical data subject to change according to technical update.



Printed on recycled paper at New Horizon Graphic, Inc., FSC certified as an environmental friendly printing plant.

Festo North America



**[1] Festo Canada
Headquarters**
Festo Inc.
5300 Explorer Drive
Mississauga, ON
L4W 5G4

[2] Montréal
5600, Trans-Canada
Pointe-Claire, QC
H9R 1B6

[3] Québec City
2930, rue Watt#117
Québec, QC
G1X 4G3



**[4] Festo United States
Headquarters**
Festo Corporation
395 Moreland Road
Hauppauge, NY
11788

[5] Appleton
North 922 Tower View Drive, Suite N
Greenville, WI
54942

[7] Detroit
1441 West Long Lake Road
Troy, MI
48098

[6] Chicago
85 W Algonquin - Suite 340
Arlington Heights, IL
60005

[8] Silicon Valley
4935 Southfront Road, Suite F
Livermore, CA
94550

Festo Regional Contact Center

Canadian Customers

Commercial Support:
Tel: 1 877 GO FESTO (1 877 463 3786)
Fax: 1 877 FX FESTO (1 877 393 3786)
Email: festo.canada@ca.festo.com

Technical Support:
Tel:1 866 GO FESTO (1 866 463 3786)
Fax:1 877 FX FESTO(1 877 393 3786)
Email: technical.support@ca.festo.com

USA Customers

Commercial Support:
Tel:1 800 99 FESTO (1 800 993 3786)
Fax:1 800 96 FESTO (1 800 963 3786)
Email: customer.service@us.festo.com

Technical Support:
Tel:1 866 GO FESTO (1 866 463 3786)
Fax:1800 96 FESTO(1 800 963 3786)
Email: product.support@us.festo.com