

Pneumatic valves VUWS/valve manifold VTUS

FESTO



Pneumatic valves VUWS/valve manifold VTUS

Key features – Pneumatics

FESTO



Innovative

- A reliable, heavy-duty valve with a long service life
- Flow rate up to 2300 l/min
- Low-cost universal valve with no performance limitations
- Wide range of valve functions
- Several sizes

Versatile

- In-line valves can be used as individual valves or manifold valves
- Variable pressure zones
- Wide range of mounting options

Reliable

- Ergonomic, reliable operation
- Durable thanks to tried and tested piston spools
- Reliable servicing thanks to valves that can be replaced quickly and easily

Easy to install

- Pre-assembled units on rails
- Individual valves assembled ready for installation
- Supply manifolds for mounting on one or both sides
- Secure mounting on wall or H-rail

Valve manifold selection

Configurator

The appropriate valve manifold VTUS can be chosen quickly and easily using the online catalogue. This includes a convenient configurator, making it much easier to order the right product.

The valve manifold is fully assembled according to your order specification and individually checked. This reduces assembly and installation time to a minimum.

Ordering system for valve manifold VTUS

➔ Internet: [vtus](#)

2D/3D CAD data



The CAD data for a configured valve manifold can be retrieved online using the configurator.

Pneumatic valves VUWS/valve manifold VTUS


Key features

Pneumatic valves VUWS


In-line valve VUWS as individual valve



Valve manifold VTUS



Equipment options



- Size 20 (21 mm)
- Size 25 (26.5 mm)
- Size 30 (31 mm)
- 3/2-, 5/2- and 5/3-way valves
- In-line valves

All valves are equipped with a piston spool and patented sealing system to facilitate efficient sealing, a broad pressure range and a long service life. Pneumatic valves VUWS have a sturdy design that enables them to be used in harsh environments.

Pneumatic valves VUWS are extremely well suited for controlling cylinders or compressed air networks for easy clamping and locking processes in semi-automatic assembly and manufacturing.

Valve functions

3/2-way valve, normal position open, monostable:
 • External pneumatic spring connection (M32U-E)
 • Reset via pneumatic/mechanical spring
 • Direction of flow reversible with return via mechanical spring or external pneumatic spring connection
 • Dual-pressure operation possible
 • If the external pneumatic spring connection is used as signal input, the result is a dominant bistable valve

3/2-way valve, normal position closed, monostable:
 • External pneumatic spring connection (M32C-E)
 • Reset via pneumatic/mechanical spring
 • Direction of flow reversible with return via mechanical spring or external pneumatic spring connection
 • Dual-pressure operation possible
 • If the external pneumatic spring connection is used as signal input, the result is a dominant bistable valve

5/2-way valve, monostable:
 • External pneumatic spring connection (M52-E)
 • Reset via pneumatic/mechanical spring
 • Direction of flow reversible with return via mechanical spring or external pneumatic spring connection

5/2-way valve, bistable:
 • Direction of flow reversible
 • Can also be used as 3/2-way valve by closing one outlet port

5/3-way valve, mid-position exhausted, pressurised or closed:
 • Direction of flow reversible
 • Reset via mechanical spring

Key features

• A maximum of 16 valve positions can be configured in the standard version
 • A maximum of 12 valve positions can be configured in the compact version

• Valve positions 2 ... 10 can be configured in increments of 1, valve positions 10 ... 16 in increments of 2
 • Manifold block with a maximum of 10 valve positions

• Extension module with 2 valve positions
 • Supply manifold with a maximum of 10 valve positions

• Creation of pressure zones (maximum 9 pressure zones in the case of a valve manifold with 16 valve positions)

Design

Valve replacement

Each valve is attached to the manifold block using two screws. The appropriate seal is mounted on the valve.

This means that the valves can be easily replaced.

Extension

Valve positions covered with blanking plates can be replaced with valves at a later date. The dimensions, mounting points and existing pneumatic installations

remain unchanged. For the standard manifold block, extension modules with 2 valve positions are available.

- New

Size 30


Pneumatic valves VUWS/valve manifold VTUS

FESTO

Key features


Standard manifold block

For 3/2-way valves



- Connection:
Size 20: G3/8
Size 25: G1/2
Size 30: G3/4
- Maximum 10 valve positions


For 5/2- and 5/3-way valves



- Connection:
Size 20: G3/8
Size 25: G1/2
Size 30: G3/4
- Maximum 10 valve positions


Extension for standard manifold block

For 3/2-way valves



- Connection:
Size 20: G3/8
Size 25: G1/2
Size 30: G3/4
- Maximum two valve positions


For 5/2- and 5/3-way valves



- Connection:
Size 20: G3/8
Size 25: G1/2
Size 30: G3/4
- Maximum two valve positions


Compact manifold block

For 3/2-way valves



- Connection:
Size 20: G1/4
Size 25: G3/8
Size 30: G1/2
- Maximum 10 valve positions


For 5/2- and 5/3-way valves



- Connection:
Size 20: G1/4
Size 25: G3/8
Size 30: G1/2
- Maximum 10 valve positions


Supply manifold

Mounting on both sides




- Connection:
Size 20: G3/8
Size 25: G1/2
Size 30: G3/4
- Maximum 10 valve positions

Mounting on one side



- Connection:
Size 20: G3/8
Size 25: G1/2
Size 30: G3/4
- Maximum 4 valve positions

Blanking plate for unused valve position



For covering unused valve positions

Supply plate



For additional air supply and exhaust via a valve position

Separator for pressure zones



For creating pressure zones (maximum 9 pressure zones permitted)

Note

A filter must be installed upstream of valves operated in vacuum mode. This prevents any foreign matter in

the intake air getting into the valve (e.g. when operating a suction cup).

Pneumatic valves VUWS/valve manifold VTUS

Key features – Pneumatics

Creating pressure zones and separating exhaust air

Compressed air is supplied and exhausted via the manifold block/supply manifold and via supply plates.

The position of the supply plates and duct separations can be freely selected with the VTUS.

A pressure zone is created by isolating the internal ducts between the valve positions by means of an appropriate separator.

The separator can be used in the following ducts:

- Duct 1
- Duct 3
- Duct 5



- Use a separator if the exhaust air pressures are high
- Use at least one supply plate/supply for each pressure zone

Duct separation


Duct separation	Description
	<p>The pressure zones can be freely configured with the VTUS. The following duct separations are possible:</p> <ul style="list-style-type: none"> • Duct 1 closed • Duct 1/3/5 closed • Duct 3/5 closed
	<p>The number of pressure zones with the VTUS is limited by the number of valve positions on the manifold block/supply manifold. Note that each supply plate occupies one valve position. There must always be at least 2 valve positions between 2 separators. In the case of a maximum extension of 16 valve positions, a maximum of 9 pressure zones can be created.</p>

Pneumatic valves VUWS/valve manifold VTUS

Key features – Pneumatics


Standard nominal flow rate q_{nN} , with several valves n switched simultaneously, size 20

For 3/2-way valves, valve manifold




Standard nominal flow rate q_n , with several valves n switched in parallel, size 20

For 3/2-way valves, individual valve




Standard nominal flow rate q_{nN} , with several valves n switched in parallel, size 20

For 5/2- and 5/3-way valves, valve manifold



Standard nominal flow rate q_n , with several valves n switched in parallel, size 20

For 5/2- and 5/3-way valves, individual valve




Pneumatic valves VUWS/valve manifold VTUS

Key features – Pneumatics


Standard nominal flow rate q_{nN} , with several valves n switched in parallel, size 25

For 3/2-way valves, valve manifold




Standard nominal flow rate q_n , with several valves n switched in parallel, size 25

For 3/2-way valves, individual valve




Standard nominal flow rate q_{nN} , with several valves n switched in parallel, size 25

For 5/2- and 5/3-way valves, valve manifold



Standard nominal flow rate q_n , with several valves n switched in parallel, size 25

For 5/2- and 5/3-way valves, individual valve




Pneumatic valves VUWS/valve manifold VTUS


Key features – Pneumatics


Standard nominal flow rate q_{nN} , with several valves n switched in parallel, size 30


For 3/2-way valves, valve manifold


Standard nominal flow rate q_n , with several valves n switched in parallel, size 30


For 3/2-way valves, individual valve


Standard nominal flow rate q_{nN} , with several valves n switched in parallel, size 30

For 5/2- and 5/3-way valves, valve manifold


Standard nominal flow rate q_n , with several valves n switched in parallel, size 30

For 5/2- and 5/3-way valves, individual valve



Pneumatic valves VUWS/valve manifold VTUS

Key features – Assembly

Mounting the valve manifold


Sturdy valve manifold owing to:

- Four through-holes for wall mounting
- H-rail mounting



Note
Use the thread M4 (M5 for size 30) provided on the manifold block for earthing the valve manifold.


Wall mounting



Sturdy wall mounting of the manifold block using four through-holes.

[1] Earth terminal

H-rail mounting



The H-rail mounting VAME-T-M... consists of two mounting clips. These are screwed to the manifold block on the left and right.

The prepared manifold block is then lowered onto the H-rail from above (arrow A) and clipped into the H-rail at the bottom (arrow B).



Note
• Note the max. tightening torque of the screws for H-rail mounting.
• Only horizontal H-rail mounting is permissible.
• Mounting only possible on H-rail TH 35... to EN 60715.
• Vibration/shock loads are not permissible with H-rail mounting.
• Further note on assembly
→ Assembly instructions for H-rail mounting VAME-T-M...


Pneumatic valves VUWS/valve manifold VTUS

Key features – Assembly

FESTO

Mounting individual valve VUWS


Wall mounting



For mounting individual valves on a flat surface, e.g. aluminium profile systems.
The pneumatic valves are provided with two through-holes for attaching to the wall mounting
VAME-B10-20-W.

The screw set required is included with the wall mounting
VAME-B10-20-W.
The wall mounting VAME-B10-20-W can be used for sizes 20, 25 and 30.

Foot mounting



For mounting individual valves on a flat surface, e.g. aluminium profile systems.
The pneumatic valves are provided with two through-holes for attaching to the foot mounting
VAME-B10-...-A.




The screw set required is included with the foot mounting
VAME-B10-...-A.




 - Note

Further mounting options for foot mounting VAME-B10-...-A
➔ Technical data – Pneumatic valves, dimensions

Pneumatic valves VUWS/valve manifold VTUS

Product range overview





Design	Size	Working port	Order code for valves and flow rate [l/min]							➔ Page/ Internet
			M32C	M32U	M52	B52	P53C	P53E	P53U	
3/2-way valve										
	20	G1/8	700	700	-	-	-	-	-	39
	25	G1/4	1000	1000	-	-	-	-	-	47
	30	G3/8	2300	2300	-	-	-	-	-	55
5/2-way valve										
	20	G1/8	-	-	700	700	-	-	-	39
	25	G1/4	-	-	1300	1300	-	-	-	47
	30	G3/8	-	-	2300	2300	-	-	-	55
5/3-way valve										
	20	G1/8	-	-	-	-	700	600	600	39
	25	G1/4	-	-	-	-	1200	1000	1000	47
	30	G3/8	-	-	-	-	2000	1600	1600	55

Design	Size	Description	➔ Page/ Internet
Manifold block for 3/2-way valves, standard			
	20	VABM-B10-20E-G38- ... -P3	Connection G3/8
	25	VABM-B10-25E-G12- ... -P3	Connection G1/2
	30	VABM-B10-30E-G34- ... -P3	Connection G3/4
Manifold block extension module for 3/2-way valves, standard			
	20	VABM-B10-20EEE-G38- ... -P3	Connection G3/8
	25	VABM-B10-25EEE-G12- ... -P3	Connection G1/2
	30	VABM-B10-30EEE-G34- ... -P3	Connection G3/4
Manifold block for 5/2- and 5/3-way valves, standard			
	20	VABM-B10-20E-G38- ...	Connection G3/8
	25	VABM-B10-25E-G12- ...	Connection G1/2
	30	VABM-B10-30E-G34- ...	Connection G3/4
Manifold block extension module for 5/2- and 5/3-way valves, standard			
	20	VABM-B10-20EEE-G38- ...	Connection G3/8
	25	VABM-B10-25EEE-G12- ...	Connection G1/2
	30	VABM-B10-30EEE-G34- ...	Connection G3/4

Pneumatic valves VUWS/valve manifold VTUS








Product range overview







Design	Size	Description		➔ Page/ Internet
Manifold block for 3/2-way valves, compact				
	20	VABM-B10-20S-G14- ... -P3	Connection G1/4	65
	25	VABM-B10-25S-G38- ... -P3	Connection G3/8	78
	30	VABM-B10-30S-G12- ... -P3	Connection G1/2	91
Manifold block for 5/2- and 5/3-way valves, compact				
	20	VABM-B10-20S-G14- ...	Connection G1/4	65
	25	VABM-B10-25S-G38- ...	Connection G3/8	78
	30	VABM-B10-30S-G12- ...	Connection G1/2	91
Supply manifold, for mounting on both sides				
	20	VABM-B10-20-G38- ... -P53	Connection G3/8	66
	25	VABM-B10-25-G12- ... -P53	Connection G1/2	79
	30	VABM-B10-30-G34- ... -P53	Connection G3/4	92
Supply manifold, for mounting on one side				
	20	VABM-B10-20-G38- ... -P53-E	Connection G3/8	66
	25	VABM-B10-25-G12- ... -P53-E	Connection G1/2	79
	30	VABM-B10-30-G34- ... -P53-E	Connection G3/4	92

Pneumatic valves VUWS

Valve function




3/2-way valves			
Order code for valves	Circuit symbol	Size	Description
3/2-way valves, NC, monostable			
M32C-A		20 25 30	<ul style="list-style-type: none"> • Normally closed • Internal pneumatic spring supply • Direction of flow: not reversible • Reset: pneumatic spring
M32C-E		20 25 30	<ul style="list-style-type: none"> • Normally closed • External pneumatic spring supply • Direction of flow: reversible • Reset: pneumatic spring
M32C-M		20	<ul style="list-style-type: none"> • Normally closed • Direction of flow: reversible • Reset: mechanical spring, supported internally by pneumatic spring
M32C-M		25 30	<ul style="list-style-type: none"> • Normally closed • Direction of flow: reversible • Reset: mechanical spring
3/2-way valve, NO, monostable			
M32U-A		20 25 30	<ul style="list-style-type: none"> • Normally open • Internal pneumatic spring supply • Direction of flow: not reversible • Reset: pneumatic spring
M32U-E		20 25 30	<ul style="list-style-type: none"> • Normally open • External pneumatic spring supply • Direction of flow: reversible • Reset: pneumatic spring
M32U-M		20	<ul style="list-style-type: none"> • Normally open • Direction of flow: reversible • Reset: mechanical spring, supported internally by pneumatic spring
M32U-M		25 30	<ul style="list-style-type: none"> • Normally open • Direction of flow: reversible • Reset: mechanical spring

5/2-way valves			
Order code for valves	Circuit symbol	Size	Description
5/2-way valve, monostable			
M52-A		20 25 30	<ul style="list-style-type: none"> • Internal pneumatic spring supply • Direction of flow: not reversible • Reset: pneumatic spring
M52-E		20 25 30	<ul style="list-style-type: none"> • External pneumatic spring supply • Direction of flow: reversible • Reset: pneumatic spring
M52-M		20 25 30	<ul style="list-style-type: none"> • Direction of flow: reversible • Reset: mechanical spring
5/2-way valve, bistable			
B52		20 25 30	<ul style="list-style-type: none"> • Direction of flow: reversible

Pneumatic valves VUWS

Valve function


FESTO

5/3-way valves			
Order code for valves	Circuit symbol	Size	Description
5/3-way valve, mid-position closed			
P53C		20 25 30	<ul style="list-style-type: none">• Direction of flow: reversible
5/3-way valve, mid-position exhausted			
P53E		20 25 30	<ul style="list-style-type: none">• Direction of flow: reversible
5/3-way valve, mid-position pressurised			
P53U		20 25 30	<ul style="list-style-type: none">• Direction of flow: reversible

Pneumatic valves VUWS/valve manifold VTUS

Peripherals overview

Manifold block for 3/2-way valves



Accessories


Description	Brief description	➔ Page/Internet
[1] Standard manifold block	For 3/2-way valves	65, 78, 91
[2] Supply plate	For 3/2-way valves	67, 80, 93
[3] Silencer	For exhaust ports (3)	69, 82, 95
[4] Push-in fitting	For supply/exhaust ports (1, 3)	40, 48, 56
[5] Blanking plate	VABB-B10...	67, 80, 93
[6] Push-in fitting	M5 for pilot air port	40, 48, 56
[7] Pneumatic valve	3/2-way valve	39, 47, 55
[8] Blanking plug	For supply/exhaust ports (1, 3)	69, 82, 95
[9] Standard manifold block extension module	For 3/2-way valves	65, 78, 91
[10] Compact manifold block	For 3/2-way valves	65, 78, 91
[11] H-rail mounting	For mounting on standard H-rails	69, 82, 95
[12] Standard H-rail	Mounting rail to EN 60715	-
[13] Separator	For creating pressure zones (in duct 1 and/or 3)	69, 82, 95

Pneumatic valves VUWS/valve manifold VTUS

Peripherals overview

FESTO

Manifold block for 5/2- and 5/3-way valves




Accessories			➔ Page/Internet
Description	Brief description		
[1] Standard manifold block	For 5/2- and 5/3-way valves		65, 78, 91
[2] Supply plate	For 5/2- and 5/3-way valves		67, 80, 93
[3] Silencer	For exhaust ports (5 and/or 3)		69, 82, 95
[4] Push-in fitting	For supply/exhaust ports (1, 3, 5)		40, 48, 56
[5] Blanking plate	VABB-B10...		67, 80, 93
[6] Push-in fitting	M5 for pilot air port		40, 48, 56
[7] Push-in fitting	For working ports (2, 4)		40, 48, 56
[8] Pneumatic valve	5/2-way, 5/3-way valve		39, 47, 55
[9] Blanking plug	For supply/exhaust ports (1, 3, 5)		69, 82, 95
[10] Standard manifold block extension module	For 5/2- and 5/3-way valves		65, 78, 91
[11] Compact manifold block	For 5/2- and 5/3-way valves		65, 78, 91
[12] H-rail mounting	For mounting on standard H-rails		69, 82, 95
[13] Standard H-rail	Mounting rail to EN 60715		-
[14] Separator	For creating pressure zones (in ducts 1, 3, 5)		69, 82, 95

Pneumatic valves VUWS/valve manifold VTUS

Peripherals overview

Supply manifold for mounting on both sides




Accessories			➔ Page/Internet
Description	Brief description		
[1] Supply manifold	For mounting on both sides Mounting bracket can be adjusted through $\pm 30^\circ$		66, 79, 92
[2] Supply plate	For supplying air (1) (VABF-B10-...-P1...)		67, 80, 93
[3] Push-in fitting	For supplying air (1) for working ports (2, 4)		40, 48, 56
[4] Blanking plate	VABB-B10-...		67, 80, 93
[5] Pneumatic valve	3/2-way valve		39, 47, 55
[6] Push-in fitting	M5 for pilot air port		40, 48, 56
[7] Pneumatic valve	5/2-way, 5/3-way valve		39, 47, 55
[8] Push-in fitting	For exhaust ports (3, 5)		40, 48, 56
[9] Silencer	For exhaust ports (3, 5)		69, 82, 95
[10] Push-in fitting	For supplying air (1)		68, 81, 94
[11] Blanking plug	For working port (duct 1)		69, 82, 95
[12] Separator	For creating pressure zones (in duct 1)		69, 82, 95

Pneumatic valves VUWS/valve manifold VTUS

Peripherals overview



Supply manifold for mounting on one side



Accessories			➔ Page/Internet
Description	Brief description		
1 Supply manifold	For mounting on one side Mounting bracket can be adjusted through ±30°		66, 79, 92
2 Supply plate	For supplying air (1) (VABF-B10-...-P1...)		67, 80, 93
3 Push-in fitting	For supplying air (1) for working ports (2, 4)		40, 48, 56
4 Blanking plate	VABB-B10-...		67, 80, 93
5 Pneumatic valve	3/2-way valve		39, 47, 55
6 Push-in fitting	M5 for pilot air port		40, 48, 56
7 Pneumatic valve	5/2-way, 5/3-way valve		39, 47, 55
8 Push-in fitting	For exhaust ports (3, 5)		40, 48, 56
9 Silencer	For exhaust ports (3, 5)		69, 82, 95
10 Push-in fitting	For supplying air (1)		68, 81, 94
11 Blanking plug	For working port (duct 1)		69, 82, 95
12 Separator	For creating pressure zones (in duct 1)		69, 82, 95

Valve manifold VTUS

Technical data – Valve manifold

-  Flow rate
Size 20 – up to 700 l/min
Size 25 – up to 1300 l/min
Size 30 – up to 2300 l/min

-  Valve width
Size 20 – 21 mm
Size 25 – 26.5 mm
Size 30 – 31 mm



General technical data

Valve manifold configuration	Fixed grid
Size 20 [mm]	21
Size 25 [mm]	26.5
Size 30 [mm]	31
Valve design	Piston spool
Reset method	Pneumatic or mechanical spring
Pneumatic spring	Internal or external
Direction of flow	Reversible with restrictions
Suitability for vacuum	Yes
Type of pilot control	Direct
Sealing principle	Soft
Max. no. of valve positions	16 (a maximum of 18 valve positions with extension for standard manifold block)
Max. number of pressure zones	9
Exhaust air function	With flow control
Type of actuation	Pneumatic
Standard nominal flow rate	
Size 20 [qnN]	600...700
Size 25 [qnN]	1000...1300
Size 30 [qnN]	1600...2300
Mounting position	Any
CRC ¹⁾	2 ¹⁾
Note on materials	RoHS compliant
Information on materials: seals	HNBR, NBR

1) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.

Operating and environmental conditions

Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Pilot medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating/pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Operating pressure	
With external pilot air [bar]	-0.9 ... +10
With internal pilot air [bar]	+1.5 ... +10
Pilot pressure [bar]	1.5 ... 10
Ambient temperature [°C]	-10 ... +50
Temperature of medium [°C]	-10 ... +50
Storage temperature [°C]	-20 ... +60

Valve manifold VTUS


Technical data

FESTO

Dimensions

With 3/2-way valves, standard manifold rail

Download CAD data → www.festo.com



- - Note

Port 12 on the manifold rail (number 3 in the dimensional drawing) is not

used when equipped with pneumatic valves.

Valve manifold VTUS

Technical data

Type	B3	B4	B5	B6	B7	B8	B9	B11	B12	B14	B15	B16
VTUS-20	77	75.5	53	66.5	63	50	24	12.5	41.2	11.5	25	5.5
VTUS-25	92	93	67.5	80.5	78	62	30	16	-	14	32	6
VTUS-30	109.2	108.2	79	93.2	94.7	75.7	36.2	19	55.5	17.2	38	6.5

Type	D1 Ø	D2	H1	H2	H3	H4	H5	H6	H7	H8	H9	L3	L4	L5	L6
VTUS-20	4.5	M4x6.5	77.4	61	37	23.5	8.5	18	5	91.4	32	6	25	22	1
VTUS-25	5.5	M4x9	95.5	71	45	25	9	22	5	123.4	39	6	29.8	27.5	1
VTUS-30	6.3	M5x11	118	91	61	35	9	28.5	6.5	170.1	54.5	7.2	34	32	-

Valve positions	2	3	4	5	6	7	8	9	10	
VTUS-20	L1 [mm]	72	94	116	138	160	182	204	226	248
	L2 [mm]	60	82	104	126	148	170	192	214	236
VTUS-25	L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
	L2 [mm]	75	102.5	130	157.5	185	212.5	240	267.5	295
VTUS-30	L1 [mm]	100	132	164	196	228	260	292	324	356
	L2 [mm]	85	117	149	181	213	245	277	309	341

Valve manifold VTUS


Technical data – Valve manifold

FESTO

Dimensions – Valve manifold

With 3/2-way valves, compact manifold rail

Download CAD data → www.festo.com



[1] Ports 1 and 3 (at both ends):

G1/4 for VTUS 20

G3/8 for VTUS 25

G1/2 for VTUS 30

[3] Port 10 and 12 on the valve:

M5 for VTUS 20,

M5 for VTUS 25,

G1/8 for VTUS 30

[5] Port 2:

G1/8 for VTUS 20

G1/4 for VTUS 25

G3/8 for VTUS 30

[7] H-rail mounting VAME-T-M4 for

VTUS 20

VAME-T-M5 for VTUS 25

VAME-T-M6 for VTUS 30

[8] Blanking plate

[9] Supply plate, ports 1 and 3:

G1/8 for VTUS 20

G1/4 for VTUS 25

G3/8 for VTUS 30

[10] Pneumatic valve, monostable,
3/2

Valve manifold VTUS

Technical data – Valve manifold

Type	B3	B4	B7	B8	B9	B11	B12	B14	B15
VTUS-20	77	56.1	53.1	47	22	10.5	41.2	11.5	25
VTUS-25	92	703	67.3	58.8	30	16	47	14	32
VTUS-30	109.2	83	80	69.4	36	19	55.5	17	38

Type	D1 Ø	D2	H1	H2	H3	H4	H6	H8	L3	L4	L5	L6
VTUS-20	4.5	M4x6.5	73.4	57	33	9.7	18	87.4	6	25	22	1
VTUS-25	5.5	M4x9	84.5	60	34	13.5	20	112.4	6	29.8	27.5	1
VTUS-30	6.3	M5x11	99.5	72.5	42.5	17.5	26	151.6	7.5	38	32	-

Valve positions	2	3	4	5	6	7	8	9	10	
VTUS-20	L1 [mm]	72	94	116	138	160	182	204	226	248
	L2 [mm]	60	82	104	126	148	170	192	214	236
VTUS-25	L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
	L2 [mm]	75	102.5	130	157.5	185	212.5	240	267.5	295
VTUS-30	L1 [mm]	100	132	164	196	228	260	292	324	356
	L2 [mm]	85	117	149	181	213	245	277	309	341



Valve manifold VTUS

Technical data – Valve manifold

Dimensions – Valve manifold

With 5/2- and 5/3-way valves, standard manifold rail

Download CAD data → www.festo.com



- [1] Ports 1, 3 and 5 (at both ends):
G3/8 for VTUS 20
G1/2 for VTUS 25
G3/4 for VTUS 30
- [3] Port 12 and 14 on the manifold block at both ends: G1/8
Port 12 and 14 on the valve:
M5 for VTUS 20,
M5 for VTUS 25,
G1/8 for VTUS 30

- [4] Thread for extension module:
M5x15.5 for VTUS 20
M5x18 for VTUS 25
M5x18 for VTUS 30
- [5] Ports 2 and 4: G1/8 for VTUS 20
G1/4 for VTUS 25
G3/8 for VTUS 30
- [6] Profile slot IPM-05, system 5
- [7] H-rail mounting VAME-T-M4 for VTUS 20
VAME-T-M5 for VTUS 25
VAME-T-M6 for VTUS 30
- [8] Blanking plate

- [9] Supply plate, ports 1, 3 and 5:
G1/8 for VTUS 20
G1/4 for VTUS 25
G3/8 for VTUS 30
- [10] Pneumatic valve, monostable, 5/2
- [11] Pneumatic valve, bistable, 5/2, 5/3



Note

Port 12 on the manifold rail (number 3 in the dimensional drawing) is not used when equipped with pneumatic valves.

Valve manifold VTUS

Technical data – Valve manifold

Type	B3	B4	B5	B6	B7	B8	B9	B10	B11	B14	B15
VTUS-20	107.4	110	100.5	97.5	73	81	55	29	12.5	42.5	25
VTUS-25	126	126	119	113.5	80	95	63	31	16	47	32
VTUS-30	149	144	137	129	104	111.5	72	32.5	19	53	38

Type	D1 Ø	D2	H1	H2	H3	H4	H5	H6	H7	H8	L3	L4	L5	L6
VTUS-20	4.5	M4x6.5	77.4	61	37	23.5	22	18	8.5	91.4	6	25	22	1
VTUS-25	5.5	M4x9	95.5	71	45	25	22	22	9	123.4	6	29.8	27.5	1
VTUS-30	6.3	M5x11	118	91	61	35	22	28.5	9	170.1	7.5	34	32	-

Valve positions	2	3	4	5	6	7	8	9	10	
VTUS-20	L1 [mm]	72	94	116	138	160	182	204	226	248
	L2 [mm]	60	82	104	126	148	170	192	214	236
VTUS-25	L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
	L2 [mm]	75	102.5	130	157.5	185	212.5	240	267.5	295
VTUS-30	L1 [mm]	100	132	164	196	228	260	292	324	356
	L2 [mm]	85	117	149	181	213	245	277	309	341

Valve manifold VTUS


Technical data – Valve manifold

FESTO

Dimensions – Valve manifold

With 5/2- and 5/3-way valves, compact manifold rail

Download CAD data → www.festo.com



[1] Ports 1, 3 and 5 (at both ends):
G1/4 for VTUS 20
G3/8 for VTUS 25
G1/2 for VTUS 30

[3] Port 12 and 14 on the valve:

M5 for VTUS 20,
M5 for VTUS 25,
G1/8 for VTUS 30

[5] Ports 2 and 4: G1/8 for
VTUS 20
G1/4 for VTUS 25
G3/8 for VTUS 30

[7] H-rail mounting VAME-T-M4 for

VTUS 20
VAME-T-M5 for VTUS 25
VAME-T-M6 for VTUS 30

[8] Blanking plate
[9] Supply plate, ports 1, 3 and 5:
G1/8 for VTUS 20
G1/4 for VTUS 25
G3/8 for VTUS 30

[10] Pneumatic valve, monostable,
5/2

[11] Pneumatic valve, bistable, 5/2,
5/3

Valve manifold VTUS

Technical data – Valve manifold

Type	B3	B4	B7	B8	B9	B10	B11	B12	B13	B14	B15
VTUS-20	107.4	64.2	47	55.1	32.1	9.1	12.5	41.2	41.2	19.6	25
VTUS-25	126	80.5	61.5	69	40.3	11.5	16	47	47	24.3	32
VTUS-30	149	94	77	80.4	47	13.6	19	55.5	55.5	28	38

Type	D1 Ø	D2	H1	H2	H3	H4	H6	H8	L3	L4	L5	L6
VTUS-20	4.5	M4x6.5	76.4	60	36	9.7	22.5	90.4	6	25	22	1
VTUS-25	5.5	M4x9	84.5	60	34	13.5	20	112.1	6	29.8	27.5	1
VTUS-30	6.3	M5x11	99.5	72.5	42.5	17.5	26	151.6	7.5	34	32	-

Valve positions	2	3	4	5	6	7	8	9	10	
VTUS-20	L1 [mm]	72	94	116	138	160	182	204	226	248
	L2 [mm]	60	82	104	126	148	170	192	214	236
VTUS-25	L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
	L2 [mm]	75	102.5	130	157.5	185	212.5	240	267.5	295
VTUS-30	L1 [mm]	100	132	164	196	228	260	292	324	356
	L2 [mm]	85	117	149	181	213	245	277	309	341

Valve manifold VTUS


Technical data – Valve manifold

FESTO

Dimensions – Supply manifold

Download CAD data → www.festo.com

Mounting on both sides



Valve manifold VTUS

Technical data – Valve manifold

Type	B2	B3	B4	B12	B13	B17	B18	B19	H1	H2	H3
VTUS-20	107.4	77	23	33.7	33.7	55	40	20	80.4	59	40
VTUS-25	126	92	28.7	33	33	75	60	35	102.5	78	52
VTUS-30	149	109.2	34	42	42	85	65	35	122	95	65

Type	H10	H12	D1 Ø	D2	D3 Ø	L3	L4	L5	L7	W1
VTUS-20	11.5	2	4.5	M4x6.5	5.2	9	21	22	22	31.3°
VTUS-25	18	2	4.5	M4x9	6.6	8	29.8	27.5	24	30°
VTUS-30	17.5	2.5	5.5	M5x11	8.6	9	34	32	26	28°

Valve positions	2	3	4	5	6	7	8	9	10	
VTUS-20	L1 [mm]	64	86	108	130	152	174	196	218	240
	L2 [mm]	90	112	134	156	178	200	222	244	266
VTUS-25	L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
	L2 [mm]	119	156.5	174	201.5	229	256.5	284	311.5	339
VTUS-30	L1 [mm]	100	132	164	196	228	260	292	324	356
	L2 [mm]	134	166	198	230	262	294	326	358	390


Valve manifold VTUS

Technical data – Valve manifold

FESTO

Dimensions – Supply manifold

Mounting on one side



Valve manifold VTUS

Technical data – Valve manifold

Type	B2	B3	B4	B17	B18	B19
VTUS-20	107.4	77	23	55	40	20
VTUS-25	126	92	28.7	80	60	35
VTUS-30	149	109.2	34	85	65	35








Type	D1 Ø	D3 Ø	H1	H3	H10	H13	H14	H15	L7	L8
VTUS-20	4.5	5.2	80.4	40	33	107	89	8	50	2
VTUS-25	4.5	6.6	102.5	52	38	128	112	8	64	2
VTUS-30	5.5	8.6	122	65	38	146	128	9	74	2.5

Valve positions	2	3	4	
VTUS-20	L1 [mm]	64	86	108
VTUS-25	L1 [mm]	87	114.5	142
VTUS-30		100	132	164

Pneumatic valves VUWS

Order code – Pneumatic valves



VUWS	-	L	-	-	-	-	-	
Valve design								Exhausting
In-line, individual valve	L							- Without fitting
Valve width								QN With fitting
21 mm		20						U1 Silencer with metal housing
26.5 mm		25						U3 Silencer with polymer housing
31 mm		30						
Valve functions								Pneumatic connection
					M32C ¹⁾			G18 Thread G 1/8
					M32U ¹⁾			G14 Thread G 1/4
					M52 ¹⁾			G38 Thread G 3/8
					B52			Q4 Push-in connector 4 mm
					P53C			Q6 Push-in connector 6 mm
					P53U			Q8 Push-in connector 8 mm
					P53E			Q10 Push-in connector 10 mm
								Q12 Push-in connector 12 mm
								Reset method
								- None (for bistable valves)
								A Pneumatic spring
								E Pneumatic spring, external
								M Mechanical spring

1) The circuit diagram is a symbolic representation. In the case of M32C, for example, the order code is possible only in combination with -A, -E, -M.

Pneumatic valves VUWS

Technical data – Pneumatic valves, size 20

-  - Flow rate
Up to 700 l/min

-  - Valve width
21 mm



General technical data

Valve function	3/2	5/2	5/3				
Order code for valves	M32C	M32U	M52	B52	P53C	P53U	P53E
Valve width [mm]	21						
Design	Piston spool						
Pneumatic spring supply	Internal or external (external: identified by E in type code)						
Type of piloting	Direct						
Manual override (MO)	None						
Direction of flow	Reversible with restrictions (not reversible: identified by A in type code)						
Non-overlapping	Yes						
Sealing principle	Soft						
Type of mounting	Optionally via through-holes ¹⁾ or on manifold rail						
Standard nominal flow rate [qN]	700	700	700	600	600		
Through-holes [mm] (nominal width)	5.7	5.7	5.0	4.8	4.5		
Product weight [g]	145	178/190 ²⁾	211	207	207	207	
Type of actuation	Pneumatic						
Mounting position	Any						
Exhaust air function	With flow control						
Venting hole	Not ducted						
Pneumatic connection 1, 2, 4, 3, 5	G1/8						
Pneumatic spring connection 12/14, 10	M5						

1) If several valves are to be screwed together via the through-holes to form a block, a minimum distance of 0.3 mm must be ensured by placing spacer discs between them.

2) With external pneumatic spring: 190 g, with internal pneumatic spring or mechanical spring: 178 g

Technical data – 3/2-way valves

Order code for valves	M32C		M32U	
Normal position	Closed		Open	
Stable positions	Monostable		Monostable	
Reset method	Pneumatic spring	Mechanical spring (supported internally by pneumatic spring)	Pneumatic spring	Mechanical spring (supported internally by pneumatic spring)
Switching times	On	7	10	7
	Off	15	28	15
	Change-over	–	–	–

Pneumatic valves VUWS

Technical data – Pneumatic valves, size 20

Technical data – 5/2-way valves						
Order code for valves	M52			B52		
Stable position	Monostable			Bistable		
Reset method	Pneumatic spring			Mechanical spring		
Switching times	On	13	7	–	–	–
	Off	26	39	–	–	–
	Change-over	–	–	–	6	–

Technical data – 5/3-way valves						
Order code for valves	P53C	P53U	P53E			
Stable position	Monostable					
Reset method	Mechanical spring					
Switching times	On	10	10	10	10	10
	Off	44	43	46	46	46
	Change-over	26	21	21	21	21

Safety characteristics						
Note on forced checking procedure	Min. 1/week					
Resistance to shocks	Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27					
Vibration resistance	Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6					


Operating and environmental conditions						
Valve function	M32 ... A M32 ... M	M32C-E M32U-E	M52-A M52-M	M52-E M52-M	B52	P53
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]					
Pilot medium	Compressed air to ISO 8573-1:2010 [7:4:4]					
Note on operating/pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)					
Operating pressure [bar]	2.5 ... 10	-0.9 ... +10	2.5 ... 10	-0.9 ... +10	-0.9 ... +10	-0.9 ... +10
Pilot pressure [bar]	2.5 ... 10	2.5 ... 10	2.5 ... 10	2.5 ... 10	1.5 ... 10	2.5 ... 10
Ambient temperature [°C]	-10 ... +60					
Temperature of medium [°C]	-10 ... +60					
Corrosion resistance class CRC ¹⁾	2					

- 1) Corrosion resistance class CRC 2 to Festo standard FN 940070
 Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.

Information on materials						
Housing	Die-cast aluminium					
Piston spool	Wrought aluminium alloy (P53 types: high-alloy stainless steel)					
Seals	HNBR, NBR					
Note on materials	RoHS compliant					

Special features of pneumatic 3/2-way valves


Reset: mechanical spring



Internal pneumatic spring

- Faster switch-off time
- In the case of dual-pressure operation, the higher pressure must always be present at port 1
- Pressure on port 2 not permitted

Reset: pneumatic spring



External pneumatic spring

- Can be used as a bistable valve
- Signal pressure depends on the pressure of the pneumatic spring
- No impairment of the switching function caused by vacuum
- Pressure is permitted on port 2

Pneumatic valves VUWS


Technical data – Pneumatic valves, size 20

Dimensions

3/2-way valve, normally closed/open

Download CAD data → www.festo.com

3/2-way valve, normally closed/open, external pilot air



- [3] Port 10: pilot air (...-M32U-...)
Port 12: pilot air (...-M32C-...)
- [4] Port 10: for external pneumatic spring (...-M32C-E-...)
Port 12: for external pneumatic spring (...-M32U-E-...)
- [7] For mounting screw M3

Type	B1	B2	B3	B4	B5	D1	D2	D3	H1	H3
VUWS-L20-M32C-...-G18	21.1	16.1	-	2.5	2	G1/8	M5	-	40.4	6.2
VUWS-L20-M32U-...-G18			-					-		
VUWS-L20-M32C-E-...-G18			1.5					M5		
VUWS-L20-M32U-E-...-G18			1.5					M5		

Type	L6	L7	L8	L10	L12	L14	L15	L16	L17	L19
VUWS-L20-M32C-...-G18	77	44.1	19.2	-	8.8	53.7	33.7	8	42.5	49.7
VUWS-L20-M32U-...-G18				-						
VUWS-L20-M32C-E-...-G18				72						
VUWS-L20-M32U-E-...-G18				72						

Pneumatic valves VUWS

Technical data – Pneumatic valves, size 20


FESTO

Dimensions

5/2-way valve, monostable, external pilot air

Download CAD data → www.festo.com

5/2-way valve, monostable



- [3] Port 14: pilot air (-M52-...)
- [4] Port 12: pilot air/(pneumatic spring) (...-M52-E-...)
- [7] For mounting screw M5

Type	B1	B2	B4	B5	D1	D2	D3	H1	H3
VUWS-L20-M52-...-G18	21.1	16.1	2.5	2	G1/8	M5	–	40.4	6.2
VUWS-L20-M52-E-G18					G1/8	M5	M5		

Type	L6	L7	L8	L10	L12	L13	L14	L15	L16	L17	L18	L19
VUWS-L20-M52-...-G18	107.4	44.1	19.2	–	8.8	73.7	53.7	33.7	8	42.5	22.5	49.7
VUWS-L20-M52-E-G18				98.6								


Pneumatic valves VUWS

Technical data – Pneumatic valves, size 20

Dimensions

Download CAD data → www.festo.com

5/2-way valve, bistable, 5/3-way valve



Type	B1	B2	B4	B5	D1	D2	D3	H1	H3
VUWS-L20-P53-...-M-G18	21.1	16.1	2.5	2	G1/8	M5	M5	40.4	6.2
VUWS-L20-B52-G18									

Type	L6	L7	L8	L10	L12	L13	L14	L15	L16	L17	L18	L19
VUWS-L20-P53-...-M-G18	107.4	44.1	19.2	98.6	8.8	73.7	53.7	33.7	8	42.5	22.5	49.7
VUWS-L20-B52-G18												


Pneumatic valves VUWS

Technical data – Pneumatic valves, size 20

FESTO

Dimensions

Foot mounting




Type	B1	B2	B3	D1 Ø	D2 Ø	D3 Ø	H1	H2	H3	H4	H5	H6	H7	H8	
VAME-B10-20-A	VUWS-L20-B52/P53	20	13.1	10.6	3.2	4.2	5.2	112.5	106.5	77.5	63.5	44	39	19.2	10.5
	VUWS-L20-M52														
	VUWS-L20-M32														

Type	H9	H10	H11	H12	L1	L2	L3	L4	L5	L6	L7	L8	L9
VAME-B10-20-A	2.5	150.6	97.7	121.6	55	41	29.4	19.2	40	20	19	107.4	4.1

Dimensions




Wall mounting



Type	B1	D1	D2	D3	H1	H2	H3	H4	H5	H6	H7	H8	L1	L2	L3	L4	L5	L6	L7
VAME-B10-20-W	10	M3	M4	M5	35	20	10	11.5	9.7	8.7	22.7	17.7	50	40	20	53.7	53.7	28.9	28.9


Pneumatic valves VUWS

Ordering data – Pneumatic valves, size 20



Ordering data – Pneumatic valves		Code	Valve function	Part No.	Type	
Pneumatic valves						
	3/2-way valve, monostable, closed	M32C-A	Pneumatic spring return, internal pneumatic spring, direction of flow not reversible	575669	VUWS-L20-M32C-A-G18	
	M32C-E	Pneumatic spring return, external pneumatic spring, direction of flow reversible	575670	VUWS-L20-M32C-E-G18		
	M32C-M	Mechanical spring return, supported by internal pneumatic spring, direction of flow reversible	575671	VUWS-L20-M32C-M-G18		
	3/2-way valve, monostable, open					
	M32U-A	Pneumatic spring return, internal pneumatic spring, direction of flow not reversible	575672	VUWS-L20-M32U-A-G18		
	M32U-E	Pneumatic spring return, external pneumatic spring, direction of flow reversible	575673	VUWS-L20-M32U-E-G18		
	M32U-M	Mechanical spring return, supported by internal pneumatic spring, direction of flow reversible	575674	VUWS-L20-M32U-M-G18		
	5/2-way valve, monostable					
		M52-A	Pneumatic spring return, internal pneumatic spring, direction of flow not reversible	575677	VUWS-L20-M52-A-G18	
		M52-E	Pneumatic spring return, external pneumatic spring, direction of flow reversible	575678	VUWS-L20-M52-E-G18	
M52-M		Mechanical spring return, direction of flow reversible	575681	VUWS-L20-M52-M-G18		
5/2-way valve, bistable						
B52	Direction of flow reversible	575684	VUWS-L20-B52-G18			
5/3-way valve						
	P53C	Closed, mechanical spring return, direction of flow reversible	575687	VUWS-L20-P53C-M-G18		
	P53E	Exhausted, mechanical spring return, direction of flow reversible	575693	VUWS-L20-P53E-M-G18		
	P53U	Pressurised, mechanical spring return, direction of flow reversible	575690	VUWS-L20-P53U-M-G18		

Pneumatic valves VUWS

Accessories – Pneumatic valves, size 20

Ordering data		Description	Part No.	Type	PU ¹⁾
Push-in fitting with internal hex					
	Connecting thread M5 for tubing O.D.	4 mm	153315	QSM-M5-4-I	10
	Connecting thread G1/8 for tubing O.D.	4 mm	186106	QS-G1/8-4-I	10
		4 mm	133008	QS-G1/8-4-I-100	100
		6 mm	186107	QS-G1/8-6-I	10
			133009	QS-G1/8-6-I-100	100
		8 mm	186109	QS-G1/8-8-I	10
			133010	QS-G1/8-8-I-100	100
Angled push-in fitting with external hex					
	Connecting thread G1/8 for tubing O.D.	4 mm	186116	QLS-G1/8-4	10
			132048	QLS-G1/8-4-100	100
		6 mm	186117	QLS-G1/8-6	10
			132049	QLS-G1/8-6-100	100
		8 mm	186119	QLS-G1/8-8	10
Angled push-in fitting, long, with external hex					
	Connecting thread G1/8 for tubing O.D.	4 mm	186127	QSLL-G1/8-4	10
			133015	QSLL-G1/8-4-100	100
		6 mm	186128	QSLL-G1/8-6	10
			133016	QSLL-G1/8-6-100	100
		8 mm	186130	QSLL-G1/8-8	10

1) Packaging unit

Ordering data		Description	Weight [g]	Part No.	Type
Foot mounting					
	Set for mounting valves, comprising:	<ul style="list-style-type: none"> Mounting bracket and Screw set for mounting 	97	576412	VAME-B10-20-A
Wall mounting					
	Set for mounting valves for size 20, 25, 30, comprising:	<ul style="list-style-type: none"> Wall mounting and Screw set for mounting 	53	576413	VAME-B10-20-W
Assortment of spare parts					
	Set comprising:	<ul style="list-style-type: none"> Seals and Screws 	10	8026203	VAME-B10-20-MK

Pneumatic valves VUWS

Technical data – Pneumatic valves, size 25

-  - Flow rate
Up to 1300 l/min

-  - Valve width
26.5 mm



General technical data

Valve function	3/2	5/2	5/3				
Order code for valves	M32C	M32U	M52	B52	P53C	P53U	P53E
Valve width [mm]	26.5						
Design	Piston spool						
Pneumatic spring supply	Internal or external (external: identified by E in type code)						
Type of pilot control	Direct						
Manual override (MO)	None						
Direction of flow	Reversible with restrictions (not reversible: identified by A in type code)						
Non-overlapping	Yes						
Sealing principle	Soft						
Type of mounting	Optionally via through-holes ¹⁾ or on manifold rail						
Standard nominal flow rate [qN]	1000	1000	1300	1300	1200	1000	1000
Through-holes [mm] (nominal width)	6.3	6.3	6.9	6.9	6.5	6.3	6.3
Product weight [g]	268	268	330/360 ²⁾	363	364	364	364
Type of actuation	Pneumatic						
Mounting position	Any						
Exhaust air function	With flow control						
Venting hole	Not ducted						
Pneumatic connection 1, 2, 4, 3, 5	G1/4						
Pneumatic spring connection 12/14, 10	M5						

1) If several valves are to be screwed together via the through-holes to form a block, a minimum distance of 0.3 mm must be ensured by placing spacer discs between them.

2) With external pneumatic spring: 360 g, with internal pneumatic spring or mechanical spring: 330 g

Technical data – 3/2-way valves

Order code for valves	M32C		M32U	
Normal position	Closed		Open	
Stable positions	Monostable		Monostable	
Reset method	Pneumatic spring		Mechanical spring	Pneumatic spring
Switching times	On	10	10	10
	Off	25	43	25
	Change-over	–	–	–

Pneumatic valves VUWS

Technical data – Pneumatic valves, size 25

FESTO

Technical data – 5/2-way valves						
Order code for valves	M52			B52		
Stable position	Monostable			Bistable		
Reset method	Pneumatic spring		Mechanical spring	–		
Switching times	On	15	10	–	–	–
	Off	32	42	–	–	–
	Change-over	–	–	–	10	–

Technical data – 5/3-way valves						
Order code for valves	P53C	P53U	P53E	B52	P53	–
Stable position	Monostable	–	–	–	–	–
Reset method	Mechanical spring	–	–	–	–	–
Switching times	On	13	13	13	–	–
	Off	65	65	65	–	–
	Change-over	30	30	30	–	–

Safety characteristics						
Note on forced checking procedure	Min. 1/week					
Resistance to shocks	Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27					
Vibration resistance	Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6					

Operating and environmental conditions						
Valve function	M32 ... A	M32 ... E M32 ... M	M52-A	M52-E M52-M	B52	P53
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]					
Pilot medium	Compressed air to ISO 8573-1:2010 [7:4:4]					
Note on operating/pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)					
Operating pressure [bar]	2.5 ... 10	-0.9 ... +10	2.5 ... 10	-0.9 ... +10	-0.9 ... +10	-0.9 ... +10
Pilot pressure [bar]	2.5 ... 10	2.5 ... 10	2.5 ... 10	2.5 ... 10	1.5 ... 10	2.5 ... 10
Ambient temperature [°C]	-10 ... +60					
Temperature of medium [°C]	-10 ... +60					
Corrosion resistance class CRC ¹⁾	2					

- 1) Corrosion resistance class CRC 2 to Festo standard FN 940070
 Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.

Information on materials						
Housing	Die-cast aluminium					
Piston spool	Wrought aluminium alloy (P53 types: high-alloy stainless steel)					
Seals	HNBR, NBR					
Note on materials	RoHS-compliant					

Pneumatic valves VUWS


Technical data – Pneumatic valves, size 25

Dimensions

3/2-way valve, normally closed/open

Download CAD data → www.festo.com

3/2-way valve, normally closed/open, external pilot air



Type	B1	B2	B3	B4	B5	D1	D2	D3	H1	H3
VUWS-L25-M32C-...-G14	26.5	20.2	1.9	1.9	1.9	G1/4	M5	-	50.5	8
VUWS-L25-M32U-...-G14								-		
VUWS-L25-M32C-E-...-G14								M5		
VUWS-L25-M32U-E-...-G14								M5		

Type	L6	L7	L8	L10	L12	L14	L15	L16	L17	L19
VUWS-L25-M32C-...-G14	92	50.5	25	-	7	63	38.5	13	47.6	56.5
VUWS-L25-M32U-...-G14				-						
VUWS-L25-M32C-E-...-G14				81						
VUWS-L25-M32U-E-...-G14				81						

Pneumatic valves VUWS

Technical data – Pneumatic valves, size 25


FESTO

Dimensions

5/2-way valve, monostable

Download CAD data → www.festo.com

5/2-way valve, monostable, external pilot air



Type	B1	B2	B4	B5	D1	D2	D3	H1	H3
VUWS-L25-M52-...-G14	26.5	20.2	1.9	1.9	G1/4	M5	-	50.5	8
VUWS-L25-M52-E-G14							M5		

Type	L6	L7	L8	L10	L12	L13	L14	L15	L16	L17	L18	L19
VUWS-L25-M52-...-G14	125	50.5	25	-	7	87.5	63	38.5	13	47.6	30.8	56.5
VUWS-L25-M52-E-G14				119								


Pneumatic valves VUWS

Technical data – Pneumatic valves, size 25

Dimensions

Download CAD data → www.festo.com

5/2-way valve, bistable, 5/3-way valve



- [3] Port 14: pilot air
- [4] Port 12: pilot air
- [7] For mounting screw M4

Type	B1	B2	B4	B5	D1	D2	D3	H1	H3
VUWS-L25-P53-...-M-G14	26.5	20.2	1.9	1.9	G1/4	M5	M5	50.5	8
VUWS-L25-B52-G14									

Type	L6	L7	L8	L10	L12	L13	L14	L15	L16	L17	L18	L19
VUWS-L25-P53-...-M-G14	126	50.5	25	119	7	87.5	63	38.5	13	47.6	30.8	56.5
VUWS-L25-B52-G14												


Pneumatic valves VUWS

Technical data – Pneumatic valves, size 25

FESTO

Dimensions

Foot mounting




Type		B1	B2	B3	D1 Ø	D2 Ø	D3 Ø	H1	H2	H3	H4	H5	H6	H7
VAME-B10-25-A	VUWS-L25-B52/P53	24	15.8	13.3	4.2	4.2	5.2	130	122.5	91	80.5	48.5	41.5	25
	VUWS-L25-M52													
	VUWS-L25-M32													

Type		H8	H9	H10	H11	H12	L1	L2	L3	L4	L5	L6	L7	L8	L9
VAME-B10-25-A	VUWS-L25-B52/P53	11	2.5	173	123	141.5	55	49.4	40.4	25	40	20	23.5	126	4.1
	VUWS-L25-M52			173										126	
	VUWS-L25-M32			139										92	

Dimensions




Wall mounting



Type		B1	D1	D2	D3	H1	H2	H3	H4	H5	H6	H7	H8	L1	L2	L3	L4	L5	L6	L7
VAME-B10-20-W	VUWS-L25-B52/P53	10	M3	M4	M5	35	20	10	11.5	9.7	8.7	32.8	17.7	50	40	20	63	63	37	37
	VUWS-L25-M52																62		37	
	VUWS-L25-M32																-		29	


Pneumatic valves VUWS

Ordering data – Pneumatic valves, size 25



Ordering data – Pneumatic valves		Code	Valve function	Part No.	Type	
Pneumatic valves						
	3/2-way valve, monostable, closed	M32C-A	Pneumatic spring return, internal pneumatic spring, direction of flow not reversible	575483	VUWS-L25-M32C-A-G14	
	M32C-E	Pneumatic spring return, external pneumatic spring, direction of flow reversible	575484	VUWS-L25-M32C-E-G14		
	M32C-M	Mechanical spring return, direction of flow reversible	575485	VUWS-L25-M32C-M-G14		
	3/2-way valve, monostable, open					
	M32U-A	Pneumatic spring return, internal pneumatic spring, direction of flow not reversible	575498	VUWS-L25-M32U-A-G14		
	M32U-E	Pneumatic spring return, external pneumatic spring, direction of flow reversible	575499	VUWS-L25-M32U-E-G14		
	M32U-M	Mechanical spring return, direction of flow reversible	575500	VUWS-L25-M32U-M-G14		
		5/2-way valve, monostable	M52-A	Pneumatic spring return, internal pneumatic spring, direction of flow not reversible	575507	VUWS-L25-M52-A-G14
		M52-E	Pneumatic spring return, external pneumatic spring, direction of flow reversible	575508	VUWS-L25-M52-E-G14	
		M52-M	Mechanical spring return, direction of flow reversible	575515	VUWS-L25-M52-M-G14	
5/2-way valve, bistable						
	B52	Direction of flow reversible	575522	VUWS-L25-B52-G14		
	5/3-way valve					
	P53C	Closed, mechanical spring return, direction of flow reversible	575529	VUWS-L25-P53C-M-G14		
	P53E	Exhausted, mechanical spring return, direction of flow reversible	575543	VUWS-L25-P53E-M-G14		
	P53U	Pressurised, mechanical spring return, direction of flow reversible	575536	VUWS-L25-P53U-M-G14		

Pneumatic valves VUWS

Accessories – Pneumatic valves, size 25

Ordering data		Description	Part No.	Type	PU ¹⁾
Push-in fitting with internal hex					
	Connecting thread M5 for tubing O.D.	4 mm	153315	QSM-M5-4-I	10
	Connecting thread G1/4 for tubing O.D.	6 mm	186108	QS-G1/4-6-I	10
		8 mm	186110	QS-G1/4-8-I	10
		10 mm	186112	QS-G1/4-10-I	10
Angled push-in fitting with external hex					
	Connecting thread G1/4 for tubing O.D.	6 mm	186118	QSL-G1/4-6	10
			132051	QSL-G1/4-6-100	100
		8 mm	186120	QSL-G1/4-8	10
			132052	QSL-G1/4-8-50	50
		10 mm	186122	QSL-G1/4-10	10
		132053	QSL-G1/4-10-50	50	
Angled push-in fitting, long, with external hex					
	Connecting thread G1/4 for tubing O.D.	6 mm	186129	QSLL-G1/4-6	10
		8 mm	186131	QSLL-G1/4-8	10
		10 mm	186133	QSLL-G1/4-10	10

1) Packaging unit

Ordering data		Weight [g]	Part No.	Type
Description				
Foot mounting				
	Set for mounting valves, comprising:			
	<ul style="list-style-type: none"> • Mounting bracket and • Screw set for mounting 	130	2293485	VAME-B10-25-A
Wall mounting				
	Set for mounting valves for size 20, 25, 30, comprising:			
	<ul style="list-style-type: none"> • Wall mounting and • Screw set for mounting 	53	576413	VAME-B10-20-W
Assortment of spare parts				
	Set comprising:			
	<ul style="list-style-type: none"> • Seals and • Screws 	12	8035636	VAME-B10-25-MK

Pneumatic valves VUWS

Technical data – Pneumatic valves, size 30

-  - Flow rate
Up to 2300 l/min

-  - Valve width
31 mm



General technical data

Valve function	3/2		5/2		5/3		
Order code for valves	M32C	M32U	M52	B52	P53C	P53U	P53E
Valve width [mm]	31						
Design	Piston spool						
Pneumatic spring supply	Internal or external (external: identified by E in type code)						
Type of pilot control	Direct						
Manual override (MO)	None						
Direction of flow	Reversible with restrictions (not reversible: identified by A in type code)						
Sealing principle	Soft						
Type of mounting	Optionally via through-holes ¹⁾ or on manifold rail						
Nominal flow rate [qN]	2300	2300	2300	2300	2000	1600	1600
Through-holes [mm] (nominal width)	9.4	9.4	9.4	9.4	8.9	8.1	8.1
Product weight [g]	394	394	487/546 ²⁾	545	542	542	542
Type of actuation	Pneumatic						
Mounting position	Any						
Exhaust air function	With flow control						
Venting hole	Not ducted						
Pneumatic connection 1, 2, 4, 3, 5	G3/8						
Pneumatic spring connection 12/14, 10	G1/8						

1) If several valves are to be screwed together via the through-holes to form a block, a minimum distance of 0.3 mm must be ensured by placing spacer discs between them.

2) With external pneumatic spring: 546 g, with internal pneumatic spring or mechanical spring: 487 g

Technical data – 3/2-way valves

Order code for valves	M32C-A	M32C-E	M32C-M	M32U-A	M32U-E	M32U-M
Normal position	Closed			Open		
Stable positions	Monostable			Monostable		
Reset method	Pneumatic spring		Mechanical spring	Pneumatic spring		Mechanical spring
Switching times	On	19	21	16	19	21
	Off	36	40	73	37	40
	Change-over	–	–	–	–	–

Pneumatic valves VUWS

Technical data – Pneumatic valves, size 30

FESTO

Technical data – 5/2-way valves						
Order code for valves	M52			B52		
Stable position	Monostable			Bistable		
Reset method	Pneumatic spring		Mechanical spring	–		
Switching times	On	24	17	–	–	–
	Off	59	77	–	–	–
	Change-over	–	–	–	13	–

Technical data – 5/3-way valves						
Order code for valves	P53C	P53U	P53E	B52	P53	–
Stable position	Monostable	–	–	–	–	–
Reset method	Mechanical spring	–	–	–	–	–
Switching times	On	19	19	19	19	–
	Off	98	98	98	98	–
	Change-over	41	41	41	41	–

Safety characteristics						
Note on forced checking procedure	Min. 1/week					
Resistance to shocks	Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27					
Vibration resistance	Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6					

Operating and environmental conditions						
Valve function	M32 ... A	M32 ... E	M52-A	M52-E	B52	P53
Valve function	M32 ... M	–	–	M52-M	–	–
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]					
Pilot medium	Compressed air to ISO 8573-1:2010 [7:4:4]					
Note on operating/pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)					
Operating pressure [bar]	2.5 ... 10	-0.9 ... +10	2.5 ... 10	-0.9 ... +10	-0.9 ... +10	-0.9 ... +10
Pilot pressure [bar]	2.5 ... 10	2.5 ... 10	2.5 ... 10	2.5 ... 10	1.5 ... 10	2.5 ... 10
Ambient temperature [°C]	-10 ... +60					
Temperature of medium [°C]	-10 ... +60					
Corrosion resistance class CRC ¹⁾	2					

- 1) Corrosion resistance class CRC 2 to Festo standard FN 940070
 Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.

Information on materials						
Housing	Die-cast aluminium					
Piston spool	Wrought aluminium alloy					
Seals	HNBR, NBR					
Note on materials	RoHS-compliant					

Pneumatic valves VUWS


Technical data – Pneumatic valves, size 30

Dimensions

3/2-way valve, normally closed/open

Download CAD data → www.festo.com

3/2-way valve, normally closed/open, external pilot air



Type	B1	B2	B3	B4	B5	D1	D2	D3	H1	H3
VUWS-L30-M32C-...-G38	31	23.3	2.5	2.5	2.5	G3/8	G1/8	-	57	9
VUWS-L30-M32U-...-G38								-		
VUWS-L30-M32C-E-...-G38								G1/8		
VUWS-L30-M32U-E-...-G38								G1/8		

Type	L6	L7	L8	L10	L12	L14	L15	L16	L17	L19
VUWS-L30-M32C-...-G38	109.2	59	31	-	8.3	74.5	44.5	17	55.7	66
VUWS-L30-M32U-...-G38				-						
VUWS-L30-M32C-E-...-G38				94.5						
VUWS-L30-M32U-E-...-G38				94.5						

Pneumatic valves VUWS

Technical data – Pneumatic valves, size 30







FESTO

Dimensions

5/2-way valve, monostable

Download CAD data → www.festo.com

5/2-way valve, monostable, external pilot air



[3] Port 14: pilot air (-M52-...)

[4] Port 12: pilot air/(pneumatic spring) (...-M52-E-...)

[7] For mounting screw M5

Type	B1	B2	B4	B5	D1	D2	D3	H1	H3
VUWS-L30-M52-...-G38	31	23.3	2.5	2.5	G3/8	G1/8	-	57	9
VUWS-L30-M52-E-G38							G1/8		

Type	L6	L7	L8	L10	L12	L13	L14	L15	L16	L17	L18	L19
VUWS-L30-M52-...-G38	145	59	31	-	8.3	104.5	74.5	44.5	17	55.7	37.6	66
VUWS-L30-M52-E-G38	149				140.7							


Pneumatic valves VUWS

Technical data – Pneumatic valves, size 30

Dimensions

5/2-way valve, bistable, 5/3-way valve

Download CAD data → www.festo.com



Type	B1	B2	B4	B5	D1	D2	D3	H1	H3
VUWS-L30-P53-...-M-G38	31	23.3	2.5	2.5	G3/8	G1/8	G1/8	57	9
VUWS-L30-B52-G38									

Type	L6	L7	L8	L10	L12	L13	L14	L15	L16	L17	L18	L19
VUWS-L30-P53-...-M-G38	149	59	31	140.7	8.3	104.5	74.5	44.5	17	55.7	37.6	66
VUWS-L30-B52-G38												


Pneumatic valves VUWS

Ordering data – Pneumatic valves, size 30

FESTO

Dimensions

Foot mounting




Type	B1	B2	B3	D1 Ø	D2 Ø	D3 Ø	D4 Ø	H1	H2	H3	H4	H5	H7
VAME-B10-30-A	VUWS-L30-B52/P53	26.8	18.5	15.5	5.2	4.2	5.2	146	136.5	102.5	112	50.5	31
	VUWS-L30-M52												
	VUWS-L30-M32												

Type	H8	H9	H10	H11	H12	L1	L3	L4	L5	L6	L7	L8	L9
VAME-B10-30-A	VUWS-L30-B52/P53	11.5	3	195.5	161.5	160	57	45.6	31	40	20	32	149
	VUWS-L30-M52			195.5	161.5								149
	VUWS-L30-M32			155.7	121.7								109.2

Dimensions




Wall mounting



Type	B1	D1	D2	D3	H1	H2	H3	H4	H5	H6	H7	H8	L1	L2	L3	L4	L5	L6	L7	
VAME-B10-20-W	VUWS-L30-B52/P53	10	M3	M4	M5	35	20	10	11.5	9.7	8.7	39.3	17.7	50	40	20	74.5	74.5	43	43
	VUWS-L30-M52																70.5		43	
	VUWS-L30-M32																-		34.7	

Pneumatic valves VUWS


Ordering data – Pneumatic valves, size 30

Ordering data – Pneumatic valves		Code	Valve function	Part No.	Type	
Pneumatic valves						
	3/2-way valve, monostable, closed	M32C-A	Pneumatic spring return, internal pneumatic spring, direction of flow not reversible	575576	VUWS-L30-M32C-A-G38	
	M32C-E	Pneumatic spring return, external pneumatic spring, direction of flow reversible	575577	VUWS-L30-M32C-E-G38		
	M32C-M	Mechanical spring return, direction of flow reversible	575578	VUWS-L30-M32C-M-G38		
	3/2-way valve, monostable, open					
	M32U-A	Pneumatic spring return, internal pneumatic spring, direction of flow not reversible	575591	VUWS-L30-M32U-A-G38		
	M32U-E	Pneumatic spring return, external pneumatic spring, direction of flow reversible	575592	VUWS-L30-M32U-E-G38		
	M32U-M	Mechanical spring return, direction of flow reversible	575593	VUWS-L30-M32U-M-G38		
		5/2-way valve, monostable	M52-A	Pneumatic spring return, internal pneumatic spring, direction of flow not reversible	575600	VUWS-L30-M52-A-G38
		M52-E	Pneumatic spring return, external pneumatic spring, direction of flow reversible	575601	VUWS-L30-M52-E-G38	
		M52-M	Mechanical spring return, direction of flow reversible	575608	VUWS-L30-M52-M-G38	
5/2-way valve, bistable						
	B52	Direction of flow reversible	575615	VUWS-L30-B52-G38		
	5/3-way valve					
	P53C	Closed, mechanical spring return, direction of flow reversible	575622	VUWS-L30-P53C-M-G38		
	P53E	Exhausted, mechanical spring return, direction of flow reversible	575636	VUWS-L30-P53E-M-G38		
	P53U	Pressurised, mechanical spring return, direction of flow reversible	575629	VUWS-L30-P53U-M-G38		


Pneumatic valves VUWS

Accessories – Pneumatic valves, size 30

FESTO

Ordering data		Description	Part No.	Type	PU ¹⁾
Push-in fitting with internal hex					
	Connecting thread G1/8 for tubing O.D.	4 mm	186106	QS-G1/8-4-I	10
			133008	QS-G1/8-4-I-100	100
		6 mm	186107	QS-G1/8-6-I	10
			133009	QS-G1/8-6-I-100	100
	Connecting thread G3/8 for tubing O.D.	8 mm	186111	QS-G3/8-8-I	10
		10 mm	186113	QS-G3/8-10-I	10
		12 mm	186114	QS-G3/8-12-I	10
Angled push-in fitting with external hex					
	Connecting thread G3/8 for tubing O.D.	8 mm	186121	QSL-G3/8-8	10
			132055	QSL-G3/8-8-50	50
		10 mm	186123	QSL-G3/8-10	10
			132056	QSL-G3/8-10-20	20
		12 mm	186124	QSL-G3/8-12	10
			132057	QSL-G3/8-12-20	20
Angled push-in fitting, long, with external hex					
	Connecting thread G3/8 for tubing O.D.	8 mm	186132	QSLL-G3/8-8	10
		10 mm	186134	QSLL-G3/8-10	10
		12 mm	186135	QSLL-G3/8-12	10

1) Packaging unit

Ordering data		Description	Weight [g]	Part No.	Type
Foot mounting					
	Set for mounting valves, comprising:	<ul style="list-style-type: none"> • Mounting bracket and • Screw set for mounting 	-	8026337	VAME-B10-30-A
Wall mounting					
	Set for mounting valves for size 20, 25, 30, comprising:	<ul style="list-style-type: none"> • Wall mounting and • Screw set for mounting 	53	576413	VAME-B10-20-W
Set of spare parts					
	Set comprising:	<ul style="list-style-type: none"> • Seals and • Screws 	-	8035637	VAME-B10-30-MK

Pneumatic valves VUWS/valve manifold VTUS

Order code – Manifold block

VABM	-	B10	-		-		-		-		
Manifold assembly parts											Assembly
Manifold block	VABM										E Supply manifold for mounting at one end
Valve series											- Standard mounting
VUWS		B10									
Valve width											Port for valve function
21 mm			20								- Manifold block for 5/2- and 5/3-way valves
26.5 mm			25								P3 Manifold block for 3/2-way valves
31 mm			30								P53 Supply manifold
Connection type											Number of valve positions
Supply manifold				-							2 ... 10 2 to 10
Compact manifold block				S							
Standard manifold block				E							
Extension module for standard manifold block				EEE							
Pneumatic connections 1, 3, 5											
G14					G 1/4						
G38					G 3/8						
G12					G 1/2						
G34					G 3/4						

Manifold block VABM

Technical data – Manifold block, size 20

FESTO

-  - Flow rate
Up to 700 l/min

-  - Valve width
21 mm



General technical data							
	Manifold block standard		Extension module for standard manifold block		Manifold block compact		Supply manifold
Valve function	3/2	5/2, 5/3	3/2	5/2, 5/3	3/2	5/2, 5/3	On both sides On one side
Grid dimension [mm]	22						
Type of mounting	With through-hole						With mounting bracket
Max. number of valve positions	10	10	2	2	10		10 4
Port 1	G3/8	G3/8	G3/8	G3/8	G1/4	G1/4	G3/8 G3/8
Port 3	G3/8	G3/8	G3/8	G3/8	G1/4	G1/4	– –
Port 5	–	G3/8	–	G3/8	–	G1/4	– –
Port 12	G1/8	G1/8	G1/8	G1/8	–	–	– –
Port 14	–	G1/8	–	G1/8	–	–	– –
CRC ¹⁾	2 ¹⁾						

1) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.

Weight [g]								
Valve positions	2	3	4	5	6	7	8	9 10
Manifold block for 3/2-way valves, standard								
VABM-B10-20E-G38-...-P3	449	574	699	825	950	1075	1200	1326 1451
Manifold block, extension module for 3/2-way valves, standard								
VABM-B10-20EEE-G38-2-P3	324	–	–	–	–	–	–	– –
Manifold block for 5/2- and 5/3-way valves, standard								
VABM-B10-20E-G38-...	680	866	1053	1239	1425	1612	1798	1985 2171
Manifold block, extension module for 5/2- and 5/3-way valves, standard								
VABM-B10-20EEE-G38-2	492	–	–	–	–	–	–	– –
Manifold block for 3/2-way valves, compact								
VABM-B10-20S-G14-...-P3	280	360	441	521	601	681	762	842 922
Manifold block for 5/2- and 5/3-way valves, compact								
VABM-B10-20S-G14-...	344	439	535	630	726	821	917	1012 1108
Supply manifold for mounting on both sides								
VABM-B10-20-G38-...-P53	226	268	310	352	395	437	479	521 563
Supply manifold for mounting on one side								
VABM-B10-20-G38-...-P53-E	240	282	324	–	–	–	–	– –


Information on materials								
Materials	Wrought aluminium alloy							
Note on materials	RoHS compliant							

Manifold block VABM

Technical data – Manifold block, size 20

Dimensions

Manifold block for 3/2-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B11	B14	B15	B16	B22
VABM-B10-20E-G38...-P3	75.5	53	66.5	63	50	24	12.5	11.5	25	5.5	31.5

Type	D1 Ø	D2	D4	H3	H4	H5	H6	H7	H9	L3	L4	L5	L9	T1
VABM-B10-20E-G38...-P3	4.5	M4x6.5	M5	37	23.5	8.5	18	5	32	6	25	22	9.5	15.5

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	72	94	116	138	160	182	204	226	248
L2 [mm]	60	82	104	126	148	170	192	214	236


Manifold block VABM

Technical data – Manifold block, size 20

FESTO

Dimensions

Manifold block, extension module for 3/2-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B16	H3	H4	H5	H6	H7	H9	L4	L5	L10
VABM-B10-20EEE-G38-2-P3	75.5	53	66.5	63	50	24	5.5	37	23.5	8.5	18	5	32	13	22	10


Valve positions	2
L1 [mm]	60

Manifold block VABM

Technical data – Manifold block, size 20

Dimensions

Manifold block for 5/2- and 5/3-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B10	B11	B14	B15	B22
VABM-B10-20E-G38...	110	100.5	97.5	73	81	55	29	12.5	42.5	25	20

Type	D1 Ø	D2	D4	H3	H4	H5	H6	H7	L3	L4	L5	L9	T1
VABM-B10-20E-G38...	4.5	M4x6.5	M5	37	23.5	22	18	8.5	6	25	22	9.5	15.5

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	72	94	116	138	160	182	204	226	248
L2 [mm]	60	82	104	126	148	170	192	214	236


Manifold block VABM

Technical data – Manifold block, size 20

FESTO

Dimensions

Manifold block, extension module for 5/2- and 5/3-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B10	H3	H4	H5	H6	H7	L4	L5	L10
VABM-B10-20EEE-G38-2	110	100.5	97.5	73	81	55	29	37	23.5	22	18	8.5	13	22	10


Valve positions	2
L1 [mm]	60

Manifold block VABM

Technical data – Manifold block, size 20

Dimensions

Manifold block for 3/2-way valves, compact



[1] Ports 1 and 3 (at both ends):

G1/4


Type	B4	B7	B8	B9	B11	B14	B15	B22	B23	B24
VABM-B10-20S-G14-...-P3	56.1	53.1	471	22	12.5	11.5	25	4	5	2

Type	D1 Ø	D2	H3	H4	H6	L3	L4	L5	L9
VABM-B10-20S-G14-...-P3	4.5	M4x6.5	33	9.7	18	6	25	22	9.5

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	72	94	116	138	160	182	204	226	248
L2 [mm]	60	82	104	126	148	170	192	214	236

Dimensions

Manifold block for 5/2- and 5/3-way valves, compact



[1] Ports 1, 3 and 5 (at both ends):

G1/4

Type	B4	B7	B8	B9	B10	B11	B14	B15	B22	B23
VABM-B10-20S-G14-...	64.2	47	55.1	32.1	9.1	12.5	149.6	25	4	5

Type	D1 Ø	D2	H3	H4	H6	L3	L4	L5	L9
VABM-B10-20S-G14-...	4.5	M4x6.5	36	9.7	22.5	6	25	22	9.5

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	72	94	116	138	160	182	204	226	248
L2 [mm]	60	82	104	126	148	170	192	214	236


Manifold block VABM

Technical data – Manifold block, size 20

FESTO

Dimensions

Supply manifold, mounting on both sides




Type	B4	B17	B18	B19	B20	B21	D1 Ø	D2	D3 Ø	H3	H12	H16	L3	L4	L5	L7	L9	W1
VABM-B10-20-G38....P53	23	55	40	20	20	8.5	4.5	M4x6.5	5.2	40	2	13	9	21	22	22	5	31.3°

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	64	86	108	130	152	174	196	218	240
L2 [mm]	90	112	134	156	178	200	222	244	266
L8 [mm]	106	128	150	172	194	216	238	260	282

Dimensions

Supply manifold, mounting on one side









Type	B4	B17	B18	B19	B21	D1 Ø	D2	D3 Ø	H3	H13	H14	L4	L5	L7	L9	W1
VABM-B10-20-G38....P53-E	23	55	40	20	8.5	4.5	M4x6.5	5.2	40	106	90	21	22	50	5	30°

Valve positions	2	3	4
L1 [mm]	64	86	108
L8 [mm]	114	136	158

Manifold block VABM



Ordering data – Manifold block, size 20

Ordering data		Valve positions	Part No.	Type
Description				
Standard manifold block				
	For 3/2-way valves, incl. seals and screws for mounting valves -  - Note Blanking plugs for sealing the supply ports (1, 3 and 14) at one end are included in the scope of delivery.	2 3 4 5 6 7 8 9 10	576441 576442 576443 576444 576445 576446 576447 576448 576449	VABM-B10-20E-G38-2-P3 VABM-B10-20E-G38-3-P3 VABM-B10-20E-G38-4-P3 VABM-B10-20E-G38-5-P3 VABM-B10-20E-G38-6-P3 VABM-B10-20E-G38-7-P3 VABM-B10-20E-G38-8-P3 VABM-B10-20E-G38-9-P3 VABM-B10-20E-G38-10-P3
	For 5/2 and 5/3-way valves, incl. seals and screws for valve assembly -  - Note Blanking plugs for sealing the supply ports (1, 3, 5, 12 and 14) at one end are included in the scope of delivery.	2 3 4 5 6 7 8 9 10	576339 576340 576341 576342 576343 576344 576345 576346 576347	VABM-B10-20E-G38-2 VABM-B10-20E-G38-3 VABM-B10-20E-G38-4 VABM-B10-20E-G38-5 VABM-B10-20E-G38-6 VABM-B10-20E-G38-7 VABM-B10-20E-G38-8 VABM-B10-20E-G38-9 VABM-B10-20E-G38-10
Manifold block, extension module for standard manifold block				
	For 3/2-way valves, incl. seals and screws for valve assembly	2	576490	VABM-B10-20EEE-G38-2-P3
	For 5/2 and 5/3-way valves, incl. seals and screws for valve assembly	2	576489	VABM-B10-20EEE-G38-2
Compact manifold block				
	For 3/2-way valves, incl. seals and screws for mounting valves -  - Note Blanking plugs for sealing the supply ports (1 and 3) at one end are included in the scope of delivery.	2 3 4 5 6 7 8 9 10	576465 576466 576467 576468 576469 576470 576471 576472 576473	VABM-B10-20S-G14-2-P3 VABM-B10-20S-G14-3-P3 VABM-B10-20S-G14-4-P3 VABM-B10-20S-G14-5-P3 VABM-B10-20S-G14-6-P3 VABM-B10-20S-G14-7-P3 VABM-B10-20S-G14-8-P3 VABM-B10-20S-G14-9-P3 VABM-B10-20S-G14-10-P3
	For 5/2 and 5/3-way valves, incl. seals and screws for valve assembly -  - Note Blanking plugs for sealing the supply ports (1, 3 and 5) at one end are included in the scope of delivery.	2 3 4 5 6 7 8 9 10	576417 576418 576419 576420 576421 576422 576423 576424 576425	VABM-B10-20S-G14-2 VABM-B10-20S-G14-3 VABM-B10-20S-G14-4 VABM-B10-20S-G14-5 VABM-B10-20S-G14-6 VABM-B10-20S-G14-7 VABM-B10-20S-G14-8 VABM-B10-20S-G14-9 VABM-B10-20S-G14-10

Manifold block VABM



Ordering data – Manifold block, size 20

Ordering data		Valve positions	Part No.	Type
Description				
Supply manifold				
	For mounting on both sides, incl. seals and screws for mounting valves	2	576363	VABM-B10-20-G38-2-P53
		3	576364	VABM-B10-20-G38-3-P53
		4	576365	VABM-B10-20-G38-4-P53
		5	576366	VABM-B10-20-G38-5-P53
		6	576367	VABM-B10-20-G38-6-P53
		7	576368	VABM-B10-20-G38-7-P53
		8	576369	VABM-B10-20-G38-8-P53
		9	576370	VABM-B10-20-G38-9-P53
		10	576371	VABM-B10-20-G38-10-P53
	For mounting on one side, incl. seals and screws for valve assembly	2	576414	VABM-B10-20-G38-2-P53-E
		3	576415	VABM-B10-20-G38-3-P53-E
		4	576416	VABM-B10-20-G38-4-P53-E







Note

Blanking plug for sealing the supply port (1) at one end included in the scope of delivery.

Manifold block VABM

Accessories – Manifold block, size 20

Ordering data		Weight [g]	Part No.	Type
Description				
Blanking plate				
	For valve position on manifold block for 5/2-, 5/3-way valves	78	576410	VABB-B10-20-E
	For valve position on manifold block for 3/2-way valves	56	576411	VABB-B10-20-E-P3
	For valve position on supply manifold	13	576409	VABB-B10-20-A
Supply plate				
	For valve position on manifold block for 5/2-, 5/3-way valves	78	576492	VABF-B10-20-P1A4-G18
	For valve position on manifold block for 3/2-way valves	56	576493	VABF-B10-20-P1A4-G18-P3
Supply plate				
	For valve position on supply manifold	13	576491	VABF-B10-20-P1-G18

Manifold block VABM


Accessories – Manifold block, size 20

Ordering data		Description	Part No.	Type	PU ¹⁾
Push-in fitting with external hex					
	Connecting thread M5 for tubing O.D.	12 mm	186350	QS-G1/4-12	10
	Connecting thread G3/8 for tubing O.D.	16 mm	186347	QS-G3/8-16	1
Push-in fitting with internal hex					
	Connecting thread M5 for tubing O.D.	4 mm	153315	QSM-M5-4-I	10
	Connecting thread G1/8 for tubing O.D.	4 mm	186106	QS-G1/8-4-I	10
		6 mm	133008	QS-G1/8-4-I-100	100
		8 mm	186107	QS-G1/8-6-I	10
		10 mm	133009	QS-G1/8-6-I-100	100
		12 mm	186109	QS-G1/8-8-I	10
		14 mm	133010	QS-G1/8-8-I-100	100
	Connecting thread G1/4 for tubing O.D.	8 mm	186110	QS-G1/4-8-I	10
	Connecting thread G3/8 for tubing O.D.	10 mm	186112	QS-G1/4-10-I	10
		12 mm	186111	QS-G3/8-8-I	10
		14 mm	186113	QS-G3/8-10-I	10
		16 mm	186114	QS-G3/8-12-I	10
Angled push-in fitting with external hex					
	Connecting thread G1/8 for tubing O.D.	4 mm	186116	QSL-G1/8-4	10
		6 mm	132048	QSL-G1/8-4-100	100
		8 mm	186117	QSL-G1/8-6	10
		10 mm	132049	QSL-G1/8-6-100	100
		12 mm	186119	QSL-G1/8-8	10
		14 mm	132050	QSL-G1/8-8-50	50
		16 mm	186120	QSL-G1/4-8	10
		18 mm	132052	QSL-G1/4-8-50	50
	Connecting thread G1/4 for tubing O.D.	20 mm	186122	QSL-G1/4-10	10
		22 mm	132053	QSL-G1/4-10-50	50
		24 mm	186351	QSL-G1/4-12	10
		26 mm	132054	QSL-G1/4-12-20	20
	Connecting thread G3/8 for tubing O.D.	28 mm	186121	QSL-G3/8-8	10
		30 mm	132055	QSL-G3/8-8-50	50
		32 mm	186123	QSL-G3/8-10	10
		34 mm	132056	QSL-G3/8-10-20	20
		36 mm	186124	QSL-G3/8-12	10
		38 mm	132057	QSL-G3/8-12-20	20
Angled push-in fitting with external hex					
	Connecting thread G1/8 for tubing O.D.	4 mm	186116	QSL-G1/8-4	10
		6 mm	132048	QSL-G1/8-4-100	100
		8 mm	186117	QSL-G1/8-6	10
		10 mm	132049	QSL-G1/8-6-100	100
		12 mm	186119	QSL-G1/8-8	10
		14 mm	132050	QSL-G1/8-8-50	50

1) Packaging unit

Manifold block VABM

Accessories – Manifold block, size 20

Ordering data		Description	Part No.	Type	PU ¹⁾
Silencer					
	With connecting thread G	G1/8	2307	U-1/8	1
			534222	U-1/8-50	50
		G1/4	2316	U-1/4	1
			534223	U-1/4-20	20
		G3/8	6843	U-3/8-B	1
Blanking plug					
	With connecting thread G	G1/8	3568	B-1/8	10
			534213	B-1/8-100	100
		G1/4	3569	B-1/4	10
			534214	B-1/4-50	50
		G3/8	3570	B-3/8	10
			534215	B-3/8-20	20
Separator					
	For creating pressure zones	G1/4	569996	VABD-10-B	1
		G3/8	574483	VABD-14-B	1
H-rail mounting					
	For size 20, for mounting on standard H-rails TH 35-7.5 or TH 35-15 to EN 60715		569998	VAME-T-M4	2

1) Packaging unit

Manifold block VABM

Technical data – Manifold block, size 25

FESTO

-  - Flow rate
Up to 1300 l/min

-  - Valve width
26.5 mm



General technical data								
	Manifold block standard		Extension module for standard manifold block		Manifold block compact		Supply manifold	
							On both sides	On one side
For valves	3/2	5/2, 5/3	3/2	5/2, 5/3	3/2	5/2, 5/3	3/2, 5/2, 5/3	
Grid dimension [mm]	27.5							
Type of mounting	With through-hole							With mounting bracket
Maximum number of valve positions	10	10	2	2	10	10	10	4
Port 1	G1/2	G1/2	G1/2	G1/2	G3/8	G3/8	G1/2	G1/2
Port 3	G1/2	G1/2	G1/2	G1/2	G3/8	G3/8	–	–
Port 5	–	G1/2	–	G1/2	–	G3/8	–	–
Port 12	G1/8	G1/8	G1/8	G1/8	–	–	–	–
Port 14	–	G1/8	–	G1/8	–	–	–	–
CRC ¹⁾	2 ¹⁾							

1) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.

Weight [g]									
Valve positions	2	3	4	5	6	7	8	9	10
Manifold block for 3/2-way valves, standard									
VABM-B10-25E...G12...-P3	726	960	1194	1428	1662	1896	2130	2364	2598
Manifold block, extension module for 3/2-way valves, standard									
VABM-B10-25EEE-G12-2-P3	340	–	–	–	–	–	–	–	–
Manifold block for 5/2- and 5/3-way valves, standard									
VABM-B10-25E...G12...-P3	927	1224	1521	1818	2115	2412	2709	3006	3303
Manifold block, extension module for 5/2- and 5/3-way valves, standard									
VABM-B10-25EEE-G12-2	258	–	–	–	–	–	–	–	–
Manifold block for 3/2-way valves, compact									
VABM-B10-25S...G38...-P3	369	488	607	726	845	964	1083	1202	1321
Manifold block for 5/2- and 5/3-way valves, compact									
VABM-B10-25S...G38...-P3	438	579	720	861	1002	1143	1284	1425	1566
Supply manifold for mounting on both sides									
VABM-B10-25...G12...-P53	258	340	422	504	586	668	750	832	914
Supply manifold for mounting on one side									
VABM-B10-25-G12...-P53-E	258	340	422	–	–	–	–	–	–


Information on materials									
Materials	Wrought aluminium alloy								
Note on materials	RoHS compliant								

Manifold block VABM

Technical data – Manifold block, size 25

Dimensions

Manifold block for 3/2-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B11	B14	B15	B16	B22
VABM-B10-25-E...G12-...P3	93	67.5	80.5	78	62	30	16	14	32	6	37

Type	D1 Ø	D2	D4	H3	H4	H5	H6	H7	H9	L3	L4	L5	L9	T1
VABM-B10-25-E...G12-...P3	5.5	M4x9	M5	45	25	9	22	5	39	6	29.8	27.5	9.5	18

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
L2 [mm]	75	102.5	130	157.5	185	212.5	240	267.5	295


Manifold block VABM

Technical data – Manifold block, size 25

FESTO

Dimensions

Manifold block, extension module for 3/2-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B16	H3	H4	H5	H6	H7	H9	L4	L5	L10
VABM-B10-25EEE-G12-2-P3	93	67.5	80.5	78	62	30	6	45	25	9	22	5	39	18.8	27.5	9


Valve positions	2
L1 [mm]	76

Manifold block VABM

Technical data – Manifold block, size 25

Dimensions

Manifold block for 5/2- and 5/3-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B10	B11	B14	B15	B22
VABM-B10-25E...-G12...	126	119	113.5	80	95	63	31	16	47	32	27

Type	D1 Ø	D2	D4	H3	H4	H5	H6	H7	L3	L4	L5	L9	T1
VABM-B10-25E...-G12...	5.5	M4x9	M5	45	25	22	22	9	6	29.8	27.5	10.5	18

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
L2 [mm]	75	102.5	130	157.5	185	212.5	240	267.5	295


Manifold block VABM

Technical data – Manifold block, size 25

FESTO

Dimensions

Manifold block, extension module for 5/2- and 5/3-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B10	H3	H4	H5	H6	H7	L4	L5	L10
VABM-B10-20EEE-G12-2	126	119	113.5	80	95	63	31	45	25	22	22	9	18.8	27.5	9


Valve positions	2
L1 [mm]	76

Manifold block VABM

Technical data – Manifold block, size 25

Dimensions

Manifold block for 3/2-way valves, compact



Type	B4	B7	B8	B9	B11	B14	B15	B22	B23
VABM-B10-25S...G38-...-P3	70.3	67.3	58.8	30	16	14	32	6.5	5

Type	D1 Ø	D2	H3	H4	H6	L3	L4	L5	L9
VABM-B10-25S...G38-...-P3	5.5	M4x9	34	13.5	20	6	29.8	27.5	9.5

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
L2 [mm]	75	102.5	130	157.5	185	212.5	240	267.5	295


Manifold block VABM

Technical data – Manifold block, size 25

FESTO

Dimensions

Manifold block for 5/2- and 5/3-way valves, compact



Type	B4	B7	B8	B9	B10	B11	B14	B15	B22	B23
VABM-B10-25S...G38-...	80.5	61.5	69	40.3	11.5	16	24.3	32	6.5	8

Type	D1 Ø	D2	H3	H4	H6	L3	L4	L5	L9
VABM-B10-25S...G38-...	5.5	M4x9	34	13.5	20	6	29.8	27.5	9.5


Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
L2 [mm]	75	102.5	130	157.5	185	212.5	240	267.5	295

Manifold block VABM

Technical data – Manifold block, size 25

Dimensions

Supply manifold, mounting on both sides




Type	B4	B17	B18	B19	B20	B21	D1 Ø	D2	D3 Ø	H3	H12	H16	L3	L4	L5	L7	L9	W1
VABM-B10-25-G12...-P53	28.7	75	60	35	27.5	11.4	4.5	M4x9	6.6	52	2	19	8	29.8	27.5	24	6	30

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	87	114.5	142	169.5	197	224.5	252	279.5	307
L2 [mm]	119	146.5	174	201.5	229	256.5	284	311.5	339
L8 [mm]	135	162.5	190	217.5	245	272.5	300	327.5	355

Dimensions

Supply manifold, mounting on one side









Type	B4	B17	B18	B19	B21	D1 Ø	D2	D3 Ø	H3	H13	H14	L4	L5	L7	L9	W1
VABM-B10-25-G12...-P53-E	28.7	80	60	35	11.4	4.5	M4x9	6.6	52	128	112	29.8	27.5	64	6	30°

Valve positions	2	3	4
L1 [mm]	87	114.5	142
L8 [mm]	151	178.5	206

Manifold block VABM





Ordering data – Manifold block, size 25

Ordering data			
Description	Valve positions	Part No.	Type
Standard manifold block			
	For 3/2-way valves, incl. seals and screws for mounting valves	2 3 4 5 6 7 8 9 10	8026279 VABM-B10-25E-G12-2-P3 8026280 VABM-B10-25E-G12-3-P3 8026281 VABM-B10-25E-G12-4-P3 8026282 VABM-B10-25E-G12-5-P3 8026283 VABM-B10-25E-G12-6-P3 8026284 VABM-B10-25E-G12-7-P3 8026285 VABM-B10-25E-G12-8-P3 8026286 VABM-B10-25E-G12-9-P3 8026287 VABM-B10-25E-G12-10-P3
	For 5/2 and 5/3-way valves, incl. seals and screws for valve assembly	2 3 4 5 6 7 8 9 10	8026243 VABM-B10-25E-G12-2 8026244 VABM-B10-25E-G12-3 8026245 VABM-B10-25E-G12-4 8026246 VABM-B10-25E-G12-5 8026247 VABM-B10-25E-G12-6 8026248 VABM-B10-25E-G12-7 8026249 VABM-B10-25E-G12-8 8026250 VABM-B10-25E-G12-9 8026251 VABM-B10-25E-G12-10
Manifold block, extension module for standard manifold block			
	For 3/2-way valves, incl. seals and screws for valve assembly	2	8026316 VABM-B10-25EEE-G12-2-P3
	For 5/2 and 5/3-way valves, incl. seals and screws for valve assembly	2	8026315 VABM-B10-25EEE-G12-2
Compact manifold block			
	For 3/2-way valves, incl. seals and screws for mounting valves	2 3 4 5 6 7 8 9 10	8026297 VABM-B10-25S-G38-2-P3 8026298 VABM-B10-25S-G38-3-P3 8026299 VABM-B10-25S-G38-4-P3 8026300 VABM-B10-25S-G38-5-P3 8026301 VABM-B10-25S-G38-6-P3 8026302 VABM-B10-25S-G38-7-P3 8026303 VABM-B10-25S-G38-8-P3 8026304 VABM-B10-25S-G38-9-P3 8026305 VABM-B10-25S-G38-10-P3
	For 5/2 and 5/3-way valves, incl. seals and screws for valve assembly	2 3 4 5 6 7 8 9 10	8026261 VABM-B10-25S-G38-2 8026262 VABM-B10-25S-G38-3 8026263 VABM-B10-25S-G38-4 8026264 VABM-B10-25S-G38-5 8026265 VABM-B10-25S-G38-6 8026266 VABM-B10-25S-G38-7 8026267 VABM-B10-25S-G38-8 8026268 VABM-B10-25S-G38-9 8026269 VABM-B10-25S-G38-10

Manifold block VABM

Ordering data – Manifold block, size 25

Ordering data		Valve positions	Part No.	Type
Description				
Supply manifold				
	For mounting on both sides, incl. seals and screws for mounting valves	2 3 4 5 6 7 8 9 10	8026219 8026220 8026221 8026222 8026223 8026224 8026225 8026226 8026227	VABM-B10-25-G12-2-P53 VABM-B10-25-G12-3-P53 VABM-B10-25-G12-4-P53 VABM-B10-25-G12-5-P53 VABM-B10-25-G12-6-P53 VABM-B10-25-G12-7-P53 VABM-B10-25-G12-8-P53 VABM-B10-25-G12-9-P53 VABM-B10-25-G12-10-P53
	For mounting on one side, incl. seals and screws for valve assembly	2 3 4	8026237 8026238 8026239	VABM-B10-25-G12-2-P53-E VABM-B10-25-G12-3-P53-E VABM-B10-25-G12-4-P53-E





-  - Note

Blanking plug for sealing the supply port (1) at one end included in the scope of delivery.

Manifold block VABM


Accessories – Manifold block, size 25

FESTO

Ordering data			
Description	Weight [g]	Part No.	Type
Blanking plate			
	For valve position on manifold block for 5/2-, 5/3-way valves	117	8026209 VABB-B10-25-E
	For valve position on manifold block for 3/2-way valves	84	8026210 VABB-B10-25-E-P3
	For valve position on supply manifold	28	8026208 VABB-B10-25-A
Supply plate			
	For valve position on manifold block for 5/2-, 5/3-way valves	110	8026318 VABF-B10-25-P1A4-G14
	For valve position on manifold block for 3/2-way valves	80	8026319 VABF-B10-25-P1A4-G14-P3
Supply plate			
	For valve position on supply manifold	26	8026317 VABF-B10-25-P1-G14

Manifold block VABM

Accessories – Manifold block, size 25


Ordering data		Description	Part No.	Type	PU ¹⁾
Push-in fitting with external hex					
	Connecting thread G3/8 for tubing O.D.	16 mm	186347	QS-G3/8-16	1
	Connecting thread G1/2 for tubing O.D.	16 mm	186105	QS-G1/2-16	1
			132047	QS-G1/2-16-20	20
Push-in fitting with internal hex					
	Connecting thread M5 for tubing O.D.	4 mm	153315	QSM-M5-4-I	10
	Connecting thread G1/8 for tubing O.D.	6 mm	186107	QS-G1/8-6-I	10
			133009	QS-G1/8-6-I-100	100
	Connecting thread G1/4 for tubing O.D.	6 mm	186108	QS-G1/4-6-I	10
		8 mm	186110	QS-G1/4-8-I	10
		10 mm	186112	QS-G1/4-10-I	10
	Connecting thread G3/8 for tubing O.D.	8 mm	186111	QS-G3/8-8-I	10
		10 mm	186113	QS-G3/8-10-I	10
		12 mm	186114	QS-G3/8-12-I	10
	Connecting thread G1/2 for tubing O.D.	12 mm	186115	QS-G1/2-12-I	1
Angled push-in fitting with external hex					
	Connecting thread G1/4 for tubing O.D.	6 mm	186118	QSL-G1/4-6	10
			132051	QSL-G1/4-6-100	100
		8 mm	186120	QSL-G1/4-8	10
			132052	QSL-G1/4-8-50	50
		10 mm	186122	QSL-G1/4-10	10
			132053	QSL-G1/4-10-50	50
	Connecting thread G3/8 for tubing O.D.	8 mm	186121	QSL-G3/8-8	10
			132055	QSL-G3/8-8-50	50
		10 mm	186123	QSL-G3/8-10	10
			132056	QSL-G3/8-10-20	20
		12 mm	186124	QSL-G3/8-12	10
			132057	QSL-G3/8-12-20	20
	Connecting thread G1/2 for tubing O.D.	16 mm	186348	QSL-G3/8-16	1
		12 mm	186125	QSL-G1/2-12	1
			132058	QSL-G1/2-12-20	20
		16 mm	186126	QSL-G1/2-16	1
		132059	QSL-G1/2-16-20	20	
Angled push-in fitting, long, with external hex					
	Connecting thread G1/4 for tubing O.D.	6 mm	186129	QSLL-G1/4-6	10
		8 mm	186131	QSLL-G1/4-8	10
		10 mm	186133	QSLL-G1/4-10	10

1) Packaging unit

Manifold block VABM

Accessories – Manifold block, size 25

FESTO

Ordering data		Description	Part No.	Type	PU ¹⁾
Silencer					
	With connecting thread G	G1/4	2316	U-1/4	1
			534223	U-1/4-20	20
		G3/8	6843	U-3/8-B	1
			534224	U-3/8-20	20
		G1/2	6844	U-1/2-B	1
Blanking plug					
	With connecting thread G	G1/8	3568	B-1/8	10
			534213	B-1/8-100	100
		G3/8	3570	B-3/8	10
			534215	B-3/8-20	20
		G1/2	3571	B-1/2	10
			534216	B-1/2-20	20
Separator					
	For creating pressure zones	G1/8	569995	VABD-8-B	1
		G3/8	574483	VABD-14-B	1
		G1/2	8022483	VABD-17.5-B	1
H-rail mounting					
	For size 25, for mounting on standard H-rails TH 35-7.5 or TH 35-15 to EN 60715		2636436	VAME-T-M5	2

1) Packaging unit

Manifold block VABM

Technical data – Manifold block, size 30

-  - Flow rate
Up to 2300 l/min

-  - Valve width
31 mm

**General technical data**

	Manifold block standard		Extension module for standard manifold block		Manifold block compact		Supply manifold	
							On both sides	On one side
For valves	3/2	5/2, 5/3	3/2	5/2, 5/3	3/2	5/2, 5/3	3/2, 5/2, 5/3	3/2, 5/2, 5/3
Grid dimension [mm]	32							
Type of mounting	With through-hole							
Maximum number of valve positions	10	10	2	2	10	10	10	4
Port 1	G3/4	G3/4	G3/4	G3/4	G1/2	G1/2	G3/4	G3/4
Port 3	G3/4	G3/4	G3/4	G3/4	G1/2	G1/2	–	–
Port 5	–	G3/4	–	G3/4	–	G1/2	–	–
Port 12	G1/8	G1/8	G1/8	G1/8	–	–	–	–
Port 14	–	G1/8	–	G1/8	–	–	–	–
CRC ¹⁾	2 ¹⁾							

1) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation may occur. External visible parts with primarily decorative requirements for the surface and which are in direct contact with the ambient atmosphere typical for industrial applications.

Weight [g]

Valve positions	2	3	4	5	6	7	8	9	10
Manifold block for 3/2-way valves, standard									
VABM-B10-30E-G34-...-P3	1411	1828	2245	2662	3079	3496	3913	4330	4747
Manifold block, extension module for 3/2-way valves, standard									
VABM-B10-30EEE-G34-2-P3	1111	–	–	–	–	–	–	–	–
Manifold block for 5/2- and 5/3-way valves, standard									
VABM-B10-30E-G34-...	1722	2213	2703	3194	3684	4175	4665	5156	5646
Manifold block, extension module for 5/2- and 5/3-way valves, standard									
VABM-B10-30EEE-G34-2	1318	–	–	–	–	–	–	–	–
Manifold block for 3/2-way valves, compact									
VABM-B10-30S-G12-...-P3	652	872	1093	1313	1533	1753	1973	2193	2413
Manifold block for 5/2- and 5/3-way valves, compact									
VABM-B10-30S-G12-...	759	1013	1267	1522	1776	2030	2285	2539	2793
Supply manifold for mounting on both sides									
VABM-B10-30-G34-...-P53	818	977	1135	1293	1452	1610	1768	1927	2085
Supply manifold for mounting on one side									
VABM-B10-30-G34-...-P53-E	852	1011	1169	–	–	–	–	–	–

Information on materials

Materials	Wrought aluminium alloy
Note on materials	RoHS compliant


Manifold block VABM

Technical data – Manifold block, size 30

FESTO

Dimensions

Manifold block for 3/2-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B11	B14	B15	B16	B22
VABM-B10-30-E-G34-...-P3	108.2	79	93.2	94.7	75.7	36.2	19	17.2	38	6.5	44.5

Type	D1 Ø	D2	D4	H3	H4	H5	H6	H7	H9	L3	L4	L5	L9	T1
VABM-B10-30-E-G34-...-P3	6.3	M5x11	M5	61	35	9	28.5	6.5	54.5	7.5	34	32	12	18


Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	100	132	164	196	228	260	292	324	356
L2 [mm]	85	117	149	181	213	245	277	309	341

Manifold block VABM

Technical data – Manifold block, size 30

Dimensions

Manifold block, extension module for 3/2-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B10	H3	H4	H5	H6	H7	H9	L4	L5	L10
VABM-B10-30EEE-G34-2-P3	108.2	79	93.2	94.7	75.7	36.2	6.5	61	35	9	28.5	6.5	54.5	19	32	15

Valve positions	2
L1 [mm]	85


Manifold block VABM

Technical data – Manifold block, size 30

FESTO

Dimensions

Manifold block for 5/2- and 5/3-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B10	B11	B14	B15	B22
VABM-B10-30E-G34-...	144	137	129	104	111.5	72	32.5	19	53	38	30

Type	D1 Ø	D2	D4	H3	H4	H5	H6	H7	L3	L4	L5	L9	T1
VABM-B10-30E-G34-...	6.3	M5*11	M5	61	35	22	28.5	9	7.5	34	32	12	18


Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	100	132	164	196	228	260	292	324	356
L2 [mm]	85	117	149	181	213	245	277	309	341

Manifold block VABM

Technical data – Manifold block, size 30

Dimensions

Manifold block, extension module for 5/2- and 5/3-way valves, standard



Type	B4	B5	B6	B7	B8	B9	B10	H3	H4	H5	H6	H7	L4	L5	L10
VABM-B10-30EEE-G34-2	144	137	129	104	111.5	72	32.5	61	35	22	28.5	9	19	32	15

Valve positions	2
L1 [mm]	85


Manifold block VABM

Technical data – Manifold block, size 30

FESTO

Dimensions

Manifold block for 3/2-way valves, compact



Type	B4	B7	B8	B9	B11	B14	B15	B22	B23
VABM-B10-30S-G12-...-P3	83	80	69.4	36	19	17	38	7	8

Type	D1 Ø	D2	H3	H4	H6	L3	L4	L5	L9
VABM-B10-30S-G12-...-P3	6.3	M5x11	42.5	17.5	26	7.5	38	32	12


Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	100	132	164	196	228	260	292	324	356
L2 [mm]	85	117	149	181	213	245	277	309	341

Manifold block VABM

Technical data – Manifold block, size 30

Dimensions

Manifold block for 5/2- and 5/3-way valves, compact



Type	B4	B7	B8	B9	B10	B11	B14	B15	B22	B23
VABM-B10-30S-G12-...	94	77	80.4	47	13.6	19	28	38	6.5	10

Type	D1 Ø	D2	H3	H4	H6	L3	L4	L5	L9
VABM-B10-30S-G12-...	6.3	M5x11	42.5	17.5	26	7.5	34	32	12

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	100	132	164	196	228	260	292	324	356
L2 [mm]	85	117	149	181	213	245	277	309	341


Manifold block VABM

Technical data – Manifold block, size 30

FESTO

Dimensions

Supply manifold, mounting on both sides




Type	B4	B17	B18	B19	B20	B21	D1 Ø	D2	D3 Ø	H3	H12	H16	L3	L4	L5	L7	L9	W1
VABM-B10-30-G34-...-P53	34	85	65	35	33.5	13	5.5	M5x11	8.6	65	2.5	19.5	9	34	32	26	10	28°

Valve positions	2	3	4	5	6	7	8	9	10
L1 [mm]	100	132	164	196	228	260	292	324	356
L2 [mm]	134	166	198	230	262	294	326	358	390
L8 [mm]	152	184	216	248	280	312	344	376	408

Dimensions

Supply manifold, mounting on one side









Type	B4	B17	B18	B19	B21	D1 Ø	D2	D3 Ø	H3	H13	H14	L4	L5	L7	L9	W1
VABM-B10-30-G34-...-P53-E	34	85	65	35	13	5.5	M5x11	8.6	65	146	128	34	32	74	10	30°

Valve positions	2	3	4
L1 [mm]	100	132	164
L8 [mm]	168	200	232

Manifold block VABM



Ordering data – Manifold block, size 30

Ordering data		Valve positions	Part No.	Type
Description				
Standard manifold block				
	For 3/2-way valves, incl. seals and screws for mounting valves -  - Note Blanking plugs for sealing the supply ports (1, 3 and 14) at one end are included in the scope of delivery.	2 3 4 5 6 7 8 9 10	8026395 8026396 8026397 8026398 8026399 8026400 8026401 8026402 8026403	VABM-B10-30E-G34-2-P3 VABM-B10-30E-G34-3-P3 VABM-B10-30E-G34-4-P3 VABM-B10-30E-G34-5-P3 VABM-B10-30E-G34-6-P3 VABM-B10-30E-G34-7-P3 VABM-B10-30E-G34-8-P3 VABM-B10-30E-G34-9-P3 VABM-B10-30E-G34-10-P3
	For 5/2 and 5/3-way valves, incl. seals and screws for valve assembly -  - Note Blanking plugs for sealing the supply ports (1, 3, 5, 12 and 14) at one end are included in the scope of delivery.	2 3 4 5 6 7 8 9 10	8026359 8026360 8026361 8026362 8026363 8026364 8026365 8026366 8026367	VABM-B10-30E-G34-2 VABM-B10-30E-G34-3 VABM-B10-30E-G34-4 VABM-B10-30E-G34-5 VABM-B10-30E-G34-6 VABM-B10-30E-G34-7 VABM-B10-30E-G34-8 VABM-B10-30E-G34-9 VABM-B10-30E-G34-10
Manifold block, extension module for standard manifold block				
	For 3/2-way valves, incl. seals and screws for valve assembly	2	8026432	VABM-B10-30EEE-G34-2-P3
	For 5/2 and 5/3-way valves, incl. seals and screws for valve assembly	2	8026431	VABM-B10-30EEE-G34-2
Compact manifold block				
	For 3/2-way valves, incl. seals and screws for mounting valves -  - Note Blanking plugs for sealing the supply ports (1 and 3) at one end are included in the scope of delivery.	2 3 4 5 6 7 8 9 10	8026413 8026414 8026415 8026416 8026417 8026418 8026419 8026420 8026421	VABM-B10-30S-G12-2-P3 VABM-B10-30S-G12-3-P3 VABM-B10-30S-G12-4-P3 VABM-B10-30S-G12-5-P3 VABM-B10-30S-G12-6-P3 VABM-B10-30S-G12-7-P3 VABM-B10-30S-G12-8-P3 VABM-B10-30S-G12-9-P3 VABM-B10-30S-G12-10-P3
	For 5/2 and 5/3-way valves, incl. seals and screws for valve assembly -  - Note Blanking plugs for sealing the supply ports (1, 3 and 5) at one end are included in the scope of delivery.	2 3 4 5 6 7 8 9 10	8026377 8026378 8026379 8026380 8026381 8026382 8026383 8026384 8026385	VABM-B10-30S-G12-2 VABM-B10-30S-G12-3 VABM-B10-30S-G12-4 VABM-B10-30S-G12-5 VABM-B10-30S-G12-6 VABM-B10-30S-G12-7 VABM-B10-30S-G12-8 VABM-B10-30S-G12-9 VABM-B10-30S-G12-10

Manifold block VABM



Ordering data – Manifold block, size 30

Ordering data		Valve positions	Part No.	Type
Description				
Supply manifold				
	For mounting on both sides, incl. seals and screws for mounting valves	2	8026338	VABM-B10-30-G34-2-P53
		3	8026339	VABM-B10-30-G34-3-P53
		4	8026340	VABM-B10-30-G34-4-P53
		5	8026341	VABM-B10-30-G34-5-P53
		6	8026342	VABM-B10-30-G34-6-P53
		7	8026343	VABM-B10-30-G34-7-P53
		8	8026344	VABM-B10-30-G34-8-P53
		9	8026345	VABM-B10-30-G34-9-P53
		10	8026346	VABM-B10-30-G34-10-P53
	For mounting on one side, incl. seals and screws for valve assembly	2	8026356	VABM-B10-30-G34-2-P53-E
		3	8026357	VABM-B10-30-G34-3-P53-E
		4	8026358	VABM-B10-30-G34-4-P53-E







Note

Blanking plug for sealing the supply port (1) at one end included in the scope of delivery.

Manifold block VABM

Accessories – Manifold block, size 30

Ordering data		Weight [g]	Part No.	Type
Description				
Blanking plate				
	For valve position on manifold block for 3/2-way valves	128	8026336	VABB-B10-30-E-P3
	For valve position on manifold block for 5/2-, 5/3-way valves	179	8026335	VABB-B10-30-E
	For valve position on supply manifold	43	8026334	VABB-B10-30-A
Supply plate				
	For valve position on manifold block for 3/2-way valves	121	8026435	VABF-B10-30-P1A4-G38-P3
	For valve position on manifold block for 5/2-, 5/3-way valves	167	8026434	VABF-B10-30-P1A4-G38
Supply plate				
	For valve position on supply manifold	40	8026433	VABF-B10-30-P1-G38

Manifold block VABM

Accessories – Manifold block, size 30

Ordering data		Description	Part No.	Type	PU ¹⁾
Push-in fitting with internal hex					
	Connecting thread G1/8 for tubing O.D.	4 mm	186106	QS-G1/8-4-I	10
			133008	QS-G1/8-4-I-100	100
	Connecting thread G3/8 for tubing O.D.	6 mm	186107	QS-G1/8-6-I	10
			133009	QS-G1/8-6-I-100	100
	Connecting thread G1/2 for tubing O.D.	8 mm	186111	QS-G3/8-8-I	10
			186113	QS-G3/8-10-I	10
			186114	QS-G3/8-12-I	10
		12 mm	186115	QS-G1/2-12-I	1
Push-in fitting with external hex					
	Connecting thread G1/2 for tubing O.D.	16 mm	186105	QS-G1/2-16	1
			132047	QS-G1/2-16-20	20
Angled push-in fitting with external hex					
	Connecting thread G3/8 for tubing O.D.	8 mm	186121	QSL-G3/8-8	10
			132055	QSL-G3/8-8-50	50
		10 mm	186123	QSL-G3/8-10	10
			132056	QSL-G3/8-10-20	20
	Connecting thread G1/2 for tubing O.D.	12 mm	186124	QSL-G3/8-12	10
			132057	QSL-G3/8-12-20	20
		12 mm	186125	QSL-G1/2-12	1
			132058	QSL-G1/2-12-20	20
		16 mm	186126	QSL-G1/2-16	1
			132059	QSL-G1/2-16-20	20
Angled push-in fitting, long, with external hex					
	Connecting thread G1/2 for tubing O.D.	8 mm	186132	QSLL-G3/8-8	10
		10 mm	186134	QSLL-G3/8-10	10
		12 mm	186135	QSLL-G3/8-12	10
Barbed fitting with external hex					
	Connecting thread G3/4 for tubing I.D. Aluminium design	13 mm	3612	N-3/4-P-13	1
		19 mm	3613	N-3/4-P-19	1
	Connecting thread G3/4 for tubing I.D. Brass design	13 mm	15637	N-3/4-P-13-MS	1
		19 mm	15638	N-3/4-P-19-MS	1

1) Packaging unit

Manifold block VABM

Accessories – Manifold block, size 30

Ordering data		Description	Part No.	Type	PU ¹⁾
Silencer					
	With connecting thread G	G3/8	6843	U-3/8-B	1
			534224	U-3/8-20	20
		G1/2	6844	U-1/2-B	1
		G3/4	6845	U-3/4-B	1
Blanking plug					
	With connecting thread G	G1/8	3568	B-1/8	10
			534213	B-1/8-100	100
		G1/2	3571	B-1/2	10
			534216	B-1/2-20	20
		G3/4	3572	B-3/4	1
Separator					
	For creating pressure zones	G1/8	569995	VABD-8-B	1
		G1/2	8022483	VABD-17.5-B	1
		G3/4	8022484	VABD-22.7-B	1
H-rail mounting					
	For size 30, for mounting on standard H-rails TH 35-7.5 or TH 35-15 to EN 60715		3488412	VAME-T-M6	2

1) Packaging unit

Product Range and Company Overview

A Complete Suite and Company Overview

Our experienced engineers provide complete support at every stage of your development process, including: conceptualization, analysis, engineering, design, assembly, documentation, validation, and production.



Custom Automation Components
Complete custom engineered solutions



Custom Control Cabinets
Comprehensive engineering support and on-site services



Complete Systems
Shipment, stocking and storage services

The Broadest Range of Automation Components

With a comprehensive line of more than 30,000 automation components, Festo is capable of solving the most complex automation requirements.



Electromechanical
Electromechanical actuators, motors, controllers & drivers



Pneumatics
Pneumatic linear and rotary actuators, valves, and air supply



PLCs and I/O Devices
PLC's, operator interfaces, sensors and I/O devices

Supporting Advanced Automation... As No One Else Can!

Festo is a leading global manufacturer of pneumatic and electromechanical systems, components and controls for industrial automation, with more than 16,000 employees in 60 national headquarters serving more than 180 countries. For more than 80 years, Festo has continuously elevated the state of manufacturing with innovations and optimized motion control solutions that deliver higher performing, more profitable automated manufacturing and processing equipment. Our dedication to the advancement of automation extends beyond technology to the education and development of current and future automation and robotics designers with simulation tools, teaching programs, and on-site services.

Quality Assurance, ISO 9001 and ISO 14001 Certifications

Festo Corporation is committed to supply all Festo products and services that will meet or exceed our customers' requirements in product quality, delivery, customer service and satisfaction.

To meet this commitment, we strive to ensure a consistent, integrated, and systematic approach to management that will meet or exceed the requirements of the ISO 9001 standard for Quality Management and the ISO 14001 standard for Environmental Management.



© Copyright 2013, Festo Corporation. While every effort is made to ensure that all dimensions and specifications are correct, Festo cannot guarantee that publications are completely free of any error, in particular typing or printing errors. Accordingly, Festo cannot be held responsible for the same. For Liability and Warranty conditions, refer to our "Terms and Conditions of Sale", available from your local Festo office. All rights reserved. No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, electronic, mechanical, photocopying or otherwise, without the prior written permission of Festo. All technical data subject to change according to technical update.



Printed on recycled paper at New Horizon Graphic, Inc., FSC certified as an environmental friendly printing plant.

Festo North America



**[1] Festo Canada
Headquarters**
Festo Inc.
5300 Explorer Drive
Mississauga, ON
L4W 5G4

[2] Montréal
5600, Trans-Canada
Pointe-Claire, QC
H9R 1B6

[3] Québec City
2930, rue Watt#117
Québec, QC
G1X 4G3



**[4] Festo United States
Headquarters**
Festo Corporation
395 Moreland Road
Hauppauge, NY
11788

[5] Appleton
North 922 Tower View Drive, Suite N
Greenville, WI
54942

[7] Detroit
1441 West Long Lake Road
Troy, MI
48098

[6] Chicago
85 W Algonquin - Suite 340
Arlington Heights, IL
60005

[8] Silicon Valley
4935 Southfront Road, Suite F
Livermore, CA
94550

Festo Regional Contact Center

Canadian Customers

Commercial Support:
Tel: 1 877 GO FESTO (1 877 463 3786)
Fax: 1 877 FX FESTO (1 877 393 3786)
Email: festo.canada@ca.festo.com

Technical Support:
Tel:1 866 GO FESTO (1 866 463 3786)
Fax:1 877 FX FESTO(1 877 393 3786)
Email: technical.support@ca.festo.com

USA Customers

Commercial Support:
Tel:1 800 99 FESTO (1 800 993 3786)
Fax:1 800 96 FESTO (1 800 963 3786)
Email: customer.service@us.festo.com

Technical Support:
Tel:1 866 GO FESTO (1 866 463 3786)
Fax:1800 96 FESTO(1 800 963 3786)
Email: product.support@us.festo.com