


Guide axes ELFA, without drive

FESTO



Guide axes ELFA, without drive


Key features

FESTO

At a glance

- Driveless linear guide units with guide and freely movable slide
- The guide axis is designed to support force and torque capacity in multi-axis applications
- Higher torsional resistance
- Reduced vibrations with dynamic loads
- Drive axis and guide axis can be placed next to or above one another

System product for handling and assembly technology



System components and accessories

		Description	→ Internet
1	Motors	Servo and stepper motors, with or without gear unit	motor
2	Axes	Wide range of combinations possible within handling and assembly technology	axis
3	Guide axes	For supporting force and torque capacity in multi-axis applications	guide axis
4	Drives	Wide range of combinations possible within handling and assembly technology	drive
5	Adapters	For drive/drive and drive/gripper connections	gripper
6	Grippers	Wide range of variations possible within handling and assembly technology	gripper

Guide axes ELFA, without drive

Overview

FESTO

Guide axes and the corresponding axes

Guide axis EGC-FA



- Can be combined with:
 - Toothed belt axis EGC-TB
 - Spindle axis EGC-BS
- For size 70 ... 185
- Load capacity up to max. 15,200 N or 1157 Nm

Guide axis DGC-FA





- Can be combined with:
 - Linear drive DGC-KF
- For size 8 ... 63
- Load capacity up to max. 15,200 N or 1157 Nm

Guide axis ELFR



- Can be combined with:
 - Toothed belt axis ELGR
- For size 35 ... 55
- Load capacity up to max. 300 N or 124 Nm

Design	Can be combined with	Size	Working stroke [mm]	Speed [m/s]	Guide characteristics					→ Page/ Internet
					Forces and torques					
					Fy [N]	Fz [N]	Mx [Nm]	My [Nm]	Mz [Nm]	
ELFA-KF – Recirculating ball bearing guide										
	<ul style="list-style-type: none">• Toothed belt axis ELGA-TB-KF• Spindle axis ELGA-BS-KF	70	50 ... 5000	5	1500	1850	16	132	132	7
		80	50 ... 8500	5	2500	3050	36	228	228	
		120	50 ... 8500	5	5500	6890	104	680	680	
ELFA-RF – Roller bearing guide										
	Toothed belt axis ELGA-TB-RF	70	50 ... 7000	10	500	500	11	20	20	23
		80	50 ... 7000	10	800	800	30	90	90	

Sealing air connections




- 1** Sealing air connections
- Application of vacuum prevents abraded particles from being released into the environment
 - Application of gauge pressure prevents dirt from getting into the axis

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

Peripherals overview

FESTO





Slide variants

ELFA-...

Standard slide

ELFA-...-ZL/-ZR

Additional slide, left or right



Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

Peripherals overview

Variants and accessories		
Type	Description	→ Page/Internet
1 Centring sleeve/centring pins ZBH/ZBS	<ul style="list-style-type: none"> For centring loads and attachments on the slide 2 centring sleeves/centring pins included in the scope of delivery of the axis 	39
2 Switch lug SF-EGC	For sensing the slide position	37
3 Sensor bracket HWS-EGC	Adapter for mounting the inductive proximity sensors (round design) on the axis	38
4 Proximity sensor, M8 SIEN-M8	Inductive proximity sensor, round design	41
5 Clamping component EADT	Tool for retensioning the cover strip	39
6 Slot cover ABP	For protecting against contamination	39
7 Proximity sensor, T-slot SIES-8M	Inductive proximity sensor, for T-slot	41
8 Connecting cable NEBU	For proximity sensor	41
9 Clip SMBK	For mounting the proximity sensor cable in the slot	39
10 Slot nut NST	For mounting attachments	39
11 Adapter kit DHAM	For mounting the support profile on the axis	40
12 Support profile HMIA	For guiding an energy chain	40
13 Profile mounting MUE	For mounting the axis on the side of the profile	35
14 Central support EAHF-L5	For mounting the axis from underneath on the profile	36
15 Foot mounting HPE	<ul style="list-style-type: none"> For mounting the axis on the end cap With higher forces and torques, the axis should be mounted using the profile 	34

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO

Type codes


		ELFA	-	KF	-	70	-	800	-	20H	-		-	
Type														
ELFA	Guide axis													
Guide														
KF	Recirculating ball bearing guide													
Size														
Stroke [mm]														
Stroke reserve														
Slide design														
-	None													
ZL	1 slide on left													
ZR	1 slide on right													
Operating instructions														
-	With operating instructions													
DN	Without operating instructions													

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO

Technical data

Function



- Ø - Size
70, 80, 120
- I - Stroke length
50 ... 8500 mm
- T - www.festo.com



General technical data			
Size	70	80	120
Design	Guide		
Guide	Recirculating ball bearing guide		
Mounting position	Any		
Working stroke [mm]	50 ... 5000	50 ... 8500	
Max. no-load resistance to shifting [N]	11	12	23
Max. speed [m/s]	5		
Max. acceleration [m/s ²]	50		

Operating and environmental conditions	
Ambient temperature ¹⁾ [°C]	-10 ... +60
Degree of protection	IP40

1) Note operating range of proximity sensors

Weight [kg]			
Size	70	80	120
Product weight with 0 mm stroke ¹⁾	2.22	3.74	8.5
Additional weight per 1000 mm stroke	3.84	4.89	10.32
Moving mass	0.77	1.57	3.35

1) Incl. slide


Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO

Technical data

Materials


Sectional view



Axis

1	End cap	Anodised wrought aluminium alloy
2	Cover strip	Stainless steel
3	Slide	Anodised wrought aluminium alloy
4	Roller carriage	Stainless steel, tempered steel
5	Guide rail	Stainless steel, corrotect-coated tempered steel
6	Profile	Anodised wrought aluminium alloy
Note on materials		RoHS-compliant
		Contains paint-wetting impairment substances

Stroke reserve



L19 = Nominal stroke
L20 = Stroke reserve

- The stroke reserve is a safety distance which is generally not used as work space
- The sum of the nominal stroke and 2x stroke reserve must not exceed the maximum working stroke
- The stroke reserve length can be freely selected
- The stroke reserve is defined via the "stroke reserve" characteristic in the modular product system.


Example:

Type ELFA-KF-70-500-20H-...
Nominal stroke = 500 mm
2x stroke reserve = 40 mm
Working stroke = 540 mm
(540 mm = 500 mm + 2x 20 mm)

Identical installation length between toothed belt axis ELGA-TB-KF and guide axis ELFA-KF

The different end cap lengths result in different overall lengths despite the nominal stroke and stroke reserve being the same.

To achieve the same overall length between two axes, the compensation dimension L21 must be added to the stroke reserve in the case of the guide axis ELFA-KF.



1 ELGA-TB-KF
2 ELFA-KF
L19 = Nominal stroke
L20 = Stroke reserve
L21 = Compensation dimension

Size	70	80	120
Compensation dimension [mm]	41.5	48	75


Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO


Technical data

Characteristic load values

The indicated forces and torques refer to the centre of the guide. The point of application of force is the point where the centre of the guide and the longitudinal centre of the slide intersect. These values must not be exceeded during dynamic operation. Special attention must be paid to the cushioning phase.



Distance from the slide surface to the centre of the guide



Distance from the slide surface to the centre of the guide

Size	70	80	120
Dimension x [mm]	37	50	70

Max. permissible forces and torques for a service life of 5000 km

Size	70	80	120
Fy _{max.}	1500	2500	5500
Fz _{max.}	1850	3050	6890
Mx _{max.}	16	36	104
My _{max.}	132	228	680
Mz _{max.}	132	228	680



Note

For a guide system to have a service life of 5000 km, the load comparison factor must have a value of $f_v < 1$,

based on the maximum permissible forces and torques for a service life of 5000 km.

If the axis is subjected to two or more of the indicated forces and torques simultaneously, the following

equation must be satisfied in addition to the indicated maximum loads:

Calculating the load comparison factor:

$$f_v = \frac{|F_{y,dyn}|}{F_{y,max}} + \frac{|F_{z,dyn}|}{F_{z,max}} + \frac{|M_{x,dyn}|}{M_{x,max}} + \frac{|M_{y,dyn}|}{M_{y,max}} + \frac{|M_{z,dyn}|}{M_{z,max}}$$

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO

Technical data

Calculating the service life

The service life of the guide depends on the load. To provide a rough indication of the service life of the

guide, the graph below plots the load comparison factor f_v against the service life.


These values are only theoretical. You must consult your local contact person at Festo for load comparison factors f_v greater than 1.5.

Load comparison factor f_v as a function of service life

Example:

A user wants to move an X kg load. Using the formula $\rightarrow 9$ gives a value of 1.5 for the load comparison factor f_v . According to the graph, the guide would have a service life of

approx. 3000 km. Reducing the acceleration reduces the M_z and M_y values. A load comparison factor f_v of 1 now gives a service life of 10,000 km.



Note

PositioningDrives
engineering software
www.festo.com

The software can be used to calculate a guide workload for a service life of 10,000 km.

$f_v > 1.5$ are only theoretical comparison values for the roller bearing guide.

Comparison of the characteristic load values for 5000 km with dynamic forces and torques of recirculating ball bearing guides

The characteristic load values of roller guides are standardised to ISO and JIS using dynamic and static forces and torques. These forces and torques are based on an expected guide system service life of 100 km to ISO or 50 km to JIS.

As the characteristic load values are dependent on the service life, the maximum permissible forces and torques for a 5000 km service life cannot be compared with the dynamic forces and torques of roller guides to ISO/JIS.

To make it easier to compare the guide capacity of linear axes ELGA with roller guides, the table below lists the theoretically permissible forces and torques for a calculated service life of 100 km. This corresponds to the dynamic forces and torques to ISO.

These 100 km values have been calculated mathematically and are only to be used for comparing with dynamic forces and torques to ISO. The drives must not be loaded with these characteristic values as this could damage the axes.


Max. permissible forces and torques for a theoretical service life of 100 km (from a guide perspective only)				
Size		70	80	120
Fy _{max.}	[N]	5520	9200	20240
Fz _{max}	[N]	6808	11224	25355
Mx _{max.}	[Nm]	59	132	383
My _{max.}	[Nm]	486	839	2502
Mz _{max.}	[Nm]	486	839	2502

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO

Technical data

Second moment of area




Size		70	80	120
I_y	[mm ⁴]	1.46×10^5	2.57×10^5	1.26×10^5
I_z	[mm ⁴]	4.59×10^5	9.14×10^6	4.37×10^6


Maximum permissible support span L (without profile mounting MUE/central support EAHF) as a function of force F

In order to limit deflection in the case of large strokes, the axis may need to be supported.

The following graphs can be used to determine the maximum permissible support span L as a function of force F acting on the axis. The deflection is $f = 0.5$ mm.




Force Fy



- ELFA-KF-70
- - - ELFA-KF-80
- · - ELFA-KF-120

Force Fz



Recommended deflection limits

Adherence to the following deflection limits is recommended so as not to impair the functional performance of

the axes. Greater deformation can result in increased friction, greater wear and reduced service life.

Size	Dyn. deflection (moving load)	Stat. deflection (stationary load)
70 ... 120	0.05% of the axis length, max. 0.5 mm	0.1% of the axis length

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO

Technical data

Central lubrication

The lubrication connections enable the guide of the guide axis ELFA-KF to be permanently lubricated in applications in humid or wet ambient conditions using semi- or fully automatic relubrication devices.

- The axes are suitable for oils and greases
- The connection options are already available in the standard design of the axes
- There is a dedicated lubrication connection for the spindle nut and the two ball cassettes


Slide dimensions
→ 15

Structure of a central lubrication system

A central lubrication system requires various additional components. The illustration shows different options (using a hand pump, pneumatic container pump or electric container pump) required as a minimum for designing a central lubrication system. Festo does not sell these additional components; however, they can be obtained from the following companies:

- Lincoln
- Bielomatik
- SKF (Vogel)

Festo recommends these companies because they can supply all the necessary components.



- 1 Hand pump
- 2 Pneumatic container pump
- 3 Electric container pump
- 4 Manually operated container pump
- 5 Nipple block
- 6 Distributor block
- 7 Tubing or piping
- 8 Fittings


Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

Technical data

FESTO

Dimensions

Download CAD data → www.festo.com



+ = plus stroke length + 2 x stroke reserve

1 Sealing air connection

Size	B1	B2	B4	B5	B6	D5 Ø H7	D6	D8 Ø H7	D10	H1	H4
70	69	48.2	30	45	30	–	M5	5	G $\frac{1}{8}$	64	50.5
80	82	63.2	20	60	42	9	M5	5	G $\frac{1}{8}$	76.5	62
120	120	95	40	80	68	–	M8	9	G $\frac{1}{8}$	111.5	89

Size	H5	H6	H14	L1	L2 Min.	L3	L6	T5	T6	T7	T9
70	13	13	32	263	136.5	16	2.3	8	–	10	3.1
80	17.5	12	40	290	145	17	2.3	8	2.1	10.1	3.1
120	22	22	65	396	198	25	2.5	8	–	16	2.1

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide


FESTO

Technical data


Dimensions

Download CAD data → www.festo.com

Profile



Size	B10	B11	H10
70	67	40	20
80	80	40	20
120	116	40	20

-  - Note

Requirements for the flatness of the bearing surface and of attachments as well as for use in parallel structures

→ www.festo.com/sp

User Documentation

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO


Technical data

Dimensions

Download CAD data → www.festo.com

Slide

Size 70



- 3 Lubrication connections
- 5 Hole for centring sleeve ZBH
- 6 Hole for centring pin ZBS

Size	B1	D1	D2	D3 Ø H7	D5	D6	D7 Ø H7	H1	H2	L1	L2	L3
70	±0.1	M6	M5	9	M4	M6	5	±0.1	±0.1	221	±0.1	±0.1

Size	L4	L5	L6	L7	L8	L9	T1	T3	T4	T5	T6	
	±0.1		±0.1	±0.03		±0.1		+0.1		±0.1	Min.	Max.
70	90	120	20	20	5	10	5.1	2.1	7.5	3.1	4.2	4.6 _{-0.1}

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO


Technical data

Dimensions

Download CAD data → www.festo.com

Slide

Size 80



- 3 Lubrication connections
- 5 Hole for centring sleeve ZBH

Size	B1	D1	D2	D3 Ø H7	D5	D6	H1	H2	L1	L2
80	±0.1	M3	M5	9	M4	M6	±0.1	±0.1	246	±0.1

Size	L3	L4	L5	L6	T1	T2	T3	T4	T6
80	±0.1	±0.1	±0.03	±0.1	6	9	+0.1	-0.2	4

FESTO

Download CAD data ➔ www.festo.com

Slide

[illegible]

- 3 Lubrication connections
- 5 Hole for centring sleeve ZBH


Size	B1	B2	D1	D2	D3 Ø H7	D5	D6	H1	H2	L1
	±0.1	±0.03						±0.1		
120	55	20	M6	M5	9	M5	M6	24.5	6	335

Size	L2	L3	L4	L5	L6	T1	T2	T3	T4	T6
	±0.1	±0.1	±0.1	±0.03	±0.1			+0.1	-0.3	
120	140	48	116	40	76	8	9.7	2.1	12.6	6

Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

Ordering data – Modular product system

FESTO



Guide axes ELFA-KF, without drive, with recirculating ball bearing guide

FESTO

Ordering data – Modular product system

Ordering table							
Size	70	80	120	Condi- tions	Code		Entry code
[M] Module no.	8037970	8037971	8037972				
Design	Guide axis				ELFA		ELFA
Guide	Recirculating ball bearing guide				-KF		-KF
Size [mm]	70	80	120		-...		-...
Stroke length [mm]	50 ... 5000	50 ... 8500			-...		-...
Stroke reserve [mm]	0 ... 999 (0 = no stroke reserve)			[1]	-...H		
[O] Slide design	Standard slide						
	1 slide on left				-ZL		
	1 slide on right				-ZR		
Operating instructions	With operating instructions						
	Without operating instructions				-DN		

[1] ... The sum of the nominal stroke and 2x stroke reserve must be at least 50 mm and must not exceed the maximum stroke length.

[M] Mandatory data

[O] Options


Transfer order code

ELFA - **KF** - - - - - -

Guide axes ELFA-RF, without drive, with roller bearing guide

Peripherals overview

FESTO





Slide variants


ELFA-...
Standard slide

ELFA-...-S
Short slide

ELFA-...-L
Long slide



This variant is only available without strip cover.



Guide axes ELFA-RF, without drive, with roller bearing guide

Peripherals overview

Variants and accessories		
	Type	Description
		→ Page/Internet
1	Centring sleeve ZBH	<ul style="list-style-type: none"> For centring loads and attachments on the slide 2 centring sleeves included in the scope of delivery of the axis
2	Switch lug SF-EGC	For sensing the slide position
3	Sensor bracket HWS-EGC	Adapter for mounting the inductive proximity sensors (round design) on the axis
4	Proximity sensor, M8 SIEN-M8	Inductive proximity sensor, round design
5	Clamping component EADT	Tool for retensioning the cover strip
6	Slot cover ABP	For protecting against contamination
7	Proximity sensor, T-slot SIES-8M	Inductive proximity sensor, for T-slot
8	Connecting cable NEBU	For proximity sensor
9	Clip SMBK	For mounting the proximity sensor cable in the slot
10	Slot nut NST	For mounting attachments
11	Adapter kit DHAM	For mounting the support profile on the axis
12	Support profile HMIA	For guiding an energy chain
13	Profile mounting MUE	For mounting the axis on the side of the profile
14	Central support EAHF-L5	For mounting the axis from underneath on the profile
15	Foot mounting HPE	<ul style="list-style-type: none"> For mounting the axis on the end cap With higher forces and torques, the axis should be mounted using the profile

Guide axes ELFA-RF, without drive, with roller bearing guide

FESTO

Type codes


		ELFA	-	RF	-	70	-	800	-	20H	-		-		-	
Type																
ELFA	Guide axis															
Guide																
RF	Roller bearing guide															
Size																
Stroke [mm]																
Stroke reserve																
Slide design																
-	Standard slide															
S	Short slide															
L	Long slide															
Protection against particles																
-	Standard															
P0	Without strip cover															
Operating instructions																
-	With operating instructions															
DN	Without operating instructions															




Guide axes ELFA-RF, without drive, with roller bearing guide


FESTO

Technical data

Function



-  - Size
70, 80
-  - Stroke length
50 ... 7000 mm
-  - www.festo.com



General technical data			
Size		70	80
Design		Guide	
Guide		Roller bearing guide	
Mounting position		Any	
Working stroke			
ELFA-...	[mm]	50 ... 7000	50 ... 7000
ELFA-...-S	[mm]	50 ... 7000	50 ... 7000
ELFA-...-L	[mm]	50 ... 6900	50 ... 6900
Max. no-load resistance to shifting	[N]	25	40
Max. speed	[m/s]	10	10
Max. acceleration	[m/s²]	50	50

Operating and environmental conditions		
Ambient temperature ¹⁾	[°C]	-10 ... +60
Degree of protection		
ELFA-...		IP40
ELFA-...-P0		IP00

1) Note operating range of proximity sensors

Weight [kg]		
Size	70	80
Product weight with 0 mm stroke ¹⁾		
ELFA-...	1.92	4.28
ELFA-...-S	1.56	3.67
ELFA-...-L	2.45	5.45
Additional weight per 1000 mm stroke		
ELFA-...	3.05	4.71
ELFA-...-P0	2.96	4.61
Moving mass		
ELFA-...	0.66	1.65
ELFA-...-S	0.56	1.48
ELFA-...-L	0.89	2.16

1) Incl. slide


Guide axes ELFA-RF, without drive, with roller bearing guide

FESTO

Technical data

Materials


Sectional view



Axis

1	End cap	Anodised wrought aluminium alloy
2	Cover strip	Stainless steel
3	Slide	Anodised wrought aluminium alloy
4	Guide roller	Hardened rolled steel
5	Guide rod	Hardened tempered steel
6	Wiper ring	Oil-impregnated felt
7	Profile	Anodised wrought aluminium alloy
Note on materials		RoHS-compliant
		Contains paint-wetting impairment substances

Stroke reserve



L19 = Nominal stroke

L20 = Stroke reserve

- The stroke reserve is a safety distance which is generally not used as work space
- The sum of the nominal stroke and 2x stroke reserve must not exceed the maximum working stroke
- The stroke reserve length can be freely selected
- The stroke reserve is defined via the “stroke reserve” characteristic in the modular product system.

Example:

Type ELFA-RF-70-500-20H-...

Nominal stroke = 500 mm

2x stroke reserve = 40 mm


Working stroke = 540 mm

(540 mm = 500 mm + 2x 20 mm)

Identical installation length between toothed belt axis ELGA-TB-RF and guide axis ELFA-RF

The different end cap lengths result in different overall lengths despite the nominal stroke and stroke reserve being the same.

To achieve the same overall length between two axes, the compensation dimension L21 must be added to the stroke reserve in the case of the guide axis ELFA-RF.



1 ELGA-TB-RF

2 ELFA-RF

L19 = Nominal stroke

L20 = Stroke reserve

L21 = Compensation dimension

Size		70	80
Compensation dimension	[mm]	41.5	48


Guide axes ELFA-RF, without drive, with roller bearing guide

FESTO

Technical data

Characteristic load values

The indicated forces and torques refer to the slide surface. The point of application of force is the point where the centre of the guide and the longitudinal centre of the slide intersect. These values must not be exceeded during dynamic operation. Special attention must be paid to the cushioning phase.



If the axis is subjected to two or more of the indicated forces and torques simultaneously, the following equation must be satisfied in addition to the indicated maximum loads:

Calculating the load comparison factor:

$$f_v = \frac{|F_{y,dyn}|}{F_{y,max}} + \frac{|F_{z,dyn}|}{F_{z,max}} + \frac{|M_{x,dyn}|}{M_{x,max}} + \frac{|M_{y,dyn}|}{M_{y,max}} + \frac{|M_{z,dyn}|}{M_{z,max}}$$

Permissible forces and torques for a service life of 10000 km

Size	70	80
$F_{y,max}$	500	800
$F_{z,max}$	500	800
$M_{x,max}$	11	30
$M_{y,max}$		
ELFA-...	20	90
ELFA-...-S	20	90
ELFA-...-L	40	180
$M_{z,max}$		
ELFA-...	20	90
ELFA-...-S	20	90
ELFA-...-L	40	180

Calculating the service life

The service life of the guide depends on the load. To provide a rough indication of the service life of the

guide, the graph below plots the load comparison factor f_v against the service life.

These values are only theoretical. You must consult your local contact person


at Festo for load comparison factors f_v greater than 1.5.

Load comparison factor f_v as a function of service life

Example:

A user wants to move an X kg load. Using the formula → 25 gives a value of 1.5 for the load comparison factor f_v . According to the graph, the guide would have a service life of

approx. 3000 km. Reducing the acceleration reduces the M_z and M_y values. A load comparison factor f_v of 1 now gives a service life of 10000 km.



Note

PositioningDrives
engineering software
www.festo.com

The software can be used to calculate a guide workload for a service life of 10000 km.


$f_v > 1.5$ are only theoretical comparison values for the roller bearing guide.

Guide axes ELFA-RF, without drive, with roller bearing guide

FESTO

Technical data

Second moment of area




Size		70	80
I_y	[mm ⁴]	1.39×10^5	2.70×10^5
I_z	[mm ⁴]	4.33×10^5	1.02×10^6


Maximum permissible support span L (without profile mounting MUE/central support EAHF) as a function of force F

In order to limit deflection in the case of large strokes, the axis may need to be supported.

The following graphs can be used to determine the maximum permissible support span L as a function of force F acting on the axis. The deflection is $f = 0.5$ mm.




Force F_y



— ELFA-RF-70
- - - ELFA-RF-80

Force F_z



Recommended deflection limits

Adherence to the following deflection limits is recommended so as not to impair the functional performance of

the axes. Greater deformation can result in increased friction, greater wear and reduced service life.

Size	Dyn. deflection (moving load)	Stat. deflection (stationary load)
70, 80	0.05% of the axis length, max. 0.5 mm	0.1% of the axis length


Guide axes ELFA-RF, without drive, with roller bearing guide

FESTO

Technical data

Dimensions

Download CAD data → www.festo.com



+ = plus stroke length + 2 x stroke reserve

1 Sealing air connection

Size	B1	B2	B4	B5	B6	D5 Ø H7	D6	D8 Ø H7	D10	H1
70	69	48.2	30	45	30	–	M5	5	G1/8	64
80	82	63.2	20	60	42	9	M5	5	G1/8	76.5

Size	H4	H5	H6	H14	L3	L6	T5	T6	T7	T9
70	50.5	13	13	37.5	16	2.3	8	–	10	3.1
80	62	17.5	12	45.5	17	2.3	8	2.1	10.1	3.1

Size	L1			L2		
	ELFA-...	-S	-L	ELFA-...	-S	-L
				Min.	Min.	Min.
70	337	259	437	168.5	129.5	218.5
80	484	400	624	242	200	312

Guide axes ELFA-RF, without drive, with roller bearing guide



Technical data

Dimensions Download CAD data → www.festo.com

Profile

Size 70

Size 80

1 Sensor slot for proximity sensor

2 Mounting slot for slot nut

Size	B10	B11	H10
70	67	40	20
80	80	40	20

- Note

Requirements for the flatness of the bearing surface and of attachments as well as for use in parallel structures

→ www.festo.com/sp

User documentation

Guide axes ELFA-RF, without drive, with roller bearing guide

FESTO


Technical data

Dimensions

Download CAD data → www.festo.com


ELFA-... – Standard slide

Size 70



View A

Size 80



View A

[5] Hole for centring sleeve

Size	B1	B2	D2	D3 Ø H7	D5	D6	H1	L1
	±0.1	±0.1					±0.1	
70	20	–	M5	9	M4	–	11.7	290
80	32	20	M5	9	M4	M6	16	435

Size	L2	L3	L4	L6	T1	T2	T3	T4
	±0.2	±0.1	±0.03	±0.2				
70	90	56	80	–	3.5	7.5	2.1	–
80	74	78	40	200	5.1	9	2.1	9.7

Guide axes ELFA-RF, without drive, with roller bearing guide

FESTO


Technical data

Dimensions

Download CAD data → www.festo.com


ELFA-...-S – Short slide

Size 70



View A

Size 80



View A

5 Hole for centring sleeve

Size	B1	B2	D2	D3 Ø H7	D5	D6	H1	L1
70	±0.1	±0.1	M5	9	M4	–	±0.1	212
80	32	20	M5	9	M4	M6	16	351

Size	L2	L3	L4	L6	T1	T2	T3	T4
70	±0.2	±0.1	±0.03	±0.2	3.5	7.5	2.1	–
80	74	78	40	200	5.1	9	2.1	9.7

Guide axes ELFA-RF, without drive, with roller bearing guide

FESTO


Technical data

Dimensions


Download CAD data → www.festo.com

ELFA-...-L – Long slide


Size 70




View A



Size 80



View A



[5] Hole for centring sleeve

Size	B1	B2	D2	D3 Ø H7	D5
	±0.1	±0.1			
70	20	–	M5	9	M4
80	32	20	M5	9	M4


Size	D6	H1	L1	L2	L3	L4
		±0.1		±0.2	±0.1	±0.03
70	–	11.7	390	90	56	80
80	M6	16	575	74	78	40

Size	L5	L6	T1	T2	T3	T4
	±0.2	±0.2				
70	190	–	3.5	7.5	2.1	–
80	400	200	5.1	9	2.1	9.7

Guide axes ELFA-RF, without drive, with roller bearing guide

Ordering data – Modular product system

FESTO



Guide axes ELFA-RF, without drive, with roller bearing guide

FESTO

Ordering data – Modular products

Ordering table					
Size	70	80	Condi- tions	Code	Entry code
M Module no.	8037967	8037968			
Design	Guide axis			ELFA	ELFA
Guide	Roller bearing guide			-RF	-RF
Size [mm]	70	80		-...	-...
Stroke length [mm]	50 ... 7000			-...	-...
Stroke reserve [mm]	0 ... 999 (0 = no stroke reserve)		1	-...H	
O Slide design	Standard slide 50 ... 7000				
	Short slide 50 ... 7000		2	-S	
	Long slide 50 ... 6900			-L	
	Protection against particles				
	Standard				
	Without strip cover			-P0	
Operating instructions	With operating instructions				
	Without operating instructions			-DN	

1 ... The sum of the nominal stroke and 2x stroke reserve must be at least 50 mm and must not exceed the maximum stroke length.

2 **S** Only with P0.

M Mandatory data

O Options

Transfer order code

ELFA - **RF** - - - - - -

Guide axes ELFA, without drive

Accessories


FESTO

Foot mounting HPE

Materials:

Galvanised steel

RoHS-compliant



Dimensions and ordering data							
For size	AB Ø	A0	AT	AU	B1	B2	H1
70	5.5	6	3	13	20	14.5	64
80	5.5	6	3	15	20	21	76.5
120	9	8	6	22	40	20	111.5

For size	H8	SA	TR	US
70	0.5	289	40	67
80	0.5	320	40	80
120	0.5	440	80	116

For size	Weight [g]	Part No.	Type
70	115	558321	HPE-70
80	150	558322	HPE-80
120	578	558323	HPE-120

Guide axes ELFA, without drive

Accessories


FESTO

Profile mounting MUE

Materials:

Anodised aluminium

RoHS-compliant



Dimensions and ordering data								
For size	B1	B2	B3	B4	D1 Ø	H1	H2	H3
70	91	12	79	39.5	5.5	64	17.5	12
80	104	12	92	46	5.5	76.5	17.5	12
120	154	19	135	67.5	9	111.5	16	14

For size	H4	H5	L1	L2	Weight [g]	Part No.	Type
70	6.2	22	52	40	80	558043	MUE-70/80
80	6.2	22	52	40	80	558043	MUE-70/80
120	5.5	29.5	90	40	290	558044	MUE-120/185

Guide axes ELFA, without drive

Accessories

FESTO

Central support EAHF


Materials:

Anodised aluminium


RoHS-compliant



Size 70, 80



Size 120



Dimensions and ordering data								
For size	AH	B1	B2	D1 Ø	D2 Ø	D3 Ø	H1	L1
70	32.2	35	22	5.8	10	5.8	10	102
80	36.5							112
120	74.6	50	26	9	15	9	16	160

For size	L2	L3	L4	L5	T1	Weight [g]	Part No.	Type
70	51	45	25	-	5.7	113	2349256	EAHF-L5-70-P
80	56	50	30			123	3535188	EAHF-L5-80-P
120	80	70	30	20	11	384	2410274	EAHF-L5-120-P

Guide axes ELFA, without drive

Accessories

FESTO


Switch lug SF-EGC-1

For sensing via proximity sensor
SIES-8M

Materials:

Galvanised steel

RoHS-compliant



Dimensions and ordering data									
For size	B2	D1	H1	L1	L2	L6	Weight [g]	Part No.	Type
70	3	M4	4.65	70	56	50	50	558047	SF-EGC-1-70
80	3	M4	4.65	90	78	70	60	558048	SF-EGC-1-80
120	3	M5	8	170	140	170	147	558049	SF-EGC-1-120

Guide axes ELFA, without drive

Accessories

FESTO

Switch lug SF-EGC-2

For sensing via proximity sensor
SIEN-M8B/SIES-8M

Material:



Galvanised steel
RoHS-compliant

Sensor bracket HWS-EGC

For proximity sensor SIEN-M8B

Materials:

Galvanised steel
RoHS-compliant



Dimensions and ordering data									
For size	B1	B2	B3	B4	D1	D2	D3 Ø	H1	H2
70	31.5	3	25.5	18	M4	M5	8.4	9.5	35
80	31.5	3	25.5	18	M4	M5	8.4	9.5	35
120	32	3	25.5	18	M5	M5	8.4	13.2	65

For size	H3	H5	H6 Max.	L1	L2	L3	L4	L5	L6
70	25	45	13.5	70	56	135	20	35	50
80	25	45	23.5	90	78	135	20	35	70
120	55	75	24	170	140	215	20	35	170







For size	Weight [g]	Part No.	Type
Switch lug			
70	100	558052	SF-EGC-2-70
80	130	558053	SF-EGC-2-80
120	277	558054	SF-EGC-2-120

For size	Weight [g]	Part No.	Type
Sensor bracket			
70	110	558057	HWS-EGC-M5
80	110	558057	HWS-EGC-M5
120	217	570365	HWS-EGC-M8-B

Guide axes ELFA, without drive

Accessories

FESTO

Ordering data					
	For size	Comments	Part No.	Type	PU ¹⁾
Slot nut NST					
	70, 80	For mounting slot	150914	NST-5-M5	1
	120		8047843	NST-5-M5-10	10
			8047878	NST-5-M5-50	50
			150915	NST-8-M6	1
			8047868	NST-8-M6-10	10
			8047869	NST-8-M6-50	50
Centring pin ZBS/centring sleeve ZBH ²⁾					
	70	For slide	150928	ZBS-5	10
	70, 80, 120		150927	ZBH-9	
Slot cover ABP					
	70, 80	• For mounting slot • Every 0.5 m	151681	ABP-5	2
	120		151682	ABP-8	
Slot cover ABP-S					
	70, 80, 120	• For sensor slot • Every 0.5 m	563360	ABP-5-S1	2
Clip SMBK					
	70, 80, 120	For sensor slot, for attaching the proximity sensor cables	534254	SMBK-8	10
Clamping component EADT					
	70, 80	Tool for retensioning the cover strip	8058451	EADT-S-L5-70	1
	120		8058450	EADT-S-L5-120	

1) Packaging unit

2) 2 centring sleeves included in the scope of delivery of the axis

Guide axes ELFA, without drive

Accessories







Mounting options between axis and support profile

Depending on the adapter kit, the spacing between the axis and the support profile is:
x = 20 mm or 50 mm

The support profile must be mounted using at least 2 adapter kits. For longer strokes, an adapter kit must be used every 500 mm.

Example:





Ordering data					
	For size	Comments	Part No.	Type	PU ¹⁾
Adapter kit DHAM					
	80	<ul style="list-style-type: none">• For mounting the support profile on the axis• Spacing between axis and profile is 20 mm	562241	DHAM-ME-N1-CL	1
	120		562242	DHAM-ME-N2-CL	
	70, 80	<ul style="list-style-type: none">• For mounting the support profile on the axis• Spacing between axis and profile is 50 mm	574560	DHAM-ME-N1-50-CL	1
	120		574561	DHAM-ME-N2-50-CL	
Support profile HMIA					
	70, 80, 120	For guiding an energy chain	539379	HMIA-E07-	1





1) Packaging unit



Guide axes ELFA, without drive

Accessories

FESTO

Ordering data – Proximity sensor for T-slot, inductive						Technical data → Internet: sies	
	Type of mounting	Electrical connection	Switching output	Cable length [m]	Part No.	Type	
N/O contact							
	Insertable in the slot from above, flush with the cylinder profile	Cable, 3-wire	PNP	7.5	551386	SIES-8M-PS-24V-K-7,5-OE	
		Plug M8x1, 3-pin		0.3	551387	SIES-8M-PS-24V-K-0,3-M8D	
		Cable, 3-wire	NPN	7.5	551396	SIES-8M-NS-24V-K-7,5-OE	
		Plug M8x1, 3-pin		0.3	551397	SIES-8M-NS-24V-K-0,3-M8D	
N/C contact							
	Insertable in the slot from above, flush with the cylinder profile	Cable, 3-wire	PNP	7.5	551391	SIES-8M-PO-24V-K-7,5-OE	
		Plug M8x1, 3-pin		0.3	551392	SIES-8M-PO-24V-K-0,3-M8D	
		Cable, 3-wire	NPN	7.5	551401	SIES-8M-NO-24V-K-7,5-OE	
		Plug M8x1, 3-pin		0.3	551402	SIES-8M-NO-24V-K-0,3-M8D	

Ordering data – Proximity sensor M8 (round design), inductive						Technical data → Internet: sien
	Electrical connection	LED	Switching output	Cable length [m]	Part No.	Type
N/O contact						
	Cable, 3-wire	■	PNP	2.5	150386	SIEN-M8B-PS-K-L
	Plug M8x1, 3-pin	■	PNP	–	150387	SIEN-M8B-PS-S-L
N/C contact						
	Cable, 3-wire	■	PNP	2.5	150390	SIEN-M8B-PO-K-L
	Plug M8x1, 3-pin	■	PNP	–	150391	SIEN-M8B-PO-S-L

Ordering data – Connecting cables					Technical data → Internet: nebu
	Electrical connection, left	Electrical connection, right	Cable length [m]	Part No.	Type
	Straight socket, M8x1, 3-pin	Cable, open end, 3-wire	2.5	159420	SIM-M8-3GD-2,5-PU
			2.5	541333	NEBU-M8G3-K-2.5-LE3
			5	541334	NEBU-M8G3-K-5-LE3
	Angled socket, M8x1, 3-pin	Cable, open end, 3-wire	2.5	541338	NEBU-M8W3-K-2.5-LE3
			5	541341	NEBU-M8W3-K-5-LE3