
# **Linear drives DGC**





**★**/☆

Festo core product range

Covers 80% of your automation tasks

Worldwide:

Always in stock

Superb: Easy: Festo quality at an attractive price Simplified procurement and warehousing ★ Generally ready for dispatch from the factory within 24 hours In stock at 13 Service Centres worldwide More than 2200 products

Just look for the star!

☆ Generally ready for dispatch from the factory within 5 days Assembled for you in 4 Service Centres worldwide Up to 6 × 10<sup>12</sup> variants per product family

#### At a glance

- Compact installation length relative to stroke
- Loads and devices can be directly mounted on the slide.
- Three types of cushioning available:
  - Elastic cushioning
  - Pneumatic cushioning
  - Hydraulic cushioning
- · All settings accessible from one
  - Precision end-position adjustment
  - Position of proximity sensors
  - Mounting of drive
  - Regulating speed
  - Pneumatic end-position cushioning

· Sealing system



Advantages of the sealing system

- Long strokes with no restrictions

• Optional: NSF-H1 lubricant for the food area

The linear drive is of limited suitability for the food area. Additional information:

www.festo.com/sp → Certificates

Not approved for use in the food area:

- DGC-...-GP (protected version)
- · DGC-... with integrated shock absorbers

- Virtually no leakage

#### **Guide variants**

# Compact design DGC-K




- Piston diameter 18 ... 80 mm
- Stroke lengths from 1 ... 8500 mm
- 30% narrower than the DGC-G
- · Low moving dead weight
- Symmetrical design

# Basic design DGC-G




- Piston diameter 8 ... 63 mm
- Stroke lengths from 1 ... 8500 mm
- Guide backlash = 0.2 mm
- · For small loads
- Operating behaviour under torque load = average

# Plain-bearing guide DGC-GF




- Piston diameter 18 ... 63 mm
- Stroke lengths from 1 ... 8500 mm
- Guide backlash = 0.05 mm
- · For small and medium loads
- · Operating behaviour under torque load = average

# Recirculating ball bearing guide DGC-KF



- Piston diameter 8 ... 63 mm
- Stroke lengths from 1 ... 8500 mm
- Guide backlash = 0 mm
- For medium and large loads
- Precision mounting interface with stainless steel slide
- · Operating behaviour under torque load = very good

# Heavy-duty guide DGC-HD



- Piston diameter 18, 25, 40 mm
- Stroke lengths from 10 ... 5000 mm
- Guide backlash = 0 mm
- For large loads
- · Operating behaviour under torque load = very good

# Guide axis DGC-FA



- · Without drive
- Piston diameter 8 ... 63 mm
- Stroke lengths from 1 ... 8500 mm
- Guide backlash = 0 mm
- Precision guide, suitable for the DGC-KF. Can be used as machine component or as a twin guide with the DGC-KF

# Versatility

#### [1] Compressed air supply ports



- Optionally on 2 sides (on the side or at the front)
- For DGC-G/DGC-GF/DGC-KF

#### DL – Compressed air supply port at the left end or at both ends

The linear drive is actuated at the right end or at both ends by default.

The linear drive can be actuated at the left end or at both ends by specifying the order code DL in the modular product system.

- For piston diameters 18, 25, 32, 40, 50, 63 mm
- For DGC-G, DGC-GF, DGC-KF

#### [2] G/H/I/J - Proximity sensors



- Proximity sensors can be integrated, which means there is no projection.
   The cable can be guided through the slot behind the second sensor
- For DGC-G/DGC-GF/DGC-KF

#### [3] Precision end-position adjustment




- Between 0 ... 25 mm per side
- For DGC-GF/DGC-KF/DGC-FA

#### [4] M - Profile mounting




- Profile mounting remains on the base plate after the drive is dismantled. This means faster assembly and removal without repeat adjustment
- For DGC-G/DGC-GF/DGC-KF/DGC-FA

#### [5] YWZ - Mechanical end-position limiter



- For variable stroke adjustment, e.g. for format adjustments
- The end stop can be mounted at any position along the stroke
- For DGC-GF/DGC-KF/DGC-FA

# [6] Z1/Z2/Z3 – Intermediate-position module




- Enables variable intermediate positions
- The intermediate-position module can be mounted at any place along the stroke
- Precision repetition accuracy (0.02 mm) with high dynamic response
- For DGC-KF


# FK – Moment compensator



- Compensates for inaccuracies during mounting of the linear drive and external guide
- Max. offset 2.5 mm
- For DGC-G


# Example





#### Options

C - Central lubrication




The lubrication adapters enable the guide of the linear drive DGC-KF to be permanently lubricated in applications in humid or wet ambient conditions using semi or fully automatic relubrication devices.

The adapters are suitable for oils and greases.

- For piston diameters 25, 32, 40, 63 mm
- For DGC-KF
- Connections:
  - On both sides of the slide
  - In three places (front, top, rear) on each side

Technical data → page 48

1H-PN - Clamping unit



- 1-channel design, for holding loads
- Reliable holding is guaranteed since the forces act directly on the slide
- A limited number of emergency braking operations are permissible with the sizes 40 and 50
- For piston diameters 25, 32, 40, 50 mm
- For DGC-KF

Technical data → page 45

Product variants					ŢF2			
	Piston diameter	Theoretical force at 6 bar	M <sub>X</sub> Guide chara	cteristics		y <sub>M</sub> y S		→ Page/
	[mm]	[N]	Fy	Fz	Mx [Nm]	My	Mz [Nm]	
Comment design BCC V	[]	[ta]	[N]	[N]	[Nm]	[Nm]	[Nm]	
Compact design DGC-K	18	153		120	0.8	11	1	dac k
	25	295		330	1.2	20	3	dgc-k
03/1	32	483	-	480	1.2	40	5	
	40	754	-	800	3.8	60	8	
	50	1178	-	1200	6	120	15	$\overline{}$
	63	1870	-	1600	5.7	150	24	$\dashv$
	80	3016	-	2500	30.6	400	100	
	80	7010		2300	70.0	400	100	
Basic design DGC-G								
	8	30	150	150	0.5	2	2	8
die	12	68	300	300	1.3	5	5	
	18	153	70	340	1.9	12	4	
	25	295	180	540	4	20	5	
	32	483	250	800	9	40	12	
	40	754	370	1100	12	60	25	
	50	1178	480	1600	20	150	37	
	63	1870	650	2000	26	150	48	
Plain-bearing guide DGC-GF								
	18	153	440	540	3.4	20	8.5	22
	25	295	640	1300	8.5	40	20	
-	32	483	900	1800	15	70	33	
	40	754	1380	2000	28	110	54	
50	50	1178	1500	2870	54	270	103	
3	63	1870	2300	4460	96	450	187	
locirculating hall bearing guide DC	C VE	•						,
Recirculating ball bearing guide DG	8 8	30	300	300	1.7	4.5	4.5	40
	12	68	650	650	3.5	10	10	
	18	153	1850	1850	16	51	51	_
	25	295	3050	3050	36	97	97	_
	32	483	3310	3310	54	150	150	_
100	40	754	6890	6890	144	380	380	_
3	50	1178	6890	6890	144	634	634	$\dashv$
	63	1870	15200	15200	529	1157	1157	-
	رن	10/0	13200	13200	727	113/	113/	
leavy-duty guide DGC-HD								
	18	153	3650	3650	140	275	275	dgc-hd
-	25	295	5600	5600	300	500	500	
	40	754	13000	13000	900	1450	1450	

# Type codes

001	Series	
DGC	Linear drive	
002	Piston diameter	
8	8	
12	12	
18	18	
25	25	
32	32	
40	40	
50	50	
63	63	
003	Stroke	
	1 8500	
004	Guide	·——
G	Basic variant San Control of the Con	
GF	Plain bearing	
KF	Recirculating ball bearing guide	
FA	Passive guide axis	
005	Cushioning	
P	Elastic cushioning rings/plates on both sides	
PPV YSR	Pneumatic cushioning, adjustable at both ends	
YSRW	Self-adjusting shock absorber Shock absorber, self-adjusting, progressive	
ISKW	Shock absorber, sea-adjusting, progressive	
006	Position sensing	
Α	For proximity sensor	
007	Compressed air connection	
	At the right end or at both ends	
DL	At the left or at both ends	
Laca	Line e.	
800	Lubrication	
114	Standard	
H1	Food-safe lubrication	
009	Slide	
	Standard	
GP	Protected recirculating ball bearing guide	
010	Lubrication function	
	None	
С	Lubrication adapter	
011	Additional slide left	
	None	
KL	Additional slide, standard, left	$\vdash$
		اللل
012	Additional slide, right	
L/D	None	
KR	Additional slide standard, right	
013	Clamping unit	
	None	
1H	Holding function, 1-channel	

014	Actuation type
014	None
PN	Pneumatically actuated
015	EU certification
	None
EX2	II 3GD
EX3	II 2G
016	Accessories
010	None
ZUB	Accessories supplied loose
200	Accessories supplied toose
017	Foot mounting
	None
F	1 record
	la a
018	Profile mounting
	None
М	1 9 pieces
019	Slot nut, mounting slot
	Without
В	1 9 pieces
020	Moment compensator
	None
FK	Moment compensator
021	Proximity switch, cable 2.5 m
	None
G	1 9 pieces
022	Proximity switch, plug M8
	None
Н	1 9 pieces
023	Proximity switch, contactless, cable 2.5 m
023	None
l	1 9 pieces
	- my protect
024	Proximity switch, contactless, plug M8
	None
J	1 9 pieces
025	Connecting cable, M8, 2.5 m
023	None
V	1 9 pieces
_ <del></del>	> F
026	Slot cover, sensor slot
	Without
L	1 9 pieces
027	Advantage and a particular state of the state of
027	Mechanical end position limitation
V/M74	None
YWZ1 YWZ2	Variable end position, one side  Variable end position, both sides
1 4477	variable ella position, both sides

# Type codes

028	Intermediate position			
	None			
<b>Z1</b>	1 intermediate position			
<b>Z2</b>	2 intermediate positions			
Z3	3 intermediate positions			

029	Operating instructions	
	Standard	
0	Express waiver - no operating instructions to be included as already available (operating instructions in PDF format are available free of charge on our website at http://www.festo.com)	

# Linear drives DGC-G


# Peripherals overview




DGC-8/-12



1) Operation without cushioning components is not permitted.



# DGC-18 ... 63



# Peripherals overview

	nts and accessories Type/order code	For piston diam.	Description	→ Page/Internet
	,, ,		·	
[1]	Linear drive	8 63	Linear drive without accessories, basic design	10
[0]	DGC-G	0.10		
[2]	Centring pin <sup>1)</sup>	8, 12	For centring loads and attachments on the slide	74
[2]	ZBS	863	Community for in a superior desired and the linear define and advanced and a	68
[3]	Moment compensator FK	8 63	Compensates for inaccuracies during mounting of the linear drive and external guide	68
-	Cushioning P	8, 12	Non-adjustable, elastic cushioning. Used only at low speeds.	21
-	Cushioning PPV	18 63	Adjustable, pneumatic end-position cushioning. Used at medium speeds.	21
[4]	Shock absorber YSR	8, 12	Self-adjusting, hydraulic shock absorber with spring return and linear cushioning characteristics.	21
[5]	Shock absorber YSRW	8, 12	Self-adjusting, hydraulic shock absorber with spring return and progressive cushioning characteristics	21
[6]	One-way flow control valve GRLA	8 63	For regulating speed	75
[7]	Proximity sensor G/H/I/J	8 63	For sensing the slide position	75
[8]	Connecting cable V	8 63	For proximity sensor	76
[9]	Slot cover L	18 63	For protecting against contamination and securing the proximity sensor cable in place	74
[10]	Profile mounting M	8 63	Simple and precise mounting option via dovetail connection.	66
[11]	Foot mounting F	8 63	For mounting on the end cap	64
[12]	Centring pin/sleeve ZBS/ZBH	8, 12, 50, 63	For centring the drive without foot mountings (user-specific)	74
[13]	Slot nut B	25 63	For mounting attachments	74

<sup>1)</sup> Included in the scope of delivery of the drive







Diameter

8 ... 63 mm



Stroke length

1 ... 8500 mm



General technical data										
Piston diameter		8	12	18	25	32	40	50	63	
Design		Rodless drive	2							
Moment compensator principle		Slotted cylind	der, mechanical	y coupled						
Guide		Basic design								
Mode of operation		Double-acting	g							
Stroke	[mm]	1 1500	1 2000	1 3000	1 8500			1 5000		
Pneumatic connection		M5			G1/8		G1/4		G3/8	
Cushioning → page 1										
DGCP		Non-adjustat	ole at both ends	s  -						
DGCPPV		-		Adjustable at both ends						
DGCYSR		Self-adjusting	g at both ends	-						
Cushioning length with cushioning PPV	[mm]	-		16.5	15.5	17.5	29.5	29.8	31.1	
Max. speed	[m/s]	1	1.2	3					-	
Position sensing		Via proximity	sensor							
Type of mounting		Profile mount	ting							
		Foot mountin	g							
		Direct mount	ing							
Mounting position		Any								

 $<sup>| \</sup>label{eq:norms} |$  Note: This product conforms to ISO 1179-1 and ISO 228-1.

Operating and environmental conditions										
Piston diameter		8	12	18	25	32	40	50	63	
Operating pressure	[bar]	2.5 8		2 8			1.5 8			
Operating medium		Compressed a	Compressed air to ISO 8573-1:2010 [7:-:-]							
Note on operating/		Lubricated op	eration possible (	in which case lu	bricated oper	ation will alway	s be required)	quired)		
pilot medium										
Ambient temperature <sup>1)</sup>	[°C]	+5 +60	-10 +60					,		
Food-safe <sup>2)</sup>		-	`	→ suppleme	ntary informa	tion on material	S			
Corrosion resistance class CRC <sup>3)</sup>		2								

<sup>1)</sup> Note operating range of proximity sensors

- 2) Additional information is available at www.festo.com/sp  $\rightarrow$  Certificates.
- 3) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation can occur. External visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment.

Forces [N] and impact energy [J]								
Piston diameter	8	12	18	25	32	40	50	63
Theoretical force at 6 bar	30	68	153	295	483	754	1178	1870
Impact energy at the end positions	→ page 1							

ATEX1)					
Size	8	12 63			
Explosion-proof ambient temperature [°C]	+5°C ≤ Ta ≤ +60°C	-10°C ≤ Ta ≤ +60°C			
CE marking	To EU Explosion Protection Directive (ATEX)				
(see declaration of conformity)					
EX2 certification					
ATEX category for gas	II 3G				
Type of ignition protection for gas	Ex h IICT4 Gc X				
ATEX category for dust	II 3D				
Type of ignition protection for dust	Ex h IIIC T120°C Dc X				
EX3 certification					
ATEX category for gas	II 2G				
Type of ignition protection for gas Ex h IIC T4 Gb X					

<sup>1)</sup> Note the ATEX certification of the accessories.

Weight [g]								
Piston diameter	8	12	18	25	32	40	50	63
Basic weight with 0 mm stroke	170	290	546	1004	2126	4121	9050	14040
Additional weight per 10 mm stroke	9	12	22	34	54	77	116	150
Moving mass	36	65	178	287	508	1312	2850	4330


# Adjustable end-position range d [mm]



Piston diameter	8	12
Cushioning		
DGCYSR/YSRW	12.8 22.8	14 24

# Materials


Sectional view



Linea	r drives	
[1]	Guide rail	Anodised aluminium
[2]	Slide	Anodised aluminium
[3]	End cap	Anodised aluminium
[4]	Cylinder barrel	Anodised aluminium
-	Piston seal	Polyurethane
	Sealing band/cover strip	Polyurethane
	Slide elements	Polyacetal
	Note on materials	RoHS-compliant

#### Characteristic load values

The indicated forces and torques refer to the centre of the slide surface. These values must not be exceeded during dynamic operation. Special attention must be paid to the deceleration phase.





To prevent the guide of the basic drive DGC-G from self-locking when used vertically and with a high torque load, the variant with the recirculating ball bearing guide DGC-KF → page 40 is recommended.

If the drive is subjected to two or more of the indicated forces and torques simultaneously, the following equation must be satisfied in addition to the indicated maximum loads:


$$\frac{Fy}{Fy_{max.}} + \frac{Fz}{Fz_{max.}} + \frac{Mx}{Mx_{max.}} + \frac{My}{My_{max.}} + \frac{Mz}{Mz_{max.}} \leq 1$$

Permissible forces and torques											
Piston diameter		8	12	18	25	32	40	50	63		
Fy <sub>max</sub> .	[N]	150	300	70	180	250	370	480	650		
Fz <sub>max</sub> .	[N]	150	300	340	540	800	1100	1600	2000		
Mx <sub>max.</sub>	[Nm]	0.5	1.3	1.9	4	9	12	20	26		
My <sub>max</sub> .	[Nm]	2	5	12	20	40	60	150	150		
Mz <sub>max.</sub>	[Nm]	2	5	4	5	12	25	37	48		

# Influence of ferritic materials on proximity sensors

Ferritic materials (steel parts or sheet metal) in the immediate vicinity of the proximity sensors can cause sensing malfunctions. The following safety distances must be observed.


The distance depends on the position of the proximity sensor (see [1] and [2]).




Piston diameter			8	12	18	25	32	40	50	63
Distance L1	[1]	[mm]	0	0	0	0	0	0	0	0
	[2]	[mm]	-	-	0	0	0	0	0	0
Distance L2	[1]	[mm]	20	10	10	10	0	0	0	0
	[2]	[mm]	-	-	25	25	25	25	25	25
Distance L3	[1]	[mm]	30	25	25	25	25	25	25	25
	[2]	[mm]	-	-	10	10	0	0	0	0
Distance L4	[1]	[mm]	0	0	0	0	0	0	0	0
	[2]	[mm]	-	-	0	0	0	0	0	0

# Maximum permissible speed v as a function of payload m and distance $r_{max}$ from centre of mass


Piston diameter 8/12 with cushioning P




Piston diameter 18 ... 63 with cushioning PPV



Piston diameter 8/12 with cushioning YSR



Piston diameter 8/12 with cushioning YSRW




- 🖣 - Note

These specifications represent the maximum values that can be achieved. In practice, these values can fluctuate dependent on the position of the payload and mounting position.

# Operating range of the cushioning

The end-position cushioning must be adjusted to ensure jerk-free operation. If the operating conditions are outside the permissible range, the moving mass must be cushioned using suitable equipment (external shock absorbers), preferably at the centre of mass.



- 🖣 - Note

To avoid distortion in the slide, the bearing surfaces of the attachments must maintain a flatness of at least 0.03 mm.


Data for horizontal mounting position


Data for Horizonta	at illoulitilig	s positi	011:							
Piston diameter		8	12	18	25	32	40	50	63	
Distance r	[mm]	25	35	35	50	50	50	50	50	۱


# Number of profile mountings MUC as a function of weight force F and distance I between supports

In order to limit deflection in the case of large strokes, the drive may need to be supported. The following graphs are provided to determine the maximum permissible distance between supports as a function of the mounting position and the applied weight and normal forces.


# Horizontal mounting position









# Vertical mounting position







 ø8
 Ø 12
 Ø 18
 Ø 25

 Ø 32
 Ø 40
 ø 50
 Ø 63

# Example:

The drive DGC-25-1500 is subjected to a force of 300 N in a horizontal mounting position.

The drive has an overall length of:

- l = stroke length + L1
   (see dimensions)
  - = 1500 mm + 200 mm
  - = 1700 mm


According to the graph, the max. distance between supports for the drive DGC-25 with a force of 300 N is 1300 mm.


In this example, profile mountings are required as the max. distance between supports (1300 mm) is smaller than the overall length of the drive (1700 mm).

# Dimensions

Download CAD data → www.festo.com

Ø 8 and 2





- + = plus stroke length
- [1] Compressed air supply port options on 3 sides
- [3] Mounting hole for foot mounting or centring pin
- [5] Drilled hole for centring pin ZBS
- [2] Sensor slot for proximity sensor

Ø	B1	B2	B4	B5	В6	В7	B8	В9	B13	D1	D2 Ø	D3 ø	D6
[mm]							±0.05	±0.1			Н8	H7	
8	25	26	25.5	18.6	11.7	3	6	3.2	20.5	M4	2	5	M3
12	30.2	31	30.5	20.6	13.5	3	8	4.8	25	M4	2	5	M4
ø	EE	H1	H2	Н3	H4	Н5	Н6	H7	Н9	H10	J4	L1	L2
[mm]													
8	M5	32	23	29	8.5	11.7	16.5	4.5	12.3	8.7	2.2	100	50.1
12	M5	37.5	28.5	34.5	8.7	13.5	20.5	5	14.7	9.8	3	125	62.4

Ø	L3	L5		L6		L7	L8	L9	L17	T1	T2	T3	T4	Stroke tolerance
[mm]			Р	YSR	YSRW	±0.03	±0.1	±0.1					+0.2	
8	6	11.4	0	16	16.2	20	20	10	52	5	2	4	3	0 1.7
12	8	15.9	0	11.3	12.3	20	20	10	65	6	2	5	3	

Length tole	erance		
For stroke	[mm]	≤ 1000	≤ 2000
L1	[mm]	+0.90	+1.10

Profile barrel

ø8


ø 12





[1] Sensor slot for proximity sensor

# Dimensions Download CAD data → www.festo.com ø 18 ... 40 ВЗ B11 $\downarrow$ A $\rightarrow$ page 18 В $\bigoplus$ $\oplus$ Ξ £ 욷 EE 1 3 L2 В1 L1+ View B Ø 18 Ø 25 ... 40 ø 18 ... 40 4 B2 EE 1



Ø	B1	B2	В3	B4	B5	B6	B7	B8	В9	B10
[mm]					±0.05					
18	44.5	46.3	19.5	8.8	21	31	0.3	3.8	3.3	2.4
25	59.8	61.6	30	12.65	30	42	1	6.65	5.6	3.5
32	73	75.5	38.5	5.7	63.1	57.5	1	8.5	5	14
40	91	94.5	45	17.2	55	65	1	12.2	5.3	8
50	113	122	60	8	52.8	81.6	-	12	0	-
63	142	147	68	15.5	68	97	-	19.5	6	_
ø	B11	B12	B13	D1 Ø	D2	EE	H1	H2	H3	H4
[mm]				·						±0.2
18	5.5	19.3	20	2±0.05	M4	M5	49.8	23.1	48.3	10.3
25	9.3	20.15	30	3±0.05	M5	G1/8	58.5	29	56.5	13
32	14.9	20.5	35	3±0.05	M6	G1/8	73	30	71.5	5.7
40	16.5	19.8	45	4±0.05	M6	G1/4	88	41.5	85	17.2
50	21	24	64	9 <sup>H7</sup>	M8	G1/4	120	38.5	116	52.8
63	21	30	64	9 <sup>H7</sup>	M10	G3/8	140	48.5	137.5	68
ø	H5	Н6	H7	H8	H9	H10	J1	J2	J3	L1
[mm]										
18	13.4	20	5.3	2.4	25.2	0.4	20	16.5	11	150
25	15.8	24	7	4.5	29		26.1	18.6	17	200
32	17	27.7	8.5	14	35.2		30	22	18.5	250
40	25	36.5	12.2	8	44	1	35	26	26	300
50	29.3	36	12	8	53	-	30.5	30.5	28	350
63	34.8	46	19.5	15.5	67	-	41.5	39.5	31.5	400
ø	L2	L3	L4	L5	L6	T1	T2	T6	Stroke t	colerance
[mm]										
18	74.5	5.7	5.8	15	5.5	9	2	10.7	0	. 2.5
25	100	10.5	10.6	24.5	10.6	17.5	2	12	1	
32	124.8	14.5	14.5	30.5	14.5	15	2	13.8	1	
40	150	14.6	14.6	33.5	14.6	20	3	16.8	1	
50	175	17	_	41	17	24	2.1+0.2	20.75	1	
63	200	20	_	44	20	27.5	2.1+0.2	20.75	1	




This product conforms to ISO 1179-1 and ISO 228-1.

Length tole	erance									
For stroke	[mm]	≤ 1000	≤ 2000	≤ 3000	≤ 4000	≤ 5000	≤ 6000	≤ 7000	≤ 8000	≤ 9000
L1	[mm]	+0.90	+1.10	+1.40	+1.50	+1.60	+1.70	+2.20	+2.30	+2.40

# Dimensions Download CAD data → www.festo.com Slide - View A ø 18 Ø 25 ø 32 Ø 40 ø 50 £

# Dimensions Slide – View A Ø 63


Ø [mm]	B2	D1	H2 ±0.1	H3 ±0.1	H4	H5	L1	L2 ±0.1	T1
18	-	M5	15.6	-	16	2	117±0.05	50	7
25	-	M5	21.35	15	14.55	4.85	148±0.05	50	8
32	-	M5	28.5	15	15.5	7.5	186±0.05	30	8.6
40	_	M6	35	30	14.5	15	228±0.05	30	10.5
50	14	M8	_	40	44	20	263±0.1	50	13
63	14	M8	-	40	44	20	307±0.1	50	13




Ø	B10	B11	H10	H11
[mm]				
25	15.23	-	-	-
32	18	-	26.5	-
40	20.5	40	20.5	20
50	43.8	30	30.5	30
63	49	30	37	30

# Ordering data – Modular product system

# Order code DGC-8/-12



# DGC-18 ... 63




→ page 74

# Ordering data – Modular product system

Ordering table	<b>!</b>											
Size		8	12	18	25	32	40	50	63	Condi- tions	Code	Enter code
Module no.		530906	530907	532446	532447	532448	532449	532450	532451			
Function		Linear drive		:			·		•		DGC	DGC
Piston diam.	[mm]	8	12	18	25	32	40	50	63		☆	
Stroke	[mm]	1 1500	1 2000	1 3000	1 8500	•		1 5000	•		☆	
Guide		Basic design	•								<b>☆</b> -G	-G
Cushioning	At both ends	Elastic cushi plates	oning rings/	-							<b>☆</b> -P	
	Adjustable at both ends	-	-	Pneumatic c	ushioning						☆ -PPV	
	Self-adjusting	Shock absor	ber	-	-	-	-	-	-		-YSR	
		Shock absor	ber,	-	-	-	-	-	-		☆ -YSRW	
Position sensir	ng	Via proximity	sensor /						•		<b>☆</b> -A	-A
Compressed ai	r supply port	At the right end or at both ends									☆	
·	,.	- At the left end or at both ends									-DL	
Lubrication		Standard								☆		
		-	-	Lubrication a	approved for u	se in food ap	plications				-H1	
EU certification	1	Without									☆	
		II 3GD							[1]	-EX2		
		II 2G								[1]	-EX3	
Accessories		Enclosed sep	arately (can b	e retrofitted)							ZUB-	ZUB-
Foot mounting		1									F	
Profile mountii	ng	19									M	
Moment comp	ensator	Without										
		Moment com	pensator coup	oling							FK	
Slot nut for mo		-	-	-	1 9						В	
Proximity	2.5 m cable	1 9									G	
sensor	Plug M8	1 9									Н	
Proximity	2.5 m cable	1 9									l	
sensor, contactless, PNP	Plug M8	1 9									J	
Connecting cable	M8, 2.5 m	1 9									V	
Slot cover for s	ensor slot	-	-	19							L	
Operating inst	ructions	Express waiv	er – no operat	ing instruction	ns to be includ	led (already a	vailable)				-0	


 $<sup>[1] \</sup>quad {\sf EX2,EX3} \quad \ {\sf Not\,with\,moment\,compensator\,FK,\,proximity\,sensor\,G,\,H,\,I,\,J,\,connecting\,cable\,V}$ 

# Peripherals overview





1) Operation without cushioning components is not permitted.



# Peripherals overview

Varia	nts and accessories			
	Type/order code	For piston diam.	Description	→ Page/Internet
[1]	Linear drive DGC-GF	18 63	Linear drive without accessories, plain-bearing guide	24
[2]	Mechanical end-position limiter YWZ	18 63	For variable end-position adjustment, e.g. for format adjustments	70
[3]	Centring pin/sleeve <sup>1)</sup> ZBS/ZBH	18 63	For centring loads and attachments on the slide	74
-	Cushioning PPV	18 63	Adjustable, pneumatic end-position cushioning. Used at medium speeds.	39
[4]	Shock absorber YSR	18 63	Self-adjusting, hydraulic shock absorber with spring return and linear cushioning characteristics.	39
[5]	Shock absorber YSRW	18 63	Self-adjusting, hydraulic shock absorber with spring return and progressive cushioning characteristics	39
[6]	One-way flow control valve GRLA	18 63	For regulating speed	75
[7]	Proximity sensor G/H/I/J	18 63	For sensing the slide position	75
[8]	Connecting cable V	18 63	For proximity sensor	76
[9]	Slot cover L	18 63	For protecting against contamination and securing the proximity sensor cable in place	74
[10]	Profile mounting M	18 63	Simple and precise mounting option via dovetail connection.	66
[11]	Slot nut B	25 63	For mounting attachments	74
[12]	Foot mounting F	18 63	For mounting on the end cap	64
[13]	Centring sleeve ZBH	50, 63	For centring the drive without foot mountings (user-specific)	74

<sup>1)</sup> Included in the scope of delivery of the drive

# Linear drives DGC-GF, with plain-bearing guide

# Data sheet








Diameter

18 ... 63 mm



Stroke length

1 ... 8500 mm



General technical data										
Piston diameter		18	25	32	40	50	63			
Design		Rodless drive	Rodless drive							
Moment compensator principle		Slotted cylinder	, mechanically cou	oled						
Guide	Plain-bearing g	uide								
Mode of operation	Double-acting									
Stroke	[mm]	1 3000	1 8500		1 5000					
Pneumatic connection		M5	G1/8		G1/4		G3/8			
Cushioning → page 27	,									
DGCPPV	'	Adjustable at b	oth ends	'						
DGCYSR	'	Self-adjusting a	t both ends	'						
Cushioning length	[mm]	16.5	15.5	17.5	29.5	29.8	31.1			
with cushioning PPV										
Max. speed	[m/s]	3								
Position sensing		Via proximity se	nsor							
Type of mounting	'	Profile mounting								
		Foot mounting				·				
		Direct mounting	5		-					
Mounting position		Any								

<sup>♦</sup> Note: This product conforms to ISO 1179-1 and ISO 228-1.

Operating and environmental conditions									
Piston diameter		18	25	32	40	50	63		
Operating pressure	[bar]	2 8	2 8						
Operating medium		Compressed	Compressed air to ISO 8573-1:2010 [7:-:-]						
Note on operating/		Lubricated o	peration possible (in	which case lubricated o	peration will always be	e required)			
pilot medium									
Ambient temperature <sup>1)</sup>	[°C]	-10 +60	-10 +60						
Food-safe <sup>2)</sup>		→ suppleme	→ supplementary information on materials						
Corrosion resistance class CRC <sup>3)</sup>		2							

- 1) Note operating range of proximity sensors
- 2) Additional information is available at www.festo.com/sp  $\Rightarrow$  Certificates.
- 3) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation can occur. External visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment.

Forces [N] and impact energy [J]								
Piston diameter	18	25	32	40	50	63		
Theoretical force at 6 bar	153	295	483	754	1178	1870		
Impact energy at the end positions	→ page 27							

ATEX <sup>1)</sup>						
Explosion-proof ambient temperature [°C]	-10°C ≤ Ta ≤ +60°C					
CE marking	To EU Explosion Protection Directive (ATEX)					
(see declaration of conformity)						
EX2 certification						
ATEX category for gas	3G					
Type of ignition protection for gas	Ex h IICT4 Gc X					
ATEX category for dust	II 3D					
Type of ignition protection for dust	Ex h IIIC T120°C Dc X					
EX3 certification						
ATEX category for gas	12G					
Type of ignition protection for gas	Ex h IIC T4 Gb X					

<sup>1)</sup> Note the ATEX certification of the accessories.

Weight [g]						
Piston diameter	18	25	32	40	50	63
Basic weight with 0 mm stroke	763	1609	2532	5252	10065	16308
Additional weight per 10 mm stroke	23	35	55	76	117	180
Moving mass	267	526	824	1725	3319	5226

# Adjustable end-position range d [mm]






The permissible kinetic energy decreases if the stroke is reduced with PPV adjustable cushioning at both ends.

Piston diameter	18	25	32	40	50	63
Cushioning						
DGCPPV	13.8 15.8	21.1 25.1	25.2 30.2	28.7 33.7	28.7 33.7	38.8 43.8
DGCYSR/YSRW	14.5 24.5	22.5 32.5	27.3 37.3	31 41	31 56	41 76

# Materials

Sectional view




Linea	r drives	
[1]	Guide rail	Anodised aluminium
[2]	Slide	Anodised aluminium
[3]	End cap	Anodised aluminium
[4]	Cylinder barrel	Anodised aluminium
-	Piston seal	Polyurethane
	Sealing band/cover strip	Polyurethane
	Slide elements	Polyacetal
	Note on materials	RoHS-compliant

#### Characteristic load values

The indicated forces and torques refer to the centre of the slide surface.

These values must not be exceeded during dynamic operation. Special attention must be paid to the deceleration phase.



- Note

To prevent the drive with plain-bearing guide DGC-GF from self-locking when used vertically and with a high torque load, the variant with the recirculating ball bearing guide DGC-KF → page 40 is recommended.

If the drive is subjected to two or more of the indicated forces and torques simultaneously, the following equation must be satisfied in addition to the indicated maximum loads:


$$\frac{Fy}{Fy_{max.}} + \frac{Fz}{Fz_{max.}} + \frac{Mx}{Mx_{max.}} + \frac{My}{My_{max.}} + \frac{Mz}{Mz_{max.}} \leq 1$$

Permissible forces and torques in relation to a travel speed of 0.2 m/s									
Piston diameter		18	25	32	40	50	63		
Fy <sub>max</sub> .	[N]	440	640	900	1380	1500	2300		
Fz <sub>max</sub> .	[N]	540	1300	1800	2000	2870	4460		
Mx <sub>max</sub> .	[Nm]	3.4	8.5	15	28	54	96		
My <sub>max</sub> .	[Nm]	20	40	70	110	270	450		
Mz <sub>max.</sub>	[Nm]	8.5	20	33	54	103	187		

# Influence of ferritic materials on proximity sensors

Ferritic materials (steel parts or sheet metal) in the immediate vicinity of the proximity sensors can cause sensing malfunctions. The following safety distances must be observed.


The distance depends on the position of the proximity sensor (see [1] and [2]).




Piston diameter			8	12	18	25	32	40	50	63
Distance L1	[1]	[mm]	0	0	0	0	0	0	0	0
	[2]	[mm]	-	-	0	0	0	0	0	0
Distance L2	[1]	[mm]	20	10	10	10	0	0	0	0
	[2]	[mm]	-	-	25	25	25	25	25	25
Distance L3	[1]	[mm]	30	25	25	25	25	25	25	25
	[2]	[mm]	-	-	10	10	0	0	0	0
Distance L4	[1]	[mm]	0	0	0	0	0	0	0	0
	[2]	[mm]	-	_	0	0	0	0	0	0

# Maximum permissible piston speed v as a function of payload m and distance $r_{max}$ from the centre of mass


With cushioning PPV



# With cushioning YSR



# With cushioning YSRW





These specifications represent the maximum values that can be achieved. In practice, these values can fluctuate dependent on the position of the payload and mounting position.

# Operating range of the cushioning

The end-position cushioning must be adjusted to ensure jerk-free operation. If the operating conditions are outside the permissible range, the moving mass must be cushioned using suitable equipment (external shock absorbers), preferably at the centre of mass.




Note

To avoid distortion in the slide, the bearing surfaces of the attachments must maintain a flatness of at least 0.03 mm.

Data for horizontal mounting position:


bata for nonzontal mounting position:										
Piston diameter		8	12	18	25	32	40	50	63	
Distance r <sub>max.</sub>	[mm]	25	35	35	50	50	50	50	50	



# Number of profile mountings MUC as a function of weight force F and distance I between supports

In order to limit deflection in the case of large strokes, the drive may need to be supported. The following graphs are provided to determine the maximum permissible distance between supports as a function of the mounting position and the applied weight and normal forces.


Horizontal mounting position





# Number of profile mountings MUC as a function of weight force F and distance I between supports

In order to limit deflection in the case of large strokes, the drive may need to be supported. The following graphs are provided to determine the maximum permissible distance between supports as a function of the mounting position and the applied weight and normal forces.

# Vertical mounting position











# Example:

The drive DGC-25-1500 is subjected to a force of 300 N in a horizontal mounting position.

The drive has an overall length of:

- l = stroke length + L1
   (see dimensions)
  - = 1500 mm + 200 mm
  - = 1700 mm

According to the graph, the max. distance between supports for the drive DGC-25 with a force of 300 N is 1300 mm.

In this example, profile mountings are required as the max. distance between supports (1300 mm) is smaller than the overall length of the drive (1700 mm).

# **Dimensions** Download CAD data → www.festo.com ø 18 ... 40 В2 B13 6 D4 5 В9 £ EE 1 2 EE -[3] В1 L1+ View B Ø18 018...40 D4 6 D4 6 B10 plus stroke length Note [1] Compressed air supply port options on 2 sides The linear drive is actuated at the right end or at both ends by default. [2] Compressed air supply port options on 2 sides, for compressed air supply The linear drive can be actuated at the left end or at both ends by specifying the port at one end order code DL in the modular product system. [3] Sensor slot for proximity sensor Mounting hole for foot mounting HPC [4] Drilled hole for centring pin/sleeve [5]


Thread for end stop

Ø	B1	B2	В3	B4	B	5	В6	B7	B8		В9	B10		B11	B12
[mm]					±0.0	05									
18	44.5	49.9	19.5	8.8	21	l l	31	0.8	3.8		1	2.4	+	5.5	15.5
25	59.8	66	30	12.65	30	)	42	1	6.65		1	3.5	,	9.3	21
32	73	79	38.5	5.7	63.	.1	57.5	-	8.5		1.5	14		14.9	18
40	91	98.5	45	17.2	55	5	65	-	12.2		2	8		16.5	24.8
ø	B13	B14	D1 Ø	D2	D3		D4	EE	H1		H2	Н3		H4	Н5
[mm]			±0.05		H7									±0.2	
18	39	19.5	2	M4	5		M12x1	M5	56.3		23.1	55		9.6	13.4
25	53.5	30	3	M5	9		M12x1	G1/8	68		29	67		13.65	15.8
32	66.5	38.5	3	M6	9		M14x1	G1/8	78.5		30	77		5.7	17
40	80.5	45	4	M6	9		M16x1	G1/4	99.5		41.5	97.	5	17.2	25
ø	H6	H7	Н8	Н9	H10	H11	H12	2   J1		J2	J3		L1	L2	L3
[mm]						±0.15	5 ±0.0	5							
18	20	4.6	2.4	25.2	46	8.5	30	20	)	16.5	11	1	150	74.5	5.7
25	24	7.65	4.5	29	55.5	12	35	26	.1	18.6	17	2	200	100	10.5
32	27.7	8.5	14	35.2	63.8	11.45	5 50	3(	)	22	18.5	2	250	124.8	14.5
40	36.5	12.2	8	44	81.5	15	60	3	5	26	26	3	300	150	14.6
Ø	L4	L5	L6			L7		T1		T2	T3		T4	Stro	ke tolerance
[mm]				PP'	V	YSR	YSRW				+0.2	2			
18	5.8	15	5.5	0		15.9	19.4	9		2	3.1		17.1		0 2.5
25	10.6	24.5	10.6	0		12.5	15	17.5	5	2	2.1		20.5		
32	14.5	30.5	14.5	0		8.5	15.5	15		2	2.1		21.3		
40	14.6	33.5	14.6	0		12.8	21	20		3	2.1		30.7		

- 🖣 - Note

This product conforms to ISO 1179-1 and ISO 228-1.

Length tolerance											
For stroke	e [mm]	≤ 1000	≤ 2000	≤ 3000	≤ 4000	≤ 5000	≤ 6000	≤ 7000	≤ 8000	≤ 9000	
L1	[mm]	+0.90	+1.10	+1.40	+1.50	+1.60	+1.70	+2.20	+2.30	+2.40	



30.4

36.2

0 ... 2.5

# Data sheet

Ø	B1	B2	В3	B6	B8	В9	B11	B12	B13	B14	B15	D2	D3 Ø	D4
[mm]										±0.05			H7	
50	113	126.5	60	81.6	12	-	21	24	97	52.8	8	M8	9	M22x1.5
63	142	149	68	97	19.5	5	21	30	123.5	68	15.5	M10	9	M26x1.5
Ø	EE	H1	H2	Н3	H5	Н6	H7	H9	H10	H11	H12	H13	J1	J2
[mm]										±0.2	±0.05			
50	G1/4	124.5	38.5	122.5	29.3	36	12	53	104.5	8	100	52.8	30.5	30.5
63	G3/8	153.5	48.5	151	34.8	46	19.5	67	131	15.5	120	68	41.5	39.5
ø	J3	L1	L2	L3	L4	L5	L6		L7	Т Т	1 T	3 T4	Strol	ke tolerance
[mm]	1							PPV	YSR Y	SRW	+0	2		

- 🏺 - Note

31.5

63

This product conforms to ISO 1179-1 and ISO 228-1.

350

400

200

20

20

Length to	olerance					
For strok	e [mm]	≤ 1000	≤ 2000	≤ 3000	≤ 4000	≤ 5000
L1	[mm]	+0.90	+1.10	+1.40	+1.50	+1.60

20

38.3

0

48.3

27.5

2.1

#### Dimensions Download CAD data → www.festo.com Slide Ø 18 Ø 25 View A View A 6 D4 L3 L1 [5] Drilled hole for centring sleeve ZBH L6 [6] Drilled hole for centring pin ZBS В3 D1 D2 D3 D4 D5 Н3 Н4 Н5 L1 Ø H2 Ø Ø [mm] ±0.05 Н7 Н7 ±0.03 ±0.1 ±0.1 18 4.5 M5 М5 18 107 5 5 16.5 M5 9 M6 22 32±0.2 25.5 136 25 М5 Ø L2 L3 L4 L5 L6 L7 T1 T2 T3 T4 [mm] ±0.1 ±0.03 ±0.1 ±0.05 ±0.1 20 18 20±0.1 10 3.1±0.1 6.3

74

44±0.2

25

40

30


60


8.5

2.1+0.2

10

11.8





20

30

30

# Data sheet

[mm] 25

32

40

50

63


15.23

18

20.5

43.8

49



40

30

30

26.5

20.5

30.5


37

# Ordering data - Modular product system

#### Order code



1) Operation without cushioning components is not permitted.



# Ordering data – Modular product system

Ordering table		18	125	32	40	50	63	Condi-	Code	l
Size		18	25	32	40	50	63	tions	Code	Enter code
Module no.		532446	532447	532448	532449	532450	532451			
Function		Linear drive		·			•		DGC	DGC
Piston diameter	[mm]	18	25	32	40	50	63		☆	
Stroke	[mm]	1 3000								
Guide		Plain-bearing	guide			, , , , , , , , , , , , , , , , , , ,			☆ -GF	-GF
Cushioning			shioning, adjusta		☆ -PPV					
			er, self-adjusting			-YSR				
	Shock absorber, self-adjusting, progressive								☆ -YSRW	
Position sensing		Via proximity							<b>☆</b> -A	-A
Compressed air supp	ly port		d or at both end	S					☆	
			or at both ends		-DL					
Lubrication		Standard							☆	
EU certification		Without	proved for use ii	n food application	15			[1]	-H1	
EU CEITIICATION		II 3GD		[2]	-EX2					
		II 2G						[2]	-EX3	
Accessories	:	Enclosed sepa	arately (can be re	trofitted)	:	:	<u> </u>		ZUB-	ZUB-
Foot mounting		1			F					
Profile mounting		1 9	1						M	
Slot nut for mounting	slot slot	-	1 9						В	
Proximity sensor	2.5 m cable	1 9	•		-				G	
I	Plug M8	1 9							Н	
Proximity sensor,	2.5 m cable	1 9							l	
contactless, PNP	Plug M8	1 9							J	
Connecting cable	M8, 2.5 m	M8, 2.5 m 1 9								
Slot cover for sensor slot 1 9								L		
Mechanical end-posi	tion	Without								
limiter			osition, at one e	[3]	YWZ1					
Variable end position, at both ends								[3]	YWZ2	
Operating instruction	ıs	Express waive	r – no operating	instructions to be	e included (already	v available)			-0	

[1] H1 [2] EX2, EX3 [3] YWZ1, YWZ2


Not with cushioning YSR, YSRW Not with proximity sensor G, H, I, J, connecting cable V Only with cushioning YSR or YSRW

# Peripherals overview



- 🖣 - Note

1) Operation without cushioning components is not permitted.



# Peripherals overview

	nts and accessories Type/order code	For piston diam.	Description	→ Page/Internet
[1]	Linear drive DGC-KF	8 63	Linear drive without accessories, with recirculating ball bearing guide	42
[2]	Intermediate-position module Z1/Z2/Z3	25, 32, 40	Enables up to three intermediate positions	72
[3]	Mechanical end-position limiter YWZ	18 63	For variable end-position adjustment, e.g. for format adjustments	70
[4]	Centring pin/sleeve <sup>1)</sup> ZBS/ZBH	8 63	For centring loads and attachments on the slide	74
[5]	Clamping unit 1H-PN	25, 32, 40, 50	For holding loads	45
-	Cushioning P	8, 12	Non-adjustable, elastic cushioning. Used only at low speeds.	62
-	Cushioning PPV	18 63	Adjustable, pneumatic end-position cushioning. Used at medium speeds.	62
[6]	Shock absorber YSR	8 63	Self-adjusting, hydraulic shock absorber with spring return and linear cushioning characteristics.	62
[7]	Shock absorber YSRW	8 63	Self-adjusting, hydraulic shock absorber with spring return and progressive cushioning characteristics	62
[8]	One-way flow control valve GRLA	8 63	For regulating speed	75
[9]	Proximity sensor G/H/I/J	8 63	For sensing the slide position	75
[10]	Connecting cable V	8 63	For proximity sensor	76
[11]	Slot cover L	18 63	For protecting against contamination and securing the proximity sensor cable in place	74
[12]	Profile mounting M	8 63	Simple and precise mounting option via dovetail connection.	66
[13]	Slot nut B	25 63	For mounting attachments	74
[14]	Foot mounting	8 63	For mounting on the end cap	64
[15]	Centring pin/sleeve ZBS/ZBH	863	For centring the drive without foot mountings (user-specific)	74

<sup>1)</sup> Included in the scope of delivery of the drive

#### Linear drives DGC-KF, with recirculating ball bearing guide

#### Data sheet








Diameter

8 ... 63 mm



Stroke length

1 ... 8500 mm



General technical data												
Piston diameter		8	12	18	25	32	40	50	63			
Design		Rodless drive										
Moment compensator principle		Slotted cylind	er, mechanically	er, mechanically coupled								
Guide		External recirc	ulating ball bear	ing guide								
Mode of operation	[											
Stroke	[mm]	1 1300	1 1900	1 3000	1 8500			1 5000				
Pneumatic connection		M5			G1/8		G1/4	·	G3/8			
Cushioning → page 46						,						
DGCP		Non-adjustab	le at both ends	-								
DGCPPV		-		Adjustable a	t both ends	,						
DGCYSR		Self-adjusting	at both ends									
Cushioning length	[mm]	-		16.5	15.5	17.5	29.5	29.8	31.1			
with cushioning PPV												
Max. speed	[m/s]	1	1.2	3								
Repetition accuracy	[mm]	0.02 (with she	ock absorber YSR	/YSRW)								
Position sensing		Via proximity	sensor									
Type of mounting		Profile mount	ing									
		Foot mounting	nting									
		Direct mounti	ng									
Mounting position		Any										

### - 🌓

Note

This product conforms to ISO 1179-1 and ISO 228-1.

Operating and environmental conditions												
Piston diameter		8	12	18	25	32		40	50	63		
Operating pressure	[bar]	2.5 8		2 8				1.5 8				
Operating medium Compressed air to ISO 8573-1:2010 [7:-:-]												
Note on operating/		Lubricated or	Lubricated operation possible (in which case lubricated operation will always be required)									
pilot medium												
Ambient temperature <sup>1)</sup>	[°C]	-10 +60				·						
Food-safe <sup>2)</sup>	-	-		→ supple	mentary informa	tion on mate	rials					
Corrosion resistance class CRC <sup>3)</sup>		1										

<sup>1)</sup> Note operating range of proximity sensors

<sup>2)</sup> Additional information is available at www.festo.com/sp  $\rightarrow$  Certificates.

<sup>3)</sup> Corrosion resistance class CRC 1 to Festo standard FN 940070

Low corrosion stress. Dry indoor application or transport and storage protection. Also applies to parts behind coverings, in the non-visible interior area, and parts which are covered in the application (e.g. drive trunnions).

Forces [N]								
Piston diameter	8	12	18	25	32	40	50	63
Theoretical force at 6 bar	30	68	153	295	483	754	1178	1870
Impact energy at the end positions	→ page 46							

ATEX <sup>1)</sup>	
Explosion-proof ambient temperature [°C]	-10°C ≤ Ta ≤ +60°C
CE marking	To EU Explosion Protection Directive (ATEX)
(see declaration of conformity)	
EX2 certification	
ATEX category for gas	II 3G
Type of ignition protection for gas	Ex h IIC T4 Gc X
ATEX category for dust	II 3D
Type of ignition protection for dust	ExhIIICT120°CDcX
EX3 certification	
ATEX category for gas	II 2G
Type of ignition protection for gas	Ex h IICT4 Gb X

<sup>1)</sup> Note the ATEX certification of the accessories.

Weight [g]								
Piston diameter	8	12	18	25	32	40	50	63
DGC								
Basic weight with 0 mm stroke	225	391	975	2113	2837	6996	13342	22220
Additional weight per 10 mm stroke	11	16	31	49	74	117	153	236
Moving mass	77	149	331	732	1146	2330	4511	8225
DGC1H-PN – With clamping unit	,					,		
Basic weight with 0 mm stroke	-	-	-	3134	4272	12009	19394	-
Additional weight per 10 mm stroke	-	-	-	49	74	117	153	-
Moving mass	-	-	-	1405	2059	5494	8411	-

#### Adjustable end-position range d [mm]






- Note

The permissible kinetic energy decreases if the stroke is reduced with PPV adjustable cushioning at both ends.

Piston diameter	8	12	18	25	32	40	50	63
Cushioning								
DGCP/PPV	11.3 16.3	12.7 17.7	13.8 15.8	21.1 25.1	25.2 30.2	28.7 33.7	28.7 33.7	38.8 43.8
DGCP/PPV-GP	-	-	16.9 18.9	23.6 27.6	25.2 30.2	34.7 39.7	-	-
DGCYSR/YSRW	12.8 22.8	14 24	14.5 34.5	22.5 47.5	27.3 52.3	31 56	31 56	41 76

#### Materials

Sectional view




Linea	ar drives	
[1]	Guide rail	High-alloy steel
[2]	Slide	High-alloy steel
[3]	End cap	Anodised aluminium
[4]	Cylinder barrel	Anodised aluminium
-	Piston seal	Polyurethane
-	Sealing band/cover strip	Polyurethane
	Note on materials	RoHS-compliant, free of copper and PTFE

#### Influence of ferritic materials on proximity sensors

Ferritic materials (steel parts or sheet metal) in the immediate vicinity of the proximity sensors can cause sensing malfunctions. The following safety distances must be observed.

The distance depends on the position of the proximity sensor (see [1] and [2]).




Piston diameter			8	12	18	25	32	40	50	63
Distance L1	[1]	[mm]	0	0	0	0	0	0	0	0
	[2]	[mm]	-	-	0	0	0	0	0	0
Distance L2	[1]	[mm]	20	10	10	10	0	0	0	0
	[2]	[mm]	-	-	25	25	25	25	25	25
Distance L3	[1]	[mm]	30	25	25	25	25	25	25	25
	[2]	[mm]	-	-	10	10	0	0	0	0
Distance L4	[1]	[mm]	0	0	0	0	0	0	0	0
	[2]	[mm]	-	-	0	0	0	0	0	0

#### Characteristic load values

The indicated forces and torques refer to the centre of the slide surface.

These values must not be exceeded during dynamic operation. Special attention must be paid to the deceleration phase.



If the drive is subjected to two or more of the indicated forces and torques simultaneously, the following equation must be satisfied in addition to the indicated maximum loads:

$$\frac{Fy}{Fy_{max.}} + \frac{Fz}{Fz_{max.}} + \frac{Mx}{Mx_{max.}} + \frac{My}{My_{max.}} + \frac{Mz}{Mz_{max.}} \le 1$$

Permissible forces and torques											
Piston diameter		8	12	18	25	32	40	50	63		
Fy <sub>max.</sub>	[N]	300	650	1850	3050	3310	6890	6890	15200		
Fz <sub>max.</sub>	[N]	300	650	1850	3050	3310	6890	6890	15200		
Mx <sub>max</sub> .	[Nm]	1.7	3.5	16	36	54	144	144	529		
My <sub>max</sub> .	[Nm]	4.5	10	51	97	150	380	634	1157		
Mz <sub>max.</sub>	[Nm]	4.5	10	51	97	150	380	634	1157		

Technical data – Clamping unit					Dimensions → page 58
Size		25	32	40	50
Pneumatic connection		M5	M5	M5	M5
Clamping type		Clamping via spring force,	compressed air to release		
Static holding force	[N]	320	500	1200	1200
Max. number of emergency braking operations <sup>1)</sup>		-	-	750	750
at reference energy	[J]			35	35
Number of clamping operations under rated load	[millions of	0.45	0.55	0.05	0.05
	switching cycles]				

 $<sup>1) \</sup>quad \hbox{Emergency braking refers to braking the payload if the drive axis loses power.}$ 


Operating and environmental conditions – Clamping unit								
Operating medium		Compressed air to ISO 8573-1:2010 [7:4:4]						
Operating pressure								
Clamping unit open	[bar]	4.5 8						
Clamping unit closed	[bar]	Unpressurised						
Ambient temperature	[°C]	-10 +60						


#### Maximum permissible piston speed v as a function of payload m and distance $r_{max}$ from the centre of mass

Ø 50


Piston diameter 8/12 with cushioning P


Piston diameter 18 ... 63 with cushioning PPV






Piston diameter 8 ... 63 with cushioning YSR







- 🏺 - Note

These specifications represent the maximum values that can be achieved. In practice, these values can fluctuate dependent on the position of the payload and mounting position.

#### Operating range of the cushioning

Ø 18


Ø 25


The end-position cushioning must be adjusted to ensure jerk-free operation. If the operating conditions are outside the permissible range, the moving mass must be cushioned using suitable equipment (shock absorbers, stops, etc.), preferably at the centre of mass.



To avoid distortion in the slide, the bearing surfaces of the attachments must maintain a flatness of at least 0.01 mm.

Data for horizontal mounting position:








#### Number of profile mountings MUC as a function of weight force F and distance I between supports

In order to limit deflection in the case of large strokes, the drive may need to be supported. The following graphs are provided to determine the maximum permissible distance between supports as a function of the mounting position and the applied weight and normal forces.


#### Horizontal mounting position









#### Vertical mounting position











#### Example:

The drive DGC-25-1500 is subjected to a force of 300 N in a horizontal mounting position.

The drive has an overall length of:

- l = stroke length + L1
   (see dimensions)
  - = 1500 mm + 200 mm
  - = 1700 mm

According to the graph, the max. distance between supports for the drive DGC-25 with a force of 300 N is 1300 mm.

In this example, profile mountings are required as the max. distance between supports (1300 mm) is smaller than the overall length of the drive (1700 mm).

#### Central lubrication

The lubrication adapters enable the guide of the linear drive DGC-KF to be permanently lubricated in applications in humid or wet ambient conditions using semi or fully automatic relubrication devices.

- For piston diameters 25, 32, 40, 63
- The modules are suitable for oils and greases.
- The dimensions of the linear drive DGC-KF are the same with and without central lubrication modules.
- Both lubrication adapters must be connected
- There are three connection options on each side
- Can be used in combination with:
  - Standard slide GK
  - Additional slide KL, KR
- Cannot be used in combination with:
  - Protected recirculating ball bearing guide GP


Slide dimensions

→ page 56

Order code C in the modular product system → page 63


#### Connection options

Only the connection at the rear or on the top can be used in combination with shock absorbers in the end caps.



#### Connection option for customer design

The drawing on the right shows the connection option on the top lubrication interface using a customer design.



- D1 8+0.2 mm
- D2 6 mm
- T1 0.6<sub>-0.05</sub> mm
- T2 0.1<sup>+0.2</sup> mm
- O-ring diameter 6x1 mm (DIN 3771)
- [1] Slot depth for O-ring
- [2] Required air gap


Additional dimensions → page 56

#### Structure of a central lubrication system


A central lubrication system requires various additional components. The illustration shows different options (using a hand pump, pneumatic container pump or electric container pump) required as a minimum for designing a central lubrication system. Festo does not sell these additional components; however, they can be obtained from the following companies:

- Lincoln
- Bielomatik
- SKF (Vogel)

Festo recommends these companies because they can supply all the necessary components.



- [1] Hand pump
- [2] Pneumatic container pump
- [3] Electric container pump
- [4] Manually operated container pump
- [5] Nipple block
- [6] Distributor block
- [7] Tubing or piping
- [8] Fittings



Ø [mm]	B1	B2	В3	B5	В6	В7	B8 ±0.05	B9 ±0.1	B13	D1	D2 Ø H8	D3 Ø H7	D6
8	25	26	25	18.6	11.7	3	6	3.2	20.5	M4	2	5	М3
12	30.2	31	31	20.6	13.5	3	8	4.8	25	M4	2	5	M4
ø	EE	H1	H2	Н3	H4	Н5	Н6	H7	Н9	H10	J4	L1	L2
[mm]													
[mm] 8	M5	32	23	29	8.5	11.7	16.5	4.5	12.3	8.7	2.2	100	50.1

Ø	L3	L5	L6		L7	L8	L9	L17	T1	T2	T3	T4	Stroke tolerance	
[mm]			Р	YSR	YSRW	±0.03	±0.1	±0.1					+0.2	
8	6	11.4	0	16	16.2	20	20	10	52	5	2	4.3	3	0 1.7
12	8	15.9	0	11.3	12.3	20	20	10	65	6	2	5	3	

Length tol	erance		1
For stroke	[mm]	≤ 1000	≤ 2000
L1	[mm]	+0.90	+1.10

Profile barrel


Ø 8


Ø 12





[1] Sensor slot for proximity sensor





- port at one end Sensor slot for proximity sensor [3]
- [4] Mounting hole for foot mounting HPC
- Drilled hole for centring pin/sleeve [5]
- Thread for end stop
- [7] Additional slide

The linear drive is actuated at the right end or at both ends by default.


The linear drive can be actuated at the left end or at both ends by specifying the order code DL in the modular product system.


ø	B1	B2	В3	B4	B5	В6	В	7	В8	В9	B10	B11
[mm]			±0.05	±0.1	±0.05				±0.1			
18	44.5	49.9	19.5	8.8	21	31	0.	8	3.8	1	2.4	5.5
25	59.8	66	30	12.65	30	42	1		6.65	1	3.5	9.3
32	73	79	38.5	5.7	63.1	57.5	-	-	8.5	1.5	14	14.9
40	91	98.5	45	17.2	55	65	-	-	12.2	2	8	16.5
50	113	126.5	52.8	-	-	81.6	-	-	12	-	-	21
63	142	149	68	-	-	97	-		19.5	5	-	21
Ø	B12	B13	B14	B15	D1	D2	D	3	D4	EE	H1	H2
					Ø		Q	5				
[mm]					±0.05		H	7				
18	15.5	39	19.5	-	2	M4	5		M12x1	M5	56.3	23.1
25	21	53	29	-	3	M5	9		M16x1	G1/8	68	29
32	18	65	38.5	-	3	M6	9		M16x1	G1/8	78.5	30
40	24.5	80.5	45	-	4	M6	9		M22x1.5	G1/4	99.5	41.5
50	24	97	60	8	_	M8	9		M22x1.5	G1/4	124.5	38.5
63	30	123.5	68	15.5	-	M10	9	)	M26x1.5	G3/8	153.5	48.5
ø	H3	H4	H5	Н6	H7	Н8	H9		H10	H11	H12	H13
[mm]		±0.2									±0.05	
18	55	9.6	13.4	20	4.6	2.4	25.	2	46	8.5±0.15	30	-
25	67	13.65	15.8	24	7.65	4.5	29	)	55.5	12±0.15	35	-
32	77	13.65	17	27.7	8.5	14	35.	2	63.8	11.45±0.1	.5 50	_
40	97.5	17.2	25	36.5	12.2	8	44		81.5	15±0.15	60	-
50	122.5	-	29.3	36	12	=	53		104.5	8±0.2	100±0.05	52.8
63	151	-	34.8	46	19.5	-	67	'	131	15.5±0.2	120±0.05	68
ø	J1	J2	J3		L1		1		L2		L3	L4
_		,	,-	KF	KF-GP	1H-PN	K	F	KF-GP	1H-PN		
[mm]												
18	20	16.5	11	150	157	-	74	.5	78	-	5.7	5.8
25	26.1	18.6	17	200	205	271	10	00	102.5	100	10.5	10.6
32	30	22	18.5	250	250	320.5	124	4.8	124.8	124.8	14.5	14.5
40	35	26	26	300	312	458	15		156	150	14.6	14.6
50	30.5	30.5	28	350	-	555.8	17		-	-	17	17
63	41.5	39.5	31.5	400	-	-	20	00	-	_	20	20
ø	L5	L6	1	L <i>7</i>		1	T1	T2	1	T3	T6	Stroke tolerance
_			PPV	YSR	YSRV	N		12		.,	.0	
[mm]				.51	.51					+0.2		
18	15	5.5	0	29.9	32.4	4	9	2		3.1	15	0 2.5
25	24.5	10.6	0	35.6	38.6		17.5	2		2.1	17.3	1
32	30.5	14.5	0	19.5	28		15	2		2.1	20	1
40	33.5	14.6	0	38.5	43.5	5	20	3		2.1	25.7	1
50	41	17	0	31	36.3	3	24	_		2.1	28.75	1
63	44	20	0	38.3	48.3	3	27.5	_		2.1	36.1	]



This product conforms to ISO 1179-1 and ISO 228-1.

Length tole	rance									
For stroke	[mm]	≤ 1000	≤ 2000	≤ 3000	≤ 4000	≤ 5000	≤ 6000	≤ 7000	≤ 8000	≤ 9000
L1	[mm]	+0.90	+1.10	+1.40	+1.50	+1.60	+1.70	+2.20	+2.30	+2.40






Dimensions

# Slide, variant GP – Protected recirculating ball bearing guide Ø 18 Ø 25 View A View A Ø 32 Ø 40 View A View A L8 [5] Drilled hole for centring sleeve ZBH [6] Drilled hole for centring pin ZBS

Download CAD data → www.festo.com

ø	B3	D1	D2 Ø	D3	D4	D5 Ø	H2	Н3
[mm]	±0.05		H7			H7		
18	4.5	M5	5	_	M5	5	16.5	-
25	5	M5	9	M6	M5	7	22	32±0.2
32	5	M5	9	M6	M5	7	19.5	47±0.2
40	7	M5	9	M6	M6	7	26.8	55±0.2
ø	H4	H5	L1	L2	L3	L4	L5	L6
[mm]	±0.03	±0.1		±0.2		±0.03	±0.1	±0.05
18	-	18	88±0.1	-	20±0.1	20	10	-
25	-	25.5	104±0.2	74	44±0.2	40	30	60
32	20	29.5	131±0.2	100	70±0.2	40	45	85
40	20	34.7	169±0.2	116	76±0.2	40	60	110
ø	L7	L8	L9	T1	Т2	Т3	Т	4
[mm]	±0.1							
18	-	99	120	-	3.1±0.1	7.5	6	.7
25	-	118.5	144	10	2.1±0.2	7.5		8
32	-	145.7	173	10	2.1±0.2	7.5	:	8
40	-	195.4	231	10.5	2.1±0.2	7.5	8	.5



Ø	В3	B5	В6	D1	D2	D3	D4	D5	D6	H2	Н3	H4	H5
					Ø			Ø					
[mm]	±0.05	±0.05			H7			H7				±0.03	±0.1
25	5	1	8.5	M5	9	M6	M5	7	M6x1	22	32±0.2	-	25.5
32	5	1.5	7.5	M5	9	M6	M5	7	M6x1	19.5	47±0.2	20	29.5
40	7	18.2	18.2	M5	9	M6	M6	7	M6x1	26.8	55±0.2	20	34.7
63	8	12.5	27.5	M8	9	M6	M8	9	M6x1	55	90±0.3	40	-
Ø	L1	L2	L3	L4	L5	L6	L7	L8	L10	T1	T2	T3	T4
[mm]		±0.2	±0.2	±0.03	±0.1	±0.05	±0.1				±0.2		
25	104±0.2	74	44	40	30	60	-	145	132	10	2.1	7.5	8
32	131±0.2	100	70	40	45	85	-	172	158	10	2.1	7.5	8
40	169±0.2	116	76	40	60	110	-	224.4	210.4	10.5	2.1	7.5	8.5
63	256±0.1	169	99	40	70	130	190	308.4	293.8	15.5	2.1	18	13.6

Profile barrel

Ø 18


Ø 25


ø 32

ø 40












ø 50






- [1] Sensor slot for proximity sensor
- [2] Mounting slot for slot nut

Ø	B10	B11	H10	H11
[mm]				
25	15.23	-	-	-
32	18	-	26.5	-
40	20.5	40	20.5	20
50	43.8	30	30.5	30
63	49	30	37	30






# Ordering data - Modular product system

#### Order code




1) End stops or shock absorbers must not be removed.




# Ordering data - Modular product system

#### Order code

KL/KR - With additional slide



GP – With protected recirculating ball bearing guide



#### Working stroke reduction when ordering an additional slide KL or KR

For a linear drive DGC with additional slide, the working stroke is reduced by the length of the additional slide and the distance between both slides.

Assuming: DGC-12-500-... L = 20 mm

L17 = 65 mm

ø [mm]	8	12	18	25	32	40	50	63
L17	52	65	99	118.5	145.7	195.4	256.8	280

The working stroke is reduced to 415 mm = 500 mm - 20 mm - 65 mm

# Linear drives DGC-KF, with recirculating ball bearing guide

# Ordering data - Modular product system

Ordering table											
Size	8	12	18	25	32	40	50	63	Condi- tions	Code	Enter code
Module no.	530906	530907	532446	532447	532448	532449	532450	532451			
Function	Linear drive									DGC	DGC
Piston diameter [mm]	8	12	18	25	32	40	50	63		☆	
Stroke [mm]	1 1300	1 1900	1 3000	1 8500			1 5000			☆	
Guide	Recirculating	g ball bearing	guide	•			•			☆ -KF	-KF
Cushioning	Elastic cushioning rings/ plates at both ends							<b>☆</b> -P			
	-	-	Pneumatic o	cushioning, a	djustable at b	oth ends	_			☆ -PPV	
	Shock absor	rber, self-adju	sting							-YSR	İ
	Shock absor	rber, self-adju	sting, progress	sive						☆ -YSRW	
Position sensing	Via proximit	y sensor								<b>☆</b> -A	-A
Compressed air supply port	At the right	end or at both	ends							☆	
	_	-	At the left e	nd or at both	ends					-DL	
Slide	-	-	Protected re	circulating ba	all bearing gui	de	-	-	[1]	-GP	
Lubrication	_	-	Standard							☆	
	_	-	Lubrication	approved for	use in food ap	plications			[2]	-H1	
Lubrication function	Standard									☆	
	_	_	_	Lubrication	adapter				[3]	-C	
Additional slide on left		lide, standar	<u> </u>						[4]	-KL	
Additional slide on right	Additional s	lide, standard	d, on right						[4]	-KR	
Clamping unit	_	-		Without				-		☆	
	-	-	-	1-channel				-	[5]	-1H	
Actuation type	_	-	-	Without				-		☆	
	-	-	-	Pneumatic				-	[5]	-PN	
EU certification	Without									☆	
	II 3GD								[6]	-EX2	
	II 2G								[6]	-EX3	

		NOT WITH ADDITIONAL STIDE KE, KK
[2]	H1	Not with protected version GP, cushioning YSR, YSRW or clamping unit 1H
[3]	C	Not with slide GP
		For size 50, only with clamping unit 1H
[4]	KL, KR	For a linear drive DGC with additional slide, the working stroke is reduced by the length of the additional slide and the distance between both slides.
		Not with cushioning PPV
[5]	1H, PN	Not with intermediate-position module Z1, Z2, Z3; end-position limiter YWZ1, YWZ2; protected version GP; additional slide KL, KR or lubrication H1
		Only with cushioning YSRW
		1H only with PN

[6] EX2, EX3 Not with protected recirculating ball bearing guide GP, lubrication adapter C, clamping unit 1H-PN, proximity sensor G, H, I, J, connecting cable V, intermediate-position module Z1, Z2, Z3

[1] GP

Not with cushioning YSR, YSRW

# Ordering data – Modular product system

Ordering table												
Size		8	12	18	25	32	40	50	63	Condi- tions	Code	Enter code
Accessories		Enclosed s	Enclosed separately (can be retrofitted)								ZUB-	ZUB-
Foot mounting		1									F	
Profile mounting		1 9									M	
Slot nut for mounting slo	nting slot 1 9							В				
roximity sensor 2.5 m cable 1 9						G						
	1 9	19							İ	Н		
Proximity sensor, 2.5 m cable		1 9									l	
contactless, PNP	Plug M8	1 9								İ	J	
Connecting cable	M8, 2.5 m	1 9									V	
Slot cover for sensor slot		-	-	1 9							L	
Mechanical end-position	limiter	-	1-	Variable e	nd position,	at one end				[7]	YWZ1	
		-	-	Variable e	nd position,	at both end:	S			[7]	YWZ2	İ
Intermediate-position mo	odule	-	-	-	1 intermed	diate positio	n	-	-	[8]	-Z1	
	-	-	-	2 intermed	diate positio	ns	-	-	[8]	-Z2		
		-	-	-	3 intermed	diate positio	ns	-	-	[8]	-Z3	
Operating instructions		Express w	aiver – no or	erating inst	ructions to b	e included (	already avai	ilable)			-0	

<sup>[7]</sup> YWZ1, YWZ2 Only with cushioning YSR or YSRW


<sup>[8]</sup> YWZ1, YWZ2 Only with cushioning YSR or YSRW and mechanical end-position limiter YWZ1 or YWZ2

#### Foot mounting HPC

(order code: F)



#### Material: Galvanised steel



Dimensions	and ordering data								
For diam.	AB	AC	AH	AO	AT	AU	В	B1	
	Ø								
[mm]							G	GF/KF	
8	3.4	1.5	16.7	3	2	9	6	6	-
12	4.5	2	18.5	4.5	2	11.5	5.4	5.4	-
18	5.5	2	-	6.75	3	13.25	15	11.2	4.3
25	5.5	2	-	9	4	15	12.5	13.35	7.65
32	6.6	2	-	10	5	19	11.5	9	9
40	6.6	2	-	10	6	20	7.6	12.6	12.2
50	9	3	-	11	8	25	12.5	12.5	11.5
63	11	3	-	13.5	8	28	17.5	17.5	12.5

For diam.	В3	В	B4		5	H1		
[mm]		GF	KF	G	GF/KF	G	GF/KF	
8	-	-	-	-	-	37	37	
12	-	-	-	-	-	42.5	42.5	
18	15.2	-	5.3	27	23.2	57.5	64	
25	21.35	-	8.65	28.65	29.5	67	76.5	
32	29.5	-	10.5	29.5	27	82	87.5	
40	32.8	-	14.2	31.8	36.8	100	111.5	
50	48.5	11.5	11.5	41	41	137	141.5	
63	55.5	6.5	17.5	49	49	159	172.5	

Dimensions	and ordering data						
For diam.	H2	H3	H4		H6	S	SA
[mm]	GF/KF	GF/KF	G	GF/KF		G/GF/KF KF-GP	
	,	,	-	,	_	• •	
8	-	-	-	-	5	118 <sub>-0.2</sub>	-
12	_	-	-	-	5	148_0.2	-
18	59.5	16	14	21.2	7.7	176.5_0.2	183.5-0.2
25	71.5	14.35	9.85	19.35	8.5	2300.2	235_0.2
32	82.5	8	7.5	13	9	288_0.2	288_0.2
40	104.5	15.3	10.8	22.3	12	340_0.2	352_0.2
50	134.5	23.4	25.9	30.4	17	400_0.2	-
63	164.5	22	24	30	19	456 <sub>-0.2</sub>	-

For diam.	TR	TR1	US	Weight	Part no.	Type <sup>1)</sup>
[mm]	±0.1	±0.1		[g]		
8	18	-	24.4	25	526385	HPC-8
12	20	-	29.6	41	526388	HPC-12
18	30	-	38.6	58	533667	HPC-18
25	40	-	55	131	533668	HPC-25
32	56.5	19.5	68	239	533669	HPC-32
40	65	25	78	348	533670	HPC-40
50	82.6	47.4	102	754	545236	HPC-50
63	111	39	133	1245	545237	HPC-63


<sup>1)</sup> Suitable for ATEX

#### Profile mounting MUC

(order code: M)

Material: High-alloy steel





Dimensions	and ordering data					
For diam.	АН	B1	B2	1	B4	
[mm]				G	GF/KF	
8	17.7	47	36.7	15.35	15.35	-
12	18.5	52.5	42.2	16.5	16.5	-
18	27.2	67.8±0.2	56±0.15	30.5	28.7	27.2
25	32.5	79.5±0.2	65.5±0.15	32.5	28.5	37.5
32	37.5	94±0.2	80±0.15	35	35	47.5
40	47	110.5±0.2	96±0.15	43	43	57
50	61	145±0.5	125±0.2	56	56	77
63	75	169±0.5	149±0.2	72.5	72.5	87

For diam.	В	35	В6	D1 ø	D2 Ø		H1	
[mm]	G	GF/KF		H13	H7	G	GF/KF	1H-PN
8	-	_	5.1	3.5	-	37	37	_
12	-	-	5.1	3.5	-	42.5	42.5	-
18	25	23.2	5.7	5.5	5	57.5	64	-
25	33.5	29.5	7	5.5	5	67	76.5	87.5
32	37	37	7	5.5	5	82	87.5	97.5
40	46.8	46.8	7	6.5	6	100	111.5	125.5
50	61	61	7	9	6	137	141.5	151
63	69	69	10	9	6	159	172.5	-


Dimensions	Dimensions and ordering data										
For diam.	H2	H3	ŀ	L1							
[mm]			G	GF/KF							
[IIIIII]			ų d	GF/KF							
8	5	7	_	_	24						
12	4.5	7	_	_	24						
18	5.7_0.2	9.9±0.1	0.1	6.4	33±0.1						
25	6.5_0.2	12.5±0.1	2.07	7.43	35±0.1						
32	6.5 <sub>-0.2</sub>	13±0.1	1.5	4	45±0.1						
40	8.5_0.2	16±0.1	0.2	11.3	60±0.1						
50	11	23.5	4.7	9.2	80±0.4						
63	11	25.5	1.5	15	80±0.4						

For diam.	L2	L3	Weight	Part no.	Type <sup>1)</sup>
[mm]	±0.05	±0.2	[g]		
8	-	=	28	526384	MUC-8
12	-	-	32	526387	MUC-12
18	20.5	-	78	531752	MUC-18
25	22.5	-	113	531753	MUC-25
32	30	-	174	531754	MUC-32
40	44	-	346	531755	MUC-40
50	26	56	874	531756	MUC-50
63	26	56	1080	531757	MUC-63

<sup>1)</sup> Suitable for ATEX

#### Moment compensator FKC

(order code: FK) for DGC-G Materials: Plate: wrought aluminium alloy Articulated joint: polyamide Ball stud: high-alloy steel





For diam.	Max. offset betwe	en linear drive and	d Max. peri	nissible load in d	irection of force				Ambient te	emperature		
. 1	external guide		TNI)						[0.0]			
[mm]	[mm]		[N]						[°C]			
8	±2.5		550			Backlash-free				_10 +60		
12			550			Backlash-free						
18			1400			Backlash-free						
25			1400			Backlash-free						
32			1400									
40			1400	1400 Bao								
50	±4		5000	5000 Lov								
63			5000			Low backlash						
For diam.	B1	B2	В3	B4	D1	D2	H1	H2	2	Н3	L1	
[mm]												
8	17.5	10.2	30	16	M5	20	43.5	42	2	48	40	
12	18.5	10.2	31	16	M5	20	49	47.	.5	53.5	40	
18	29.3	16.5	47.8	20	M8	30	66.8	59.	.8	73.8	60	
25	42.65	16.5	61.15	30	M8	30	75.5	68	3	82.5	60	
32	43	16.5	61.5	30	M8	30	90	82.	.5	97	60	
40	57.3	16.5	75.8	45	M8	30	105	97.		113	60	
50	44	16	74	60	12 <sup>H7</sup>	32	156.5	14	0	172.4	120 125	
63	50	16	80	60	12 <sup>H7</sup>	32	176.5	161	.5	192.4	120 125	
For diam.	L2	L3	L4	L5	L6	CRC <sup>1)</sup>	Weigh	t Part	no.	Туре		
[mm]							[g]					
8	5.1	62.6	35	13	9	1	29	5	29350	FKC-8/12		
12	17.1	74.6	35	13	9		29	5	29350	FKC-8/12		
18	24.5	107	65	15.5	14		97	5	38714	FKC-18		
25	50	132.5	65	15.5	14		119	5	38715	FKC-25		
32	77.5	162	75	17.5	14		122	5	38961	FKC-32		
40	103	187.5	75	17.5	14		180	5	38962	FKC-40		
50	50 55	260	170	45	80		1200	5	45240	FKC-50/63		
63	75 80	260	170	45	80		1200	5	45240	FKC-50/63		

<sup>1)</sup> Corrosion resistance class CRC 1 to Festo standard FN 940070

Low corrosion stress. Dry indoor application or transport and storage protection. Also applies to parts behind coverings, in the non-visible interior area, and parts which are covered in the application (e.g. drive trunnions).

#### **Shock absorber retainer DADP-DGC** Stop KYC

(order code: YWZ1 or YWZ2) for DGC-GF, DGC-KF, DGC-FA

Shock absorber retainer DADP








Materials: Shock absorber retainer, housing: anodised aluminium Free of copper and PTFE

Materials:

Stop, housing: anodised aluminium Stop bracket: stainless steel casting

Clamp: high-alloy steel Free of copper and PTFE



#### Note

Shock absorbers are not included in the scope of delivery.

Existing shock absorbers can be removed from the end caps of the linear drive and installed in the shock absorber retainer.

Under no circumstances may the linear drive and the intermediate-position module be operated without a shock absorber.

Dimension	s							
For diam. [mm]		B1	B2	В3	H1	H2	Н3	H4
18	GF KF	16	34.5	29	20.7	0.2	12.5	0.7
25	GF KF	16.5	35	28 30	25.5	0.5	15	1.4
32	GF KF	16.5	35	28 30	25.5	0.5	15	1.7
40	GF KF	16	35.7	29 35	32 37	0.5	21.5	1.6
50	GF KF	25	50	41	40.5	0.5	24	0
63	GF KF	25	50	40	51.5	1.5	33	0
For diam. [mm]		L1	L2	L3	L4	L5	L6	L7 min.
18	GF KF	128	74.5	107	80	118.5	23.5	14.5
25	GF KF	168	100	136	80	125	20.5	22.5
32	GF KF	206.8	124.8	164	120	165	14.5	42.8 27.3
40	GF KF	255	150	210	156	220.5	31	30.8 31
50	GF KF	301	175	252	170	238	27	31
63	GF KF	328	200	256	200	268	24	41

# Technical data and ordering data Precision adjustment Mounting example - Note The stop KYC can be used in both directions. Mounting example - Note The stop KYC can be mounted at any position along the stroke.

For diam.		Max. impact force	Ambient temperature	CRC <sup>1)</sup>	Weight	Part no.	Type <sup>2)</sup>
[mm]		[N]	[°C]		[g]		
Shock abso	rber re	tainer			,		
18	GF	1100	-10 +80	2	140	541725	DADP-DGC-18-GF
	KF				130	541729	DADP-DGC-18-KF
25	GF	1400			205	541726	DADP-DGC-25-GF
	KF				180	541730	DADP-DGC-25-KF
32	GF	1700			225	541727	DADP-DGC-32-GF
	KF				215	541731	DADP-DGC-32-KF
40	GF	3500			380	541728	DADP-DGC-40-GF
	KF				460	541732	DADP-DGC-40-KF
50	GF	3500			890	545244	DADP-DGC-50
	KF						
63	GF	4300			1080	545245	DADP-DGC-63
	KF						

<sup>1)</sup> Corrosion resistance class CRC 2 to Festo standard FN 940070 Moderate corrosion stress. Indoor applications in which condensation can occur. External visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment.

2) Suitable for ATEX

For diam. [mm]	Precision adjustment L [mm]	Ambient temperature [°C]	CRC <sup>1)</sup>	Weight [g]	Part no.	Type <sup>2)</sup>
Stop						
18	10	-10 +80	2	400	541691	KYC-18
25	10			560	541692	KYC-25
32	10			790	541693	KYC-32
40	15			1525	541694	KYC-40
50	15			2270	545242	KYC-50
63	15			2950	545243	KYC-63

<sup>1)</sup> Corrosion resistance class CRC 2 to Festo standard FN 940070 Moderate corrosion stress. Indoor applications in which condensation can occur. External visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment.


<sup>2)</sup> Suitable for ATEX

# Intermediate-position module DADM-DGC

(order code: Z1, Z2 or Z3)

for DGC-KF


Materials: Housing: anodised aluminium Stop screw, nut: Galvanised steel Clamp, lever: High-alloy steel Free of copper and PTFE



Dimensions												
For diam. [mm]	B1	B2	В3	D1	H1	H2	Н3	H4	L1	L2	L3	L4
25	105	16.5	40	19	69.4	68.6	41	1.4	116	100	13.4	52.2
32	117.5	16.5	40	19	80.2	79.7	52	1.7	116	100	13.4	52.2
40	137.5	16	41	27	101.6	101.1	63	2.1	186	170	13.4	76.5


#### Minimum distance

Between end stop and intermediate position




	For diam. [mm]	L1
ſ	25	145.3
ſ	32	185.3
	40	271.5

#### Between two intermediate positions




For diam. [mm]	L2	L3	L4
25	105	100	2.5
32	105	100	2.5
40	175	170	2.5

- 🖣 Note
- Shock absorbers are not included in the scope of delivery.
   Existing shock absorbers can be removed from the end caps of the linear drive and installed in the shock absorber retainer.
- Under no circumstances may the linear drive and the intermediate-position module be operated without a shock absorber.
- A shock absorber retainer DADP-DGC and a stop KYC are additionally required when using an intermediate-position module.
- The projection (dimension H4) must be observed when using the drive in combination with the intermediate-position module DADM-DGC. Mounting via foot mountings HP or profile mountings MUC is recommended in this
- The stop lever positions can be sensed via proximity sensors SME/SMT-10
   → page 75.
- After reaching the intermediate position, the slide cannot directly travel further in the same direction. After an intermediate stop, the slide must first move back so that the stop lever of the intermediate-position module can swing in. The intermediate position can then be travelled through.



The intermediate-position module DADM-DGC can be used in both directions. A shock absorber retainer DADP-DGC and a stop KYC are additionally needed when using an intermediate-position module.

#### Mounting example





The intermediate-position module DADM-DGC can be mounted at any place along the stroke.

Technical data							
For diam.	[mm]	25	32	40			
Pneumatic connection		QS-4					
Operating pressure	[bar]	2.5 8					
Mounting position		Any					
Impact speed	[m/s]	→ page 46	→ page 46				
Swivel time	[ms]	≤100	≤100	≤300			
Precision adjustment L	[mm]	2	2	4			
Repetition accuracy	[mm]	0.02		•			
Position sensing		Via proximity sensors SME/SM	MT-10				
Weight	[g]	430	530	970	_		
Ambient temperature	[°C]	-10 +60		`			
Corrosion resistance class CRC <sup>1)</sup>		2					
Note on materials		Free of copper and PTFE	Free of copper and PTFE				
		RoHS-compliant		-			

1) Corrosion resistance class CRC 2 to Festo standard FN 940070

Moderate corrosion stress. Indoor applications in which condensation can occur. External visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment.

Ordering data			
	For diam.	Part no.	Туре
	[mm]		
	25	541700	DADM-DGC-25-A
	32	541701	DADM-DGC-32-A
	40	541702	DADM-DGC-40-A

#### Linear drives DGC

# Accessories

Ordering data									
	For diam.	Comment	Order code	Part no.	Туре	PU <sup>1)</sup>			
Slot nut HMBN <sup>2)</sup>				•	Data sheets •	→ Internet: hmbn			
	25 40	For mounting slot	В	547264	HMBN-5-1M5	10			
	50,63			186566	HMBN-5-2M5				
Centring pin/sleeve ZBS/ZBH <sup>2)</sup>			<u>'</u>		Data sheets →	Internet: zbs, zbh			
	For DGC-G								
	8, 12	For slide	1-	150928	ZBS-5	10			
	8, 12	For cap	-	525273	ZBS-2				
	50,63	<u> </u>		150927	ZBH-9				
	For DGC-GF	l			-				
	18	For slide	_	150928	ZBS-5	10			
	25 63			150927	ZBH-9				
	50, 63	For cap	_	150927	ZBH-9				
	For DGC-KF	1.0.04		150527					
	8, 12, 18	For slide	_	150928	ZBS-5	10			
	25 63			150927	ZBH-9				
	8, 12	For cap	-	525273	ZBS-2				
	18			150928	ZBS-5				
	25 63			150927	ZBH-9				
	25 05			1,0,2,	2511 7				
Slot cover ABP-S <sup>2)</sup>					Data sheet	s → Internet: abp			
	18 63	For sensor slot Each 0.5 m	L	151680	ABP-5-S	2			
Shock absorber YSRW <sup>2)</sup>					Data sheets	→ Internet: ysrv			
	8	For DGC basic design and	YSRW	540344	YSRW-DGC-8	1			
	12	recirculating ball bearing guide		540345	YSRW-DGC-12				
	18	For DGC with plain-bearing guide		540346	YSRW-DGC-18-GF				
	25			540348	YSRW-DGC-25-GF				
	32			540350	YSRW-DGC-32-GF				
	40			540352	YSRW-DGC-40-GF				
	50			1232870	YSRW-DGC-40/50-B				
	63			543069	YSRW-DGC-63				
	18	For DGC with recirculating	$\dashv$	540347	YSRW-DGC-18-KF				
	25	ball bearing guide		540349	YSRW-DGC-25-KF				
	32			540351	YSRW-DGC-32-KF				
	40, 50			1232870	YSRW-DGC-40/50-B				
	63			543069	YSRW-DGC-63				
	(0)			545009	13KW-DGC-03				

Packaging unit
 Suitable for ATEX

Ordering data	a									
	For diam.	Comment	Order code	Part no.	Туре	PU <sup>1)</sup>				
One-way flow	One-way flow control valve GRLA Data sheets → Internet: gr									
8	8 18	Metal design	-	<b>193137</b>	GRLA-M5-QS-3-D	1				
				<b>193138</b>	GRLA-M5-QS-4-D					
	25, 32			<b>193142</b>	GRLA-1/8-QS-3-D					
				<b>193143</b>	GRLA-1/8-QS-4-D					
				<b>193144</b>	GRLA-1/8-QS-6-D					
				<b>193145</b>	GRLA-1/8-QS-8-D					
	40, 50			<b>193146</b>	GRLA-1/4-QS-6-D					
				<b>193147</b>	GRLA-1/4-QS-8-D					
				<b>193148</b>	GRLA-1/4-QS-10-D					
	63			<b>★</b> 193149	GRLA-3/8-QS-6-D					
				<b>★</b> 193150	GRLA-3/8-QS-8-D					
				<b>★</b> 193151	GRLA-3/8-QS-10-D					

<sup>1)</sup> Packaging unit

#### Proximity sensors for piston diameter 8/12 and intermediate-position module DADM

Ordering data − Proximity sensors for C-slot, magneto-resistive  Data sheets → Internet: smt									
			Electrical connection,	Cable length	Part no.	Туре			
		output	outlet direction of connection	[m]					
N/O contact									
	Insertable in the slot from above	PNP	Plug M8x1, 3-pin, in-line	0.3	<b>★</b> 551375	SMT-10M-PS-24V-E-0.3-L-M8D			
12 S			Cable, 3-wire, in-line	2.5	<b>★</b> 551373	SMT-10M-PS-24V-E-2.5-L-OE			

Ordering data − Proximity sensors for C-slot, magnetic reed  Data sheets → Internet: sme									
	Type of mounting	Switching	Electrical connection,	Cable length	Part no.	Туре			
		output	outlet direction of connection	[m]					
N/O contact									
	Insertable in the slot from above	Contacting	Plug M8x1, 3-pin, in-line	0.3	<b>★</b> 551367	SME-10M-DS-24V-E-0.3-L-M8D			
			Cable, 3-wire, in-line	2.5	<b>★</b> 551365	SME-10M-DS-24V-E-2.5-L-OE			
•			Cable, 2-wire, in-line	2.5	<b>★</b> 551369	SME-10M-ZS-24V-E-2.5-L-0E			
	Insertable in the slot lengthwise	Contacting	Plug M8x1, 3-pin, in-line	0.3	173212	SME-10-SL-LED-24			
			Cable, 3-wire, in-line	2.5	173210	SME-10-KL-LED-24			

#### Proximity sensors for piston diameter 18 $\dots$ 63

Ordering data	a – Proximity sensors for T-slot, magr	eto-resistive				Data sheets → Internet: smt
	Type of mounting	Switching output	Electrical connection	Cable length [m]	Part no.	Туре
N/O contact						
	Insertable in the slot from above,	PNP	Cable, 3-wire	2.5	<b>★</b> 574335	SMT-8M-A-PS-24V-E-2.5-OE
THE STATE OF THE S	flush with the cylinder profile,		Plug M8x1, 3-pin	0.3	<b>★</b> 574334	SMT-8M-A-PS-24V-E-0.3-M8D
	short design		Plug M12x1, 3-pin	0.3	<b>★</b> 574337	SMT-8M-A-PS-24V-E-0.3-M12
		NPN	Cable, 3-wire	2.5	<b>★</b> 574338	SMT-8M-A-NS-24V-E-2.5-OE
			Plug M8x1, 3-pin	0.3	<b>★</b> 574339	SMT-8M-A-NS-24V-E-0.3-M8D
N/C contact						
	Insertable in the slot from above, flush with the cylinder profile, short design	PNP	Cable, 3-wire	7.5	<b>★</b> 574340	SMT-8M-A-PO-24V-E-7.5-OE

Proximity s	ensors for piston diameter	18 6	3					
Ordering dat	ta – Proximity sensors for T-slo	t, magne	tic reed					Data sheets → Internet: sme
	Type of mounting		Switching output	Electrical conn	ection	Cable length [m]	Part no.	Туре
N/O contact						<u> </u>	·	
	Insertable in the slot from	above, (	Contacting	Cable, 3-wire		2.5	<b>★</b> 543862	SME-8M-DS-24V-K-2.5-OE
<b>62.8</b>	flush with the cylinder pro	file				5.0	<b>★</b> 543863	SME-8M-DS-24V-K-5.0-OE
				Cable, 2-wire		2.5	<b>★</b> 543872	SME-8M-ZS-24V-K-2.5-OE
				Plug M8x1, 3-	pin	0.3	<b>★</b> 543861	SME-8M-DS-24V-K-0.3-M8D
N/C contact								
	Insertable in the slot from flush with the cylinder pro	· · · · ·	Contacting	Cable, 3-wire		7.5	<b>★</b> 546799	SME-8M-DO-24V-K-7.5-OE
Ordering dat	ta – Proximity sensor for T-slot	. magneto	o-resistive. fo	r ATEX zone				Data sheets → Internet: smt
<b>5</b>	Type of mounting	ATEX cat		Switching	Electrical	Cable length	Part no.	Type
	71	Gas	Dust	output	connection	[m]		71
N/O contact								
14/0 contact	Insertable in the slot	II 3G	II 3D	PNP	Plug M8x1,	0.3	574342	SMT-8M-A-PS-24V-E-0.3-M8D-EX2
ST. ST.	from above, flush with		","		3-wire	1.5	01.10.12	
<b>V</b>	the cylinder profile, short							
	design							
	<u> </u>			'	:	•	'	
Ordering dat	ta – Safety clip for ATEX zone							
	Description					For size	Part no.	Туре
	Protects "equipment	that is r	not intrinsica	ılly safe" agains	st simple	Plug M8x1	548067	NEAU-M8-GD
	disconnection, here	the plug	of the proxi	mity sensor SM	Tand			
(A)	connecting cable NEI		'	,				
	ATEX category: gas: II		ct· II 3D					
	MEX category, gas. II	70 / uu	31.11 70					
Ordering dat	ta – Connecting cables							Data sheets → Internet: nebu
•	Electrical connection, left		Electr	ical connection, r	right	Cable length	Part no.	Туре
				,	0	[m]		7
<i>^</i>	Straight socket, M8x1, 3-p	in	Cable	, open end, 3-wir	re	2.5	<b>★</b> 541333	NEBU-M8G3-K-2.5-LE3
	5		Cabic	, -po o.iu, 5 Wii	-	5	★ 541334	NEBU-M8G3-K-5-LE3
<b>3</b>	Straight socket, M12x1, 5-	pin	Cable	open end, 3-wir	re	2.5	<b>★</b> 541363	NEBU-M12G5-K-2.5-LE3
				, ,, ,		5	★ 541364	NEBU-M12G5-K-5-LE3
1	Angled socket, M8x1, 3-pi	n	Cable	, open end, 3-wir	re	2.5	<b>★</b> 541338	NEBU-M8W3-K-2.5-LE3
	, , , , , , , , , , , , , , , , , , , ,					5	<b>★</b> 541341	NEBU-M8W3-K-5-LE3
<b>40</b>	Angled socket, M12x1, 5-p	oin	Cable	, open end, 3-wir	re	2.5	541367	NEBU-M12W5-K-2.5-LE3
						5	541370	NEBU-M12W5-K-5-LE3