

MN1H-5/2-D-3-C-CT

Solenoid valve

Data sheet

Part no.: 184643

Page:1

Feature	Data/description
Switching function	5/2-way valve
Switching function short code	5/2
Direction of flow reversible	No
Operating principle	Slide
Shape of function component	Piston
With exhaust flow control	Yes
Type of regulation	Indirect
Control type	Monostable
Type of reset	Air spring
Grid dimension	71 mm
Type of mounting	Screw
Installation position	Any
Nominal size	14,5 mm
Operating pressure min.	2 bar
Operating pressure max.	10 bar
Minimum ambient temperature	-5 °C
Maximum ambient temperature	50 °C
Minimum medium temperature	-5 °C
Maximum medium temperature	50 °C
Type of connection, air supply	Sub-base
Air connection type power port	Sub-base
Type of connection, exhaust	Sub-base
Air connection type aux. pilot air suppl	Internal
Air connection type aux. pilot air exhau	Sub-base
Nominal size sub-base connection	Size 3 in accordance with ISO 5599-1
Standard sub-base connection pattern	ISO 5599-1
Actuation/reset	Single solenoid, air spring return
Manual override	Detenting manual override
Operating status display	No
Material of housing	AL, die-cast metal
Material of seals	NBR-Elastomer

MN1H-5/2-D-3-C-CT

Solenoid valve

Data sheet

Part no.: 184643

Page:2

Feature	Data/description
CT criterion	Free of copper and PTFE
Standard nominal flow rate 1 - 2	4500 l/min
Standard nominal flow rate 2 - 3	4500 l/min
Standard nominal flow rate 1 - 4	4500 l/min
Standard nominal flow rate 4 - 3/5	4500 l/min
Response time OFF/OVER (dom.)	49 ms
Response time OFF/OVER	71 ms
Voltage type	DC
Nominal voltage	24 V
Power consumption (DC)	2,5 W
Medium	Compressed air, filtered 50 µm or vacuum
Degree of protection	IP65