

Input/Output module

FED-UIM


Part number: 559870

Product to be discontinued

for controller FED-CEC.

Type to be discontinued. Available until 2017. See Support Portal for alternative products.

FESTO



Data sheet

| Feature | Value |
|--|--|
| CE mark (see declaration of conformity) | to EU directive for EMC |
| Storage temperature | -20 ... 70 °C |
| Relative air humidity | 5 - 85 % non-condensing |
| Ambient temperature | 0 ... 50 °C |
| Materials note | Contains PWIS substances |
| Digital inputs, number | 20 |
| Digital inputs, fast counting inputs | 4 |
| Digital inputs, incremental encoder connection | 4 |
| Digital inputs, input signal delay | 0,2 ms |
| Digital inputs, input voltage/current | 24 VDC / 3 mA |
| Digital inputs, nominal value for True | 12 - 30 VDC |
| Digital inputs, nominal value for False | <= 6 VDC |
| Digital inputs, electrical isolation | Yes, via optocoupler |
| Analogue inputs, number | 8 |
| Analogue inputs, resolution | 12 bit |
| Analogue inputs, signal range | 0 - 10 V 0 - 20 mA 0 - 5 V 0 - 1 V 4 - 20 mA ± 1 V ± 10 V ± 5 V PT 100 (-100 °C to 850 °C) Thermoelement E, J, K, R, S, T |
| Analogue inputs, absolute precision at 25 °C | 0,1 % |
| Analogue inputs, linearity error at 25°C | 0,1 % |
| Analogue inputs, input resistance | 47 Ohm |
| Digital outputs, number | 12 |
| Digital outputs, contact | Transistor |
| Digital outputs, output voltage | 12 - 30 VDC |
| Digital outputs, output current | 500 mA |
| Digital outputs, electrical isolation | Yes, via optocoupler |
| Digital outputs, short-circuit proof | Yes |
| Digital outputs, overload proof | Yes |
| Analogue outputs, number | 4 |
| Analogue outputs, resolution | 12 bit |
| Analogue outputs, max. load resistance | 470 Ohm |
| Analogue outputs, signal range | ± 10 V |
| Analogue outputs, linearity error at 25 °C | ± 0.15% voltage output ± 0.2% current output |