

Plug NPQR-D-Q10-Q8

Part number: 8085706

FESTO



Data sheet

| Feature | Value |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size | Standard |
| Nominal size | 7 mm |
| Tubing insertion depth | 17.25 mm...19.35 mm |
| Note on the tubing insertion depth | Ø8 depth 17.25 mm Ø10 depth 19.35 mm |
| Mounting position | optional |
| Design | Straight design Push-pull principle |
| Size of pack | 1 |
| Operating pressure complete temperature range | -0.095 MPa...1.6 MPa -0.95 bar...16 bar -13.775 psi...232 psi |
| Note on operating pressure | Water: max. 0.7 MPa at 0 - 80 °C |
| Certificate issuing authority | NSF C0556009 |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:...] Water (liquid, ice-free) |
| Note on operating and pilot medium | Lubricated operation possible |
| Corrosion resistance class CRC | 4 - Very high corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Suitability for the production of Li-ion batteries | Product corresponds to the internal product definition from Festo for use in battery production: Metals with more than 1% by mass of copper, zinc or nickel are excluded from use. The exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils |
| Cleanroom class | Class 4 according to ISO 14644-1 |
| Suitable for use with food | See declaration of conformity NSF/ANSI 169 |
| Ambient temperature | -20 °C...150 °C |
| Product weight | 25.1 g |
| Pneumatic connection, port 1 | For tubing outer diameter of 10 mm |
| Pneumatic connection, port 2 | For tubing outside diameter of 8 mm |
| Note on materials | RoHS-compliant |
| Material housing | High-alloy stainless steel |
| Guard ring material | High-alloy stainless steel |

| Feature | Value |
|---------------------------------|----------------------------|
| Material release ring | High-alloy stainless steel |
| Material tubing seal | FPM |
| Material tubing clamp component | High-alloy stainless steel |
| Thrust ring material | PPSU |