

Guided drive DGRC-GF-20-25-PA

Part number: 8218199

FESTO



Data sheet

| Feature | Value |
|--|--|
| Distance from centre of gravity of load to yoke plate xs | 50 mm |
| Stroke | 25 mm |
| Piston diameter | 20 mm |
| Operating mode, drive unit | Yoke |
| Cushioning | Elastic cushioning rings/plates at both ends |
| Mounting position | optional |
| Guide | Plain-bearing guide |
| Design | Guidance |
| Position detection | Via proximity switch |
| Protection against torque/guide | Guide rod with yoke |
| Operating pressure | 0.2 MPa...1 MPa 2 bar...10 bar |
| Max. speed | 0.8 m/s |
| Mode of operation | Double-acting |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 0 - No corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Suitability for the production of Li-ion batteries | Suitable for battery production according to the Festo internal definition of the degree of severity F1A with restrictions regarding the use of Cu/Zn/Ni |
| Ambient temperature | -10 °C...60 °C |
| Impact energy in end positions | 0.2 Nm |
| Max. force Fy | 487.2 N |
| Max. force Fy static | 487.2 N |
| Max. force Fz | 487.2 N |
| Max. force Fz static | 487.2 N |
| Max. moment Mx | 13.15 Nm |
| Max. torque Mx static | 13.15 Nm |
| Max. moment My | 6.82 Nm |
| Max. torque My static | 6.82 Nm |

| Feature | Value |
|--|----------------------------------|
| Max. moment Mz | 6.82 Nm |
| Max. torque Mz static | 6.82 Nm |
| Max. permissible torque load Mx as a function of stroke | 2.72 Nm |
| Max. effective load dependent upon stroke at defined distance xs | 57.6 N |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke | 141 N |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 188 N |
| Torsional backlash | 0.055 deg |
| Moving mass | 195.5 g |
| Product weight | 390.6 g |
| Basic weight for 0 mm stroke | 195.1 g |
| Centre of gravity of moving mass as a function of stroke | 26.6 mm |
| Pneumatic connection | M5 |
| Note on materials | RoHS-compliant |
| Material cover | Wrought aluminium alloy |
| Material seals | NBR |
| Material dynamic seals | TPE-U(PU) |
| Material end plate | Anodised wrought aluminium alloy |
| Material guide rod | High-alloy steel |
| Material housing | Anodised wrought aluminium alloy |
| Material piston rod | High-alloy steel |