


Proximity sensor SIEN-4B-NO-S-L

Part number: 150365

FESTO



Data sheet

| Feature | Value |
|--|---|
| Conforms to standard | EN 60947-5-2 |
| Certification | RCM compliance mark c UL us - Listed (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive |
| Rated operating distance | 0.8 mm |
| Assured operating distance | 0.64 mm |
| Reduction factors | Aluminum = 0.4 Stainless steel St 18/8 = 0.7 Copper = 0.3 Brass = 0.4 Steel St 37 = 1.0 |
| Ambient temperature | -25 °C...70 °C |
| Repetition accuracy | 0.04 mm |
| Switching output | NPN |
| Switching element function | N/C contact |
| Max. switching frequency | 3000 Hz |
| Max. switching frequency DC | 3000 Hz |
| Max. output current | 200 mA |
| Voltage drop | 2 V |
| Short-circuit protection | Pulsed |
| DC operating voltage range | 10 V...30 V |
| Residual ripple | 10 % |
| Idle current | 10 mA |
| Reverse polarity protection | for all electrical connections |
| Electrical connection | 3-pin M8x1 Plug |
| Size | 4 mm |
| Type of mounting | Clamped |
| Mounting type | Flush |
| Product weight | 9 g |
| Housing material | High-alloy stainless steel |
| Switching status indication | LED yellow |

| Feature | Value |
|--|----------------------------------|
| Degree of protection | IP67 |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Selection of additional sensor information | With standard switching distance |
| Electrical output | NPN |
| Selection of sensor version | Standard |