



Rotary actuator
DSM-T-10-180-P-FW
Part number: 1561556

FESTO



Data sheet

| Feature | Value |
|--|--|
| Size | 10 |
| Cushioning angle | 0.5 deg |
| Swivel angle | 0 deg...180 deg |
| Cushioning | Elastic cushioning rings/pads at both ends |
| Mounting position | Any |
| Mode of operation | Double-acting |
| Structural design | Rotary vane |
| Position sensing | None |
| Operating pressure | 3.5 bar...8 bar |
| Max. swivel frequency at 6 bar | 3 Hz |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Ambient temperature | 0 °C...60 °C |
| Theoretical torque at 6 bar | 1.7 Nm |
| Permissible mass moment of inertia | 0.0026 kgm ² |
| Product weight | 210 g |
| Type of mounting | With internal thread |
| Pneumatic connection | M3 |
| Note on materials | RoHS-compliant |
| Drive shaft material | High-alloy stainless steel |
| Seals material | TPE-U(PU) |
| Housing material | Aluminum Anodized |