
Vacuum suction cup ESS-10-BS Part number: 189376







Data sheet

| Feature | Value |
|---|--|
| Suction cup height compensation | 4 mm |
| Min. workpiece radius | 20 mm |
| Nominal width | 2 mm |
| Suction cup diameter | 10 mm |
| Suction cup volume | 0.38 cm ³ |
| Connection position | Тор |
| Mounting position | Any |
| Classification of suction cup holder | Size 3 |
| Suction cup shape | Round bellows, 1.5 convolutions |
| Operating pressure | -95 kPa0 kPa -0.95 bar0 bar -13.775 psi0 psi |
| Nominal operating pressure | -70 kPa -0.7 bar -10.15 psi |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7:-:-] |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364 zone III |
| For use in the food industry | See supplementary material information |
| Ambient temperature | -30 ℃180 ℃ |
| Holding force at nominal operating pressure | 4.7 N |
| Lateral force at nominal operating pressure | 2.5 N |
| Product weight | 1.8 g |
| Type of mounting | Via vacuum connection |
| Vacuum connection | M4 |
| Color | Transparent |
| Shore hardness | 50 +/- 5 |
| Material of screwed plug | Brass, nickel-plated |
| Note on materials | RoHS-compliant |
| Suction cup material | VMQ (silicone) |