

Compressed air filter MS6-LF-1/2-ERM

Part number: 529615

FESTO



Data sheet

| Feature | Value |
|----------------------------------|--|
| Size | 6 |
| Series | MS |
| Mounting position | Vertical +/- 5° |
| Grade of filtration | 40 µm |
| Condensate drain | Manually rotating |
| Structural design | Sinter filter with centrifugal separator |
| Bowl guard | Plastic bowl guard |
| Degree of condensate separation | 75 % |
| Operating pressure | 0 bar...20 bar |
| Standard nominal flow rate | 4100 l/min |
| Operating medium | Compressed air as per ISO 8573-1:2010 [::9:-] Inert gas |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Storage temperature | -10 °C...60 °C |
| For use in the food industry | See supplementary material information |
| Air quality class at the output | Compressed air as per ISO 8573-1:2010 [7:8:4] |
| Temperature of medium | -10 °C...60 °C |
| Ambient temperature | -10 °C...60 °C |
| Pore size | 40 µm |
| Product weight | 600 g |
| Type of mounting | Line installation With accessories Optionally: |
| Pneumatic connection 1 | G1/2 |
| Pneumatic connection 2 | G1/2 |
| Note on materials | RoHS-compliant |
| Seals material | NBR |
| Compressed air filter material | PE |
| Housing material | Die-cast aluminum |
| Material of bowl | PC |
| Separating disc material | POM |

