
Filter regulator PCRP-64-G14-12-E-R1-M-T19 Part number: 5394672

FESTO





Data sheet

ns to standard ndensate volume 30 cm³ Ider function With primary With seconda e gauge gau	ing r without pressure gauge r/ISO 15156 (housing and bowl) pressure compensation y exhausting
P or lock Adjusting scree ing position Vertical +/- 50 of filtration Adjusting scree in g position Vertical +/- 50 of filtration Adjusting scree in g position Vertical +/- 50 Adjusting scree Vertical +/- 50 Adjusting scree Vertical +/- 50 Adjusting scree Adjusting screen A	ing r without pressure gauge r/ISO 15156 (housing and bowl) pressure compensation y exhausting
Adjusting screening position Vertical +/- 50 of filtration of filtration filtration Annually rotal rail design filter regulated regulated random standard Instead to standard Indensate volume Ider function With primary with secondary and greening pressure O.1 MPa 2 March 19 derivation are regulation range essure hysteresis and ard flow rate on prevention and protection Adjusting screening screening had put in the second and protection Adjusting screening had put in the second and protection Adjusting screening had put in the second and protection Adjusting screening had put in the second and protection Adjusting screening had put in the second and protection Adjusting screening had put in the second and protection in the second and prote	ing r without pressure gauge r/ISO 15156 (housing and bowl) pressure compensation y exhausting
ng position of filtration sate drain manually rota ral design filter regulate ns to standard NACE MR017 Indensate volume der function with primary With seconda e gauge G1/4 prepare ng pressure 0.1 MPa2 N 1 bar20 bar e regulation range essure hysteresis andard flow rate on prevention and protection Vertical +/- 5° Manually rota Filter regulate With primary With seconda 0.1 MPa2 N 1 bar20 bar 3990 l/min Observe the i Zone 1 (ATEX)	ing r without pressure gauge r/ISO 15156 (housing and bowl) pressure compensation y exhausting
of filtration 40 µm sate drain Manually rota ral design Filter regulate runs to standard NACE MR017 Indensate volume 30 cm³ Iter function With primary With seconda e gauge G1/4 prepare ng pressure 0.1 MPa2 M 1 bar20 bar e regulation range 0.5 bar12 b essure hysteresis 0.2 bar andard flow rate 3990 l/min rd nominal flow rate 2845 l/min on prevention and protection Observe the i Zone 1 (ATEX)	r without pressure gauge /ISO 15156 (housing and bowl) pressure compensation y exhausting
sate drain Manually rota ral design Filter regulate ns to standard NACE MR017 Indensate volume Ider function With primary With seconda e gauge G1/4 prepare ng pressure 0.1 MPa2 M 1 bar20 bar 1 bar20 bar e regulation range essure hysteresis 0.2 bar andard flow rate d nominal flow rate on prevention and protection Observe the i Zone 1 (ATEX)	r without pressure gauge /ISO 15156 (housing and bowl) pressure compensation y exhausting
ral design Insight to standard Insight to standard Indensate volume Ider function Idensity of many Identification and protection Idensity of many Idensity of m	r without pressure gauge /ISO 15156 (housing and bowl) pressure compensation y exhausting
ns to standard ns to standard ndensate volume ler function With primary With seconda e gauge G1/4 prepare 0.1 MPa2 M 1 bar20 bar e regulation range essure hysteresis andard flow rate d nominal flow rate on prevention and protection NACE MR017 NACE MR017 With primary With seconda 0.1 MPa2 M 1 bar2 D bar 2 bar 3 990 l/min 2 bar 3 990 l/min 3 0 cm³ With primary With seconda 2 bar 3 bar12 bar 3 990 l/min 2 bar 3 observe the i Zone 1 (ATEX)	oressure compensation y exhausting
ler function With primary With secondar e gauge G1/4 prepare 0.1 MPa 2 M 1 bar 20 bar e regulation range 0.5 bar 12 bar andard flow rate 3990 l/min con prevention and protection 30 cm³ With primary With secondary With sec	oressure compensation y exhausting
der function With primary With seconda e gauge G1/4 prepare 0.1 MPa2 N 1 bar20 bar 1 bar20 bar 2 bar 2 bar 3990 l/min rd nominal flow rate on prevention and protection With primary With seconda 281/4 prepare 291/4	y exhausting I
With secondarie gauge e gauge G1/4 prepare O.1 MPa2 N 1 bar20 bar e regulation range essure hysteresis andard flow rate rd nominal flow rate on prevention and protection With secondaries O.1 MPa2 N 1 bar20 bar 3990 l/min Observe the i Zone 1 (ATEX)	y exhausting I
ng pressure 0.1 MPa2 N 1 bar20 bar e regulation range 0.5 bar12 b essure hysteresis 0.2 bar andard flow rate 7 nominal flow rate 2845 l/min on prevention and protection Observe the i Zone 1 (ATEX)	
1 bar20 bar e regulation range 0.5 bar12 b essure hysteresis 0.2 bar andard flow rate 3990 l/min rd nominal flow rate 2845 l/min on prevention and protection Observe the i Zone 1 (ATEX)	Pa
essure hysteresis 0.2 bar andard flow rate 3990 l/min rd nominal flow rate 2845 l/min on prevention and protection Observe the i Zone 1 (ATEX)	
andard flow rate 3990 l/min rd nominal flow rate 2845 l/min on prevention and protection Observe the i Zone 1 (ATEX)	ır
rd nominal flow rate 2845 I/min on prevention and protection Observe the i Zone 1 (ATEX)	
on prevention and protection Observe the i Zone 1 (ATEX)	
Zone 1 (ATEX)	
Zone 21 (ATE Zone 22 (ATE	,
ng medium Compressed a Inert gas	ir as per ISO 8573-1:2010 [-:4:-]
tion on operating and pilot media Operation wit	oil lubrication possible (required for further use)
WIS) conformity VDMA24364	one III
temperature -60 °C80 °C	
lity class at the output Compressed a	ir as per ISO 8573-1:2010 [7:4:4]
ature of medium -60 °C80 °C	
t temperature -60 °C80 °C	
t weight 1965 g	

Feature	Value
Type of mounting	Line installation With mounting kit Optionally:
Pressure gauge connection	G1/4
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Drain screw material	High-alloy stainless steel
Drain screw material number	1.4404/316L
Material of filter support	Cast stainless steel
Filter support material number	1.4409/CF3M(316L)
Note on materials	RoHS-compliant
Material of mounting bracket	High-alloy stainless steel
Seals material	CR NBR VMQ
Material of spring	High-alloy stainless steel
Compressed air filter material	High-alloy stainless steel
Compressed air filter material number	1.4404/316L
Housing material	Cast stainless steel
Material number of housing	1.4409/CF3M(316L)
Material of adjusting screw	High-alloy stainless steel
Material of bowl	Cast stainless steel
Bowl material number	1.4409/CF3M (316L)