

## Quarter turn actuator DAPS-0030-090-R-F03-CR Part number: 552870

**FESTO** 





## **Data sheet**

| Feature                                      | Value  |
|--|--|
| Size of valve actuator                       | 0030   |
| Flange hole pattern                          | F03  |
| Swivel angle                                 | 90 deg   |
| Depth shaft connection                       | 10.2 mm  |
| Cushioning                                   | No cushioning  |
| Mounting position                            | Any  |
| Mode of operation                            | Double-acting Double-acting  |
| Structural design                            | Scotch yoke system   |
| Position sensing                             | None   |
| Closing direction                            | Clockwise closing  |
| Safety integrity level (SIL)                 | Up to SIL 2 high demand mode Up to SIL 2 low demand mode           |
| Operating pressure                           | 0.25 MPa0.84 MPa<br>2.5 bar8.4 bar                                 |
| Nominal operating pressure                   | 0.56 MPa<br>5.6 bar  |
| CE marking (see declaration of conformity)   | as per EU explosion protection directive (ATEX)                    |
| UKCA marking (see declaration of conformity) | acc. to UK EX instructions   |
| Explosion prevention and protection          | Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)          |
| Certificate issuing authority                | German Technical Control Board North (TÜV Nord) 212170801          |
| ATEX category gas                            | II 2G  |
| ATEX category for dust                       | II 2D  |
| Type of ignition protection for gas          | Ex h IIC T6T3 Gb X   |
| Type of (ignition) protection for dust       | Ex h IIIC T85°CT200°C Db X   |
| Explosive ambient temperature                | -20°C <= Ta <= +60°C   |
| Operating medium                             | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media     | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)             | 3 - High corrosion stress  |
| LABS (PWIS) conformity                       | VDMA24364-B1/B2-L  |
| Ambient temperature                          | -20 °C80 °C  |

| Feature   | Value                      |
|---|----------------------------|
| Torque at nominal operating pressure and 0° swivel angle      | 30 Nm                      |
| Torque at nominal operating pressure and 50° swivel angle     | 15 Nm                      |
| Torque at nominal operating pressure and 90° swivel angle     | 22.5 Nm                    |
| Air consumption at 6 bar per cycle 0°-nominal swivel angle-0° | 1.04                       |
| Product weight  | 1200 g                     |
| Shaft connection  | Т9                         |
| Pneumatic connection  | G1/8                       |
| Note on materials   | RoHS-compliant             |
| Cover material  | High-alloy stainless steel |
| Material number of cover                                      | 1.4408                     |
| Seals material  | FPM<br>NBR<br>PUR          |
| Housing material  | High-alloy stainless steel |
| Material number of housing                                    | 1.4408                     |
| Material of screws  | High-alloy stainless steel |
| Shaft material  | High-alloy stainless steel |
| Material number for shaft                                     | 1.4301                     |