## **Pressure sensor** SPAW-P25R-G14F-2N-M12


Part number: 8022764



## **Data sheet**

| Feature                                      | Value  |
|--|--|
| Certification                                | RCM compliance mark<br>c UL us - Listed (OL)                                   |
| CE marking (see declaration of conformity)   | As per EU EMC directive<br>As per EU RoHS directive                            |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC<br>To UK RoHS instructions                          |
| Note on materials                            | RoHS-compliant   |
| Measured variable                            | Relative pressure  |
| Method of measurement                        | Metal thin-film pressure sensor  |
| Pressure measuring range initial value       | O MPa<br>O bar<br>O psi  |
| Pressure measuring range end value           | 2.5 MPa<br>25 bar<br>362.5 psi   |
| Overload pressure                            | 5 MPa<br>50 bar<br>725 psi   |
| Operating medium                             | Compressed air as per ISO 8573-1:2010 [-:-:-]<br>Liquid media<br>Gaseous media |
| Temperature of medium                        | -20 °C85 °C  |
| Ambient temperature                          | 0 °C80 °C  |
| Accuracy in ± % FS                           | 1 %FS  |
| Repetition accuracy in ± %FS                 | 0.15 %FS   |
| Switching output                             | 2xNPN  |
| Switching function                           | Freely programmable  |
| Switching element function                   | Switchable   |
| Max. output current                          | 250 mA   |
| Rise time                                    | 3 ms   |
| Short-circuit protection                     | yes  |
| DC operating voltage range                   | 15 V35 V   |
| Reverse polarity protection                  | for operating voltage  |
| Electrical connection 1, connection type     | Plug   |

**FESTO** 



| Feature  | Value  |
|--|--|
| Electrical connection 1, connection technology | M12x1 A-coded as per EN 61076-2-101            |
| Electrical connection 1, number of pins/wires  | 4  |
| Electrical connection 1, type of mounting      | Screw-type lock                                |
| Type of mounting                               | With internal thread<br>With accessories       |
| Mounting position                              | Any  |
| Pneumatic connection                           | Internal thread G1/4                           |
| Product weight                                 | 230 g  |
| Housing material                               | ABS<br>High-alloy stainless steel              |
| Materials in contact with the media            | High-alloy stainless steel                     |
| Display type                                   | 4-character alphanumeric<br>LED display        |
| Displayable unit(s)                            | MPa<br>bar<br>kPa<br>kg/cm <sup>2</sup><br>psi |
| Switching status indication                    | LED red  |
| Setting options                                | Via display and pushbuttons                    |
| Protection against tampering                   | PIN code                                       |
| Setting range threshold value                  | 0.5 %100 %                                     |
| Setting range hysteresis                       | 0.5 %99.5 %                                    |
| Degree of protection                           | IP65<br>IP67                                   |
| Corrosion resistance class (CRC)               | 4 - Particularly high corrosion stress         |
| LABS (PWIS) conformity                         | VDMA24364 zone III                             |