



## **Data sheet**

| Feature                                    | Value  |
|--|--|
| Width                                      | 44 mm  |
| Exhaust air function                       | Via throttle plate   |
| Based on norm                              | ISO 5599-1   |
| Operating pressure                         | 0 MPa1 MPa<br>0 bar10 bar  |
| Suitability for vacuum                     | yes  |
| CE marking (see declaration of conformity) | As per EU low voltage directive                                    |
| Operating medium                           | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media   | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)           | 0 - No corrosion stress  |
| LABS (PWIS) conformity                     | VDMA24364-B1/B2-L  |
| Storage temperature                        | -20 °C60 °C  |
| Temperature of medium                      | -10 °C50 °C  |
| Pilot medium                               | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Ambient temperature                        | -10 °C50 °C  |
| Product weight                             | 400 g  |
| Type of mounting                           | with through-hole for M6 screw                                     |
| Pneumatic connection 1                     | 1/2 NPT  |
| Pneumatic connection 3                     | 1/2 NPT  |
| Pneumatic connection 5                     | 1/2 NPT  |
| Note on materials                          | RoHS-compliant   |
| End plate material                         | Die-cast aluminum  |