

Round cylinder DPRA-N-...-2"- -

Part number: 8109554

FESTO



Data sheet

Feature	Value
Stroke	0.0625 in...12 in
Piston diameter	2"
Piston rod thread	1/2-20 UNF-2A
Cushioning	No cushioning Elastic cushioning rings/pads at both ends Pneumatic cushioning, adjustable at both ends
Mounting position	Any
Structural design	Piston Piston rod Cylinder barrel
Position sensing	For proximity sensor
Variants	End cap with swiveling rod eye, rotated 90° End cap with swiveling rod eye and bearing sleeve End cap with swiveling rod eye Scraper made of NBR Extended external thread piston rod Extended piston rod Bearing cap with mounting thread Axial supply port Lateral supply port With anti-twist protection Through piston rod Temperature range 0 to + 150°C Temperature range -40 to 80°C Piston rod at one end
Operating pressure	9.99 psi...150 psi
Mode of operation	Double-acting Pushing Single-acting Pulling
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress 4 - Particularly high corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
Ambient temperature	-40 °F...300 °F
Product weight	1.04 lb...4.04 lb

Feature	Value
Type of mounting	With accessories
Pneumatic connection	1 / 4 NPT
Note on materials	RoHS-compliant
Cover material	Wrought aluminum alloy High-alloy stainless steel
Seals material	FPM NBR
Piston rod material	High-alloy stainless steel
Material of cylinder barrel	High-alloy stainless steel