

# Angle gripper DHC-10-A

Part number: 8125481

FESTO



## Data sheet

Feature	Value
Size	10
Max. interchangeability	0.2 mm
Max. opening angle	30 deg
Rotational symmetry	0.2 mm
Pneumatic gripper repetition accuracy	0.1 mm
Number of gripper jaws	2
Actuator system	Pneumatic
Mounting position	Any
Mode of operation	Double-acting
Gripper function	Angle
Gripping force backup	Without
Structural design	Connection direction at side Positively driven motion sequence
Position sensing	For proximity sensor
Operating pressure	0.1 MPa...0.8 MPa 1 bar...8 bar 14.5 psi...116 psi
Max. operating frequency of pneumatic gripper	3 Hz
Min. opening time at 6 bar	8 ms
Min. closing time at 6 bar	8 ms
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	0 - No corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Ambient temperature	-10 °C...60 °C
Total gripping torque at 0.6 MPa (6 bar, 87 psi), opening	25.1 Ncm
Total gripping torque at 6 bar, closing	20.6 Ncm
Mass moment of inertia	0.035 kgcm <sup>2</sup>
Maximum force on gripper jaw F <sub>z</sub> , static	40 N
Maximum torque on gripper jaw, M <sub>x</sub> static	0.4 Nm
Maximum torque on gripper jaw, M <sub>y</sub> static	0.5 Nm
Maximum torque on gripper jaw, M <sub>z</sub> static	0.5 Nm

Feature	Value
Product weight	48 g
Type of mounting	Direct mounting via through-hole Direct fastening via thread With through-hole and dowel pin With internal thread and dowel pin Optionally:
Pneumatic connection	M3
Note on materials	RoHS-compliant
Cover cap material	Wrought aluminum alloy, anodized
Housing material	Wrought aluminum alloy, anodized
Gripper jaw material	High-alloy steel