


Radial gripper DHRC-32-A-S-NO

Part number: 8133558

FESTO



Data sheet

| Feature | Value |
|---|--|
| Size | 32 |
| Max. interchangeability | 0.2 mm |
| Max. opening angle | 180 deg |
| Rotational symmetry | 0.2 mm |
| Pneumatic gripper repetition accuracy | 0.1 mm |
| Number of gripper jaws | 2 |
| Actuator system | Pneumatic |
| Mounting position | Any |
| Mode of operation | Single-acting Open |
| Gripper function | Radial |
| Gripping force backup | On opening |
| Structural design | Connection direction at side Positively driven motion sequence |
| Position sensing | For proximity sensor |
| Operating pressure | 0.15 MPa...0.8 MPa 1.5 bar...8 bar 21.75 psi...116 psi |
| Max. operating frequency of pneumatic gripper | 2 Hz |
| Min. opening time at 6 bar | 229 ms |
| Min. closing time at 6 bar | 65 ms |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 0 - No corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Ambient temperature | -10 °C...60 °C |
| Total gripping torque at 6 bar, closing | 539.1 Ncm |
| Mass moment of inertia | 3.122 kgcm ² |
| Maximum force on gripper jaw Fz, static | 210 N |
| Maximum torque on gripper jaw, Mx static | 12 Nm |
| Maximum torque on gripper jaw, My static | 8 Nm |
| Maximum torque on gripper jaw, Mz static | 12 Nm |

| Feature | Value |
|----------------------|---|
| Product weight | 720.5 g |
| Type of mounting | Direct mounting via through-hole Direct fastening via thread With through-hole and dowel pin With internal thread and dowel pin Optionally: |
| Pneumatic connection | M5 |
| Note on materials | RoHS-compliant |
| Cover cap material | Wrought aluminum alloy, anodized |
| Housing material | Wrought aluminum alloy, anodized |
| Gripper jaw material | High-alloy steel |