

Proximity switch SOIA-M18PNB-PNLK-LE

Part number: 8161204

FESTO



Data sheet

Feature	Value
Design	Round
Conforms to standard	EN 60947-5-2
Certification	c UL us - Listed (OL)
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
Note on materials	RoHS-compliant
Measured variable	Position Displacement
Measuring principle	Inductive
Method of measurement	Distance sensor
Rated operating distance	0 mm...12 mm
Note on rated operating distance	SSC1.SP1: 10.2 mm SSC2.SP1: 6.0 mm Factory setting
Position measuring range	0 mm...12 mm
Ambient temperature	-25 °C...70 °C
Displacement resolution	0.01 mm
Repetition accuracy	±0.12 mm
Temperature drift	±10%
Switching output	PNP/NPN switchable Push-pull
Switching element function	Switchable
Note on hysteresis	Factory setting: 5 %FS
Hysteresis	1 %FS...20 %FS
On time	100 ms
Measurement range speed	1 mm/s...3000 mm/s
Accuracy speed	+/- 20 %FS
Repetition accuracy speed	+/- 5 %FS
Acceleration value range	-3270 m/s²...3270 m/s²
Max. switching frequency	1100 Hz
Max. output current	100 mA

Feature	Value
Voltage drop	1 V
Inductive protective circuit	Installed
Minimum load current	0 mA
Residual current	0.03 mA
Short-circuit protection	Pulsed
Overload protection	Available
Protocol	IO-Link®
IO-Link, revision ID	V1.1
IO-Link, device profile	Function Object detection Function Product URI Function Teach two values Identification and diagnosis Smart Sensor - SSP 4.1.1
IO-Link, transmission rate	COM2
IO-Link®, SIO mode support	Yes
IO-Link, port type	Class A
IO-Link, process data length input	32 bit
IO-Link®, process data content IN	Distance measurement 16 bit MDC Distance monitoring 2 bit SSC Maintenance warning 1 bit DSC Motion diagnostic 2 bit DSC
IO-Link®, service data contents IN	Acceleration averages 32 bit Acceleration range 32 bit Acceleration value 16 bit Maintenance monitor operating time 32 bit Maintenance monitor measurement 96 bit Maintenance monitor temperature 64 bit Maintenance diagnostic 7 bit Maintenance monitor SSC 64 bit Velocity 1 averages 32 bit Velocity 1 value 16 bit Velocity 1 value range 32 bit Velocity 2 averages 32 bit Velocity 2 value 16 bit Velocity 2 value range 32 bit
IO-Link®, minimum cycle time	3.2 ms
IO-Link®, data memory required	308 byte
DC operating voltage range	10 V...30 V
Residual ripple	20 %
Idle current	17 mA
Reverse polarity protection	yes
Electrical connection 1, connection type	Cable
Electrical connection 1, number of pins/wires	3
Cable length	2.5 m
Color cable sheath	Gray
Material of cable sheath	PUR
Cable diameter	3.8 mm
Nominal conductor cross section	0.25 mm²
Size	M18
Tightening torque	0 Nm...30 Nm
Mounting type	Not flush
Product weight	83 g
Housing colour	Blue Gray
Housing material	Brass PBT
Lock nut material	Brass
Reference material	36 mm x 36 mm x 1 mm Structural steel, 1.0037, S235JR

Feature	Value
Switching status indication	LED yellow
Storage temperature	-40 °C...85 °C
Degree of protection	IP65 IP67
Resistance to interference from magnetic fields	< 50 µT
Corrosion resistance class (CRC)	3 - High corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L