





Proximity sensors, round design

Product range overview

FESTO

Measuring principle	Version	Type	Assembly	Switching element function		Switch output	Electrical connection	
				N/O contact	N/C contact		Cable	Plug
Magneto-inductive	Operating voltage range 10 ... 30 V DC							
		SMT0-4U	Via accessories	■	–	PNP	3-wire	M8x1, 3-pin
				■	–	NPN	3-wire	M8x1, 3-pin
Magnetic reed	Operating voltage range 12 ... 30 V AC/DC							
		SME0-4U	Via accessories	■	–	Contacting	3-wire	M8x1, 3-pin
		CRSME0-4 Corrosion resistant	Via accessories	■	–	Contacting	3-wire	–
Magnetic reed	Operating voltage range 12 ... 250 V AC/DC							
		SME0-4U	Via accessories	■	–	Contacting	2-wire	–

Proximity sensors, round design

Product range overview


FESTO

Type	Connection direction		Switching status display via LED	Free of copper and PTFE	→ Page/Internet
	In-line	Lateral			
Operating voltage range 10 ... 30 V DC					
SMT0-4U	■	–	■	■	6
	■	–	■	–	
Operating voltage range 12 ... 30 V AC/DC					
SME0-4U	■	–	■	■	8
CRSME0-4 Corrosion resistant	■	–	■	–	10
Operating voltage range 12 ... 250 V AC/DC					
SME0-4U	■	–	■	–	8

Proximity sensors, round design

Peripherals overview

FESTO



Proximity sensors, round design

Peripherals overview

FESTO

Mounting attachments and accessories		
	Brief description	→ Page/Internet
Proximity sensors		
1	SMT0-4U-K	Magneto-inductive, with cable
	SME0-4U-K	Magnetic reed, with cable
2	SMT0-4U-S	Magneto-inductive, with plug M8x1
	SME0-4U-S	Magnetic reed, with plug M8x1
3	CRSME0-4	Magnetic reed, corrosion resistant, with cable
Accessories		
4	Plug socket with cable NEBU-M83GD-...	Straight socket, M8x1, 3-pin
5	Plug socket with cable NEBU-M83WD-...	Angled socket, M8x1, 3-pin
6	Mounting kit SMBR-...	For round cylinders
7	Mounting kit CRSMBR-...	Corrosion resistant, for round cylinders
8	Mounting kit CRSMB-...	Corrosion resistant
9	Sensor tester SM-TEST-1	sm-test-1
Drives		
10	Round cylinders	Ø 8 ... 63 mm
11	Round cylinders CRDG, CRDSW, CRDSNU, stainless steel	Ø 12 ... 63 mm
12	Standard cylinders CRDNG, CRDNGS, stainless steel	Ø 32 ... 125 mm

Proximity sensors, round design

Type codes

FESTO

		SMT0	–	4U	–	PS	–	K	–	LED	–	24	–	
Function														
SMT0	Proximity sensor, magneto-inductive													
SME0	Proximity sensor, magnetic reed													
CRSME0	Proximity sensor, magnetic reed, corrosion resistant													
Design														
4U	Round design, U-shaped housing													
4	Round design, straight housing													
Switch output, switching element function														
PS	PNP, N/O contact, 3-wire													
NS	NPN, N/O contact, 3-wire													
	N/O contact, 2- or 3-wire													
Electrical connection, cable length														
K	Cable, 2.5 m													
K5	Cable, 5 m													
S	Plug M8x1													
Switching status display														
LED	Yellow LED													
Rated operating voltage														
24	24 V DC													
230	230 V AC													
Generation														
B	B series													


Proximity sensors SMT0-4U, round design, magneto-resistive

FESTO

Technical data


Function

e.g. PNP, N/O contact, with plug



- Magneto-inductive measuring principle

e.g. NPN, N/O contact, with plug



Design	
Constructional design	Round
Type of mounting	Via accessories
Connection direction	In-line
Reproducibility of switching point ¹⁾ [mm]	±0.1
Switching status display	Yellow LED

1) Only applicable to drives secured against rotation

Technical data – N/O contact		
Switch output	PNP	
	NPN	
Electrical connection	Cable, 3-wire	Plug M8x1, 3-pin
Cable length [m]	2.5	–
Operating voltage range [V DC]	10 ... 30	
Max. output current [mA]	200	
Max. switching capacity [W]	6	
Voltage drop [V]	2	
Residual current [mA]	≤0.01	
Switch-on time [ms]	≤0.5	
Switch-off time [ms]	≤0.5	
Protection against short circuit	Yes	
Protection against polarity reversal	For all electrical connections	
Protection class	IP67	

Operating and environmental conditions			
Electrical connection	Cable		Plug
Cable installation	Fixed	Flexible	
Ambient temperature [°C]	–25... +70	–5 ... +70	–25... +70
Corrosion resistance class CRC ¹⁾	4		2
CE symbol (declaration of conformity)	In accordance with EU EMC directive		

- 1) Corrosion resistance class 2 according to Festo standard 940 070
Components requiring moderate corrosion resistance. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents.
- Corrosion resistance class 4 according to Festo standard 940 070
Components requiring higher corrosion resistance. Parts used with aggressive media, e.g. food or chemical industry. These applications should be supported with special tests with the media if required.

Materials	
Housing	Polyester
Cable sheath	Polyvinyl chloride
Note on materials	Free of copper and PTFE


Technical data

Product weights [g]		
Electrical connection	Cable	Cable with plug
N/O contact		
PNP	70	6
NPN	70	6

Dimensions


Download CAD data → www.festo.com

Cable type




- 1 Connecting cable
- 2 Yellow LED

Plug type M8x1



- 2 Yellow LED
- 3 Plug suitable for plug socket with cable NEBU-M8...
- 4 Installation space for angled socket

Ordering data

	Switch output	Electrical connection		Cable length [m]	Part No.	Type
		Cable	Plug M8x1			
	N/O contact					
	PNP	3-wire	–	2.5	152 836	SMT0-4U-PS-K-LED-24
		–	3-pin	–	152 742	SMT0-4U-PS-S-LED-24
	NPN	3-wire	–	2.5	152 837	SMT0-4U-NS-K-LED-24
		–	3-pin	–	152 743	SMT0-4U-NS-S-LED-24


Proximity sensors SMEO-4U, round design, magnetic reed

FESTO

Technical data


Function

e.g. N/O contact, 3-wire, with cable



- Magnetic reed measuring principle

e.g. N/O contact, 2-wire, with cable



Design	
Constructional design	Round
Type of mounting	Via accessories
Connection direction	In-line
Reproducibility of switching point ¹⁾	[mm] ±0.1
Switching status display	Yellow LED

1) Only applicable to drives secured against rotation

Technical data – N/O contact, 3-wire						
Switch output			Conventional contact, bipolar			
Electrical connection			Cable, 3-wire	Cable, 3-wire	Plug M8x1, 3-pin	
Cable length			[m]	2.5	5	–
Operating voltage range		DC	[V DC]	12 ... 27		
Max. output current			[mA]	500		
Max. switching capacity		DC	[W]	10		
Voltage drop			[V]	–		
Switch-on time			[ms]	≤0.5		
Switch-off time			[ms]	0.03		
Protection against short circuit				No		
Protection against polarity reversal				No		
Protection class				IP67		

Technical data – N/O contact, 2-wire				
Switch output			Conventional contact, bipolar ¹⁾	
Electrical connection			Cable, 2-wire	
Cable length		[m]	2.5	
Operating voltage range	DC	[V DC]	12 ... 250	
	AC	[V AC]	12 ... 250	
Max. output current		[mA]	500	
Max. switching capacity	DC	[W]	10	
	AC	[VA]	10	
Voltage drop		[V]	4.1	
Switch-on time		[ms]	≤2	
Switch-off time		[ms]	2	
Protection against short circuit			No	
Protection against polarity reversal			No	
Protection class			IP67	

1) Without LED function

Materials	
Housing	Polyethylene terephthalate
Cable sheath	Polyvinyl chloride
Note on materials	Free of copper and PTFE

Proximity sensors SMEO-4U, round design, magnetic reed

FESTO

Technical data

Operating and environmental conditions			
Electrical connection	Cable		Plug
Cable installation	Fixed	Flexible	
Ambient temperature [°C]	-20 ... +60	-5 ... +60	-20 ... +60
Corrosion resistance class CRC ¹⁾	4		2
CE symbol (declaration of conformity)	In accordance with EU EMC directive		
	In accordance with EU low voltage directive ²⁾		-

- 1) Corrosion resistance class 2 according to Festo standard 940 070
Components requiring moderate corrosion resistance. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents.
Corrosion resistance class 4 according to Festo standard 940 070
Components requiring higher corrosion resistance. Parts used with aggressive media, e.g. food or chemical industry. These applications should be supported with special tests with the media if required.
- 2) Only valid for N/O contact, 2-wire, operating voltage range 3 ... 250 V AC / 250 V DC

Product weights [g]			
Electrical connection	Cable		Plug
Cable length [m]	2,5	5,0	-
N/O contact			
3-wire	70	130	16
2-wire	70	-	-

Dimensions

Download CAD data → www.festo.com

Cable type

1 Connecting cable


2 Yellow LED

Plug type M8x1

2 Yellow LED

3 Plug suitable for plug socket with cable NEBU-M8...

4 Installation space for angled socket

Ordering data					
	Electrical connection		Cable length [m]	Part No.	Type
	Cable	Plug M8x1			
	N/O contact				
	Operating voltage range 12 ... 27 V DC				
	3-wire	–	2.5	36 198	SME0-4U-K-LED-24
			5	175 401	SME0-4U-K5-LED-24
	–	3-pin	–	151 526	SME0-4U-S-LED-24-B
	Operating voltage range 12 ... 250 V AC/DC				
2-wire	–	2.5	150 011	SME0-4U-K-LED-230	


Proximity sensors CRSMEO-4, round design, magnetic reed

FESTO

Technical data

Function

N/O contact, 3-wire, with cable



- Corrosion resistant
- Magnetic reed measuring principle



Design	
Constructional design	Round
Type of mounting	Via accessories
Connection direction	In-line
Reproducibility of switching point ¹⁾	[mm] ±0.1
Switching status display	Yellow LED

1) Only applicable to drives secured against rotation

Technical data – N/O contact, 3-wire			
Switch output			Contacting
Electrical connection			Cable, 3-wire
Cable length		[m]	2.5
Operating voltage range	DC	[V DC]	12 ... 30
	AC	[V AC]	12 ... 30
Max. output current		[mA]	500
Max. switching capacity	DC	[W]	10
	AC	[VA]	10
Switch-on time		[ms]	0.03
Switch-off time		[ms]	≤0.5
Protection against short circuit			No
Protection against polarity reversal			No
Protection class			IP65/IP67

Operating and environmental conditions		
Electrical connection	Cable	
Cable installation	Fixed	Flexible
Ambient temperature	[°C]	–20 ... +60
Corrosion resistance class CRC ¹⁾	4	
CE symbol (declaration of conformity)	In accordance with EU EMC directive	

1) Corrosion resistance class 4 according to Festo standard 940 070
Components requiring higher corrosion resistance. Parts used with aggressive media, e.g. food or chemical industry. These applications should be supported with special tests with the media if required.

Materials	
Housing	Polypropylene
Cable sheath	Thermoplastic rubber
Note on materials	Free of copper and PTFE

Product weights [g]	
N/O contact	
3-wire	70


Proximity sensors CRSMEO-4, round design, magnetic reed

Technical data

FESTO

Dimensions

Download CAD data → www.festo.com



- 1 Connecting cable
- 2 Yellow LED
- 3 Clamping range

Ordering data

	Electrical connection	Cable length [m]	Part No.	Type
	N/O contact			
	Corrosion resistant			
	Cable, 3-wire	2.5	161 775	CRSMEO-4-K-LED-24


Proximity sensors, round design

Accessories

FESTO

Mounting kit SMBR

Material:
Polyacetate




Dimensions and ordering data								
For piston Ø	B1	B2	B3	H1	H2	H3	Part No.	Type
8	21	–	14	23.5	16.5	9	19 272	SMBR-8
							166 398	SMBR-8-CT ¹⁾
10	22	0.5	14	26	18.5	10	19 273	SMBR-10
							166 399	SMBR-10-CT ¹⁾
12	22	4	11	28.5	20	10.2	19 274	SMBR-12
							166 400	SMBR-12-CT ¹⁾
16	22.5	4	11.5	33.5	22.5	12.4	19 275	SMBR-16
							166 401	SMBR-16-CT ¹⁾
20	26.5	5.5	13.5	35.5	22.5	14	19 276	SMBR-20
							166 402	SMBR-20-CT ¹⁾
25	31.5	7.5	16	40.5	25	16	19 277	SMBR-25
							166 403	SMBR-25-CT ¹⁾

1) Free of copper and PTFE

Mounting kit CRSMBR

Material:
Polypropylene



Dimensions and ordering data								
For piston Ø	B1	B2	H1	H2	H3	Part No.	Type	
12	22	4.1	28.6	20	10.2	164 581	CRSMBR-12	
16	22.3	4	33.2	22.5	12.4	164 582	CRSMBR-16	
20	26.5	5.6	35.25	22.5	14	164 583	CRSMBR-20	
25	31.5	7.4	40.2	25	16	164 584	CRSMBR-25	
32	38.6	7.9	47.8	29	19.7	163 888	CRSMBR-32	
40	46.6	8.1	55.8	33	23.8	163 889	CRSMBR-40	
50	57.4	8.2	67.2	39	29.5	163 890	CRSMBR-50	
63	70.4	8.2	80.8	45.9	36.2	163 891	CRSMBR-63	

Proximity sensors, round design


Accessories

FESTO

Mounting kit CRSMB

Material:

High-alloy stainless steel



Dimensions and ordering data				
For piston \varnothing	B1	H1	Part No.	Type
32	29	17.6	161 763	CRSMB-32
40	29	15.1	161 764	CRSMB-40
50	31.1	17.4	161 765	CRSMB-50
63	31.1	18.1	161 766	CRSMB-63
80	33	24.2	161 767	CRSMB-80
100	33	27.5	161 768	CRSMB-100
125	36.5	31.1	185 365	CRSMB-125