

End position controllers SPC11

FESTO



End position controllers SPC11

Key features

FESTO

Key features at a glance

Fast travel between two fixed stops with electronically controlled end position cushioning and up to two freely selectable intermediate positions.

- Up to 30% faster cycle rates
- Significantly reduced system vibration
- Fast problem-free commissioning, no specialists required

- Simple conversion of existing systems
- Optimum operating behaviour is maintained even with weight/load fluctuations of up to 30% of the total moving mass

- Less expensive than electromechanical drives
- Reduced noise level

Individual components

End position controller

Integrated functions:

- For determining system characteristic values of the connected components.
- Storage of the desired end positions or intermediate positions.

- Comparison of setpoint and actual position, and position control through appropriate actuation of the proportional 5/3-way valve (status control).
- Internal or external teach-in function.

SPC11



Analogue displacement encoders

Analogue displacement encoder based on a conductive-plastic linear potentiometer. The system measures absolute values. It is connected alongside a pneumatic drive. Mounting kits are

available as accessories for the mechanical coupling. The displacement encoder is available in fixed stroke lengths ranging from 100 ... 2000 mm.

MLO-POT...-TLF



MLO-POT...-LWG



Digital displacement encoders

Digital displacement encoders, magnetostrictive, contactless method of measurement. The system measures absolute values. It is connected alongside a pneumatic linear

drive. Mounting kits are available as accessories for the mechanical coupling. The displacement encoder is available in fixed stroke lengths ranging from 100 ... 2000 mm.

MME-MTS...-AIF



Pneumatic drives

Pneumatic drives ensure an easy-to-operate system. The stroke length operating range depends on the selected drive. The range extends from 225 ... 2000 mm. The swivel angle with DSMI ranges from 0° ... 270°.

Note

The linear drives DGP/DGPL with compressed air supply connections at both ends (D2) should be used for effective cylinder strokes above 600 mm.

DGCI



DGPL, DGPII



DNC



DNCI



DSMI




Proportional 5/3-way valves

Valve actuation is via the end position controller. The valve controls the volume of air supplied to the drive. The extremely short switching time of the valve makes the Smart Soft Stop solution package highly dynamic.

Note

Use a 5 µm filter for compressed air preparation. The compressed air supply must be unlubricated.

MPYE-5...-010B




End position controllers SPC11

FESTO

Key features

Possible combinations


with external displacement encoder



with external/integrated displacement encoder

End position controller

Drive with displacement encoder



End position controllers SPC11


FESTO

Key features

Conventional solution


Previously you needed to

- Harmonise individual components.
- Install additional shock absorbers and possibly replace/exchange existing shock absorbers.
- Fit proximity sensors for position detection.
- Adjust the compressed air supply by means of flow control valves in order to optimise the system.



Until now, to create intermediate positions you had to

- Construct a complex mechanical solution using stopper cylinders, for example.
- Harmonise a large number of individual components.
- Perform extensive programming.



Solution with end position controller SPC11

Fast travel between two fixed stops with up to two freely selectable intermediate positions

The Smart Soft Stop system with end position controller SPC11 facilitates travel between two fixed mechanical stops as well as travel to up to two freely selectable intermediate positions. The level of accuracy of the intermediate positions is $\pm 0.25\%$ of the

displacement encoder length, and no less than $\pm 2\text{ mm}$. The level of accuracy of the intermediate positions is $\pm 2^\circ$ for the swivel module DSM1. Typical applications for the intermediate positions are rest or ejector positions, where a low-cost solution is more

important than achieving high levels of accuracy. The intermediate positions also have sensor functionality. This means that when the relevant intermediate position is passed, a 50 ms pulse is produced at the corresponding output.

End position controllers SPC11

FESTO

Key features

The Festo solution package


Smart Soft Stop with end position controller SPC11

In an application with up to two intermediate positions you can now:

- Use the Festo solution package with a small number of harmonised components.
- Dispense with complex constructions using stopper cylinders.
- Approach the intermediate positions from both sides.
- Let optimisation be carried out by the learning system itself.

The Smart Soft Stop system with SPC11 has a remote input, which allows all three pushbuttons to be allocated to a master controller:

- All system parameters can be defined and changed externally.
- A signal at the remote input disables all pushbuttons on the end position controller SPC11.



[1] Displacement encoder

Digital:

- MME-MTS-...-AIF
- integrated in case of DGPI/ DGPIL
- integrated in case of DNCI
- Analogue:
 - MLO-POT-...-TLF
 - MLO-POT-...-LWG
 - integrated in case of DSMI

[2] Pneumatic drives

DGCI/DGP/DGPL, DGPI/DGPIL, DNC, DNCI or DSMI

[3] End position controller

SPC11-POT-TLF,
SPC11-POT-LWG or
SPC11-MTS-AIF
SPC11-INC

[4] Proportional 5/3-way valve

MPYE-5...-010B

[5] Service unit (without lubricator,
with 5 µm filter), supply
pressure 5 to 7 bar

[6] Operating voltage connection
and master controller

End position controllers SPC11

Key features

FESTO

The solution package


Individual components

- Pneumatic drives DGCI/DGP/DGPL, DGPI/DGPIL, DNC, DNCI or DSMI
- Proportional 5/3-way valve MPYE-5-...-010B
- Displacement encoder MLO-POT-...-TLF, MLO-POT-...-LWG or MME-MTS-...-AIF
- End position controller SPC11
- Valve cable KMPYE...
- Controller cable KMPV-...
- Manual

Solution packages are uniquely defined, i.e. all components are harmonised for optimum performance. For details of this unique allocation please see → 19 or 33 or
→ Smart Soft Stop software tool:
www.festo.com/en/engineering

Accessories available on separate order (fittings, tubing, etc.) can be found in the respective solution packages. An example of an order is shown on → 18 or 32.

PPV = Open the internal cushioning 100%




Symmetrical

The desired travel distance should not therefore exceed the relevant effective cylinder stroke.

The following thus applies:


travel distance ≤ effective cylinder stroke.



[1] Fixed stops, mounted on drive or externally

Asymmetrical

The desired travel distance within the effective cylinder stroke must be limited by means of fixed stops. The same applies to the pneumatic drives DGCI/DNC, DNCI, DNCM and DSMI.



[1] Fixed stops, mounted on drive or externally

Note

External limit stops are required in order to realise the effective stroke (or effective swivel angle in the case

of DSMI) when using the pneumatic drives DGCI, DNC, DNCI and DSMI with the Smart Soft Stop system.

End position controllers SPC11

FESTO

Key features

The solution package

Advantages

- Up to 30% faster cycle rates
- Significantly reduced system vibration
- Optimum operating behaviour is maintained even with weight/load fluctuations of up to 30% of the total moving mass
- Simple conversion of existing systems
- Considerably reduced noise level
- Fast problem-free commissioning, no specialists required


- Less expensive than electromechanical drives

The graphs apply to the following example:

- GPL-25-1250-PPV-A-KF-B-GK...-D2,
- Moving load: 12 kg
- Horizontal mounting position




The shape of the curve is identical for the pneumatic drives DGCI, DNC, DNCI, DSMI and DGPII.




- [1] = Drive with electronic end position controller SPC11
- [2] = Drive with shock absorber

x = Travel distance
 t = Time



- [1] = Drive with electronic end position controller SPC11
- [2] = Drive with shock absorber

v = Velocity
 t = Time



- [1] = Drive with electronic end position controller SPC11
- [2] = Drive with shock absorber

a = Acceleration
 t = Time

Festo plug & work = Commissioning in just a few steps



- [1] Assemble the system components:
Moving mass must be attached backlash-free.
- [2] Set up the pneumatic and electrical system connections.
- [3] Switch on the compressed air and supply voltage.
- [4] Start the teaching process by means of a button. The system learns autonomously and is ready for operation after 3 minutes.
- [5] Approach and save intermediate positions by means of buttons.

End position controllers SPC11

Peripherals overview

FESTO

Variant with drive DGPL



Note

The same components are required for the drive DGPL as for the drive DGPL.

The integrated digital displacement encoder of the DGPL is replaced by an externally mounted displacement encoder (either digital or potentiometric).

End position controllers SPC11

FESTO

Peripherals overview

Individual components		Pneumatic drives					
Brief description		DGCI	DGPL/DGPL	DGPI/DGPIL	DNC	DNCI	DSMI
[1] End position controller SPC11		■	■	■	■	■	■
[1] End position controller SPC11-ASI		-	■	■	■	-	■
[2] Analogue displacement encoder MLO-POT-...-TLF		-	■	-	-	-	-
[2] Analogue displacement encoder MLO-POT-...-LWG		-	-	-	■	-	-
[2] Digital displacement encoder MME-MTS-...-AIF		-	■	-	-	-	-
[3] Air supply lines (laid symmetrically)		■	■	■	■	■	■
[4] Proportional 5/3-way valve MPYE		■	■	■	■	■	■
[5] Compressed air supply		■	■	■	■	■	■
[6] Connecting cable KMPYE to proportional 5/3-way valve		■	■	■	■	■	■
[7] Connecting cable to controller		■	■	■	■	■	■
[8] Fixed stop		■	■	■	1)	1)	■
[9] Push-in connector QS (preferably straight)		■	■	■	■	■	■
[10] Displacement encoder mounting kit		-	■	-	-	-	-
Solution packages →		12	18	18	24	28	32

1) External limit stops are required with the DNC and DNCI to limit the travel distance within the effective stroke.

Allocation of end position controller SPC11 to drive and displacement encoder					
End position controller	SPC11-POT-TLF	SPC11-POT-LWG	SPC11-MTS-AIF	SPC11-INC	SPC11-MTS-AIF-2
Drive					
DGCI	-	-	-	-	■
DGPL/DGPIL	-	-	■	-	-
DNCI	-	-	-	■	-
DSMI	-	■	-	-	-
Displacement encoder					
MLO-POT-TLF	■	-	-	-	-
MLO-POT-LWG	-	■	-	-	-
MME-MTS-AIF	-	-	■	-	-

End position controllers SPC11

Technical data

FESTO

Teach-in function

SPC11-POT-TLF

SPC11-POT-LWG

SPC11-MTS-AIF

SPC11-INC

SPC11-MTS-AIF-2

The teach-in travel (to determine the system data and end positions) can be started via a button on the end position controller SPC11 or via an external output which is connected through the control cable (e.g. the PLC).



General technical data

End position controller SPC11-...	Type	...-POT-TLF	...-POT-LWG	...-MTS-AIF	...-INC	...-MTS-AIF-2
Operating voltage	[V DC]	24 (-25 ... +25%)				
Current consumption with valve	[A]	1.3			1.1	
	[mA]	70	170	80	70	
Residual ripple	[%]	Max. 5				
Digital inputs	Number	8				
	Input voltage	[V DC]	24			
	Input current	[mA]	4 (at 24 V DC)			
	Duty cycle	[ms]	min. 20			
	Signal voltage	[V DC]	0 ... 5 (for logic 0) 15 ... 30 (for logic 1)			
Digital outputs (short circuit proof)	Number	5				
	Output voltage		min. V_b ... V_b : -3 V DC (at 0.1 A)			
	Output current	[A]	Max. 0.1			
	Max. tripping current	[mA]	500			
Displacement encoder input MLO-POT-...	Operating voltage	[V DC]	+10	-		
	Input voltage	[V DC]	0 ... +10	-		
Displacement encoder input MME-MTS-...	Operating voltage	[V DC]	-	24	-	
	Communication		-	CAN fieldbus (1 Mbaud)	-	
Standard cylinder input DNCI	Operating voltage	[V DC]	-	5	-	
	Communication		-	sin/cos	-	
Linear drive input DGCI	Operating voltage	[V DC]	-		24	
	Communication		-		CAN fieldbus (1 Mbaud)	
Valve output	Operating voltage	[V DC]	24			
Valve output	Output voltage	[V DC]	0 ... +10			
Relative air humidity	[%]	95 (non-condensing)				
Weight	[g]	Approx. 400				

Operating and environmental conditions

End position controller SPC11-...	Type	...-POT-TLF	...-POT-LWG	...-MTS-AIF	...-INC	...-MTS-AIF-2
Temperature range	[°C]	0 ... +50				
Protection class to IEC 60529		IP65				
Vibration resistance, tested to DIN/IEC 68, Part 2-6		Severity level 2				
Shock resistance, tested to DIN/IEC 68, Part 2-27		Severity level 2				
CE mark (see declaration of conformity)		In accordance with EU EMC directive				

End position controllers SPC11


FESTO

Technical data

Dimensions

SPC11-POT-TLF, SPC11-POT-LWG, SPC11-MTS-AIF


Download CAD data → www.festo.com



- [1] Slot for inscription labels:
18182 IBS-9x20
18576 IBS-6x10
- [2] Mounting options for M4 screws
- [3] Connecting cable
(length approx. 335 mm)

SPC11-INC, SPC11-MTS-AIF-2

- [1] Slot for inscription labels:
18182 IBS-9x20
18576 IBS-6x10
- [2] Mounting options for M4 screws



Type	B1	B2	B3	B4	B5	H1	H2	H3	L1	L2	L3	L4	L5
SPC11-POT-...													
SPC11-MTS-AIF	78	68	5	58	39	43		4.5	118.1	109.1	4.5	5	125
SPC11-MTS-AIF-2							2	42.6					—
SPC11-INC								4.2					—

Ordering data

Description	Part No.	Type
For analogue displacement encoder MLO-POT-....-TLF	192216	SPC11-POT-TLF
For analogue displacement encoder MLO-POT-....-LWG, swivel module DSMI	192217	SPC11-POT-LWG
For digital displacement encoder MME-MTS-....-AIF	192218	SPC11-MTS-AIF
For standard cylinder DNCI	537321	SPC11-INC
For linear drive DGCI	548129	SPC11-MTS-AIF-2

End position controllers SPC11

Technical data

FESTO

Order example

For pneumatic linear drives DGCI

A workpiece weighing 3 kg is to be moved horizontally on a loading station. A workpiece gripper attached

to the slide of the linear drive weighs 14 kg. The total weight to be moved is therefore 17 kg. The desired travel

distance is 1,100 mm. The travel time is to be < 1.5 seconds.



Sizing software
Smart Soft Stop and ProDrive
→ www.festo.com

Step 1:

Selecting the cylinder stroke

For a travel distance of 1,100 mm, use the table on → 13 to select the next-largest effective cylinder stroke of 1,250 mm. This column has a grey background.

Step 2:

Specifying the drive

For a total weight of 17 kg to be moved horizontally, there is a choice of piston diameters of 25, 32 and 40 mm (see data for max. total weight to be moved).

For the purposes of our example, the drive DGCI-32-1250-KF-..., part no. 544 427 has been selected.



Remember when selecting the drive mounting components that some of these are not backlash-free and therefore cannot be used with the Smart Soft Stop system. The drives must be mounted directly.



Check that the loads placed on the drive by a gripper during movement do not exceed permissible limits. To carry out simulation quickly and easily, use the Smart Soft Stop software tool and ProDrive.

Step 3:

Specifying a proportional 5/3-way valve

The appropriate proportional 5/3-way valve is shown at the intersection of the grey column used in step 1 and the line for the selected linear drive DGCI-32... in the "Proportional 5/3-way valve" section of the table. For the purposes of our example, the proportional 5/3-way valve MPYE-5-1/4-010B, part no. 151 694 has been selected.

Step 4:

Completing the order information

To order a complete system you must add the data for the end position controller, valve and controller cables and manual (if required). The complete ordering data for our example can be found on → 13. A manual should normally be ordered. If you already have one, leave the appropriate box blank, indicating that you do not want a manual.

Step 5:

Determining the travel time

To calculate the travel time use the "Smart Soft Stop" software tool. The travel time for the order example is 1.16 seconds.



For vertical travel, t_{up} and t_{down} are the two different travel times.

Ordering data

Pneumatic linear drive Part No. Type	Proportional 5/3-way valve Part No. Type	End position controller Part No. Type
544427 DGCI-32-1250-KF-...	151694 MPYE-5-1/4-010B	548129 SPC11-MTS-AIF-2
Valve cable Part No. Type		Controller cable Part No. Type
170238 KMPYE-AIF-1-GS-GD-2	177674 KMPV-SUB-D-15-10	

End position controllers SPC11

FESTO

Technical data

Step 1 and 2:

Pneumatic linear drives/Type	DGCI-... ¹⁾ -... ²⁾ -KF...													
Effective cylinder stroke [mm]	100	160	225	300	360	450	500	600	750	1,000	1,250	1,500	1,750	2,000
Max. overall mass to be moved horizontally/vertically by Ø	18	25	32	40	15/5	30/10	45/15	70/25						
Part No. for Ø	18	25	32	40	544 425	544 426	544 427	544 428						

Step 3:

Proportional 5/3-way valves ³⁾ Part No./Type	1 = 154 200 MPYE-5-M5-010-B 2 = 151 692 MPYE-5-1/8-LF-010-B						3 = 151 693 MPYE-5-1/8-HF-010-B 4 = 151 694 MPYE-5-1/4-010-B							
Effective cylinder stroke [mm]	100	160	225	300	360	450	500	600	750	1,000	1,250	1,500	1,750	2,000
Horizontal/vertical for Ø	18	25	32	40	1/1	1/1	1/1	2/2	2/2	2/2	2/2	2/2	2/2	3/3
					2/2	2/2	2/2	3/2	3/2	3/2	3/2	3/2	3/2	3/3
					2/2	3/2	3/2	3/2	3/3	3/3	3/3	4/3	4/3	4/4
					3/2	3/2	3/2	3/3	3/3	3/3	4/3	4/4	4/4	4/4

Step 5:

End position controllers and accessories	Part No.	Type	Brief description
End position controller SPC11	548129	SPC11-MTS-AIF-2	
Cable Valve	170238	KMPYE-AIF-1-GS-GD-2	Cable length 2 m
	170239	KMPYE-AIF-1-GS-GD-0,3	Cable length 0.3 m
SPC11/PLC	177673	KMPV-SUB-D-15-5	Cable length 5 m
	177674	KMPV-SUB-D-15-10	Cable length 10 m

-  - Note

Manuals ➔ 37

- 1) Indicate piston Ø. Technical data and dimensions ➔ www.festo.com.
- 2) Indicate piston Ø. Technical data and dimensions ➔ www.festo.com.
- 3) Indicate calculated effective stroke of cylinder.
- 4) Technical data and dimensions ➔ Internet: mpye.
- 5) Technical data and dimensions ➔ www.festo.com. (not needed for DGPI/DGPIL, has integrated displacement encoder).
- 6) Technical data and dimensions ➔ www.festo.com.



End position controllers SPC11

Technical data

FESTO

Accessories for the solution package for DGCI horizontally mounted

For effective cylinder stroke 100 ... 2,000 mm



Ordering data		Fittings ¹⁾		Compressed air tubing		Silencer ²⁾	
Effective cylinder stroke DGCI-... [mm]	Proportional 5/3-way valve Type	For MPYE-5-... Part No.	For DGCI Part No.	Part No.	Type	Part No.	Type
Ø 18 mm							
100 ... 160	MPYE-5-M5-010-B	153306 QSM-M5-6	153306 QSM-M5-6	152586 PUN-6x1-SI		165003 UC-M5	
225 ... 300	MPYE-5-M5-010-B						
360 ... 1,750	MPYE-5-1/8-LF-010-B	153002 QS-1/8-6	153306 QSM-M5-6	152586 PUN-6x1-SI		2307 U-1/8	
2,000	MPYE-5-1/8-HF-010-B						
Ø 25 mm							
100 ... 160	MPYE-5-1/8-LF-010-B	153002 QS-1/8-6	153002 QS-1/8-6	152586 PUN-6x1-SI		2307 U-1/8	
225 ... 300	MPYE-5-1/8-LF-010-B	153004 QS-1/8-8	153004 QS-1/8-8	152587 PUN-8x1,25-SI		2307 U-1/8	
360 ... 2,000	MPYE-5-1/8-HF-010-B						
Ø 32 mm							
100	MPYE-5-1/8-LF-010-B	153002 QS-1/8-6	153002 QS-1/8-6	152586 PUN-6x1-SI		2307 U-1/8	
160 ... 1,000	MPYE-5-1/8-HF-010-B	153004 QS-1/8-8	153004 QS-1/8-8	152587 PUN-8x1,25-SI			
1,250 ... 2,000	MPYE-5-1/4-010-B	153005 QS-1/4-8				2316 U-1/4	
Ø 40 mm							
100 ... 160	MPYE-5-1/8-HF-010-B	153004 QS-1/8-8	153005 QS-1/4-8	152587 PUN-8x1,25-SI		2307 U-1/8	
225 ... 500	MPYE-5-1/8-HF-010-B						
600 ... 750	MPYE-5-1/4-010-B	153005 QS-1/4-8	153005 QS-1/4-8	152587 PUN-8x1,25-SI		2316 U-1/4	
1,000 ... 2,000	MPYE-5-1/4-010-B	153007 QS-1/4-10	153007 QS-1/4-10	152588 PUN-10x1,5-SI		2316 U-1/4	

1) Fittings sold only in packs of 10.

2) 2 pieces are required.

End position controllers SPC11

FESTO

Technical data

Accessories for the solution package for DGCI horizontally mounted

For effective cylinder stroke 100 ... 2,000 mm



Ordering data

Effective cylinder stroke DGCI... [mm]	Part No.	Type	Filter regulator, D series with filter cartridge 5 µm D series	Part No.	Type	Filter regulator, MS series with filter cartridge 5 µm	Part No.	Type	Filter cartridge 5 µm MS series	Part No.	Type
Ø 18 mm											
100 ... 2,000	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
Ø 25 mm											
100 ... 2,000	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
Ø 32 mm											
100 ... 1,000	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
1,250 ... 2,000	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	
Ø 40 mm											
100 ... 500	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
600 ... 2,000	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	


End position controllers SPC11

Technical data

FESTO

Accessories for the solution package for DGCI vertically mounted

For effective cylinder stroke 100 ... 2,000 mm



Ordering data

Effective cylinder stroke DGCI [mm]	Proportional 5/3-way valve Type	Fittings ¹⁾				Compressed air tubing		Silencer ²⁾	
		For MPYE-5-...		DGCI		Part No.	Type	Part No.	Type
Ø 18 mm									
100 ... 300	MPYE-5-M5-010-B	153306	QSM-M5-6	153306	QSM-M5-6	152586	PUN-6x1-SI	165003	UC-M5
360 ... 1,750	MPYE-5-1/8-LF-010-B	153002	QS-1/8-6					2307	U-1/8
2,000	MPYE-5-1/8-HF-010-B								
Ø 25 mm									
100 ... 160	MPYE-5-1/8-LF-010-B	153002	QS-1/8-6	153002	QS-1/8-6	152586	PUN-6x1-SI	2307	U-1/8
225 ... 750	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153004	QS-1/8-8	152587	PUN-8x1,25-SI		
1,000 ... 2,000	MPYE-5-1/8-HF-010-B								
Ø 32 mm									
100	MPYE-5-1/8-LF-010-B	153002	QS-1/8-6	153002	QS-1/8-6	152586	PUN-6x1-SI	2307	U-1/8
160 ... 300	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153004	QS-1/8-8	152587	PUN-8x1,25-SI	2307	U-1/8
360 ... 1,750	MPYE-5-1/8-HF-010-B								
2,000	MPYE-5-1/4-010-B	153005	QS-1/4-8					2316	U-1/4
Ø 40 mm									
100 ... 225	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153005	QS-1/4-8	152587	PUN-8x1,25-SI	2307	U-1/8
300 ... 750	MPYE-5-1/8-HF-010-B								
1,000	MPYE-5-1/8-HF-010-B	190643	QS-1/8-10	153007	QS-1/4-10	152588	PUN-10x1,5-SI		
1,250 ... 2,000	MPYE-5-1/4-010-B	153007	QS-1/4-10					2316	U-1/4

1) Fittings sold only in packs of 10.

2) 2 pieces are required.

End position controllers SPC11

FESTO

Technical data

Accessories for the solution package for DGCI vertically mounted

For effective cylinder stroke 100 ... 2,000 mm



Ordering data

Effective cylinder stroke DGCI [mm]	Part No.	Type	Filter regulator, D series with filter cartridge 5 µm D series	Part No.	Type	Filter regulator, MS series with filter cartridge 5 µm	Part No.	Type	Filter cartridge 5 µm MS series	Part No.	Type
Ø 18 mm											
100 ... 2,000	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
Ø 25 mm											
100 ... 2,000	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
Ø 32 mm											
100 ... 1,000	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
1,250 ... 2,000	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	
Ø 40 mm											
100 ... 500	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
600 ... 2,000	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	

End position controllers SPC11

Technical data

FESTO

Order example

For pneumatic linear drives DGP/DGPL, DGPI/DGPIL

A workpiece weighing 3 kg is to be moved horizontally on a loading station. A workpiece gripper attached

to the slide of the linear drive weighs 14 kg. The total weight to be moved is therefore 17 kg. The desired travel

distance is 1,100 mm. The travel time is to be < 1.5 seconds.



Sizing software
Smart Soft Stop and ProDrive
→ www.festo.com

Step 1:

Selecting the cylinder stroke

For a travel distance of 1,100 mm, use the table on → 19 to select the next-largest effective cylinder stroke of 1,250 mm. This column has a grey background.

Step 2:

Specifying the drive

For a total weight of 17 kg to be moved horizontally, there is a choice of piston diameters of 25, 32, 40, 50 and 63 mm (see data for max. total weight to be moved).

For the purposes of our example, the drive DGPL-32-1250-PPV-A-B-KF-GK-...-D2, part no. 175 135 has been selected.

Step 3:

Specifying the displacement encoder

The appropriate length of the displacement encoder is governed by the effective cylinder stroke. The column with the grey background in the "Displacement encoder" section of the table shows Part No. 152 633 for this example. Alternatively, the digital displacement encoder MME-MTS-...-AIF can be used.



Remember when selecting the drive mounting components that some of these are not backlash-free and therefore cannot be used with the Smart Soft Stop system. The drives must be mounted directly.



Check that the loads placed on the drive by a gripper during movement do not exceed permissible limits. To carry out simulation quickly and easily, use the Smart Soft Stop software tool and ProDrive.



The moment compensator FKP is not backlash-free. It must not therefore be used in combination with linear drives DGP/DGPL.

Step 4:

Specifying a proportional 5/3-way valve

The appropriate proportional 5/3-way valve is shown at the intersection of the grey column used in step 1 and the line for the selected linear drive DGPL-32-... in the "Proportional 5/3-way valve" section of the table. For the purposes of our example, the proportional 5/3-way valve MPYE-5-1/4-010B, part no. 151 694 has been selected.

Step 5:

Completing the order information

To order a complete system you must add the data for the end position controller, valve and controller cables and manual (if required). The complete ordering data for our example can be found on → 19. A manual should normally be ordered. If you already have one, leave the appropriate box blank, indicating that you do not want a manual.

Step 6:

Determining the travel time

To calculate the travel time use the "Smart Soft Stop" software tool. The travel time for the order example is 1.16 seconds.



For vertical travel, t_{up} and t_{down} are the two different travel times.

Ordering data

Pneumatic linear drive Part No. Type	Displacement encoder Part No. Type	Proportional 5/3-way valve Part No. Type	End position controller Part No. Type
175135 DGPL-32-1250-PPV-A-B-KF-GK-...-D2	152633 MLO-POT-1250-TLF	151694 MPYE-5-1/4-010B	192216 SPC11-POT-TLF

Valve cable Part No. Type	Controller cable Part No. Type
170238 KMPYE-AIF-1-GS-GD-2	177674 KMPV-SUB-D-15-10

End position controllers SPC11

FESTO

Technical data

Step 1 and 2:												
Pneumatic linear drives/Type	DGP-... ¹⁾ -... ³⁾ .PPV-A-B-D2							DGPI-... ²⁾ -... ³⁾ .PPV-A-B-D2				
	DGPL-... ¹⁾ -... ³⁾ .PPV-A-KF-B-GK-...-D2							DGPIL-... ²⁾ -... ³⁾ .PPV-A-B-KF-...-D2				
Effective cylinder stroke [mm]	225	300	360	450	500	600	750	1,000	1,250	1,500	1,750	2,000
Max. overall mass to be moved horizontally/vertically by Ø	25	30/10 kg										
	32	45/15 kg										
	40	70/25 kg										
	50	120/40 kg										
	63	180/60 kg										
Part No. for Ø	25	175 134										
	32	175 135										
	40	175 136										
	50	175 137										
	63	175 138										

Step 3:												
Displacement encoder ⁵⁾	MLO-POT-...-TLF MME-MTS-...-AIF											
Effective cylinder stroke [mm]	225	300	360	450	500	600	750	1,000	1,250	1,500	1,750	2,000
Potentiometer length [mm]	225	300	360	450	500	600	750	1,000	1,250	1,500	1,750	2,000
Part No.	MLO-POT-...-TLF	152 62	152 626	152 627	152 628	152 629	152 630	152 631	152 632	152 633	152 63	152 635
	MME-MTS-...-AIF	5	178 31	178 309	178 308	178 307	178 306	178 305	178 304	178 303	178 302	178 301
		0										178 299

Step 4:												
Proportional 5/3-way valves ⁶⁾	1 = 151 692 MPYE-5-1/8-LF-010-B						3 = 151 694 MPYE-5-1/4-010-B					
Part No./Type	2 = 151 693 MPYE-5-1/8-HF-010-B						4 = 151 695 MPYE-5-3/8-010-B					
Effective cylinder stroke [mm]	225	300	360	450	500	600	750	1,000	1,250	1,500	1,750	2,000
Horizontal/vertical for Ø	25	1/4)	1/1	2/1	2/1	2/1	2/2	2/2	2/3	2/3	2/3	2/3
	32	1/4)	2/1	2/1	2/1	2/1	2/1	3/2	3/3	3/3	3/3	3/3
	40	2/1	2/1	2/1	2/1	2/2	3/3	3/4	3/4	3/4	3/4	3/4
	50	1/1	2/1	2/2	3/2	3/3	4/3	4/4	4/4	4/4	4/4	4/4
	63	2/1	2/2	3/3	3/3	4/4	4/4	4/4	4/4	4/4	4/4	4/4

Step 5:											
End position controllers and accessories	Part No.	Type	Brief description								
End position controller SPC11	192216	SPC11-POT-TLF									
	192218	SPC11-MTS-AIF									
Cable Valve	170238	KMPYE-AIF-1-GS-GD-2	Cable length 2 m								
	170239	KMPYE-AIF-1-GS-GD-0,3	Cable length 0.3 m								
SPC11/PLC	177673	KMPV-SUB-D-15-5	Cable length 5 m								
	177674	KMPV-SUB-D-15-10	Cable length 10 m								

-  - Note
Manuals → 37

- 1) Indicate piston Ø. Technical data and dimensions → www.festo.com.
- 2) Indicate piston Ø. Technical data and dimensions → www.festo.com.
- 3) Indicate calculated effective stroke of cylinder.
- 4) On request
- 5) Technical data and dimensions → www.festo.com.
(not needed for DGP/DGPIL, has integrated displacement encoder).
- 6) Technical data and dimensions → www.festo.com.



End position controllers SPC11

Technical data

FESTO

Accessories for the solution package for DGP/DGPL, DGPI/DGPIL horizontally mounted

For effective cylinder stroke 225 ... 2,000 mm



Ordering data		Fittings ¹⁾		Compressed air tubing		Silencer ²⁾	
Effective cylinder stroke DGP/L, DGPI/L... [mm]	Type	For MPYE-5...	DGP/L, DGPI/L	Part No.	Type	Part No.	Type
Ø 25 mm							
225 ... 300	MPYE-5-1/8-LF-010-B	153004 QS-1/8-8		153004 QS-1/8-8		152587 PUN-8x1,25	2307 U-1/8
360 ... 2,000	MPYE-5-1/8-HF-010-B						
Ø 32 mm							
225	MPYE-5-1/8-LF-010-B	153004 QS-1/8-8		153004 QS-1/8-8		152587 PUN-8x1,25	2307 U-1/8
300 ... 600	MPYE-5-1/8-HF-010-B						
750 ... 2,000	MPYE-5-1/4-010-B	153005 QS-1/4-8		153004 QS-1/8-8		152587 PUN-8x1,25	2316 U-1/4
Ø 40 mm							
225 ... 500	MPYE-5-1/8-HF-010-B	153004 QS-1/8-8		153005 QS-1/4-8		152587 PUN-8x1,25	2307 U-1/8
600 ... 2,000	MPYE-5-1/4-010-B	153007 QS-1/4-10		153007 QS-1/4-10		152588 PUN-10x1,5	2316 U-1/4
Ø 50 mm							
225	MPYE-5-1/8-LF-010-B	153004 QS-1/8-8		153005 QS-1/4-8		152587 PUN-8x1,25	2307 U-1/8
300 ... 360	MPYE-5-1/8-HF-010-B						
450 ... 500	MPYE-5-1/4-010-B	153007 QS-1/4-10		153007 QS-1/4-10		152588 PUN-10x1,5	2316 U-1/4
600 ... 2,000	MPYE-5-3/8-010-B	153008 QS-3/8-10					2309 U-3/8
Ø 63 mm							
225 ... 300	MPYE-5-1/8-HF-010-B	153004 QS-1/8-8		153006 QS-3/8-8		152587 PUN-8x1,25	2307 U-1/8
360 ... 450	MPYE-5-1/4-010-B	153007 QS-1/4-10		153008 QS-3/8-10		152588 PUN-10x1,5	2316 U-1/4
500 ... 2,000	MPYE-5-3/8-010-B	153009 QS-3/8-12		153009 QS-3/8-12		152589 PUN-12x2	2309 U-3/8

1) Fittings sold only in packs of 10.

2) 2 pieces are required.

End position controllers SPC11

FESTO

Technical data

Accessories for the solution package for DGP/DGPL, DGPI/DGPII horizontally mounted

For effective cylinder stroke 225 ... 2,000 mm



Ordering data

Effective cylinder stroke DGP/L, DGPI/L-... [mm]	Part No.	Type	Filter regulator, D series with filter cartridge 5 µm D series	Part No.	Type	Filter regulator, MS series with filter cartridge 5 µm	Part No.	Type	Filter cartridge 5 µm MS series
Ø 25 mm									
225 ... 2,000	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C	
Ø 32 mm									
225 ... 600	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C	
750 ... 2,000	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M	529204	MS6-LFR-1/4-D7-CRM-AS	534499	MS6-LFP-C	
Ø 40 mm									
225 ... 500	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C	
600 ... 2,000	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M	529204	MS6-LFR-1/4-D7-CRM-AS	534499	MS6-LFP-C	
Ø 50 mm									
225 ... 360	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C	
450 ... 500	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M	529204	MS6-LFR-1/4-D7-CRM-AS	534499	MS6-LFP-C	
600 ... 2,000	162724	LFR-3/4-D-5M-MAXI	159641	LFP-D-MAXI-5M	529224	MS6-LFR-3/8-D7-CRM-AS	534499	MS6-LFP-C	
Ø 63 mm									
225 ... 300	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C	
360 ... 450	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M	529204	MS6-LFR-1/4-D7-CRM-AS	534499	MS6-LFP-C	
500 ... 2,000	162724	LFR-3/4-D-5M-MAXI	159641	LFP-D-MAXI-5M	529224	MS6-LFR-3/8-D7-CRM-AS	534499	MS6-LFP-C	


End position controllers SPC11

Technical data

FESTO

Accessories for the solution package for DGP/DGPL, DGPI/DGPIL vertically mounted

For effective cylinder stroke 225 ... 2,000 mm



Ordering data

Effective cylinder stroke DGP/L, DGPI/L [mm]	Proportional 5/3-way valve Type	Fittings ¹⁾				Compressed air tubing Part No.	Silencer ²⁾ Part No.	
		For MPYE-5...		DGP/L, DGPI/L				
Ø 25 mm		Part No.	Type	Part No.	Type	Part No.	Type	
225 ... 500	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153004	QS-1/8-8	152587	PUN-8x1,25	2307 U-1/8
600 ... 750	MPYE-5-1/8-HF-010-B							
1,000 ... 2,000	MPYE-5-1/4-010-B	153005	QS-1/4-8					2316 U-1/4
Ø 32 mm								
225 ... 600	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153004	QS-1/8-8	152587	PUN-8x1,25	2307 U-1/8
750	MPYE-5-1/8-HF-010-B							
1,000 ... 2,000	MPYE-5-1/4-010-B	153005	QS-1/4-8					2316 U-1/4
Ø 40 mm								
225 ... 450	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153005	QS-1/4-8	152587	PUN-8x1,25	2307 U-1/8
500	MPYE-5-1/8-HF-010-B			153005	QS-1/4-8			
600	MPYE-5-1/4-010-B	153007	QS-1/4-10	153007	QS-1/4-10	152588	PUN-10x1,5	2316 U-1/4
750 ... 2,000	MPYE-5-3/8-010-B	153008	QS-3/8-10					2309 U-3/8
Ø 50 mm								
225 ... 300	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153005	QS-1/4-8	152587	PUN-8x1,25	2307 U-1/8
360 ... 450	MPYE-5-1/8-HF-010-B							
500 ... 600	MPYE-5-1/4-010-B	153007	QS-1/4-10	153007	QS-1/4-10	152588	PUN-10x1,5	2316 U-1/4
750 ... 2,000	MPYE-5-3/8-010-B	153008	QS-3/8-10					2309 U-3/8
Ø 63 mm								
225	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153006	QS-3/8-8	152587	PUN-8x1,25	2307 U-1/8
300	MPYE-5-1/8-HF-010-B							
360 ... 450	MPYE-5-1/4-010-B	153007	QS-1/4-10	153008	QS-3/8-10	152588	PUN-10x1,5	2316 U-1/4
500 ... 2,000	MPYE-5-3/8-010-B	153009	QS-3/8-12	153009	QS-3/8-12	152589	PUN-12x2	2309 U-3/8

1) Fittings sold only in packs of 10.

2) 2 pieces are required.

End position controllers SPC11

FESTO

Technical data

Accessories for the solution package for DGP/DGPL, DGPI/DGPII vertically mounted

For effective cylinder stroke 225 ... 2,000 mm



Ordering data

Effective cylinder stroke DGP/L, DGPI/L [mm]	Part No.	Type	Filter regulator, D series with filter cartridge 5 μm D series	Part No.	Type	Filter cartridge 5 μm D series	Part No.	Type	Filter regulator, MS series with filter cartridge 5 μm	Part No.	Type	Filter cartridge 5 μm MS series	Part No.	Type
Ø 25 mm														
225 ... 750	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C						
1,000 ... 2,000	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M	529204	MS6-LFR-1/4-D7-CRM-AS	534499	MS6-LFP-C						
Ø 32 mm														
225 ... 750	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C						
1,000 ... 2,000	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M	529204	MS6-LFR-1/4-D7-CRM-AS	534499	MS6-LFP-C						
Ø 40 mm														
225 ... 500	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C						
600	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M	529204	MS6-LFR-1/4-D7-CRM-AS							534499	MS6-LFP-C
750 ... 2,000	162724	LFR-3/4-D-5M-MAXI	159641	LFP-D-MAXI-5M	529224	MS6-LFR-3/8-D7-CRM-AS								
Ø 50 mm														
225 ... 300	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C						
360 ... 600	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M	529204	MS6-LFR-1/4-D7-CRM-AS							534499	MS6-LFP-C
750 ... 2,000	162724	LFR-3/4-D-5M-MAXI	159641	LFP-D-MAXI-5M	529224	MS6-LFR-3/8-D7-CRM-AS								
Ø 63 mm														
225 ... 300	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M	529152	MS4-LFR-1/4-D7-CRM-AS	534501	MS4-LFP-C						
360 ... 450	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M	529204	MS6-LFR-1/4-D7-CRM-AS							534499	MS6-LFP-C
500 ... 2,000	162724	LFR-3/4-D-5M-MAXI	159641	LFP-D-MAXI-5M	529224	MS6-LFR-3/8-D7-CRM-AS								

End position controllers SPC11

Technical data

FESTO

Order example

For the pneumatic drive DNC with displacement encoder LWG

A workpiece weighing 55 kg is to be moved horizontally on a loading station. The workpiece gripper attached to the piston rod of the drive weighs 40 kg. The total weight to be moved is therefore 95 kg. The desired

travel distance is 300 mm. The travel time is to be < 1.5 seconds.



Note
Sizing software
Smart Soft Stop and ProDrive
→ www.festo.com

Step 1: Selecting the cylinder stroke

For a travel distance of 300 mm, use the table on → 25 to select the next-largest standard stroke of 320 mm or the effective cylinder stroke of 291 ... 350 mm. This column has a grey background.

Step 2: Specifying the drive

For a total weight of 95 kg to be moved horizontally, there is a choice of piston diameters of 50, 63 and 80 mm (see data for max. total weight to be moved).
For the purposes of our example, the drive DNC-50-320-PPV-A, part no. 163 378 has been selected.

Step 3: Specifying the displacement encoder

The appropriate length of the displacement encoder is governed by the effective cylinder stroke.
The column with the grey background in the "Displacement encoder" section of the table shows Part No. 152 647 for this example.



Remember when selecting the drive mounting components that some of these are not backlash-free and therefore cannot be used with the Smart Soft Stop system. The drives must be mounted directly.



Note
Check that the loads placed on the drive by a gripper during movement do not exceed permissible limits.
To carry out simulation quickly and easily, use the Smart Soft Stop software tool.

Step 4: Specifying a proportional 5/3-way valve

The appropriate proportional 5/3-way valve is shown at the intersection of the grey column used in step 1 and the line for the selected pneumatic drive DNC-50... in the "Proportional 5/3-way valve" section of the table.
For the purposes of our example, the proportional 5/3-way valve MPYE-5-1/8-HF-010B, part no. 151 693 has been selected.

Step 5: Completing the order information

To order a complete system you must add the data for the end position controller, valve and controller cables and manual (if required). The complete ordering data for our example can be found on → 25. A manual should normally be ordered. If you already have one, leave the appropriate box blank, indicating that you do not want a manual.

Step 6: Determining the travel time

To calculate the travel time use the "Smart Soft Stop" software tool.
The travel time for the order example is 0.96 seconds.



Note
The self-aligning rod coupler FK is not backlash-free. It must not therefore be used in combination with standard cylinder DNC.

Ordering data

Pneumatic drive Part No. Type	Displacement encoder Part No. Type	Proportional 5/3-way valve Part No. Type	End position controller Part No. Type
163378 DNC-50-320-PPV-A	152647 MLO-POT-360-LWG	151693 MPYE-5-1/8-HF-010B	192217 SPC11-POT-LWG

Valve cable

Part No. Type

170238 KMPYE-AIF-1-GS-GD-2

Controller cable

Part No. Type

177674 KMPV-SUB-D-15-10

End position controllers SPC11

FESTO

Technical data

Step 1 and 2:											
Standard cylinders/Type	DNC-... ¹⁾ ... ²⁾ -PPV-A										
Max. effective cylinder stroke [mm]	100	150	150	225	225	300	360	450	600	750	
Effective cylinder stroke (standard stroke) [mm]	80	100	125	160	200	250	320	400	500	650	
Max. overall mass to be moved horizontally by Ø [kg]	32	45 kg									
	40	75 kg									
	50	120 kg									
	63	180 kg									
	80	300 kg									
Part No. for Ø	32	163 308	163 309	163 310	163 311	163 312	163 313	163 314	163 315	163 316	163 304
	40	163 340	163 341	163 342	163 343	163 344	163 345	163 346	163 347	163 348	163 336
	50	163 372	163 373	163 374	163 375	163 376	163 377	163 378	163 379	163 380	163 368
	63	163 404	163 405	163 406	163 407	163 408	163 409	163 410	163 411	163 412	163 400
	80	163 436	163 437	163 438	163 439	163 440	163 441	163 442	163 443	163 444	163 432

Step 3:										
Displacement encoder ³⁾	MLO-POT-...-LWG									
Max. effective cylinder stroke [mm]	100	150	150	225	225	300	360	450	600	750
Potentiometer length [mm]	100	150	150	225	225	300	360	450	600	750
Part No.	192 213	192 214	192 214	152 645	152 645	152 646	152 647	152 648	152 650	152 651

Step 4:										
Proportional 5/3-way valves ⁴⁾	1 = 151 692 MPYE-5-1/8-LF-010-B					3 = 151 694 MPYE-5-1/4-010-B				
Part No./Type	2 = 151 693 MPYE-5-1/8-HF-010-B					4 = 151 695 MPYE-5-3/8-010-B				
Max. effective cylinder stroke [mm]	100	150	150	225	225	300	360	450	600	750
Horizontal for Ø	32	1	1	1	1	1	1	1	2	2
	40	1	1	1	1	1	2	2	3	3
	50	1	1	1	1	1	2	2	3	3
	63	1	1	1	1	2	2	3	3	4
	80	1	1	2	2	3	3	3	4	4

Step 5:										
End position controllers and accessories		Part No.	Type	Brief description						
End position controller	SPC11	192217	SPC11-POT-LWG							
Cable	Valve	170238	KMPYE-AIF-1-GS-GD-2	Cable length 2 m						
		170239	KMPYE-AIF-1-GS-GD-0,3	Cable length 0.3 m						
	SPC11/PLC	177673	KMPV-SUB-D-15-5	Cable length 5 m						
		177674	KMPV-SUB-D-15-10	Cable length 10 m						



- 1) Indicate piston Ø. Technical data and dimensions → www.festo.com.
- 2) Indicate calculated effective stroke of cylinder.
- 3) Technical data and dimensions → www.festo.com.
- 4) Technical data and dimensions → www.festo.com.

Manuals → 37


End position controllers SPC11

Technical data

FESTO

Accessories for the solution package for DNC horizontally mounted

For effective cylinder stroke 80 ... 750 mm



Ordering data

Effective cylinder stroke DNC-... [mm]	Proportional valve Type	Fittings ¹⁾				Compressed air tubing	Silencer ²⁾	
		For MPYE-5-...		DNC				
Ø 32 mm		Part No.	Type	Part No.	Type	Part No.	Type	
80 ... 440	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153004	QS-1/8-8	152587	PUN-8x1,25	2307 U-1/8
441 ... 735	MPYE-5-1/8-HF-010-B							
Ø 40 mm								
80 ... 290	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153005	QS-1/4-8	152587	PUN-8x1,25	2307 U-1/8
291 ... 440	MPYE-5-1/8-HF-010-B			153005	QS-1/4-8			
441 ... 735	MPYE-5-1/4-010-B	153007	QS-1/4-10	153007	QS-1/4-10	152588	PUN-10x1,5	2316 U-1/4
Ø 50 mm								
80 ... 290	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153005	QS-1/4-8	152587	PUN-8x1,25	2307 U-1/8
291 ... 440	MPYE-5-1/8-HF-010-B							
441 ... 735	MPYE-5-1/4-010-B	153007	QS-1/4-10	153007	QS-1/4-10	152588	PUN-10x1,5	2316 U-1/4
Ø 63 mm								
80 ... 175	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153006	QS-3/8-8	152587	PUN-8x1,25	2307 U-1/8
176 ... 350	MPYE-5-1/8-HF-010-B			153006	QS-3/8-8			
351 ... 590	MPYE-5-1/4-010-B	153007	QS-1/4-10	153008	QS-3/8-10	152588	PUN-10x1,5	2316 U-1/4
591 ... 735	MPYE-5-3/8-010-B	153009	QS-3/8-12	153009	QS-3/8-12	152589	PUN-12x2	2309 U-3/8
Ø 80 mm								
80 ... 115	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153006	QS-3/8-8	152587	PUN-8x1,25	2307 U-1/8
116 ... 175	MPYE-5-1/8-HF-010-B			153006	QS-3/8-8			
176 ... 440	MPYE-5-1/4-010-B	153007	QS-1/4-10	153008	QS-3/8-10	152588	PUN-10x1,5	2316 U-1/4
441 ... 735	MPYE-5-3/8-010-B	153009	QS-3/8-12	153009	QS-3/8-12	152589	PUN-12x2	2309 U-3/8

1) Fittings sold only in packs of 10.

2) 2 pieces are required.

End position controllers SPC11

FESTO

Technical data

Accessories for the solution package for DNC horizontally mounted

For effective cylinder stroke 80 ... 750 mm



Ordering data

Effective cylinder stroke DNC-... [mm]	Part No.	Type	Filter regulator, D series with filter cartridge 5 µm D series	Part No.	Type	Filter regulator, MS series with filter cartridge 5 µm	Part No.	Type	Filter cartridge 5 µm MS series	Part No.	Type
Ø 32 mm											
80 ... 735	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
Ø 40 mm											
80 ... 440	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
441 ... 735	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	
Ø 50 mm											
80 ... 440	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
441 ... 735	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	
Ø 63 mm											
80 ... 350	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
351 ... 590	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	
591 ... 735	162724	LFR-3/4-D-5M-MAXI	159641	LFP-D-MAXI-5M		529224	MS6-LFR-3/8-D7-CRM-AS		534499	MS6-LFP-C	
Ø 80 mm											
80 ... 175	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
176 ... 440	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	
441 ... 735	162724	LFR-3/4-D-5M-MAXI	159641	LFP-D-MAXI-5M		529224	MS6-LFR-3/8-D7-CRM-AS		534499	MS6-LFP-C	

End position controllers SPC11

Technical data

FESTO

Order example

For pneumatic standard drive DNCI with integrated displacement encoder

A workpiece weighing 55 kg is to be moved horizontally on a loading station. The workpiece gripper attached to the piston rod of the drive weighs 40 kg. The total weight to be moved is therefore 95 kg. The desired

travel distance is 300 mm. The travel time is to be < 1.5 seconds.

- - Note

Sizing software
Smart Soft Stop and ProDrive
→ www.festo.com

Step 1: Selecting the cylinder stroke

For a travel distance of 300 mm, use the table on → 29 to select the next-largest standard stroke of 320 mm or the effective cylinder stroke of 320 mm. This column has a grey background.

Step 2: Specifying the drive

For a total weight of 95 kg to be moved horizontally, there is a choice of piston diameters of 50 and 63 mm (see data for max. total weight to be moved).
For the purposes of our example, the drive DNCI-50-320-P-A, part no. 535 413 has been selected.

Remember when selecting the drive mounting components that some of these are not backlash-free and therefore cannot be used with the Smart Soft Stop system. The drives must be mounted directly.

- - Note

Check that the loads placed on the drive by a gripper during movement do not exceed permissible limits.
To carry out simulation quickly and easily, use the Smart Soft Stop software tool.

Step 3: Specifying a proportional 5/3-way valve

The appropriate proportional 5/3-way valve is shown at the intersection of the grey column used in step 1 and the line for the selected pneumatic drive DNCI-50... in the "Proportional 5/3-way valve" section of the table.
For the purposes of our example, the proportional-5/3-way valve MPYE-5-1/8-HF-010B, part no. 151 693 has been selected.

Step 4: Completing the order information

To order a complete system you must add the data for the end position controller, valve and controller cables and manual (if required). The complete ordering data for our example can be found on → 29. A manual should normally be ordered. If you already have one, leave the appropriate box blank, indicating that you do not want a manual.

Step 5: Determining the travel time

To calculate the travel time use the "Smart Soft Stop" software tool.
The travel time for the order example is 0.92 seconds.

- - Note

The self-aligning rod coupler FK is not backlash-free. It must not therefore be used in combination with standard cylinder DNCI.

Ordering data

Pneumatic drive Part No.	Type	Proportional 5/3-way valve Part No.	Type	End position controller Part No.	Type
535413	DNCI-50-320-P-A	151693	MPYE-5-1/8-HF-010B	537321	SPC11-INC
Valve cable Part No.			Controller cable Part No.		
170238 KMPYE-AIF-1-GS-GD-2			177674 KMPV-SUB-D-15-10		

End position controllers SPC11

FESTO

Technical data

Step 1 and 2:

Standard cylinders/Type	DNCI-... ¹⁾ -... ²⁾ -P-A						
Effective cylinder stroke (standard stroke)	100	160	200	250	320	400	500
Max. overall mass to be moved horizontally by Ø	32	45 kg					
	40	75 kg					
	50	120 kg					
	63	180 kg					
Part No. for Ø	32	535 411					
	40	535 412					
	50	535 413					
	63	535 414					

Step 3:

Proportional 5/3-way valves ³⁾	1 = 151 692 MPYE-5-1/8-LF-010-B				3 = 151 694 MPYE-5-1/4-010-B		
Part No./Type	2 = 151 693 MPYE-5-1/8-HF-010-B						
Effective cylinder stroke (standard stroke)	100	160	200	250	320	400	500
Horizontal for Ø	32	1	1	1	1	1	2
	40	1	1	1	1	2	2
	50	1	1	1	1	2	3
	63	1	1	2	2	3	3

Step 4:

End position controllers and accessories	Part No.	Type	Brief description
End position controller SPC11	537321	SPC11-INC	
Cable Valve	170238	KMPYE-AIF-1-GS-GD-2	Cable length 2 m
	170239	KMPYE-AIF-1-GS-GD-0,3	Cable length 0.3 m
SPC11/PLC	177673	KMPV-SUB-D-15-5	Cable length 5 m
	177674	KMPV-SUB-D-15-10	Cable length 10 m

-  - Note

Manuals ➔ 37

1) Indicate piston Ø. Technical data and dimensions ➔ www.festo.com.

2) Indicate calculated effective stroke of cylinder.

3) Technical data and dimensions ➔ www.festo.com.


End position controllers SPC11

Technical data

FESTO

Accessories for the solution package for DNCI horizontally mounted

For effective cylinder stroke 100 ... 500 mm



Ordering data								
Effective cylinder stroke DNCI-... [mm]	Proportional 5/3-way valve	Fittings ¹⁾			Compressed air tubing		Silencer ²⁾	
		For MPYE-5-...		DNCI	Part No.	Type	Part No.	Type
\varnothing 32 mm								
100 ... 400	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8		153004	QS-1/8-8	152587	PUN-8x1,25
500	MPYE-5-1/8-HF-010-B						2307	U-1/8
\varnothing 40 mm								
100 ... 250	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8		153005	QS-1/4-8	152587	PUN-8x1,25
320 ... 500	MPYE-5-1/8-HF-010-B				153005	QS-1/4-8	2307	U-1/8
\varnothing 50 mm								
100 ... 250	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8		153005	QS-1/4-8	152587	PUN-8x1,25
320 ... 400	MPYE-5-1/8-HF-010-B						2307	U-1/8
500	MPYE-5-1/4-010-B	153007	QS-1/4-10		153007	QS-1/4-10	152588	PUN-10x1,5
\varnothing 63 mm								
100 ... 160	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8		153006	QS-3/8-8	152587	PUN-8x1,25
200 ... 320	MPYE-5-1/8-HF-010-B				153006	QS-3/8-8	2307	U-1/8
400 ... 500	MPYE-5-1/4-010-B	153007	QS-1/4-10		153008	QS-3/8-10	152588	PUN-10x1,5
							2316	U-1/4

1) Fittings sold only in packs of 10.

2) 2 pieces are required.

End position controllers SPC11

FESTO

Technical data

Accessories for the solution package for DNCI horizontally mounted

For effective cylinder stroke 100 ...500 mm



Ordering data

Effective cylinder stroke DNCI-... [mm]	Part No.	Type	Filter regulator, D series with filter cartridge 5 μm D series	Part No.	Type	Filter regulator, MS series with filter cartridge 5 μm	Part No.	Type	Filter cartridge 5 μm MS series	Part No.	Type
Ø 32 mm											
100 ... 500	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
Ø 40 mm											
100 ... 400	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
500	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	
Ø 50 mm											
100 ... 400	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
500	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	
Ø 63 mm											
100 ... 320	162719	LFR-1/4-D-5M-MINI	159640	LFP-D-MINI-5M		529152	MS4-LFR-1/4-D7-CRM-AS		534501	MS4-LFP-C	
400 ... 500	162721	LFR-3/8-D-5M-MIDI	159594	LFP-D-MIDI-5M		529204	MS6-LFR-1/4-D7-CRM-AS		534499	MS6-LFP-C	

End position controllers SPC11

Technical data

FESTO

Order example for swivel module DSMI

A workpiece with a mass moment of inertia of $400 \text{ kgm}^2 \times 10^{-4}$ is to be moved on an unloading station. The workpiece gripper attached to the

shaft of the swivel module has a mass moment of inertia of $230 \text{ kgm}^2 \times 10^{-4}$. The total mass moment of inertia to be moved is therefore $630 \text{ kgm}^2 \times 10^{-4}$.

The swivel angle is 250° . The travel time is to be < 1 second.



Note
Sizing software
Smart Soft Stop and ProDrive
→ www.festo.com

Step 1: Specifying the swivel angle

The maximum swivel angle of the swivel modules DSMI-25-270 and DSMI-40-270 is 270° and can be fully exploited. The integrated displacement encoder is appropriately designed.


Step 2: Specifying the drive

DSMI-40-270 must be used for the total mass moment of inertia of $630 \text{ kgm}^2 \times 10^{-4}$ to be moved horizontally

→ 33.

Step 3: Specifying a proportional 5/3-way valve

As can be seen from the table → 33, the proportional 5/3-way valve MPYE-5-1/8-LF-010B is generally required for swivel module DSMI-40-270.



Remember when selecting the drive mounting components that some of these are not backlash-free and therefore cannot be used with the Smart Soft Stop system. The drives must be mounted directly.

Step 4: Completing the order information

To order a complete system you must add the data for the end position controller, valve and controller cables and manual (if required). The complete ordering data for our example can be found on → 33. A manual should normally be ordered. If you already have one, leave the appropriate box blank, indicating an express waiver of a manual.

Step 5: Determining the travel time

To calculate the travel time use the "Smart Soft Stop" software tool. The travel time for the order example is 0.89 seconds.



Note
Check that the loads placed on the drive by a gripper during the movement process do not exceed permissible limits.
To carry out simulation quickly and easily, use the Smart Soft Stop software tool.

Ordering data

Swivel module Part No. Type	Proportional 5/3-way valve Part No. Type	End position controller Part No. Type
561691 DSMI-40-270-A-B	151692 MPYE-5-1/8-LF-010B	192217 SPC11-POT-LWG

Valve cable Part No. Type	Controller cable Part No. Type
170238 KMPYE-AIF-1-GS-GD-2	177674 KMPV-SUB-D-15-10

End position controllers SPC11

FESTO

Technical data

Step 1 and 2:

Swivel module with integrated displacement encoder	DSMI-25-270-A-B	DSMI-40-270-A-B
Swivel angle	270°	
Max. permissible mass moment of inertia, horizontal	300 kgm ² ×10 ⁻⁴	1,200 kgm ² ×10 ⁻⁴
Part No.	561690	561691

Step 3

Proportional 5/3-way valves ¹⁾	Part No.	Type	Part No.	Type
	154200	MPYE-5-M5-010B	151692	MPYE-5-1/8-LF-010B

Step 4

End position controllers and accessories	Part No.	Type	Brief description
End position controller SPC11	192217	SPC11-POT-LWG	
Cable	170238	KMPYE-AIF-1-GS-GD-2	Cable length 2 m
	170239	KMPYE-AIF-1-GS-GD-0,3	Cable length 0.3 m
Valve	177673	KMPV-SUB-D-15-5	Cable length 5 m
SPC11/PLC	177674	KMPV-SUB-D-15-10	Cable length 10 m



1) Technical data and dimensions → www.festo.com.

Manuals → 37




End position controllers SPC11

Technical data

FESTO

Accessories for the solution package for DSMI horizontally mounted

For swivel angle 0° ... 270°



Ordering data		Fittings ¹⁾		Compressed air tubing		Silencer ²⁾	
Swivel angle DSMI	Proportional Type	For MPYE-5-...	DSMI	Part No.	Type	Part No.	Type
Ø 25 mm							
0° ... 270°	MPYE-5-M5-010-B	153306	QSM-M5-6	153306	QSM-M5-6	152586	PUN-6x1
Ø 40 mm							
0° ... 270°	MPYE-5-1/8-LF-010-B	153004	QS-1/8-8	153004	QS-1/8-8	152587	PUN-8x1,25
						2307	U-1/8

1) Fittings sold only in packs of 10.

2) 2 pieces are required.


End position controllers SPC11

FESTO

Technical data

Accessories for the solution package for DSMI horizontally mounted

For swivel angle 0° ... 270°



Ordering data

Swivel angle DSMI	Filter regulator, D series with filter cartridge 5 µm Part No. Type	Filter cartridge 5 µm D series Part No. Type	Filter regulator, MS series with filter cartridge 5 µm Part No. Type	Filter cartridge 5 µm MS series Part No. Type
Ø 25 mm				
0° ... 270°	162719 LFR-1/4-D-5M-MINI	159640 LFP-D-MINI-5M	529152 MS4-LFR-1/4-D7-CRM-AS	534501 MS4-LFP-C
Ø 40 mm				
0° ... 270°	162719 LFR-1/4-D-5M-MINI	159640 LFP-D-MINI-5M	529152 MS4-LFR-1/4-D7-CRM-AS	534501 MS4-LFP-C


End position controllers SPC11

Technical data

FESTO

Mass moment of inertia calculation with the aid of Festo software


Software tool: Mass moment of inertia



No matter whether you have discs, blocks, push-on flanges, grippers, etc: This tool does the job of calculating all mass moments of inertia for you.

Just save, send, or print – and you're finished.

- - Note
Sizing software
Inertia calculations
→ www.festo.com



End position controllers SPC11

FESTO

Technical data

Ordering data – Manuals				
	Part No.	Type	Part No.	Type
System description – End position controllers				
SPC11	German	196723 P.BE-SPC11-SYS-DE		
	English	196724 P.BE-SPC11-SYS-EN		
	French	196727 P.BE-SPC11-SYS-FR		
	Italian	196726 P.BE-SPC11-SYS-IT		
	Swedish	196728 P.BE-SPC11-SYS-SV		
	Spanish	196725 P.BE-SPC11-SYS-ES		
Drive-specific supplement				
For DGCI			For DGP/DGPL/DGPI/DGPIL	
SPC11	German	549166 P.BE-SPC11-DGCI-DE	SPC11	196729 P.BE-SPC11-DGP-DE
	English	549167 P.BE-SPC11-DGCI-EN		196730 P.BE-SPC11-DGP-EN
	French	549169 P.BE-SPC11-DGCI-FR		196733 P.BE-SPC11-DGP-FR
	Italian	549170 P.BE-SPC11-DGCI-IT		196732 P.BE-SPC11-DGP-IT
	Swedish	549171 P.BE-SPC11-DGCI-SV		196734 P.BE-SPC11-DGP-SV
	Spanish	549168 P.BE-SPC11-DGCI-ES		196731 P.BE-SPC11-DGP-ES
For DNC			For DNCI	
SPC11	German	196735 P.BE-SPC11-DNC-DE	SPC11	539888 P.BE-SPC11-DNCI-DE
	English	196736 P.BE-SPC11-DNC-EN		539889 P.BE-SPC11-DNCI-EN
	French	196739 P.BE-SPC11-DNC-FR		539891 P.BE-SPC11-DNCI-FR
	Italian	196738 P.BE-SPC11-DNC-IT		539892 P.BE-SPC11-DNCI-IT
	Swedish	196740 P.BE-SPC11-DNC-SV		539893 P.BE-SPC11-DNCI-SV
	Spanish	196737 P.BE-SPC11-DNC-ES		539890 P.BE-SPC11-DNCI-ES
For DSMI				
SPC11	German	196741 P.BE-SPC11-DSMI-DE		
	English	196742 P.BE-SPC11-DSMI-EN		
	French	196745 P.BE-SPC11-DSMI-FR		
	Italian	196744 P.BE-SPC11-DSMI-IT		
	Swedish	196746 P.BE-SPC11-DSMI-SV		
	Spanish	196743 P.BE-SPC11-DSMI-ES		

End position controllers SPC11

Technical data

FESTO

Converting existing systems

What are the points to note when converting existing systems that use the pneumatic drives DGP/DGPL or DNC?	Optimum system behaviour is guaranteed by Festo's uniquely specified solution packages, in which all components are harmonised. When converting existing systems, observe the following points:																									
Where could system behaviour possibly change when an existing system is converted?	In normal cases, the entire cylinder stroke is used, including the internal cushioning length (PPV); no stroke reserve is available.																									
What should be noted when installing the pneumatics?	<ul style="list-style-type: none">• Make sure that the system configuration is symmetrical, i.e. that the tubing used to connect the compressed air supply to each end of the cylinder is of identical length.• No flow controls between the valve and cylinder.• Open the end-position cushioning (PPV) 100%.	Accessories and tubing diameters can be found in the description for the respective solution package.																								
What should be noted when installing the electrics?	As far as the electrical actuation is concerned, the Smart Soft Stop system behaves like a standard pneumatic system with a double solenoid valve and two proximity sensors.	For further information see the manual System description: SPC11... ➔ 37.																								
Does the control program need to be adapted?	Existing systems which have provision for two digital inputs/outputs can be converted without adaptation of the control program.																									
What proportional 5/3-way valve should be selected for the conversion project?	Exactly the same valve as specified in the solution packages on ➔ 19 or 25.																									
What end position controller is suitable for each drive or displacement encoder?	<table border="1"><thead><tr><th>End position controller</th><th>Drive</th><th>Displacement encoder</th></tr></thead><tbody><tr><td>SPC11-POT-TLF</td><td>DGP/DGPL</td><td>MLO-POT-...-TLF</td></tr><tr><td>SPC11-POT-LWG</td><td>DNC</td><td>MLO-POT-...-LWG</td></tr><tr><td></td><td>DSMI</td><td>Integrated</td></tr><tr><td>SPC11-MTS-AIF</td><td>DGP/DGPL</td><td>MME-MTS-...-AIF</td></tr><tr><td></td><td>DGPI/DGPIL</td><td>Integrated</td></tr><tr><td>SPC11-INC</td><td>DNCI</td><td>Integrated</td></tr><tr><td>SPC11-MTS-AIF-2</td><td>DGCI</td><td>Adapted</td></tr></tbody></table>		End position controller	Drive	Displacement encoder	SPC11-POT-TLF	DGP/DGPL	MLO-POT-...-TLF	SPC11-POT-LWG	DNC	MLO-POT-...-LWG		DSMI	Integrated	SPC11-MTS-AIF	DGP/DGPL	MME-MTS-...-AIF		DGPI/DGPIL	Integrated	SPC11-INC	DNCI	Integrated	SPC11-MTS-AIF-2	DGCI	Adapted
End position controller	Drive	Displacement encoder																								
SPC11-POT-TLF	DGP/DGPL	MLO-POT-...-TLF																								
SPC11-POT-LWG	DNC	MLO-POT-...-LWG																								
	DSMI	Integrated																								
SPC11-MTS-AIF	DGP/DGPL	MME-MTS-...-AIF																								
	DGPI/DGPIL	Integrated																								
SPC11-INC	DNCI	Integrated																								
SPC11-MTS-AIF-2	DGCI	Adapted																								